

Densus LED Gen3

EL-DENL-3100-000



DENSUS LED GEN3 Suspended/Surface Mounted Single Luminaire Bottom
Access Direct 3100lm 18.2W LED Wide beam 4000K/ Ra80+ 240V Pc Diffuser
Non-dim Class I L:1280mm W:150mm H:100mm IP66 IK10/20J Grey.



TECHNICAL OVERVIEW

FINISH

Grey

L = LENGTH [mm]

1280

W = WIDTH/DIAMETER [mm]

150

H = HEIGHT [mm]

100

CL = RECESSING LENGTH [mm]

-

CW = RECESSING

WIDTH/DIAMETER [mm]

-


WEIGHT [KG]

2.5



INSTALLATION CENTRES	
1280x150	903
1280x150	903
680x150	473

IES INDOOR REPORT
PHOTOMETRIC FILENAME: 1906LW_EL-DENL-3100-000.IES
POLAR GRAPH



Maximum Candela = 208.203 Located At Horizontal Angle = 45, Vertical Angle = 5
1 - Vertical Plane Through Horizontal Angles (0° - 320°)
2 - Vertical Plane Through Horizontal Angles (0° - 180°)

NORMALISED POLAR CURVE

PHOTOMETRIC VALUES

CONTROL TYPE

Non-dim

CEILING TYPE/MOUNTING

Suspended/Surface Mounted

WATTAGE [W]

18.2

CLO ENABLED

No

FINAL WATTAGE CLO [W]

-

SYSTEM LUMENS [lm]

3100

LIGHTING TYPE

Direct

TARGET SPACING [m]

-

TARGET H ILLUMINANCE [LUX]

-

LPD [W/m²]

-

NPD [W/SQM/100LUX]

-

BEAMWIDTH (FWHM)

-

LUMINAIRE LUMENS [lm]

2529

EFFICACY [lm/W]

139

COLOUR QUALITY

CCT [K]

4000K

CCT1 [K]

4000K

CCT2 [K]

-

OTHER LIGHT COLOUR

-

CRI

Ra80+

COI COMPLIANCE

Non-Compliant

CLA 2.0

-

M-DER

-

LIFETIME AND MISCELLANEOUS PARAMETERS

LM80 TEST DURATION [HRS]

12000

L90B50 LIFETIME [HRS]

63000

TM21 L70 REPORTED LIFETIME [HRS]

>72000

Product Advisement Statement

- All photometric (including flicker metrics), spectrometric, electrical, and thermal data have a tolerance of ±5%.
- The value indicated by the UGR icon refers to the lowest UGR value achievable by at least one standard variant of a given product family. It may not necessarily apply to all standard variants.
- The Unified Glare Rating (UGR) is a function of the entire design space, including but not limited to the optical properties of the ceiling and walls, as well as the properties and spacing of all other luminaires in the calculation space. It is not an intrinsic property of a light fitting and should not be quoted as such.
- All UGR values stated by Eagle Lighting are calculated in compliance with AS/NZS 1680.1-2006 (aligned with CIE 117-1995) and are achievable with standard room sizes and luminaire spacing based on the specific luminaire model.
- The following design parameters apply unless otherwise specified:
 - Light Loss Factor (LLF): 0.80 (Nominal)
 - Room Reflectance Values (Ceiling/Walls/Floor): 0.70/0.50/0.20
 - Ceiling Height: 2.7m
 - Horizontal Illuminance (Eh) calculated at 0.72m above finished floor level (AFFL)
- Non-standard (custom) products may have UGR values higher than those of standard models, depending on the nature of the customization. Please consult your sales representative for details.
- UGR values obtained under conditions or parameters other than those specified above may differ from the stated values.
- All product heights are shown excluding the driver unless otherwise specified.
- For questions about our products or assistance with ordering accessories (where applicable), please contact your customer service representative.

OPTICS TYPE

PC Opal Diffuser

UGR

-

R9

11

MELANOPIC RATIO

0.69

CIRCADIAN STIMULUS CS [%]

13

CIRCADIAN LIGHT [LUX]

91

TM-30 RF

85

TM-30 RG

95

M-EDI

-

L100B50 LIFETIME (CLO) [HRS]

-

TM21 L90 REPORTED LIFETIME [HRS]

52000

SDCM INITIAL

3

