

Operating Theatre Light CRI95+ (Gen1)



EL-OPSL-1267-200

OPERATING THEATRE CRI95+ Plaster/Sandwich panel Single Luminaire Bottom
Access Direct 5700lm 40W LED Wide beam 4000K Ra95+ 240V Delta DALI Class I
Std AUS flex & plug 2.0m & 2 core dimming flex 2.0m L:1254mm W:381mm
H:105mm IP65 IK08/5J White .



TECHNICAL OVERVIEW

FINISH

White

L = LENGTH [mm]

1254

W = WIDTH/DIAMETER [mm]

381

H = HEIGHT [mm]

105

CL = RECESSING LENGTH [mm]


1230

CW = RECESSING WIDTH/DIAMETER [mm]

360

WEIGHT [KG]

13



NOMINAL POLAR CURVE

PHOTOMETRIC VALUES

CONTROL TYPE

DALI

CEILING TYPE/MOUNTING

Plaster/Sandwich panel

WATTAGE [W]

40

CLO ENABLED

No

FINAL WATTAGE CLO [W]

-

SYSTEM LUMENS [lm]

5700

LUMINAIRE LUMENS [lm]

4173

EFFICACY [lm/W]

105

LIGHTING TYPE

Direct

TARGET SPACING [m]

10 x 3 square

TARGET H ILLUMINANCE [LUX]

810

LPD [W/m²]

-

NPD [W/SQM/100LUX]

-

BEAMWIDTH (FWHM)

-

OPTICS TYPE

Delta

UGR

-

COLOUR QUALITY

CCT [K]
4000K
CCT1 [K]
4000K
CCT2 [K]
-
OTHER LIGHT COLOUR
-
CRI
Ra95+
COI COMPLIANCE
Compliant
CLA 2.0
-
M-DER
-

LIFETIME AND MISCELLANEOUS PARAMETERS

LM80 TEST DURATION [HRS]
10000
L90B50 LIFETIME [HRS]
>50000
TM21 L70 REPORTED LIFETIME [HRS]
>50000

ACCESSORIES

DESCRIPTION	CODE
Restraint Kit - 4 x gripple, 2 x 2m wire	EL-ACC-210-000
Suction Cup Mini 3-1/4" Black	EL-ACC-582-000

Product Advisement Statement

- All photometric (including flicker metrics), spectrometric, electrical, and thermal data have a tolerance of ±5%.
- The value indicated by the UGR icon refers to the lowest UGR value achievable by at least one standard variant of a given product family. It may not necessarily apply to all standard variants.
- The Unified Glare Rating (UGR) is a function of the entire design space, including but not limited to the optical properties of the ceiling and walls, as well as the properties and spacing of all other luminaires in the calculation space. It is not an intrinsic property of a light fitting and should not be quoted as such.
- All UGR values stated by Eagle Lighting are calculated in compliance with AS/NZS 1680.1-2006 (aligned with CIE 117-1995) and are achievable with standard room sizes and luminaire spacing based on the specific luminaire model.
- The following design parameters apply unless otherwise specified:
 - Light Loss Factor (LLF): 0.80 (Nominal)
 - Room Reflectance Values (Ceiling/Walls/Floor): 0.70/0.50/0.20
 - Ceiling Height: 2.7m
 - Horizontal Illuminance (Eh) calculated at 0.72m above finished floor level (AFFL)
 - 3 x 3 simple square layout in an 8.0 x 7.0m room.
- Non-standard (custom) products may have UGR values higher than those of standard models, depending on the nature of the customization. Please consult your sales representative for details.
- UGR values obtained under conditions or parameters other than those specified above may differ from the stated values.
- All product heights are shown excluding the driver unless otherwise specified.
- For questions about our products or assistance with ordering accessories (where applicable), please contact your customer service representative.

R9
86
MELANOPIC RATIO
0.8
CIRCADIAN STIMULUS CS [%]
16
CIRCADIAN LIGHT [LUX]
113
TM-30 RF
95
TM-30 RG
102
M-EDI
-

L100B50 LIFETIME (CLO) [HRS]
-
TM21 L90 REPORTED LIFETIME [HRS]
-
SDCM INITIAL
2

