

Envoy


Premium lens-based low-glare downlight designed for general lighting applications

Product Code: ENV-REC-C4097-0700-OVW-BLK-R-MDM

Designed for high visual comfort, Envoy delivers high colour-rendering, low-glare light output using a deeply-recessed optical lens. This modern downlight is incredibly versatile and offers an extensive breadth of configurable attributes. Available in models delivering between 700-2500 lumens, CCTs in 2700K, 3000K or 4000K with multiple lens options while supporting all of Digilin’s control protocols, including mains, DALI, smooth DALI, DMX and Bluetooth, Envoy can be configured to suit almost any environment requiring quality light and visual comfort.



LED Colour	White
CCT/Wavelength	4000K
Delivered Lumens	600lm
Luminaire Power	5.9W
Connected Load	6.6W
Drive Current	180mA
Forward Voltage	32.7V
Typical CRI	97
Cyanosis Observation Index	.66
LED Performance	L90(9K) >50,000hrs
Colour Consistency	2 SDCM
IC Rating	IC-4
Mounting	Recessed
Beam Option	Wide Oval (36°x55°)
Finish Colour	Black
Driver Placement	Remote
Control	Mains/Phase
Build Material	Cast Aluminium
Luminaire IP Rating	IP44 (IP65 available using DLA-ENV-IP65 accessory)
Dimensions	90mm (trim diameter), 80mm (hole cut out), 68mm/98mm/128mm (height varies with model, refer to install guide)
Weight	220-420g (varies with model, refer to install guide)



Specifications are subject to change without notice