

Pleiad G4 165

FG-73025-402



PLEIAD G4 165 Recessed Single Luminaire Direct 9W LED Medium beam 3000K
Ra90+ 240V Black reflector DALI Class III W:183mm H:98mm IP64/20 White .
Supplied as: EL-73025.0-0,EL-99474-0



TECHNICAL OVERVIEW

FINISH

White

L = LENGTH [mm]

-

W = WIDTH/DIAMETER [mm]

183

H = HEIGHT [mm]

98

CL = RECESSING LENGTH [mm]

-

CW = RECESSING WIDTH/DIAMETER [mm]

165

WEIGHT [KG]

0.5

PHOTOMETRIC VALUES

CONTROL TYPE

DALI

CEILING TYPE/MOUNTING

Recessed

WATTAGE [W]

9

CLO ENABLED

Yes

FINAL WATTAGE CLO [W]

-

SYSTEM LUMENS [lm]

-

LUMINAIRE LUMENS [lm]

820

EFFICACY [lm/W]

91

COLOUR QUALITY

CCT [K]

3000K

LIGHTING TYPE

Direct

TARGET SPACING [m]

-

TARGET H ILLUMINANCE [LUX]

-

LPD [W/m²]

-

NPD [W/SQM/100LUX]

-

BEAMWIDTH (FWHM)

-

OPTICS TYPE

Black reflector

UGR

-

R9

-

CCT1 [K]
3000K
CCT2 [K]
-
OTHER LIGHT COLOUR
-
CRI
Ra90+
COI COMPLIANCE
Non-Compliant
CLA 2.0
-
M-DER
-

MELANOPIC RATIO
-
CIRCADIAN STIMULUS CS [%]
-
CIRCADIAN LIGHT [LUX]
-
TM-30 RF
-
TM-30 RG
-
M-EDI
-

LIFETIME AND MISCELLANEOUS PARAMETERS

LM80 TEST DURATION [HRS]
-
L90B50 LIFETIME [HRS]
-
TM21 L70 REPORTED LIFETIME [HRS]
-

L100B50 LIFETIME (CLO) [HRS]
55000
TM21 L90 REPORTED LIFETIME [HRS]
-
SDCM INITIAL
3

ACCESSORIES

CODE	DESCRIPTION
EL-ACC-291-000	ANTI LIGATURE KIT TO SUIT PLEIAD Ø165MM RING WH
EL-ACC-295-000	RETROFIT RING TO SUIT PLEIAD Ø165-270MM RING WH

Product Advisement Statement

- All photometric (including flicker metrics), spectrometric, electrical, and thermal data have a tolerance of ±5%.
- The value indicated by the UGR icon refers to the lowest UGR value achievable by at least one standard variant of a given product family. It may not necessarily apply to all standard variants.
- The Unified Glare Rating (UGR) is a function of the entire design space, including but not limited to the optical properties of the ceiling and walls, as well as the properties and spacing of all other luminaires in the calculation space. It is not an intrinsic property of a light fitting and should not be quoted as such.
- All UGR values stated by Eagle Lighting are calculated in compliance with AS/NZS 1680.1-2006 (aligned with CIE 117-1995) and are achievable with standard room sizes and luminaire spacing based on the specific luminaire model.
- The following design parameters apply unless otherwise specified:
 - Light Loss Factor (LLF): 0.80 (Nominal)
 - Room Reflectance Values (Ceiling/Walls/Floor): 0.70/0.50/0.20
 - Ceiling Height: 2.7m
 - Horizontal Illuminance (Eh) calculated at 0.72m above finished floor level (AFFL)
- Non-standard (custom) products may have UGR values higher than those of standard models, depending on the nature of the customization. Please consult your sales representative for details.
- UGR values obtained under conditions or parameters other than those specified above may differ from the stated values.
- All product heights are shown excluding the driver unless otherwise specified.
- For questions about our products or assistance with ordering accessories (where applicable), please contact your customer service representative.

