

Liberty

Reliable high performance downlight with low glare output



Product Code: LIB-REC-C4097-1200-WDE-WHT-R-BTH

An outstanding example of electronic lighting engineering, Liberty is a versatile reflector-based downlight designed for applications where performance and reliability are essential. Using a high-quality metallic reflector with its LED COB set back about 50mm from the fascia trim, Liberty has extremely good glare control and creates a smooth, uniform light effect.

Liberty is very efficient, delivering 800-2800lm at 110lm per watt (90 CRI) while effectively managing thermals. Ideal for projects where facility performance is important and maintenance factors are reduced as much as possible, this fixture sees widespread application in theatres, hospitals, airports, universities and government institutions across Australia.



Liberty is proudly designed and manufactured by Digilin in Australia.	
LED Colour	Fixed White
Colour Temperature	4000K
Delivered Lumens	920lm
Luminaire Power	8.9W
Connected Load	10W
Drive Current	270mA
Forward Voltage	33V
CRI	97
Cyanosis Observation Index	.66
Performance	L90(9K) >50,000hrs
Colour Consistency	2 SDCM
Beam Option	Wide (58°)
Mounting	Recessed
Finish Colour	White
Driver Placement	Remote
Control	Bluetooth
Build Material	Cast Aluminium
Luminaire IP Rating	IP20 (IP54 & IP65 available)
Dimensions	102mm (trim diameter), 87mm (body diameter), 113mm (height)
Hole Cut Out	90mm
Weight	580g



Specifications are subject to change without notice