

MicroFlex




Micro-sized flexible linear for exterior and curved architectural applications

Product Code: MFL-SL-W4080-0400

MicroFlex is a flexible, durable IP67 linear system designed for high-exposure exterior and curved architectural applications. This unique system is available in front-lit (vertical bending) and side-lit (horizontal bending) formats in multiple CCTs and 4.5W (200lm/m) or 9W (400lm/m) versions. At 10mm squared, MicroFlex has an extremely small form factor and is ideal for mounting under exterior seating and in coffers. Although suitable for exterior use, increasingly we're seeing designers rely on the unique characteristics of MicroFlex to illuminate interior spaces as well, commonly installed in coves and contouring curved architectural elements. MicroFlex is manufactured by an international partner that Digilin has been cooperating with for over 13 years.



Illumination Type	Side-Lit (Horizontal Bending)
LED Colour	Fixed White
CCT/Wavelength	4000K
Delivered Lumens	420lm/m
Power	9Wm
Typical CRI	80
Colour Consistency (LED)	3 SDCM
Performance	L90 (6k) >60,000hrs
Module Length	83.33mm
Operating Temperature	-40 to 45 degrees Celsius
Maximum Continuous Feed	7.5m Single, 15m Dual
Input Voltage	24VDC
IP Rating	IP67
IK Rating	IK07
Beam Angle	Approx. 115 degrees
Build Material	Silicone
Minimum Bend Radius	150mm
Dimensions	10mm (width), 10mm (height)
Weight	Approx. 0.3kg/m
Durability	UV, Saltwater, Solvent and Flame Resistant
Connector Options	Injection Moulded Connectors and End Caps (fitted)
Mounting Options	Serrated Aluminium



Specifications are subject to change without notice