





SHIFT PRO ROTOSYMMETRIC



*Photometric measured using WHITE LED 3000K

NEW

Product is expected to be available from October 2026

Version available on request without price surcharge.

S.1470N.24 (Anthracite grey)

1 module LED 4000K 220-240Vac DIMMABLE DALI2; PUSH

Urban lighting



Light Source Technical Data

Light source type:	LED
Colour temperature:	4000K
Rated module luminous flux:	1579lm
Rated luminaire luminous flux:	795lm
Rated module power:	7.5W
Rated luminaire power:	9.9W
Luminaire efficacy:	80lm/W
ULR:	0.33%
BUG:	B0 - U1 - G0
CIE Flux Code:	42 86 99 100 100
Color Rendering Index:	CRI 80

Standard Deviation Color Matching: MacAdam step 3

Temperature and life time Technical Data

LED Lifetime:	L80 B10 70.000h Ta 25°C L80 B10 50.000h Ta 40°C
Lifespan of the LUMINAIRE:	min. 70.000h Ta 25°C min. 50.000h Ta 40°C
Performance ambient temperature:	Tq 25°C
Operating ambient temperature range:	da -20°C a +50°C
Storage temperature range:	da -20°C a +60°C

Power Supply Technical Data


Voltage (AC):	220-240Vac
Voltage (DC):	170-276Vdc (No PUSH DIM)
Dimmable:	DALI2; PUSH PUSH Synchronization: - Max 4 Luminaires, distance <15m; - Max 35 Luminaires, distance <300m with S.2490 accessory.

Technical Installation Data

Electrical insulation class:	II
Protection class IP:	IP66
Mechanical resistance:	IK10
Weight:	31.12Kg
Power cable:	0.2m - H05RN-F

WARRANTY

All Simes products are covered by an extended 5-year warranty. For terms and conditions, see www.simes.it/warranty

SHIFT PRO ROTOSYMMETRIC
S.1470N.24 (Anthracite grey)**SPECS SHEET****LUMINAIRE TYPE**

Bollard fitting / Urban luminaire. IP rating IP 66

MATERIAL CHARACTERISTICS

Aluminium die cast housing in EN AB-44300 (low copper content) and extruded EN AW-6060 with high resistance against corrosion. Stone wash surface treatment prior to painting process. Steel Allen screws with insulating treatment against galvanic corrosion. Pre treated Silicone Gaskets. **Extra-resistant**

Painting Process:

Extra-resistant exterior coating. Product suitable for applications in high-humidity environments, C5 ZONE (according to UNI EN ISO 9223:2012).

Mechanical resistance IK 10

LIGHTING PERFORMANCE

The rotosymmetric version of Shift Pro distributes broad, uniform light around the pole. The 360° and 180° heads, with their special optics integrated into the cylindrical design, ensure visual comfort, high performance, and downward-directed emission in compliance with light pollution regulations.

INSTALLATION AND MAINTENANCE

Shift Pro enables the creation of multifunction configurations by combining the available heads: spotlight, IP65 passive acoustic speaker, IP67 security camera, housing-ready head for an external camera, terminal head prepared for a Wi-Fi access point, or blank head for product height alignment. The rotosymmetric heads can be used individually in combination with three pole heights: 500 mm (S.1483), 3000 mm (S.1484/S.1485), or 4000 mm (S.1486/S.1487). Triple heads are recommended for 3000 mm or 4000 mm poles. This modularity makes it ideal for lighting, security, and smart management of urban public spaces, shopping centers, and private environments.

WIRING

Supply 0.2m cable section type H05RN-F . Single cable entry sealed with B component epoxy resin, wired internally. Isolation: CLASS II . Available colours: Black (cod.09), Anthracite grey (cod.24). Weight: 31.12 Kg Glow Wire test: 850°C

LED module included**SHIFT PRO PATENTED and REGISTERED DESIGN**

This luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user.

This product contains a light source of energy efficiency class (EPREL - European Product Registry for Energy Labelling): E.

LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 Ta 25 ° C (50,000 hours referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 70.000 hours Ta 25°C, min. 50,000 hours at 40°C. Performance Ambient temperature Tq 25°C. Operating ambient temperature range is from -20°C to +50°C. Storage temperature range from -20°C to +60°C.

ELECTRONIC EQUIPMENT SENSITIVE TO OVERVOLTAGE.


We recommend installing surge protection devices "SPD" in the electrical system. Protection devices prevent the intensity of these phenomena's, protecting the appliances from the risk of being damaged and extending the lifespan. Outdoor luminaires are subject to all types of permanent, temporary, or transient electrical disturbances. Such disturbances can create permanent damage or failure affecting its performance and durability. The surge protection device (supplied by SIMES) is utilized to limit the destructive effect of these phenomena. We suggest that each luminaire must be connected to one protection device at not more than 10m away. For correct coordination of the protections, a surge protection device must also be provided inside the electrical panel of the system (the selection of this device must be carried out from the electrical designer and is not supplied by SIMES).

WARRANTY

All items produced from 01/01/2026 onwards are covered by a 5 (five)-year warranty against manufacturing and conformity defects, in accordance with the terms and limits set out in the manufacturer's official documentation. For full details, exclusions and warranty activation procedures, please refer to the following link: www.simes.it/warranty

SHIFT PRO ROTOSYMMETRIC

S.1470N.24 (Anthracite grey)



ACCESSORIES



S.1479

CAP DESIGNED TO HOUSE THE IOT READY ZHAGA SENSOR

The cap, supplied by SIMES, allows integration of IoTready Zhaga sensors available on the market with a Zhaga interface. Note: The cap for the IOT READY ZHAGA sensor can be installed on all heads except for the head prepared for Wi-Fi Access Point.



S.1497

SHIFT PRO IP65 DOOR WITH IT/DE 2P+T 16A ELECTRICAL PLUG
IP65 port and integrated IT/DE 2P+T 16A electrical socket for powering outdoor electronic devices. Class I, IK06, Wmax 3500W Available upon request with European electrical sockets.



S.2499

SURGE PROTECTION DEVICE 10kV CLASS II

Compatible with all lighting fixtures and electronic ballast accessories classified under electrical Protection Class II Rated voltage 230-277V SPD type 2+3 Max Surge Protection 10kV IP67
EACH FIXTURE MUST BE CONNECTED TO ONE SINGLE SURGE PROTECTION DEVICE AT A DISTANCE OF NO MORE THAN 10m AWAY.



S.2899

POLE BASE COVER


For pole with base and pole to be buried Ø150mm. Die-cast aluminium housing.



S.2898

FLANGE

Ø 150 mm h 180mm flange to be fixed in concrete with steel screws treated with an advanced anticorrosive coating for fixing in the ground.



S.1483

H 0,5m Ø150mm CYLINDRICAL POLE WITH BASE

Cylindrical shaped poles consisting of: straight circular section shaft, Ø 150mm, 3mm in thickness, total length 0,50m ,in aluminium EN AW6060.

Suitable for installation to a planted root flange through a base plate 250mm x250mm x12mm in steel S355JO : Suggested reinforced concrete footstall dimension 1m x 1m h 0,7m. Footstall dimension can be calculated according to your country norms and ground properties.


The surface protection treatment is done through hot dip galvanization.

Painting Process: PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1500h.

Note: With the H.500 mm pole, up to 2 Heads can be installed; it is not possible to install the Shift Pro rotosymmetric Triple Head.

WE RECOMMEND THE USE OF THE FOLLOWING ACCESSORIES
:

S.2898 PLANTED ROOT FOR CYLINDRICAL POLE
S.2899 POLE BASE COVER



S.1484

H 3,0m Ø150mm CYLINDRICAL POLE WITH BASE

Cylindrical shaped poles consisting of: straight circular section shaft, Ø 150mm, 3mm in thickness, total length 3,00m , single section built by using longitudinally welded tubes by induction welding (ERW) UNI EN 10219-2-ISO 4200

Suitable for installation to a planted root flange through a base plate 300mm x 300mm x12mm in steel S355JO : Suggested reinforced concrete footstall dimension 1m x 1m h 0,7m. Footstall dimension can be calculated according to your country norms and ground properties.

The grade of steel used is S235JR (Fe360B) with material characteristics as per normative UNI EN 10025;

The surface protection treatment is done through hot dip galvanization.

Painting Process: PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1500h.


Note: With the H.3000 mm pole, up to 5 additional Heads can be installed. It is possible to install the Shift Pro rotosymmetric Triple Head. In this case, up to 4 Heads can be installed.

WE RECOMMEND THE USE OF THE FOLLOWING ACCESSORIES
:


S.2899 POLE BASE COVER

Next ...

SHIFT PRO ROTOSYMMETRIC S.1470N.24 (Anthracite grey)



ACCESSORIES



S.1485
H 3,0m Ø150mm CYLINDRICAL POLE WITH BASE

Cylindrical shaped poles consisting of: straight circular section shaft, Ø 150mm, 3mm in thickness, total length 3,60m , single section built by using longitudinally welded tubes by induction welding (ERW) UNI EN 10219-2-ISO 4200

Suitable for ground recessed installation to a cement base 0,60m:
Suggested reinforced concrete footstall dimension 1,0m x 1,0m h 1,0m.
Footstall dimension can be calculated according to your country norms and ground properties.

The grade of steel used is S235JR (Fe360B) with material characteristics as per normative UNI EN 10025;


The surface protection treatment is done through hot dip galvanization.

Painting Process: PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content.
POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions.
Resistance test protection for Marine applications for 1500h.

Note: With the H.3000 mm pole, up to 5 additional Heads can be installed. It is possible to install the Shift Pro rotosymmetric Triple Head. In this case, up to 4 Heads can be installed.

WE RECOMMEND THE USE OF THE FOLLOWING ACCESSORIES

S.2009 PLANTED ROOT for CYLINDRICAL POLE
S.2899 POLE BASE COVER



S.1486
H 4,0m Ø150mm CYLINDRICAL POLE WITH BASE

Cylindrical shaped poles consisting of: straight circular section shaft, Ø 150mm, 3mm in thickness, total length 4,00m , single section built by using longitudinally welded tubes by induction welding (ERW) UNI EN 10219-2-ISO 4200

Suitable for installation to a planted root flange through a base plate 300mm x300mm x12mm in steel S355JO : Suggested reinforced concrete footstall dimension 1m x 1m h 0,7m. Footstall dimension can be calculated according to your country norms and ground properties.

The grade of steel used is S235JR (Fe360B) with material characteristics as per normative UNI EN 10025;

The surface protection treatment is done through hot dip galvanization.

Painting Process: PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content.
POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions.
Resistance test protection for Marine applications for 1500h.


Note: With the H.4000 mm pole, up to 5 additional Heads can be installed. It is possible to install the Shift Pro rotosymmetric Triple Head. In this case, up to 4 Heads can be installed.

WE RECOMMEND THE USE OF THE FOLLOWING ACCESSORIES


S.2899 POLE BASE COVER

SHIFT PRO ROTOSYMMETRIC S.1470N.24 (Anthracite grey)

Next



ACCESSORIES



S.1487 H 4,0m Ø150mm CYLINDRICAL POLE WITH BASE

Cylindrical shaped poles consisting of: straight circular section shaft, Ø 150mm, 3mm in thickness, total length 4,80m , single section built by using longitudinally welded tubes by induction welding (ERW) UNI EN 10219-2-ISO 4200

Suitable for ground recessed installation to a cement base 0,80m:
Suggested reinforced concrete footstall dimension 1,0m x 1,0m h 1,0m.
Footstall dimension can be calculated according to your country norms and ground properties.

The grade of steel used is S235JR (Fe360B) with material characteristics as per normative UNI EN 10025;

The surface protection treatment is done through hot dip galvanization.

Painting Process: PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1500h.

Note: With the H.4000 mm pole, up to 5 additional Heads can be installed. It is possible to install the Shift Pro rotosymmetric Triple Head. In this case, up to 4 Heads can be installed.

WE RECOMMEND THE USE OF THE FOLLOWING ACCESSORIES :

S.2009 PLANTED ROOT for CYLINDRICAL POLE
S.2899 POLE BASE COVER



**S.2492
IP20 Interface Virtual Midnight/Bilevel (Step-Dimming)**
This device is designed to maximize energy savings in various lighting applications. The devices can operate in two modes and are compatible exclusively with Simes DALI lighting fixtures: 1. Virtual Midnight: This system is designed for public outdoor lighting, enabling the automatic reduction of light output during periods when full-power operation is unnecessary. Configuring the system is straightforward, as programming is done via rotary selectors built into the device. 2. Bilevel (Step-Dimming): The two-level dimming system is commonly used in urban and street lighting, as well as in industrial facilities, emergency stairwells, parking lots, and other similar applications. The Bilevel function allows for adjusting the light intensity between two levels, using controls such as a relay, a twilight switch paired with a timer, or a motion sensor. The lighting level can be increased or decreased through simple programming using the rotary selectors built into the device. Dimensions 60mm x33mm x15mm
It can manage a maximum of 7 DALI luminaires/devices. Possibility to extend up to max. 64 luminaires through the DALI Expander (S.2494).



**S.2493
IP67 Interface Virtual Midnight/Bilevel (Step-Dimming)**
This device is designed to maximize energy savings in various lighting applications. The devices can operate in two modes and are compatible exclusively with Simes DALI lighting fixtures: 1. Virtual Midnight: This system is designed for public outdoor lighting, enabling the automatic reduction of light output during periods when full-power operation is unnecessary. Configuring the system is straightforward, as programming is done via rotary selectors built into the device. 2. Bilevel (Step-Dimming): The two-level dimming system is commonly used in urban and street lighting, as well as in industrial facilities, emergency stairwells, parking lots, and other similar applications. The Bilevel function allows for adjusting the light intensity between two levels, using controls such as a relay, a twilight switch paired with a timer, or a motion sensor. The lighting level can be increased or decreased through simple programming using the rotary selectors built into the device. Dimensions 175.5mm x86.5mm x43mm
It can manage a maximum of 7 DALI luminaires/devices. Possibility to extend up to max. 64 luminaires through the DALI Expander (S.2494).



**S.2494
DALI EXPANDER**
The IP20 DINrail device is used to extend a DALI circuit via broadcast. The received input signal is amplified and transmitted in broadcast to the DALI luminaires / DALI control gears. The DALI Expander has an integrated DALI bus power supply (200mA) which can control up to a maximum of 64 DALI devices within 300 meters.