




BELL SUSPENSION



h(m)	84° Ø(m)	3000K E(lx)
1	1.79	625
2	3.58	156
3	5.36	69
4	7.15	39
5	8.94	25

*Photometric measured using WHITE LED 3000K

Version available on request without price surcharge.

S.8030H.01 (White)module LED 2700K 220-240Vac **DIMMABLE PHASE-CUT (R-C)**

Ceiling surface mounted

**DARK SKY
FRIENDLY****Light Source Technical Data**

Light source type:	LED
Colour temperature:	2700K
Rated module luminous flux:	2300lm
Rated luminaire luminous flux:	1025lm
Rated module power:	17.7W
Rated luminaire power:	20.4W
Luminaire efficacy:	50lm/W
ULR:	0%
BUG:	B1 - U0 - G0
CIE Flux Code:	69 96 100 100 100
Color Rendering Index:	CRI 90
Standard Deviation Color Matching:	MacAdam step 3

Power Supply Technical Data

Voltage (AC):	220-240Vac
Frequency (AC):	50/60Hz
Dimmable:	PHASE-CUT (R-C)
Inrush Current:	13A 30µsec
Max. quantity of fixtures for Minature Circuit Breaker type B16A:	92
Max. quantity of fixtures for Minature Circuit Breaker type C16A:	156
Surge protection (between L-N):	1kV

Temperature and life time Technical Data

LED Lifetime:	L80 B10 70.000h Ta 25°C L80 B10 50.000h Ta 40°C
Lifespan of the LUMINAIRE:	min. 70.000h Ta 25°C min. 50.000h Ta 40°C
Performance ambient temperature:	Tq 25°C
Operating ambient temperature range:	da -20°C a +50°C
Storage temperature range:	da -20°C a +60°C

Technical Installation Data

Electrical insulation class:	I
Protection class IP:	IP65
Mechanical resistance:	IK06
Weight:	1.9321Kg
Power cable:	4m - H05RN-F

WARRANTY

All Simes products are covered by an extended 5-year warranty. For terms and conditions, see www.simes.it/warranty

SPECIAL VERSION ON REQUEST: this Luminaires can be supplied with a surcharge in class III (without power supply). Requires working remote power supply in constant current at 500mA V_{fmin}=33.6Vdc V_{fmax}=39.6Vdc. Example SIMES compatible power supplies (check the complete list of the drivers on the catalogue):

Art. S.2418 POWER SUPPLY DALI2 / PUSH MULTI-POWER 230V/700mA-1050mA IP20

Art. S.2444 POWER SUPPLY MULTI-POWER 230V/700mA-1050mA DALI2, PUSH DIM IN BOX IP67 35W

NB: Use 1 Power Supply for each Luminaires

S.8030H.01 REV: 0

BELL SUSPENSION
S.8030H.01 (White)**SPECS SHEET****LUMINAIRE TYPE**

Down-light luminaire. IP rating IP 65

MATERIAL CHARACTERISTICS

Decorative elements and reflector in solid bronze are treated with a transparent protective layer that maintains the color and ensures quality and durability. Die-cast EN AB-47100 aluminium housing with high corrosion resistance. Stone wash surface treatment prior to painting process. Steel screws treated with an advanced anticorrosive coating. Silicone Gaskets.

Extra-resistant Painting Process:

Extra-resistant exterior coating. Product suitable for applications in high-humidity environments, C5 ZONE (according to UNI EN ISO 9223:2012).

Mechanical resistance IK 06

LIGHTING PERFORMANCE

Glass diffuser 5mm thick acid-etched. LOR --

CONTROL AND LIGHT MANAGEMENT

Check the compatibility with the Trailing Edge dimmers chosen (adjust the minimum level using the trimmer to avoid lamp flickering).

Costruttore Modello Controllo

Casambi CBU-TED-C-526 Bluetooth

Dalcnec DAC230-1CH Push

Tecnel TE7636 Push

Cloud Even QS-BLE-DO2-TRIAC Push/Wi-Fi/Bluetooth

WIRING

Supply 4m cable section type H05RN-F. Isolation: CLASS I. Available colours: White (cod.01), Burnished bronze (cod.20). Weight: 1.9321 Kg Glow Wire test: 850°C

LED module included

BELL REGISTERED DESIGN

This luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user.

This product contains a light source of energy efficiency class (EPREL - European Product Registry for Energy Labelling): E.

LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 Ta 25 ° C (50,000 hours referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 70.000 hours Ta 25°C, min. 50,000 hours at 40°C. Performance Ambient temperature Tq 25°C. Operating ambient temperature range is from -20°C to +50°C. Storage temperature range from -20°C to +60°C.

DARK SKY FRIENDLY

This luminaire is designed according to the principles of light pollution reduction: zero light emission above 90°, color temperature 2700K/3000K, and full shielding. It is not a DarkSky Approved certified product, but it complies with the main criteria of the International Dark-Sky Association (IDA).

ELECTRONIC EQUIPMENT SENSITIVE TO OVERVOLTAGE.

We recommend installing surge protection devices "SPD" in the electrical system. Protection devices prevent the intensity of these phenomena's, protecting the appliances from the risk of being damaged and extending the lifespan. Outdoor luminaires are subject to all types of permanent, temporary, or transient electrical disturbances. Such disturbances can create permanent damage or failure affecting its performance and durability. The surge protection device (supplied by SIMES) is utilized to limit the destructive effect of these phenomena. We suggest that each luminaire must be connected to one protection device at not more than 10m away. For correct coordination of the protections, a surge protection device must also be provided inside the electrical panel of the system (the selection of this device must be carried out from the electrical designer and is not supplied by SIMES).

WARRANTY

All items produced from 01/01/2026 onwards are covered by a 5 (five)-year warranty against manufacturing and conformity defects, in accordance with the terms and limits set out in the manufacturer's official documentation. For full details, exclusions and warranty activation procedures, please refer to the following link: www.simes.it/warranty

BELL SUSPENSION**S.8030H.01 (White)****ACCESSORIES****S.2498****SURGE PROTECTION DEVICE 10kV CLASS I**

Compatible with all lighting fixtures classified under electrical Protection Class I Rated voltage 230-277V SPD type 2+3 Max Surge Protection 10kV IP67

EACH FIXTURE MUST BE CONNECTED TO ONE SINGLE SURGE PROTECTION DEVICE AT A DISTANCE OF NO MORE THAN 10m AWAY.

**S.2491****Signal converter Input DALI Output PHASE CUT**

Monochannel Dimmers with Output phase cut. - Input Range: 80-230V AC 50/60Hz. - Max resistive load 1A. *For Electronic and/or LED

Electronic loads consider the maximum half power compared to the nominal value. Example: 220V AC 110W Max. Do not connect inductive loads. Do not connect UPS with output different from Pure Sine Wave. -

The device is not equipped with earth connection Protection against accidental contact with live parts is guaranteed by the enclosure. - Cross-section of conductors 14-22 AWG (0.205-2.08 mmq). - Input Controls: DALI x1. - Printed Circuit UL. - Protection Class: IP20. - Standard

Dimension 40x80x24.45 mm. - Dimension with accessories 40x100x24.45 mm. - Surge voltage protection. - Over current protection. -

Use only in dry conditions IP20 Dimensions 40mm x 80mm x 24mm