

Space

Immense versatility - the go-to linear system for ambient lighting applications

Product Code: SPC-035-SUW-RGBA-1400-O-ANO




The most versatile linear offering from Digilin, Space linear systems are the go-to option for general ambient lighting and other specialist applications that require high-lumen outputs for entire rooms and other larger spaces.

Space linear systems are comprised of profiles with core body widths of 35mm, 50mm, 75mm or 100mm, all available either as surface mount, recessed or suspended, combined with any of Digilin’s constant voltage LED options, including fixed white (800-8800lm per metre), tuneable white, RGB, RGBW, backstage (blue/white) and Sunlike growlights.

All Digilin linear systems are manufactured in Australia to custom project lengths and supplied with factory-fitted connectors using Digilin’s chemical anchoring process for super durability and ease of installation.

super durability and ease of installation.

LED Colour	RGBA				
CCT/Wavelength	Red (625nm)	Green (530nm)	Blue (470nm)	Amber	Combined
LED Lumens	70lm/m	460lm/m	100lm/m	860lm/m	1490lm/m
Power	6.8W/m	6.8W/m	6.8W/m	16.8W/m	37W/m
Input Current	280mA/m	280mA/m	280mA/m	700mA/m	1540mA/m
Input Voltage	24VDC				
Typical CRI	N/A				
LED Performance	L70 (6k) >36,000hrs				
LED Configuration	Dual RGBA 700lm LED				
LED Module Increment	100mm				
LED Spacing	16.7mm				
Maximum Continuous Run	7m (Single Feed), 14mm (Dual Feed)				
Body Width	35mm				
Mounting	Suspended (Wire)				
Beam Option	Opal Diffuser				
Finish Colour	Natural Anodised Aluminium				
Control	Mains/Phase, DALI, Smooth DALI, DMX, Bluetooth, Non-Dim				
Driver Placement	Remote, Integral				
Build Material	Extruded Aluminium				
Luminaire IP Rating	IP20				
LED Module IP Rating	IP20 (IP44 & IP65 available)				
Dimensions - 35mm version	35mm (width), 50mm (recessed flange width), 35mm (height)				
Dimensions - 50mm version	50mm (width), 68mm (recessed flange width), 75mm (height)				
Dimensions - 75mm version	75mm (width), 95mm (recessed flange width), 75mm (height)				
Dimensions - 100mm version	100mm (width), 122mm (recessed flange width), 75mm (height)				



Specifications are subject to change without notice