

PAPER TITLE TO BE DEFINED (in common.yaml)

1-bulkRNAseq: refilled lung IMs

2021-12-02 10:35:12 +0100

Abstract

Lung interstitium macrophages (IMs) are non-alveolar resident tissue macrophages which contribute to the lung homeostasis. These cells were reported to be heterogeneous by our group and other teams, which contains two main distinct subpopulations: CD206+ IMs and CD206- IMs. However, the exact origin of IMs and the transcriptional programs that control IM differentiation remains unclear. In recent report, we analyzed the refilled IMs in the course of time after induced IM depletion with single-cell RNA sequencing (10X Genomics Chromium) and bulk RNA sequencing.

Contents

1	Description	2
2	Counting from fastq data using nf-core/rnaseq pipeline	2
3	Counts data processing	2
4	Make metadata for bulkRNAseq samples	4
5	DESeq2 analysis	5
5.1	Perform rlog transformation for distances and PCA	5
5.2	Heatmap	5
5.3	PCA analysis	6
5.4	Differentially expressed (DE) genes in comparing refilled vs control IMs	9
5.5	Differentially expressed (DE) genes in comparing refilled vs control CD206+ IMs	10
5.6	Differentially expressed (DE) genes in comparing refilled vs control CD206- IMs	10
6	Export DE genes for other analyses	11
7	Presentation of DE genes in volcano plots	12
7.1	Refilled vs control IMs	12
7.2	Refilled vs control CD206+ IMs	14
7.3	Refilled vs control CD206- IMs	15
7.4	Plot the top DE genes	17
8	Session information	20
	References	22

1 Description

Lung interstitium macrophages (IMs) are non-alveolar resident tissue macrophages which contribute to the lung homeostasis. These cells were reported to be heterogeneous by our group and other teams, which contains two main distinct subpopulations: CD206+ IMs and CD206- IMs. However, the exact origin of IMs and the transcriptional programs that regulate IM differentiation remains unclear. In recent report, we analyzed the refilled IMs in the course of time after induced IM depletion with single-cell RNA sequencing (10X Genomics Chromium) and bulk RNA sequencing.

In this study, the de novo refilled CD206+ and CD206- IMs on Day 14 post-depletion were compared to those without depletion. Alveolar macrophages (AMs) samples were also included in this analysis and served as a reference. Results showed high similarity between de novo refilled and original IMs for both CD206+ and CD206- subsets. Only genes related to cell cycling were found upregulated in de novo refilled IMs.

Total RNA was extracted and concentrated from the different samples with the RNA Clean & Concentrator 5 (Zymo Research). Possible DNA contaminant were removed with DNase I. RNA quality and quantity were evaluated using a 2100 bioanalyzer (Agilent) and the Quant-iT™ RiboGreen™ RNA Assay Kit (ThermoFisher). The RNA Integrity Number (RIN) was greater than 7 for all samples. In order to generate the libraries using the Truseq stranded mRNA kit (Illumina), 100 ng of RNA was used. These libraries were sequenced on an Illumina Novaseq sequencer on a SP flow cell. Sequence alignment with the mouse genome (version GRCm38), sequence counting and quality control were performed using the nf-core/rnaseq pipeline.¹ RNA-seq data were analyzed using R Bioconductor (3.12) and DESeq2 package (version 1.26.0)².

2 Counting from fastq data using nf-core/rnaseq pipeline

The following codes were used to do the mapping and counting.

```
nextflow run nf-core/rnaseq --input sample_list.csv --fasta GRCm38/fasta/
genome.fa --gtf GRCm38/genes/genes.gtf --outdir counts/bulkRNAseq/ -
profile docker
```

sample_list.csv is text file with 5 columns: group, replicate, fastq_1, fastq_2 and strandedness. Prepared following to the software's instructions.

3 Counts data processing

```
library(DESeq2)
library(ggplot2)
library(pheatmap)
library(RColorBrewer)
library(EnhancedVolcano)
library(forcats)

COUNTS <- read.table("./salmon.merged.gene_counts.csv", sep = "\t", header
= T, row.names = NULL)

dim(COUNTS)

## [1] 22597 19
```

Make gene names as rownames:

```
Genes <- COUNTS$gene_id
rownames(COUNTS) = make.names(Genes, unique = TRUE)
```

```
COUNTS <- COUNTS[, -1]
COUNTS <- round(COUNTS, digits = 0)
head(COUNTS, 3)
```

```
## # A tibble: 3 x 18
##   AM.WT_R1 AM.WT_R2 AM.WT_R3 CD206neg.IM.CRE_~ CD206neg.IM.CRE~
##   CD206neg.IM.CRE~
##   <dbl> <dbl> <dbl> <dbl> <dbl>
##   <dbl>
## 1 3868 4493 4063 1944 1882
##   2059
## 2 0 0 0 0 0
##   0
## 3 123 156 147 30 54
##   82
## # ... with 12 more variables: CD206neg.IM.WT_R1 <dbl>, CD206neg.IM.
##   WT_R2 <dbl>,
##   CD206neg.IM.WT_R3 <dbl>, CD206pos.IM.CRE_R1 <dbl>,
##   CD206pos.IM.CRE_R2 <dbl>, CD206pos.IM.CRE_R3 <dbl>,
##   CD206pos.IM.WT_R1 <dbl>, CD206pos.IM.WT_R2 <dbl>, CD206pos.IM.WT_R3
##   <dbl>,
##   Ly6Cpos.Mo.WT_R1 <dbl>, Ly6Cpos.Mo.WT_R2 <dbl>, Ly6Cpos.Mo.WT_R3 <
##   dbl>
```

```
library(org.Mm.eg.db)
symbols <- mapIds(org.Mm.eg.db, keys = rownames(COUNTS), keytype = "
  ENSEMBL", column = "SYMBOL")
symbols.uniq <- na.omit(unique(symbols))

# remove adundant ensembl ids:
COUNTS <- COUNTS[match(symbols.uniq, symbols), ]

# use symbols as rownames:
rownames(COUNTS) <- symbols.uniq

head(COUNTS)
```

```
## # A tibble: 6 x 18
##   AM.WT_R1 AM.WT_R2 AM.WT_R3 CD206neg.IM.CRE_~ CD206neg.IM.CRE~
##   CD206neg.IM.CRE~
##   <dbl> <dbl> <dbl> <dbl> <dbl>
##   <dbl>
## 1 3868 4493 4063 1944 1882
##   2059
## 2 0 0 0 0 0
##   0
## 3 123 156 147 30 54
##   82
## 4 0 3 0 43 20
##   16
## 5 5 10 0 0 0
##   0
```

```
## 6      270      373      213      168      266      294
## # ... with 12 more variables: CD206neg.IM.WT_R1 <dbl>, CD206neg.IM.
## #   WT_R2 <dbl>,
## #   CD206neg.IM.WT_R3 <dbl>, CD206pos.IM.CRE_R1 <dbl>,
## #   CD206pos.IM.CRE_R2 <dbl>, CD206pos.IM.CRE_R3 <dbl>,
## #   CD206pos.IM.WT_R1 <dbl>, CD206pos.IM.WT_R2 <dbl>, CD206pos.IM.WT_R3
## #   <dbl>,
## #   Ly6Cpos.Mo.WT_R1 <dbl>, Ly6Cpos.Mo.WT_R2 <dbl>, Ly6Cpos.Mo.WT_R3 <
## #   dbl>
```

4 Make metadata for bulkRNAseq samples

```
SampleSheet <- data.frame(groupName = rep(c("AM", "CD206- refilled IM", "
CD206- control IM",
"CD206+ refilled IM", "CD206+ control IM", "Ly6C+ Mo"), each = 3),
cellType1 = c(rep("Mac",
15), rep("Mo", 3)), cellType2 = c(rep("AM", 3), rep("IM", 12), rep("Mo
", 3)),
cellType3 = rep(c("AM", "CD206neg IM", "CD206neg IM", "CD206pos IM", "
CD206pos IM",
"Ly6Cpos Mo"), each = 3), treatment = c(rep(rep(c("control", "
refilled"),
each = 3), 2), rep("control", 6)))
rownames(SampleSheet) <- colnames(COUNTS)

SampleSheet
```

```
## # A tibble: 18 x 5
##   groupName      cellType1 cellType2 cellType3 treatment
##   <chr>          <chr>      <chr>      <chr>      <chr>
## 1 AM            Mac        AM        AM        control
## 2 AM            Mac        AM        AM        control
## 3 AM            Mac        AM        AM        control
## 4 CD206- refilled IM Mac        IM        CD206neg IM refilled
## 5 CD206- refilled IM Mac        IM        CD206neg IM refilled
## 6 CD206- refilled IM Mac        IM        CD206neg IM refilled
## 7 CD206- control IM Mac        IM        CD206neg IM control
## 8 CD206- control IM Mac        IM        CD206neg IM control
## 9 CD206- control IM Mac        IM        CD206neg IM control
## 10 CD206+ refilled IM Mac        IM        CD206pos IM refilled
## 11 CD206+ refilled IM Mac        IM        CD206pos IM refilled
## 12 CD206+ refilled IM Mac        IM        CD206pos IM refilled
## 13 CD206+ control IM Mac        IM        CD206pos IM control
## 14 CD206+ control IM Mac        IM        CD206pos IM control
## 15 CD206+ control IM Mac        IM        CD206pos IM control
## 16 Ly6C+ Mo      Mo        Mo        Ly6Cpos Mo control
## 17 Ly6C+ Mo      Mo        Mo        Ly6Cpos Mo control
## 18 Ly6C+ Mo      Mo        Mo        Ly6Cpos Mo control
```

```
write.csv(SampleSheet, file = "../SampleSheet_metadata.csv")
```

5 DESeq2 analysis

```
dds <- DESeqDataSetFromMatrix(countData = COUNTS, colData = SampleSheet,
  design = ~cellType3 +
    treatment)
dds
```

```
## class: DESeqDataSet
## dim: 21616 18
## metadata(1): version
## assays(1): counts
## rownames(21616): Gnai3 Pbsn ... Btbd35f19 Cldn34c3
## rowData names(0):
## colnames(18): AM.WT_R1 AM.WT_R2 ... Ly6Cpos.Mo.WT_R2 Ly6Cpos.Mo.WT_R3
## colData names(5): groupName cellType1 cellType2 cellType3 treatment
```

5.1 Perform rlog transformation for distances and PCA

```
# keep only genes with more than a single read
dds <- dds[rowSums(counts(dds)) > 1, ]

# perform rlog transformation for distances (for clustering) and PCA
rld <- rlog(dds)
```

```
dds <- dds[rowSums(counts(dds)) > 1, ]
nrow(dds)
```


```
## [1] 16677
```

Calculate sample-to-sample distances

```
sampleDists <- dist(t(assay(rld)))
sampleDistMatrix <- as.matrix(sampleDists)
```

5.2 Heatmap

```
colors <- colorRampPalette(rev(brewer.pal(ncol(COUNTS), "Blues")))(255)
heatmap <- pheatmap(sampleDistMatrix, clustering_distance_rows =
  sampleDists, clustering_distance_cols = sampleDists,
  col = colors)
```



5.3 PCA analysis

Calculate PCs:

```
PlotData <- plotPCA(rld, intgroup = c("cellType3", "treatment"),
  returnData = TRUE)
```

Construct plot:


```
percentVar<-round(100 * attr(PlotData, "percentVar"))

ggplot(PlotData,aes(PC1,PC2)) +
  geom_point(size=3, aes(color = cellType3, shape = treatment)) +
  xlab(paste0("PC1: ", percentVar[1], "% variance")) +
  ylab(paste0("PC2: ", percentVar[2], "% variance")) +
```

```

scale_color_manual(
  breaks = c( "CD206neg_IM",
              "CD206pos_IM",
              "AM",
              "Ly6Cpos_Mo"),
  values = c(
              "#B2DF8A", # CD206 -
              "#33A02C", # CD206+
              "#FF7F00", # AM
              "#A6CEE3" # Cla mo
            )) +
scale_shape_manual(
  breaks = c(
    "control",
    "refilled"
  ),
  values=c(
    16, #"CD206neg IM:control",
    1 #"CD206neg IM:refilled",
  ))+
theme(
  aspect.ratio=1,
  panel.background = element_rect(fill = "white", colour = "grey50"),
  axis.text=element_text(size=7),
  axis.title=element_text(size=7,face="bold"),
  legend.key = element_blank(),
  legend.text = element_text(size=7),
  legend.title = element_text(size = 7),
)

```



AM, IM and monocytes are grouped together. The refilled/control IMs are highly similar.

Redo PCA with only IMs:


```

rld.im <- rld[, SampleSheet$cellType2 == "IM"]
sampleDists.im <- dist(t(assay(rld.im)))
sampleDistMatrix.im <- as.matrix(sampleDists.im)


```

Heatmap

```
heatmap <- pheatmap(sampleDistMatrix.im, clustering_distance_rows = 1
  sampleDists.im,
  clustering_distance_cols = sampleDists.im, col = colors) 2
```



```
plotPCA(rld.im, intgroup = c("cellType3", "treatment")) 1
```

Nearly no difference could be found between refilled and control IM in any subset.

5.4 Differentially expressed (DE) genes in comparing refilled vs control IMs

```
# redo with only IM samples:
dds.im <- DESeqDataSetFromMatrix(countData = COUNTS[, SampleSheet$
  cellType2 == "IM"],
  colData = SampleSheet[SampleSheet$cellType2 == "IM", ], design = ~
  cellType3 +
  treatment)
dds.im <- dds.im[rowSums(counts(dds.im)) > 1, ]

dds.im <- DESeq(dds.im)
resultsNames(dds.im)
```

```
## [1] "Intercept"
## [2] "cellType3_CD206pos.IM_vs_CD206neg.IM"
## [3] "treatment_refilled_vs_control"
```

```
res_refilled_vs_control <- results(dds.im, contrast = c("treatment", "
  refilled",
  "control"))
summary(res_refilled_vs_control)
```

```
##
## out of 16424 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up)      : 831, 5.1%
## LFC < 0 (down)    : 900, 5.5%
## outliers [1]      : 59, 0.36%
## low counts [2]     : 1902, 12%
## (mean count < 2)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

```
res_refilled_vs_control_Shrunk <- lfcShrink(dds.im, contrast = c("
  treatment", "refilled",
  "control"), res = res_refilled_vs_control, type = "normal")

refilled_vs_control <- merge(x = as.data.frame(res_refilled_vs_control), y
  = as.data.frame(res_refilled_vs_control_Shrunk),
  by = c(0, 1))
```

5.5 Differentially expressed (DE) genes in comparing refilled vs control CD206+ IMs

```
# redo with only CD206+ samples:
dds.cd206pos.im <- DESeqDataSetFromMatrix(countData = COUNTS[, SampleSheet
  $cellType3 ==
    "CD206pos□IM"], colData = SampleSheet[SampleSheet$cellType3 == "
      CD206pos□IM",
    ], design = ~treatment)
dds.cd206pos.im <- dds.cd206pos.im[rowSums(counts(dds.cd206pos.im)) > 1, ]

dds.cd206pos.im <- DESeq(dds.cd206pos.im)
resultsNames(dds.cd206pos.im)
```

```
## [1] "Intercept" "treatment_refilled_vs_control"
```

```
res_refilled_vs_control_CD206pos <- results(dds.cd206pos.im, contrast = c(
  "treatment",
  "refilled", "control"))
summary(res_refilled_vs_control_CD206pos)
```

```
##
## out of 15463 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up) : 170, 1.1%
## LFC < 0 (down) : 306, 2%
## outliers [1] : 2, 0.013%
## low counts [2] : 1499, 9.7%
## (mean count < 2)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

```
res_refilled_vs_control_CD206pos_Shrunk <- lfcShrink(dds.cd206pos.im,
  contrast = c("treatment",
    "refilled", "control"), res = res_refilled_vs_control_CD206pos, type =
    "normal")

refilled_vs_control_CD206pos <- merge(x = as.data.frame(res_refilled_vs_
  control_CD206pos),
  y = as.data.frame(res_refilled_vs_control_CD206pos_Shrunk), by = c(0,
    1))
```

5.6 Differentially expressed (DE) genes in comparing refilled vs control CD206- IMs

```
# redo with only CD206- samples:
dds.CD206neg.im <- DESeqDataSetFromMatrix(countData = COUNTS[, SampleSheet
  $cellType3 ==
    "CD206neg□IM"], colData = SampleSheet[SampleSheet$cellType3 == "
      CD206neg□IM",
    ], design = ~treatment)
dds.CD206neg.im <- dds.CD206neg.im[rowSums(counts(dds.CD206neg.im)) > 1, ]
```

```
dds.CD206neg.im <- DESeq(dds.CD206neg.im)
resultsNames(dds.CD206neg.im)
```

```
## [1] "Intercept" "treatment_refilled_vs_control"
```

```
res_refilled_vs_control_CD206neg <- results(dds.CD206neg.im, contrast = c(
  "treatment",
  "refilled", "control"))
summary(res_refilled_vs_control_CD206neg)
```

```
##
## out of 16093 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up) : 328, 2%
## LFC < 0 (down) : 294, 1.8%
## outliers [1] : 1, 0.0062%
## low counts [2] : 2184, 14%
## (mean count < 4)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

```
res_refilled_vs_control_CD206neg_Shrunk <- lfcShrink(dds.CD206neg.im,
  contrast = c("treatment",
  "refilled", "control"), res = res_refilled_vs_control_CD206neg, type =
  "normal")

refilled_vs_control_CD206neg <- merge(x = as.data.frame(res_refilled_vs_
  control_CD206neg),
  y = as.data.frame(res_refilled_vs_control_CD206neg_Shrunk), by = c(0,
  1))
```

6 Export DE genes for other analyses

```
Genes2 <- refilled_vs_control$Row.names
Genes2.CD206pos <- refilled_vs_control_CD206pos$Row.names
Genes2.CD206neg <- refilled_vs_control_CD206neg$Row.names

rownames(refilled_vs_control) = make.names(Genes2, unique = TRUE)
rownames(refilled_vs_control_CD206pos) = make.names(Genes2.CD206pos,
  unique = TRUE)
rownames(refilled_vs_control_CD206neg) = make.names(Genes2.CD206neg,
  unique = TRUE)

refilled_vs_control <- refilled_vs_control[, -1]
refilled_vs_control_CD206pos <- refilled_vs_control_CD206pos[, -1]
refilled_vs_control_CD206neg <- refilled_vs_control_CD206neg[, -1]
```

Filter

```

refilled_vs_control <- refilled_vs_control[!is.na(refilled_vs_control$padj
.y), ]
refilled_vs_control_CD206pos <- refilled_vs_control_CD206pos[!is.na(
  refilled_vs_control_CD206pos$padj.y),
]
refilled_vs_control_CD206neg <- refilled_vs_control_CD206neg[!is.na(
  refilled_vs_control_CD206neg$padj.y),
]

refilled_vs_control_1 <- subset(refilled_vs_control, padj.y < 0.05)
refilled_vs_control_1_CD206pos <- subset(refilled_vs_control_CD206pos,
  padj.y < 0.05)
refilled_vs_control_1_CD206neg <- subset(refilled_vs_control_CD206neg,
  padj.y < 0.05)

```

```

refilled_vs_control_ordered <- refilled_vs_control_1[order(-refilled_vs_
control_1$log2FoldChange.y),
]
refilled_vs_control_ordered_CD206pos <- refilled_vs_control_1_CD206pos[
  order(-refilled_vs_control_1_CD206pos$log2FoldChange.y),
]
refilled_vs_control_ordered_CD206neg <- refilled_vs_control_1_CD206neg[
  order(-refilled_vs_control_1_CD206neg$log2FoldChange.y),
]

```

Save data for other analyses

```

write.table(as.data.frame(refilled_vs_control_ordered), "./Results_
refilled_vs_control_in_IMs.txt",
  sep = "\t", row.names = T, col.names = T)
write.table(as.data.frame(refilled_vs_control_ordered_CD206pos), "./
Results_refilled_vs_control_in_CD206pos_IMs.txt",
  sep = "\t", row.names = T, col.names = T)
write.table(as.data.frame(refilled_vs_control_ordered_CD206neg), "./
Results_refilled_vs_control_in_CD206neg_IMs.txt",
  sep = "\t", row.names = T, col.names = T)

```

7 Presentation of DE genes in volcano plots

7.1 Refilled vs control IMs

```

de.res <- refilled_vs_control

de.res$Gene <- rownames(de.res)
keyvals <- rep("black", nrow(de.res))
names(keyvals) <- rep("non-signif", nrow(de.res))

keyvals[which(de.res$log2FoldChange.y > 1)] <- "red"
names(keyvals)[which(de.res$log2FoldChange.y > 1)] <- "Refilled"

keyvals[which(de.res$log2FoldChange.y < -1)] <- "blue"
names(keyvals)[which(de.res$log2FoldChange.y < -1)] <- "Control"


```

```

plot.vol <- EnhancedVolcano(de.res, subtitle = "", lab = rownames(de.res),
  x = "log2FoldChange.y",
  y = "padj.y", xlim = c(-3, 3), ylim = c(0, -log10(1e-74)), labSize =
    3, pCutoff = 0.05,
  FCcutoff = 1, colAlpha = 1, colCustom = keyvals, legendLabSize = 8,
    legendIconSize = 2,
  border = "full", legendPosition = "right", axisLabSize = 20, title = "
    Refilled vs control IMs")
plot.vol

```

Refilled vs control IMs



What are these genes?

```

# the Refilled-related genes total IMs:
rownames(de.res)[names(keyvals) == "Refilled"]

```

```

## [1] "AA467197" "Cd109" "Cd226" "Cspg4" "Dpysl3" "Gm21188" "
  Igf2r"
## [8] "Rarb" "S100a4"

```

```

# the Refilled-related genes total IMs:
rownames(de.res)[names(keyvals) == "Control"]

```

##	[1]	"Adam22"	"Capn3"	"Cd22"	"Cd4"	"Cpne8"	"Edil3"	"H2.M2	1
		"							
##	[8]	"Igf2bp3"	"Il18r1"	"Ildr2"	"Klhl13"	"Lilra5"	"Lrrc3"	"Mmp13	2
		"							
##	[15]	"Nes"	"Peg10"	"Plag1"	"Ppp1r9a"	"Tcim"	"Tmem119"	"	3
		Zfp827"							


7.2 Refilled vs control CD206+ IMs

```

de.res <- refilled_vs_control_CD206pos 1
de.res$Gene <- rownames(de.res) 2
keyvals <- rep("black", nrow(de.res)) 3
names(keyvals) <- rep("non-signif", nrow(de.res)) 4
keyvals[which(de.res$log2FoldChange.y > 1)] <- "red" 5
names(keyvals)[which(de.res$log2FoldChange.y > 1)] <- "Refilled" 6
keyvals[which(de.res$log2FoldChange.y < -1)] <- "blue" 7
names(keyvals)[which(de.res$log2FoldChange.y < -1)] <- "Control" 8
plot.vol <- EnhancedVolcano(de.res, subtitle = "", lab = rownames(de.res), 9
  x = "log2FoldChange.y", 10
  y = "padj.y", xlim = c(-3, 3), ylim = c(0, -log10(1e-74)), labSize = 11
  3, pCutoff = 0.05, 12
  FCcutoff = 1, colAlpha = 1, colCustom = keyvals, legendLabSize = 8, 13
  legendIconSize = 2, 14
  border = "full", legendPosition = "right", axisLabSize = 20, title = " 15
  Refilled vs control CD206+ IMs") 16
plot.vol 17

```

Refilled vs control CD206+ IMs



total = 13962 variables

What are these genes?

```
# the Refilled-related genes CD206+ IMs:
rownames(de.res)[names(keyvals) == "Refilled"]
```

```
## [1] "AA467197" "Cd109" "Cd226" "Cspg4" "Gm21188"
```

```
# the Refilled-related genes CD206+ IMs:
rownames(de.res)[names(keyvals) == "Control"]
```

```
## [1] "Cd22" "Cd4" "Colec12" "Cpne8" "Edil3" "Fscn1" "H2.M2"
## [8] "Il18r1" "Lilra5" "Lzts2" "Mmp13" "Nbea" "Peg10"
## [15] "Ppp1r9a" "Sgce" "Siglecf" "Sort1" "Spats21" "Tcim" "Tln2"
## [22] "Tmem119" "Vcam1"
```

7.3 Refilled vs control CD206- IMs

```
de.res <- refilled_vs_control_CD206neg
de.res$Gene <- rownames(de.res)
keyvals <- rep("black", nrow(de.res))
names(keyvals) <- rep("non-signif", nrow(de.res))
```

```

keyvals[which(de.res$log2FoldChange.y > 1)] <- "red"
names(keyvals)[which(de.res$log2FoldChange.y > 1)] <- "Refilled"


keyvals[which(de.res$log2FoldChange.y < -1)] <- "blue"
names(keyvals)[which(de.res$log2FoldChange.y < -1)] <- "Control"

plot.vol <- EnhancedVolcano(de.res, subtitle = "", lab = rownames(de.res),
  x = "log2FoldChange.y",
  y = "padj.y", xlim = c(-3, 3), ylim = c(0, -log10(1e-74)), labSize =
    3, pCutoff = 0.05,
  FCcutoff = 1, colAlpha = 1, colCustom = keyvals, legendLabSize = 8,
    legendIconSize = 2,
  border = "full", legendPosition = "right", axisLabSize = 20, title = "
    Refilled vs control CD206- IMs")

plot.vol

```

Refilled vs control CD206- IMs



```

# the Refilled-related genes CD206- IMs:
rownames(de.res)[names(keyvals) == "Refilled"]

```

```

## [1] "Aldh1a2" "Cd109" "Cd209a" "Cd59a" "Cfb" "Cfp" "Cspg4"
## [8] "Ctsk" "Dpysl3" "Fabp5" "Fgfr1" "Hr" "Igf2r" "Mmp9"

```




```
## [15] "Phyhd1" "Retnla" "S100a4" "Vldlr" 3
```

```
# the Refilled-related genes CD206- IMs: 1
rownames(de.res)[names(keyvals) == "Control"] 2
```

```
## [1] "Adgrl3" "Btbd11" "Capn3" "Cd4" "Edil3" "H2.M2" 1
## [7] "Hs3st3a1" "Igf2bp3" "Il18r1" "Il1a" "Ildr2" "K1h113" 2
## [13] "Lilra5" "Lrrc3" "Mmp13" "Nes" "Oplah" "P3h2" 3
## [19] "Peg10" "Ppp1r9a" "Rcbtb2" "Serpinf2" "Tcim" "Tmem119" 4
## [25] "Unc13b" "Zfp827" 5
```

7.4 Plot the top DE genes

```
# plotCount Cspg4 1
data <- plotCounts(dds.im, gene = "Cspg4", intgroup = c("cellType3", " 2
treatment"),
returnData = TRUE) 3
4
ggplot(data, aes(x = cellType3, y = count, color = cellType3, shape = 5
treatment)) +
scale_y_log10() + geom_point(position = position_jitter(width = 0.1, 6
height = 0),
size = 3) + ggtitle("Cspg4") + theme(plot.title = element_text(hjust = 7
0.5, size = 20)) +
# scale_color_manual(values = c('#371dad', '#ff8e03', '#74c72a'))+ 8
ylab("Normalized Count") + theme_linedraw() + theme_light() 9
```




```

# plotCount Cd109
data <- plotCounts(dds.im, gene = "Cd109", intgroup = c("cellType3", "
  treatment"),
  returnData = TRUE)

ggplot(data, aes(x = cellType3, y = count, color = cellType3, shape =
  treatment)) +
  scale_y_log10() + geom_point(position = position_jitter(width = 0.1,
    height = 0),
    size = 3) + ggtitle("Cd109") + theme(plot.title = element_text(hjust =
    0.5, size = 20)) +
  # scale_color_manual(values = c('#371dad', '#ff8e03', '#74c72a')) +
  ylab("Normalized_Count") + theme_linedraw() + theme_light()


```



```

1 # plotCount Tmem119
2 data <- plotCounts(dds.im, gene = "Tmem119", intgroup = c("cellType3", "
3   treatment"),
4   returnData = TRUE)
5
6 ggplot(data, aes(x = cellType3, y = count, color = cellType3, shape =
7   treatment)) +
8   scale_y_log10() + geom_point(position = position_jitter(width = 0.1,
  height = 0),
  size = 3) + ggtitle("Tmem119") + theme(plot.title = element_text(hjust
    = 0.5,
    size = 20)) + ylab("Normalized_Count") + theme_linedraw() + theme_
    light()

```



8 Session information

Nextflow:

```
Nextflow version: version 21.03.0.edge, build 5518 (05-03-2021 10:52 UTC) 1
Workflow profile: docker 2
Workflow repository: https://github.com/nf-core/rnaseq, revision master ( 3
    commit hash 3643a94411b65f42bce5357c5015603099556ad9)
```

Software version used by Workflow:

```
bedtools      2.29.2 1
bioconductor-summarizedexperiment 1.20.0 2
bioconductor-tximeta 1.8.0 3
deseq2 1.28.0 4
dupradar 1.18.0 5
fastqc 0.11.9 6
nextflow 21.03.0.edge 7
nf-core/rnaseq 3.0 8
picard 2.23.9 9
preseq 2.0.3 10
qualimap 2.2.2-dev 11
rseqc 3.0.1 12
salmon 1.4.0 13
```

samtools	1.10	14
star	2.6.1d	15
stringtie	2.1.4	16
subread	2.0.1	17
trimgalore	0.6.6	18
ucsc	377	19

R session:

sessionInfo()	1
---------------	---


```
## R version 4.0.3 (2020-10-10)
## Platform: x86_64-pc-linux-gnu (64-bit)
## Running under: Ubuntu 20.04.3 LTS
##
## Matrix products: default
## BLAS: /usr/lib/x86_64-linux-gnu/openblas-pthread/libblas.so.3
## LAPACK: /usr/lib/x86_64-linux-gnu/openblas-pthread/liblapack.so.3
##
## locale:
##  [1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C
##  [3] LC_TIME=en_GB.UTF-8      LC_COLLATE=en_US.UTF-8
##  [5] LC_MONETARY=en_GB.UTF-8  LC_MESSAGES=en_US.UTF-8
##  [7] LC_PAPER=en_GB.UTF-8     LC_NAME=C
##  [9] LC_ADDRESS=C             LC_TELEPHONE=C
## [11] LC_MEASUREMENT=en_GB.UTF-8 LC_IDENTIFICATION=C
##
## attached base packages:
## [1] parallel stats4 stats graphics grDevices utils
## datasets
## [8] methods base
##
## other attached packages:
##  [1] org.Mm.eg.db_3.12.0      AnnotationDbi_1.52.0
##  [3] forcats_0.5.1           EnhancedVolcano_1.8.0
##  [5] ggrepel_0.9.1           RColorBrewer_1.1-2
##  [7] pheatmap_1.0.12         ggplot2_3.3.5
##  [9] DESeq2_1.30.1           SummarizedExperiment_1.20.0
## [11] Biobase_2.50.0          MatrixGenerics_1.2.1
## [13] matrixStats_0.61.0      GenomicRanges_1.42.0
## [15] GenomeInfoDb_1.26.7     IRanges_2.24.1
## [17] S4Vectors_0.28.1       BiocGenerics_0.36.1
##
## loaded via a namespace (and not attached):
##  [1] bitops_1.0-7            bit64_4.0.5            ash_1.0-15
##  [4] httr_1.4.2              tools_4.0.3            utf8_1.2.2
##  [7] R6_2.5.1                KernSmooth_2.23-20     vipor_0.4.5
## [10] DBI_1.1.1               colorspace_2.0-2       withr_2.4.3
## [13] tidyselect_1.1.1        ggtrastr_1.0.0         ggalt_0.4.0
## [16] bit_4.0.4               compiler_4.0.3         extrafontdb_1.0
## [19] textshaping_0.3.6       cli_3.1.0              formatR_1.11
## [22] DelayedArray_0.16.3     labeling_0.4.2         scales_1.1.1
## [25] proj4_1.0-10.1          genefilter_1.72.1      systemfonts_1.0.3
## [28] stringr_1.4.0           digest_0.6.29          rmarkdown_2.11
```

## [31]	XVector_0.30.0	pkgconfig_2.0.3	htmltools_0.5.2	43
## [34]	extrafont_0.17	highr_0.9	fastmap_1.1.0	44
## [37]	maps_3.4.0	rlang_0.4.12	rstudioapi_0.13	45
## [40]	RSQLite_2.2.8	farver_2.1.0	generics_0.1.1	46
## [43]	BiocParallel_1.24.1	dplyr_1.0.7	RCurl_1.98-1.5	47
## [46]	magrittr_2.0.1	GenomeInfoDbData_1.2.4	Matrix_1.3-4	48
## [49]	Rcpp_1.0.7	ggbeeswarm_0.6.0	munSELL_0.5.0	49
## [52]	fansi_0.5.0	lifecycle_1.0.1	stringi_1.7.6	50
## [55]	yaml_2.2.1	MASS_7.3-53	zlibbioc_1.36.0	51
## [58]	grid_4.0.3	blob_1.2.2	crayon_1.4.2	52
## [61]	lattice_0.20-41	splines_4.0.3	annotate_1.68.0	53
## [64]	locfit_1.5-9.4	knitr_1.36	pillar_1.6.4	54
## [67]	geneplotter_1.68.0	XML_3.99-0.8	glue_1.5.1	55
## [70]	evaluate_0.14	vcvtrs_0.3.8	Rttf2pt1_1.3.9	56
## [73]	gtable_0.3.0	purrr_0.3.4	assertthat_0.2.1	57
## [76]	cachem_1.0.6	xfun_0.28	xtable_1.8-4	58
## [79]	ragg_1.2.0	survival_3.2-7	tibble_3.1.6	59
## [82]	beeswarm_0.4.0	memoise_2.0.1	ellipsis_0.3.2	60

References

1. Ewels, P. A. *et al.* The nf-core framework for community-curated bioinformatics pipelines. *Nature Biotechnology* (2020) doi:10.1038/s41587-020-0439-x.
2. Love, M. I., Huber, W. & Anders, S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2. *Genome Biology* **15**, 550 (2014).