

[Start Here](#)[Blog](#)[Books](#)[About](#)[Contact](#)

Need help with LSTMs in Python? [Take the FREE Mini-Course.](#)

# How to Tune LSTM Hyperparameters with Keras for Time Series Forecasting

by **Jason Brownlee** on April 12, 2017 in **Long Short-Term Memory Networks**



Configuring neural networks is difficult because there is no good theory on how to do it.

You must be systematic and explore different configurations both from a dynamical and an objective results point of a view to try to understand what is going on for a given predictive modeling problem.

In this tutorial, you will discover how you can explore how to configure an LSTM network on a time series forecasting problem.


After completing this tutorial, you will know:

- How to tune and interpret the results of the number of training epochs.

[Get Your Start in Machine Learning](#)

- How to tune and interpret the results of the size of training batches.
- How to tune and interpret the results of the number of neurons.

Let's get started.



How to Tune LSTM Hyperparameters with Keras for Time Series Forecasting  
Photo by [David Saddler](#), some rights reserved.

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

## Tutorial Overview

This tutorial is broken down into 6 parts; they are:

1. Shampoo Sales Dataset
2. Experimental Test Harness
3. Tuning the Number of Epochs
4. Tuning the Batch Size

Get Your Start in Machine Learning

5. Tuning the Number of Neurons
6. Summary of Results

## Environment

This tutorial assumes you have a Python SciPy environment installed. You can use either Python 2 or 3 with this example.

This tutorial assumes you have Keras v2.0 or higher installed with either the TensorFlow or Theano backend.

The tutorial also assumes you have scikit-learn, Pandas, NumPy and Matplotlib installed.

If you need help setting up your Python environment, see this post:

- [How to Setup a Python Environment for Machine Learning and Deep Learning with Anaconda](#)

## Shampoo Sales Dataset

This dataset describes the monthly number of sales of shampoo over a 3-year period.

The units are a sales count and there are 36 observations. The original dataset is credited to Makrid

You can download and learn more about the dataset [here](#).

The example below loads and creates a plot of the loaded dataset.

```
1 # load and plot dataset
2 from pandas import read_csv
3 from pandas import datetime
4 from matplotlib import pyplot
5 # load dataset
6 def parser(x):
7     return datetime.strptime('190'+x, '%Y-%m')
8 series = read_csv('shampoo-sales.csv', header=0, parse_dates=[0], index_col=0, squeeze=True, date_parser=parser)
9 # summarize first few rows
10 print(series.head())
11 # line plot
12 series.plot()
13 pyplot.show()
```

### Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.


START MY EMAIL COURSE

Get Your Start in Machine Learning

Running the example loads the dataset as a Pandas Series and prints the first 5 rows.

```
1 Month
2 1901-01-01 266.0
3 1901-02-01 145.9
4 1901-03-01 183.1
5 1901-04-01 119.3
6 1901-05-01 180.3
7 Name: Sales, dtype: float64
```

A line plot of the series is then created showing a clear increasing trend.



Next, we will take a look at the LSTM configuration and test harness used in the experiment.

## Need help with LSTMs for Sequence Prediction?

Take my free 7-day email course and discover 6 different LSTM architectures (with sample code).

Click to sign-up and also get a free PDF Ebook version of the course.

Start Your FREE Mini-Course Now!

## Experimental Test Harness

This section describes the test harness used in this tutorial.

### Data Split

We will split the Shampoo Sales dataset into two parts: a training and a test set.

The first two years of data will be taken for the training dataset and the remaining one year of data will be used for the test dataset.

Models will be developed using the training dataset and will make predictions on the test dataset.

The persistence forecast (naive forecast) on the test dataset achieves an error of 136.761 monthly shampoo sales. This provides a lower acceptable bound of performance on the test set.

### Model Evaluation

A rolling-forecast scenario will be used, also called walk-forward model validation.

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

Each time step of the test dataset will be walked one at a time. A model will be used to make a forecast for the time step, then the actual expected value from the test set will be taken and made available to the model for the forecast on the next time step.

This mimics a real-world scenario where new Shampoo Sales observations would be available each month and used in the forecasting of the following month.

This will be simulated by the structure of the train and test datasets. We will make all of the forecasts in a one-shot method.

All forecasts on the test dataset will be collected and an error score calculated to summarize the skill of the model. The root mean squared error (RMSE) will be used as it punishes large errors and results in a score that is in the same units as the forecast data, namely monthly shampoo sales.

## Data Preparation

Before we can fit an LSTM model to the dataset, we must transform the data.

The following three data transforms are performed on the dataset prior to fitting a model and making

1. Transform the time series data so that it is stationary. Specifically, a lag=1 differencing to remove
2. Transform the time series into a supervised learning problem. Specifically, the organization of data such that the observation at the previous time step is used as an input to forecast the observation at the current time step.
3. Transform the observations to have a specific scale. Specifically, to rescale the data to values between 0 and 1 using the sigmoid tangent activation function of the LSTM model.

These transforms are inverted on forecasts to return them into their original scale before calculating

## Experimental Runs

Each experimental scenario will be run 10 times.

The reason for this is that the random initial conditions for an LSTM network can result in very different results each time a given configuration is trained.

A diagnostic approach will be used to investigate model configurations. This is where line plots of model skill over time (training iterations called epochs) will be created and studied for insight into how a given configuration performs and how it may be adjusted to elicit better performance.

The model will be evaluated on both the train and the test datasets at the end of each epoch and the

### Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

The train and test RMSE scores at the end of each scenario are printed to give an indication of progress.

The series of train and test RMSE scores are plotted at the end of a run as a line plot. Train scores are colored blue and test scores are colored orange.

Let's dive into the results.

## Tuning the Number of Epochs

The first LSTM parameter we will look at tuning is the number of training epochs.

The model will use a batch size of 4, and a single neuron. We will explore the effect of training this configuration for different numbers of training epochs.

### Diagnostic of 500 Epochs

The complete code listing for this diagnostic is listed below.

The code is reasonably well commented and should be easy to follow. This code will be the basis for changes made in each subsequent experiment will be listed.

```
1 from pandas import DataFrame
2 from pandas import Series
3 from pandas import concat
4 from pandas import read_csv
5 from pandas import datetime
6 from sklearn.metrics import mean_squared_error
7 from sklearn.preprocessing import MinMaxScaler
8 from keras.models import Sequential
9 from keras.layers import Dense
10 from keras.layers import LSTM
11 from math import sqrt
12 import matplotlib
13 # be able to save images on server
14 matplotlib.use('Agg')
15 from matplotlib import pyplot
16 import numpy
17
18 # date-time parsing function for loading the dataset
19 def parser(x):
20     return datetime.strptime('190'+x, '%Y-%m')
21
```

### Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

```

22 # frame a sequence as a supervised learning problem
23 def timeseries_to_supervised(data, lag=1):
24     df = DataFrame(data)
25     columns = [df.shift(i) for i in range(1, lag+1)]
26     columns.append(df)
27     df = concat(columns, axis=1)
28     df = df.drop(0)
29     return df
30
31 # create a differenced series
32 def difference(dataset, interval=1):
33     diff = list()
34     for i in range(interval, len(dataset)):
35         value = dataset[i] - dataset[i - interval]
36         diff.append(value)
37     return Series(diff)
38
39 # scale train and test data to [-1, 1]
40 def scale(train, test):
41     # fit scaler
42     scaler = MinMaxScaler(feature_range=(-1, 1))
43     scaler = scaler.fit(train)
44     # transform train
45     train = train.reshape(train.shape[0], train.shape[1])
46     train_scaled = scaler.transform(train)
47     # transform test
48     test = test.reshape(test.shape[0], test.shape[1])
49     test_scaled = scaler.transform(test)
50     return scaler, train_scaled, test_scaled
51
52 # inverse scaling for a forecasted value
53 def invert_scale(scaler, X, yhat):
54     new_row = [x for x in X] + [yhat]
55     array = numpy.array(new_row)
56     array = array.reshape(1, len(array))
57     inverted = scaler.inverse_transform(array)
58     return inverted[0, -1]
59
60 # evaluate the model on a dataset, returns RMSE in transformed units
61 def evaluate(model, raw_data, scaled_dataset, scaler, offset, batch_size):
62     # separate
63     X, y = scaled_dataset[:,0:-1], scaled_dataset[:, -1]
64     # reshape
65     reshaped = X.reshape(len(X), 1, 1)
66     # forecast dataset
67     output = model.predict(reshaped, batch_size=batch_size)
68     # invert data transforms on forecast

```

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning



```

69 predictions = list()
70 for i in range(len(output)):
71     yhat = output[i,0]
72     # invert scaling
73     yhat = invert_scale(scaler, X[i], yhat)
74     # invert differencing
75     yhat = yhat + raw_data[i]
76     # store forecast
77     predictions.append(yhat)
78 # report performance
79 rmse = sqrt(mean_squared_error(raw_data[1:], predictions))
80 return rmse
81
82 # fit an LSTM network to training data
83 def fit_lstm(train, test, raw, scaler, batch_size, nb_epoch, neurons):
84     X, y = train[:, 0:-1], train[:, -1]
85     X = X.reshape(X.shape[0], 1, X.shape[1])
86     # prepare model
87     model = Sequential()
88     model.add(LSTM(neurons, batch_input_shape=(batch_size, X.shape[1], X.shape[2]), stateful=True))
89     model.add(Dense(1))
90     model.compile(loss='mean_squared_error', optimizer='adam')
91     # fit model
92     train_rmse, test_rmse = list(), list()
93     for i in range(nb_epoch):
94         model.fit(X, y, epochs=1, batch_size=batch_size, verbose=0, shuffle=False)
95         model.reset_states()
96         # evaluate model on train data
97         raw_train = raw[-(len(train)+len(test)+1):-len(test)]
98         train_rmse.append(evaluate(model, raw_train, train, scaler, 0, batch_size))
99         model.reset_states()
100        # evaluate model on test data
101        raw_test = raw[-(len(test)+1):]
102        test_rmse.append(evaluate(model, raw_test, test, scaler, 0, batch_size))
103        model.reset_states()
104    history = DataFrame()
105    history['train'], history['test'] = train_rmse, test_rmse
106    return history
107
108 # run diagnostic experiments
109 def run():
110     # load dataset
111     series = read_csv('shampoo-sales.csv', header=0, parse_dates=[0], index_col=0, squeeze=True, date_parser=parser)
112     # transform data to be stationary
113     raw_values = series.values
114     diff_values = difference(raw_values, 1)
115     # transform data to be supervised learning

```

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

```

116 supervised = timeseries_to_supervised(diff_values, 1)
117 supervised_values = supervised.values
118 # split data into train and test-sets
119 train, test = supervised_values[0:-12], supervised_values[-12:]
120 # transform the scale of the data
121 scaler, train_scaled, test_scaled = scale(train, test)
122 # fit and evaluate model
123 train_trimmed = train_scaled[2:, :]
124 # config
125 repeats = 10
126 n_batch = 4
127 n_epochs = 500
128 n_neurons = 1
129 # run diagnostic tests
130 for i in range(repeats):
131     history = fit_lstm(train_trimmed, test_scaled, raw_values, scaler, n_batch, n_epochs, n_neurons)
132     pyplot.plot(history['train'], color='blue')
133     pyplot.plot(history['test'], color='orange')
134     print('%d) TrainRMSE=%f, TestRMSE=%f' % (i, history['train'].iloc[-1], history['test'].iloc[-1]))
135     pyplot.savefig('epochs_diagnostic.png')
136
137 # entry point
138 run()

```

Running the experiment prints the RMSE for the train and the test sets at the end of each of the 10 epochs.

```

1 0) TrainRMSE=63.495594, TestRMSE=113.472643
2 1) TrainRMSE=60.446307, TestRMSE=100.147470
3 2) TrainRMSE=59.879681, TestRMSE=95.112331
4 3) TrainRMSE=66.115269, TestRMSE=106.444401
5 4) TrainRMSE=61.878702, TestRMSE=86.572920
6 5) TrainRMSE=73.519382, TestRMSE=103.551694
7 6) TrainRMSE=64.407033, TestRMSE=98.849227
8 7) TrainRMSE=72.684834, TestRMSE=98.499976
9 8) TrainRMSE=77.593773, TestRMSE=124.404747
10 9) TrainRMSE=71.749335, TestRMSE=126.396615

```

A line plot of the series of RMSE scores on the train and test sets after each training epoch is also created.


## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning



The results clearly show a downward trend in RMSE over the training epochs for almost all of the experimental runs.

This is a good sign, as it shows the model is learning the problem and has some predictive skill. In fact, all of the final test scores are below the error of a simple persistence model (naive forecast) that achieves an RMSE of 136.761 on this problem.

The results suggest that more training epochs will result in a more skillful model.

Let's try doubling the number of epochs from 500 to 1000.

**Get Your Start in Machine Learning**

## Diagnostic of 1000 Epochs

In this section, we use the same experimental setup and fit the model over 1000 training epochs.

Specifically, the `n_epochs` parameter is set to `1000` in the `run()` function.

```
1 n_epochs = 1000
```

Running the example prints the RMSE for the train and test sets from the final epoch.


```
1 0) TrainRMSE=69.242394, TestRMSE=90.832025
2 1) TrainRMSE=65.445810, TestRMSE=113.013681
3 2) TrainRMSE=57.949335, TestRMSE=103.727228
4 3) TrainRMSE=61.808586, TestRMSE=89.071392
5 4) TrainRMSE=68.127167, TestRMSE=88.122807
6 5) TrainRMSE=61.030678, TestRMSE=93.526607
7 6) TrainRMSE=61.144466, TestRMSE=97.963895
8 7) TrainRMSE=59.922150, TestRMSE=94.291120
9 8) TrainRMSE=60.170052, TestRMSE=90.076229
10 9) TrainRMSE=62.232470, TestRMSE=98.174839
```

A line plot of the test and train RMSE scores each epoch is also created.

### Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



We can see that the downward trend of model error does continue and appears to slow.

The lines for the train and test cases become more horizontal, but still generally show a downward trend, although at a lower rate of change. Some examples of test error show a possible inflection point around 600 epochs and may show a rising trend.

It is worth extending the epochs further. We are interested in the average performance continuing to improve on the test set and this may continue.

Let's try doubling the number of epochs from 1000 to 2000.

Get Your Start in Machine Learning

## Diagnostic of 2000 Epochs

In this section, we use the same experimental setup and fit the model over 2000 training epochs.

Specifically, the `n_epochs` parameter is set to 2000 in the `run()` function.

```
1 n_epochs = 2000
```

Running the example prints the RMSE for the train and test sets from the final epoch.


```
1 0) TrainRMSE=67.292970, TestRMSE=83.096856
2 1) TrainRMSE=55.098951, TestRMSE=104.211509
3 2) TrainRMSE=69.237206, TestRMSE=117.392007
4 3) TrainRMSE=61.319941, TestRMSE=115.868142
5 4) TrainRMSE=60.147575, TestRMSE=87.793270
6 5) TrainRMSE=59.424241, TestRMSE=99.000790
7 6) TrainRMSE=66.990082, TestRMSE=80.490660
8 7) TrainRMSE=56.467012, TestRMSE=97.799062
9 8) TrainRMSE=60.386380, TestRMSE=103.810569
10 9) TrainRMSE=58.250862, TestRMSE=86.212094
```

A line plot of the test and train RMSE scores each epoch is also created.

### Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



As one might have guessed, the downward trend in error continues over the additional 1000 epochs on both the train and test datasets.

Of note, about half of the cases continue to decrease in error all the way to the end of the run, whereas the rest show signs of an increasing trend.

The increasing trend is a sign of overfitting. This is when the model overfits the training dataset at the cost of worse performance on the test dataset. It is exemplified by continued improvements on the training dataset and improvements followed by an inflection point and worsening skill in the test dataset. A little less than half of the runs show the beginnings of this type of pattern on the test dataset.

Get Your Start in Machine Learning

Nevertheless, the final epoch results on the test dataset are very good. If there is a chance we can see further gains by even longer training, we must explore it.

Let's try doubling the number of epochs from 2000 to 4000.

## Diagnostic of 4000 Epochs

In this section, we use the same experimental setup and fit the model over 4000 training epochs.

Specifically, the `n_epochs` parameter is set to 4000 in the `run()` function.

```
1 n_epochs = 4000
```

Running the example prints the RMSE for the train and test sets from the final epoch.

```
1 0) TrainRMSE=58.889277, TestRMSE=99.121765
2 1) TrainRMSE=56.839065, TestRMSE=95.144846
3 2) TrainRMSE=58.522271, TestRMSE=87.671309
4 3) TrainRMSE=53.873962, TestRMSE=113.920076
5 4) TrainRMSE=66.386299, TestRMSE=77.523432
6 5) TrainRMSE=58.996230, TestRMSE=136.367014
7 6) TrainRMSE=55.725800, TestRMSE=113.206607
8 7) TrainRMSE=57.334604, TestRMSE=90.814642
9 8) TrainRMSE=54.593069, TestRMSE=105.724825
10 9) TrainRMSE=56.678498, TestRMSE=83.082262
```


A line plot of the test and train RMSE scores each epoch is also created.

### Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE





A similar pattern continues.

There is a general trend of improving performance, even over the 4000 epochs. There is one case of severe overfitting where test error rises sharply.

Again, most runs end with a “good” (better than persistence) final test error.

## Summary of Results

The diagnostic runs above are helpful to explore the dynamical behavior of the model, but fall short of

**Get Your Start in Machine Learning**

3.

We can address this by repeating the same experiments and calculating and comparing summary statistics for each configuration. In this case, 30 runs were completed of the epoch values 500, 1000, 2000, 4000, and 6000.

The idea is to compare the configurations using summary statistics over a larger number of runs and see exactly which of the configurations might perform better on average.

The complete code example is listed below.

```
1 from pandas import DataFrame
2 from pandas import Series
3 from pandas import concat
4 from pandas import read_csv
5 from pandas import datetime
6 from sklearn.metrics import mean_squared_error
7 from sklearn.preprocessing import MinMaxScaler
8 from keras.models import Sequential
9 from keras.layers import Dense
10 from keras.layers import LSTM
11 from math import sqrt
12 import matplotlib
13 # be able to save images on server
14 matplotlib.use('Agg')
15 from matplotlib import pyplot
16 import numpy
17
18 # date-time parsing function for loading the dataset
19 def parser(x):
20     return datetime.strptime('190'+x, '%Y-%m')
21
22 # frame a sequence as a supervised learning problem
23 def timeseries_to_supervised(data, lag=1):
24     df = DataFrame(data)
25     columns = [df.shift(i) for i in range(1, lag+1)]
26     columns.append(df)
27     df = concat(columns, axis=1)
28     df = df.drop(0)
29     return df
30
31 # create a differenced series
32 def difference(dataset, interval=1):
33     diff = list()
34     for i in range(interval, len(dataset)):
35         value = dataset[i] - dataset[i - interval]
36         diff.append(value)
```

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

```

37     return Series(diff)
38
39 # invert differenced value
40 def inverse_difference(history, yhat, interval=1):
41     return yhat + history[-interval]
42
43 # scale train and test data to [-1, 1]
44 def scale(train, test):
45     # fit scaler
46     scaler = MinMaxScaler(feature_range=(-1, 1))
47     scaler = scaler.fit(train)
48     # transform train
49     train = train.reshape(train.shape[0], train.shape[1])
50     train_scaled = scaler.transform(train)
51     # transform test
52     test = test.reshape(test.shape[0], test.shape[1])
53     test_scaled = scaler.transform(test)
54     return scaler, train_scaled, test_scaled
55
56 # inverse scaling for a forecasted value
57 def invert_scale(scaler, X, yhat):
58     new_row = [x for x in X] + [yhat]
59     array = numpy.array(new_row)
60     array = array.reshape(1, len(array))
61     inverted = scaler.inverse_transform(array)
62     return inverted[0, -1]
63
64 # fit an LSTM network to training data
65 def fit_lstm(train, batch_size, nb_epoch, neurons):
66     X, y = train[:, 0:-1], train[:, -1]
67     X = X.reshape(X.shape[0], 1, X.shape[1])
68     model = Sequential()
69     model.add(LSTM(neurons, batch_input_shape=(batch_size, X.shape[1], X.shape[2]), stateful=True))
70     model.add(Dense(1))
71     model.compile(loss='mean_squared_error', optimizer='adam')
72     for i in range(nb_epoch):
73         model.fit(X, y, epochs=1, batch_size=batch_size, verbose=0, shuffle=False)
74         model.reset_states()
75     return model
76
77 # run a repeated experiment
78 def experiment(repeats, series, epochs):
79     # transform data to be stationary
80     raw_values = series.values
81     diff_values = difference(raw_values, 1)
82     # transform data to be supervised learning
83     supervised = timeseries_to_supervised(diff_values, 1)

```

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

```

84 supervised_values = supervised.values
85 # split data into train and test-sets
86 train, test = supervised_values[0:-12], supervised_values[-12:]
87 # transform the scale of the data
88 scaler, train_scaled, test_scaled = scale(train, test)
89 # run experiment
90 error_scores = list()
91 for r in range(repeats):
92     # fit the model
93     batch_size = 4
94     train_trimmed = train_scaled[2:, :]
95     lstm_model = fit_lstm(train_trimmed, batch_size, epochs, 1)
96     # forecast the entire training dataset to build up state for forecasting
97     train_resaped = train_trimmed[:, 0].reshape(len(train_trimmed), 1, 1)
98     lstm_model.predict(train_resaped, batch_size=batch_size)
99     # forecast test dataset
100    test_resaped = test_scaled[:, 0:-1]
101    test_resaped = test_resaped.reshape(len(test_resaped), 1, 1)
102    output = lstm_model.predict(test_resaped, batch_size=batch_size)
103    predictions = list()
104    for i in range(len(output)):
105        yhat = output[i,0]
106        X = test_scaled[i, 0:-1]
107        # invert scaling
108        yhat = invert_scale(scaler, X, yhat)
109        # invert differencing
110        yhat = inverse_difference(raw_values, yhat, len(test_scaled)+1-i)
111        # store forecast
112        predictions.append(yhat)
113    # report performance
114    rmse = sqrt(mean_squared_error(raw_values[-12:], predictions))
115    print('%d) Test RMSE: %.3f' % (r+1, rmse))
116    error_scores.append(rmse)
117 return error_scores
118
119
120 # load dataset
121 series = read_csv('shampoo-sales.csv', header=0, parse_dates=[0], index_col=0, squeeze=True, date_parser=parser)
122 # experiment
123 repeats = 30
124 results = DataFrame()
125 # vary training epochs
126 epochs = [500, 1000, 2000, 4000, 6000]
127 for e in epochs:
128     results[str(e)] = experiment(repeats, series, e)
129 # summarize results
130 print(results.describe())

```

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

```

131 # save boxplot
132 results.boxplot()
133 pyplot.savefig('boxplot_epochs.png')

```

Running the code first prints summary statistics for each of the 5 configurations. Notably, this includes the mean and standard deviations of the RMSE scores from each population of results.

The mean gives an idea of the average expected performance of a configuration, whereas the standard deviation gives an idea of the variance. The min and max RMSE scores also give an idea of the range of possible best and worst case examples that might be expected.

Looking at just the mean RMSE scores, the results suggest that an epoch configured to 1000 may be better. The results also suggest further investigations may be warranted of epoch values between 1000 and 2000.

	500	1000	2000	4000	6000
1 count	30.000000	30.000000	30.000000	30.000000	30.000000
2 mean	109.439203	104.566259	107.882390	116.339792	127.618305
3 std	14.874031	19.097098	22.083335	21.590424	24.866763
4 min	87.747708	81.621783	75.327883	77.399968	90.512409
5 25%	96.484568	87.686776	86.753694	102.127451	105.861881
6 50%	110.891939	98.942264	116.264027	121.898248	125.273050
7 75%	121.067498	119.248849	125.518589	130.107772	150.832313
8 max	138.879278	139.928055	146.840997	157.026562	166.111151

The distributions are also shown on a box and whisker plot. This is helpful to see how the distribution

The green line shows the median and the box shows the 25th and 75th percentiles, or the middle 50% of the data. The choice of setting epochs to 1000 is better than the tested alternatives. It also shows that the best possible choice is 1000 or 2000, at the cost of worse performance on average.


## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning



Next, we will look at the effect of batch size.

## Tuning the Batch Size

Batch size controls how often to update the weights of the network.

Importantly in Keras, the batch size must be a factor of the size of the test and the training dataset.

Get Your Start in Machine Learning


In the previous section exploring the number of training epochs, the batch size was fixed at 4, which cleanly divides into the test dataset (with the size 12) and in a truncated version of the test dataset (with the size of 20).

In this section, we will explore the effect of varying the batch size. We will hold the number of training epochs constant at 1000.

## Diagnostic of 1000 Epochs and Batch Size of 4

As a reminder, the previous section evaluated a batch size of 4 in the second experiment with a number of epochs of 1000.

The results showed a downward trend in error that continued for most runs all the way to the final training epoch.



## Diagnostic of 1000 Epochs and Batch Size of 2

In this section, we look at halving the batch size from 4 to 2.

This change is made to the `n_batch` parameter in the `run()` function; for example:

```
1 n_batch = 2
```

Running the example shows the same general trend in performance as a batch size of 4, perhaps with a higher RMSE on the final epoch.

The runs may show the behavior of stabilizing the RMES sooner rather than seeming to continue the downward trend.

The RSME scores from the final exposure of each run are listed below.

```
1 0) TrainRMSE=63.510219, TestRMSE=115.855819
2 1) TrainRMSE=58.336003, TestRMSE=97.954374
3 2) TrainRMSE=69.163685, TestRMSE=96.721446
4 3) TrainRMSE=65.201764, TestRMSE=110.104828
5 4) TrainRMSE=62.146057, TestRMSE=112.153553
6 5) TrainRMSE=58.253952, TestRMSE=98.442715
7 6) TrainRMSE=67.306530, TestRMSE=108.132021
8 7) TrainRMSE=63.545292, TestRMSE=102.821356
9 8) TrainRMSE=61.693847, TestRMSE=99.859398
10 9) TrainRMSE=58.348250, TestRMSE=99.682159
```

A line plot of the test and train RMSE scores each epoch is also created.


### Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE





Let's try having the batch size again.

## Diagnostic of 1000 Epochs and Batch Size of 1

A batch size of 1 is technically performing online learning.

That is where the network is updated after each training pattern. This can be contrasted with batch learning, where the weights are only updated at the end of each epoch.

Get Your Start in Machine Learning

We can change the `n_batch` parameter in the `run()` function; for example:

```
1 n_batch = 1
```

Again, running the example prints the RMSE scores from the final epoch of each run.

```
1 0) TrainRMSE=60.349798, TestRMSE=100.182293
2 1) TrainRMSE=62.624106, TestRMSE=95.716070
3 2) TrainRMSE=64.091859, TestRMSE=98.598958
4 3) TrainRMSE=59.929993, TestRMSE=96.139427
5 4) TrainRMSE=59.890593, TestRMSE=94.173619
6 5) TrainRMSE=55.944968, TestRMSE=106.644275
7 6) TrainRMSE=60.570245, TestRMSE=99.981562
8 7) TrainRMSE=56.704995, TestRMSE=111.404182
9 8) TrainRMSE=59.909065, TestRMSE=90.238473
10 9) TrainRMSE=60.863807, TestRMSE=105.331214
```

A line plot of the test and train RMSE scores each epoch is also created.


The plot suggests more variability in the test RMSE over time and perhaps a train RMSE that stabilizes. Increased variability in the test RMSE is to be expected given the large changes made to the network.

The graph also suggests that perhaps the decreasing trend in RMSE may continue if the configuration is further tuned.

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



## Summary of Results

As with training epochs, we can objectively compare the performance of the network given different batch sizes.

Each configuration was run 30 times and summary statistics calculated on the final results.

```
1 ...  
2  
3 # run a repeated experiment  
4 def experiment(repeats, series, batch_size):
```

Get Your Start in Machine Learning

```

5 # transform data to be stationary
6 raw_values = series.values
7 diff_values = difference(raw_values, 1)
8 # transform data to be supervised learning
9 supervised = timeseries_to_supervised(diff_values, 1)
10 supervised_values = supervised.values
11 # split data into train and test-sets
12 train, test = supervised_values[0:-12], supervised_values[-12:]
13 # transform the scale of the data
14 scaler, train_scaled, test_scaled = scale(train, test)
15 # run experiment
16 error_scores = list()
17 for r in range(repeats):
18     # fit the model
19     train_trimmed = train_scaled[2:, :]
20     lstm_model = fit_lstm(train_trimmed, batch_size, 1000, 1)
21     # forecast the entire training dataset to build up state for forecasting
22     train_resaped = train_trimmed[:, 0].reshape(len(train_trimmed), 1, 1)
23     lstm_model.predict(train_resaped, batch_size=batch_size)
24     # forecast test dataset
25     test_resaped = test_scaled[:, 0:-1]
26     test_resaped = test_resaped.reshape(len(test_resaped), 1, 1)
27     output = lstm_model.predict(test_resaped, batch_size=batch_size)
28     predictions = list()
29     for i in range(len(output)):
30         yhat = output[i, 0]
31         X = test_scaled[i, 0:-1]
32         # invert scaling
33         yhat = invert_scale(scaler, X, yhat)
34         # invert differencing
35         yhat = inverse_difference(raw_values, yhat, len(test_scaled)+1-i)
36         # store forecast
37         predictions.append(yhat)
38     # report performance
39     rmse = sqrt(mean_squared_error(raw_values[-12:], predictions))
40     print('%d) Test RMSE: %.3f' % (r+1, rmse))
41     error_scores.append(rmse)
42 return error_scores
43
44
45 # load dataset
46 series = read_csv('shampoo-sales.csv', header=0, parse_dates=[0], index_col=0, squeeze=True, date_parser=parser)
47 # experiment
48 repeats = 30
49 results = DataFrame()
50 # vary training batches
51 batches = [1, 2, 4]

```

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

```

52 for b in batches:
53     results[str(b)] = experiment(repeats, series, b)
54 # summarize results
55 print(results.describe())
56 # save boxplot
57 results.boxplot()
58 pyplot.savefig('boxplot_batches.png')

```

From the mean performance alone, the results suggest lower RMSE with a batch size of 1. As was noted in the previous section, this may be improved further with more training epochs.

1		1	2	4
2	count	30.000000	30.000000	30.000000
3	mean	98.697017	102.642594	100.320203
4	std	12.227885	9.144163	15.957767
5	min	85.172215	85.072441	83.636365
6	25%	92.023175	96.834628	87.671461
7	50%	95.981688	101.139527	91.628144
8	75%	102.009268	110.171802	114.660192
9	max	147.688818	120.038036	135.290829

A box and whisker plot of the data was also created to help graphically compare the distributions. The line where a batch size of 4 shows both the largest variability and also the lowest median RMSE.


Tuning a neural network is a tradeoff of average performance and variability of that performance, with variability, meaning that it is generally good and reproducible.

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



## Tuning the Number of Neurons

In this section, we will investigate the effect of varying the number of neurons in the network.

The number of neurons affects the learning capacity of the network. Generally, more neurons would be able to learn more structure from the problem at the cost of longer training time. More learning capacity also creates the problem of potentially overfitting the training data.


We will use a batch size of 4 and 1000 training epochs.

Get Your Start in Machine Learning

## Diagnostic of 1000 Epochs and 1 Neuron

We will start with 1 neuron.

As a reminder, this is the second configuration tested from the epochs experiments.



## Diagnostic of 1000 Epochs and 2 Neurons

We can increase the number of neurons from 1 to 2. This would be expected to improve the learning

Get Your Start in Machine Learning

We can do this by changing the `n_neurons` variable in the `run()` function.

```
1 n_neurons = 2
```

Running this configuration prints the RMSE scores from the final epoch of each run.

The results suggest a good, but not great, general performance.

```
1 0) TrainRMSE=59.466223, TestRMSE=95.554547
2 1) TrainRMSE=58.752515, TestRMSE=101.908449
3 2) TrainRMSE=58.061139, TestRMSE=86.589039
4 3) TrainRMSE=55.883708, TestRMSE=94.747927
5 4) TrainRMSE=58.700290, TestRMSE=86.393213
6 5) TrainRMSE=60.564511, TestRMSE=101.956549
7 6) TrainRMSE=63.160916, TestRMSE=98.925108
8 7) TrainRMSE=60.148595, TestRMSE=95.082825
9 8) TrainRMSE=63.029242, TestRMSE=89.285092
10 9) TrainRMSE=57.794717, TestRMSE=91.425071
```

A line plot of the test and train RMSE scores each epoch is also created.

This is more telling. It shows a rapid decrease in test RMSE to about epoch 500-750 where an inflection point occurs on all runs. Meanwhile, the training dataset shows a continued decrease to the final epoch.


These are good signs of overfitting of the training dataset.

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE





Let's see if this trend continues with even more neurons.

## Diagnostic of 1000 Epochs and 3 Neurons

This section looks at the same configuration with the number of neurons increased to 3.

We can do this by setting the `n_neurons` variable in the `run()` function.

```
1 n_neurons = 3
```

Get Your Start in Machine Learning

Running this configuration prints the RMSE scores from the final epoch of each run.

The results are similar to the previous section; we do not see much general difference between the final epoch test scores for 2 or 3 neurons. The final train scores do appear to be lower with 3 neurons, perhaps showing an acceleration of overfitting.

The inflection point in the training dataset seems to be happening sooner than the 2 neurons experiment, perhaps at epoch 300-400.

These increases in the number of neurons may benefit from additional changes to slowing down the rate of learning. Such as the use of regularization methods like dropout, decrease to the batch size, and decrease to the number of training epochs.


```
1 0) TrainRMSE=55.686242, TestRMSE=90.955555
2 1) TrainRMSE=55.198617, TestRMSE=124.989622
3 2) TrainRMSE=55.767668, TestRMSE=104.751183
4 3) TrainRMSE=60.716046, TestRMSE=93.566307
5 4) TrainRMSE=57.703663, TestRMSE=110.813226
6 5) TrainRMSE=56.874231, TestRMSE=98.588524
7 6) TrainRMSE=57.206756, TestRMSE=94.386134
8 7) TrainRMSE=55.770377, TestRMSE=124.949862
9 8) TrainRMSE=56.876467, TestRMSE=95.059656
10 9) TrainRMSE=57.067810, TestRMSE=94.123620
```

A line plot of the test and train RMSE scores each epoch is also created.

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



## Summary of Results

Again, we can objectively compare the impact of increasing the number of neurons while keeping all other network configurations fixed.

In this section, we repeat each experiment 30 times and compare the average test RMSE performance with the number of neurons ranging from 1 to 5.

```
1 ...  
2  
3 # run a repeated experiment  
4 def experiment(repeats, series, neurons):
```

Get Your Start in Machine Learning

```

5     # transform data to be stationary
6     raw_values = series.values
7     diff_values = difference(raw_values, 1)
8     # transform data to be supervised learning
9     supervised = timeseries_to_supervised(diff_values, 1)
10    supervised_values = supervised.values
11    # split data into train and test-sets
12    train, test = supervised_values[0:-12], supervised_values[-12:]
13    # transform the scale of the data
14    scaler, train_scaled, test_scaled = scale(train, test)
15    # run experiment
16    error_scores = list()
17    for r in range(repeats):
18        # fit the model
19        batch_size = 4
20        train_trimmed = train_scaled[2:, :]
21        lstm_model = fit_lstm(train_trimmed, batch_size, 1000, neurons)
22        # forecast the entire training dataset to build up state for forecasting
23        train_resaped = train_trimmed[:, 0].reshape(len(train_trimmed), 1, 1)
24        lstm_model.predict(train_resaped, batch_size=batch_size)
25        # forecast test dataset
26        test_resaped = test_scaled[:, 0:-1]
27        test_resaped = test_resaped.reshape(len(test_resaped), 1, 1)
28        output = lstm_model.predict(test_resaped, batch_size=batch_size)
29        predictions = list()
30        for i in range(len(output)):
31            yhat = output[i, 0]
32            X = test_scaled[i, 0:-1]
33            # invert scaling
34            yhat = invert_scale(scaler, X, yhat)
35            # invert differencing
36            yhat = inverse_difference(raw_values, yhat, len(test_scaled)+1-i)
37            # store forecast
38            predictions.append(yhat)
39        # report performance
40        rmse = sqrt(mean_squared_error(raw_values[-12:], predictions))
41        print('%d) Test RMSE: %.3f' % (r+1, rmse))
42        error_scores.append(rmse)
43    return error_scores
44
45
46 # load dataset
47 series = read_csv('shampoo-sales.csv', header=0, parse_dates=[0], index_col=0, squeeze=True, date_parser=parser)
48 # experiment
49 repeats = 30
50 results = DataFrame()
51 # vary neurons

```

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning

```

52 neurons = [1, 2, 3, 4, 5]
53 for n in neurons:
54     results[str(n)] = experiment(repeats, series, n)
55 # summarize results
56 print(results.describe())
57 # save boxplot
58 results.boxplot()
59 pyplot.savefig('boxplot_neurons.png')

```

Running the experiment prints the summary statistics for each configuration.

From the mean performance alone, the results suggest a network configuration with 1 neuron as having the best performance over 1000 epochs with a batch size of 4. This configuration also shows the tightest variance.

		1	2	3	4	5
1	count	30.000000	30.000000	30.000000	30.000000	30.000000
2	mean	98.344696	103.268147	102.726894	112.453766	122.843032
3	std	13.538599	14.720989	12.905631	16.296657	25.586013
4	min	81.764721	87.731385	77.545899	85.632492	85.955093
5	25%	88.524334	94.040807	95.152752	102.477366	104.192588
6	50%	93.543948	100.330678	103.622600	110.906970	117.022724
7	75%	102.944050	105.087384	110.235754	118.653850	133.343669
8	max	132.934054	152.588092	130.551521	162.889845	184.678185


The box and whisker plot shows a clear trend in the median test set performance where the increase in the number of neurons leads to an increase in the test RMSE.

## Get Your Start in Machine Learning ×

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree**. Find out how in this *free and practical* email course.

START MY EMAIL COURSE

## Summary of All Results

We completed quite a few LSTM experiments on the Shampoo Sales dataset in this tutorial.

Generally, it seems that a stateful LSTM configured with 1 neuron, a batch size of 4, and trained for 1000 epochs might be a good configuration.

The results also suggest that perhaps this configuration with a batch size of 1 and fit for more epochs may be worthy of further exploration.

Get Your Start in Machine Learning

Tuning neural networks is difficult empirical work, and LSTMs are proving to be no exception.

This tutorial demonstrated the benefit of both diagnostic studies of configuration behavior over time, as well as objective studies of test RMSE.

Nevertheless, there are always more studies that could be performed. Some ideas are listed in the next section.

## Extensions

This section lists some ideas for extensions to the experiments performed in this tutorial.

If you explore any of these, report your results in the comments; I'd love to see what you come up with.

- **Dropout.** Slow down learning with regularization methods like dropout on the recurrent LSTM connections.
- **Layers.** Explore additional hierarchical learning capacity by adding more layers and varied number of units.
- **Regularization.** Explore how weight regularization, such as L1 and L2, can be used to slow down learning and improve generalization across configurations.
- **Optimization Algorithm.** Explore the use of [alternate optimization algorithms](#), such as classical gradient descent. Sometimes, speeding up or slow down learning can lead to benefits.
- **Loss Function.** Explore the use of [alternative loss functions](#) to see if these can be used to lift performance.
- **Features and Timesteps.** Explore the use of lag observations as input features and input time steps. Sometimes, using more time steps can improve learning and/or predictive capability of the model.
- **Larger Batch Size.** Explore larger batch sizes than 4, perhaps requiring further manipulation of the data.

## Summary

In this tutorial, you discovered how you can systematically investigate the configuration for an LSTM model.

Specifically, you learned:

- How to design a systematic test harness for evaluating model configurations.
- How to use model diagnostics over time, as well as objective prediction error to interpret model behavior.
- How to explore and interpret the effects of the number of training epochs, batch size, and number of neurons.

### Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.**


Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Do you have any questions about tuning LSTMs, or about this tutorial?

Ask your questions in the comments below and I will do my best to answer.

## Develop LSTMs for Sequence Prediction Today!



### Develop Your Own LSTM models in Minutes

...with just a few lines of python code

Discover how in my new Ebook:

[Long Short-Term Memory Networks with Python](#)

It provides **self-study tutorial**

*CNN LSTMs, Encoder-Decoder LSTMs, generative models, data*

### Finally Bring LSTM Recurrent Your Sequence Prediction

Skip the Academics. Just

[Click to learn more](#)

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



### About Jason Brownlee

Dr. Jason Brownlee is a husband, proud father, academic researcher, author, professional developer and a machine learning practitioner. He is dedicated to helping developers get started and get good at applied machine learning. [Learn more.](#)

[View all posts by Jason Brownlee](#) →

[Get Your Start in Machine Learning](#)



[< How to Seed State for LSTMs for Time Series Forecasting in Python](#)[How to Update LSTM Networks During Training for Time Series Forecasting >](#)

## 23 Responses to *How to Tune LSTM Hyperparameters with Keras for Time Series Forecasting*



**John Richards** April 12, 2017 at 8:51 am #

REPLY ↩

Awesome Work!



**Jason Brownlee** April 12, 2017 at 9:34 am #

Thanks John!



**Kunpeng Zhang** April 12, 2017 at 10:51 am #

line 137, in

```
results[str(e)] = experiment(repeats, series, e)
```

line 104, in experiment

```
lstm_model = fit_lstm(train_trimmed, batch_size, epochs, 1)
```

line 81, in fit\_lstm

```
model.fit(X, y, epochs=1, batch_size=batch_size, verbose=0, shuffle=False)
```

File "C:\Anaconda3\lib\site-packages\keras\models.py", line 654, in fit

```
str(kwargs))
```

TypeError: Received unknown keyword arguments: {'epochs': 1}

Is there something wrong?

### Get Your Start in Machine Learning



You can master applied Machine Learning **without the math or fancy degree**. Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning



**Jason Brownlee** April 13, 2017 at 9:54 am #

REPLY ↩

You need to upgrade to Keras v2.0 or higher.



**Logan** May 17, 2017 at 12:28 am #

REPLY ↩

You should replace `model.fit(X, y, epochs=1, ...)` for `model.fit(X, y, nb_epoch=1...)` It worked perfectly for me.



**Jason Brownlee** May 17, 2017 at 8:25 am #

The example was updated to use Keras v2.0 which changed the “nb\_epochs” argument

## Get Your Start in Machine Learning



You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



**Leo** April 12, 2017 at 6:12 pm #

Nice blog post once again. What is the size of the data set that you are using? What is the max I have a system with 8GB RAM?



**Jason Brownlee** April 13, 2017 at 9:56 am #

REPLY ↩

The examples use small <1 MB datasets.

The size of supported datasets depends on data types, number of rows and number of columns.

Consider doing some experiments with synthetic data to find the limits of your system.

Get Your Start in Machine Learning



**Lorenzo** April 13, 2017 at 1:08 am #

REPLY ↩

Amazing tutorial as always. Would you have an example of running the LSTM on a multivariate regression problem like the Walmart's on Kaggle (<https://www.kaggle.com/c/walmart-recruiting-store-sales-forecasting>) ?



**Jason Brownlee** April 13, 2017 at 10:02 am #

REPLY ↩

There should be some examples on the blog soon.



**Tykimos** April 13, 2017 at 4:28 am #

Great work! I have a question regarding batch\_size. I think that only one batch\_size is reasonable. If batch\_size is 4, there are 4 states separately. That means 4 states don't share each other. Although every sample in the batch is connected to the quaternary next sample.

For example,

1 > 5 > 9

2 > 6 > 10

3 > 7 > 11

4 > 8 > 12

## Get Your Start in Machine Learning



You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



**Jason Brownlee** April 13, 2017 at 10:12 am #

REPLY ↩

Sorry, I'm not sure I understand your question, perhaps you can restate it.

We are using stateful LSTMs and regardless of the batch size, state is only reset when we reset it explicitly with a call to `model.reset_states()`

Get Your Start in Machine Learning



**tykimos** April 14, 2017 at 1:56 am #

REPLY ↩

I think that the `batch_size` depends on not user tuning parameter but dataset design relative to the number of sequence set.

When `batch_size` is 4 and `stateful` is true, output of LSTM is `weight_count * batch_size`. This means that there are 4 different and independent states. It seems good for the following dataset :

A1-B1-C1-D1-A2-B2-C2-D2-A3-B3-C3-D3

- sample is 12
- `batch_size` is 4
- sequence set is 4

Because A isn't relative to others in sequence, the next of A1 should be not B1 but A2. For this we have to choose `batch_size` as 4.

For each epoch,  
A1-A2-A3 and reset  
B1-B2-B3 and reset  
C1-C2-C3 and reset  
D1-D2-D3 and reset

Your example is one sequence set like:

A1-A2-A3-A4-A5-A6-A7-A8-A9-A10-A11-A12

If we set `batch_size` as 4, state is transferred as the following:

A1-A5-A9 and reset  
A2-A6-A10 and reset  
A3-A7-A11 and reset  
A4-A8-A12 and reset

So, I think that `batch_size` should be 1 in your dataset. Other `batch_size` values are invalid.

## Get Your Start in Machine Learning



You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



**Jason Brownlee** April 14, 2017 at 8:53 am #

REPLY ↩

I agree with the first part, it makes sense to reset state at the natural end of a sequence.

I also agree that with the dataset used that there is no natural end to the sequence other than

Get Your Start in Machine Learning

I disagree that you “have to have” a batch size of 1. We can have a batch size of 1. We can also have a batch size equal to the sequence length.

My previous point is that batch size does not matter when `stateful=True` because we manage exactly when the state is reset. It does not matter what batch size is used, as long as the state is reset at the natural end of the sequence.

Yes, you are right, there is a bug. The regime of resetting state after each batch of 4 input patterns does not make sense. I'll schedule time to fix the examples and re-run the experiments.

Thanks for pointing this out and thanks for having the patients to help me see what you saw.

UPDATE: There is no fault, all weight updates are occurring within one epoch regardless of batch size.



**Jason Brownlee** April 24, 2017 at 8:02 am #

Update I have taken a much closer look at this code (it was written months ago)

I believe there is no fault.

Take a close look at the loop for running manual epochs.

Although the batch sizes vary, we are performing one entire epoch + all weight updates

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



**Sebastian** April 13, 2017 at 7:51 pm #

Great blog post!



**Jason Brownlee** April 14, 2017 at 8:44 am #

Thanks Sebastian.

REPLY ↩

Get Your Start in Machine Learning



**Jesse** April 26, 2017 at 4:54 pm #

REPLY ↩

Hi Jason,

Cool post! I already learnt a lot from your blogs.

I have 2 questions regarding this post, I hope you can help me:

1. Why aren't you specifying activation functions in your model layers (for the LSTM layer for example?) I read on the keras docs that no activation function is used if you don't pass one. It seems to me that a tanh activation would fit the [-1,1] scaling?
2. Do you always remove the increasing trend from the data?

Thanks a lot!



**Jason Brownlee** April 27, 2017 at 8:35 am #

I am using the default for LSTMs which are tanh and sigmoid.

Yes, making time series data stationary is a recommended in general.



**Sebastian** June 16, 2017 at 12:10 am #

Hi Jason,

very nice post, but still got a question.

When reversing difference for predictions, isn't it wrong to reverse it using the raw values? Instead, shouldn't you use the last prediction to reverse the difference?

Like, instead of  $y_{hat} = y_{hat} + history[-interval]$  it is  $y_{hat} = y_{hat} + predictions[-interval]$ ?

Or am I misunderstanding something?

Freetings

## Get Your Start in Machine Learning



You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Get Your Start in Machine Learning



**Jason Brownlee** June 16, 2017 at 8:02 am #

REPLY ↩

Yes, but if you have the real observations for a past time step, we should use them instead to better reflect the “real” level.

Does that help?



**Sepideh** September 30, 2017 at 7:42 am #

REPLY ↩

Thank you Dr. Jason for the great blog. Is it possible to use GPU for this example? If so, how can I apply it! I appreciate your help. The reason I want to use GPU is that I need to get results faster. I am using google compute engine with 6vCPUs and 39 GB memory.



**Jason Brownlee** September 30, 2017 at 7:48 am #

Perhaps. The GPU configuration is controlled by the library used by Keras, such as Tensor

I have found that it is better to run models sequentially on the GPU and instead use multiple GPUs/s

## Get Your Start in Machine Learning



You can master applied Machine Learning **without the math or fancy degree.**

Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Leave a Reply

Get Your Start in Machine Learning

Name (required)

Email (will not be published) (required)

Website

[SUBMIT COMMENT](#)

## Welcome to Machine Learning Mastery



Hi, I'm Dr. Jason Brownlee.

My goal is to make practitioners like YOU awesome at applied machine learning.

[Read More](#)

## Deep Learning for Sequence Prediction

Cut through the math and research papers.  
Discover 4 Models, 6 Architectures, and 14 Tutorials.


## Get Your Start in Machine Learning



You can master applied Machine Learning **without the math or fancy degree.**  
Find out how in this *free* and *practical* email course.

[START MY EMAIL COURSE](#)[Get Your Start in Machine Learning](#)



[Get Started With LSTMs in Python Today!](#)

## POPULAR

**Time Series Prediction with LSTM Recurrent Neural Networks in Python with Keras**

JULY 21, 2016

**Your First Machine Learning Project in Python Step-By-Step**

JUNE 10, 2016

**Develop Your First Neural Network in Python With Keras Step-By-Step**

MAY 24, 2016

**Sequence Classification with LSTM Recurrent Neural Networks in Python with Keras**

JULY 26, 2016

**How to Setup a Python Environment for Machine Learning and Deep Learning with Anaconda**

MARCH 13, 2017

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

[START MY EMAIL COURSE](#)[Get Your Start in Machine Learning](#)



Time Series Forecasting with the Long Short-Term Memory Network in Python

APRIL 7, 2017




Multi-Class Classification Tutorial with the Keras Deep Learning Library

JUNE 2, 2016




Regression Tutorial with the Keras Deep Learning Library in Python

JUNE 9, 2016



Multivariate Time Series Forecasting with LSTMs in Keras

AUGUST 14, 2017



How to Implement the Backpropagation Algorithm From Scratch In Python

NOVEMBER 7, 2016

## Get Your Start in Machine Learning

You can master applied Machine Learning **without the math or fancy degree.** Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

© 2017 Machine Learning Mastery. All Rights Reserved.

[Privacy](#) | [Contact](#) | [About](#)

Get Your Start in Machine Learning