



Search...

Q

Want help with machine learning? [Take the FREE Crash-Course.](#)

How To Implement The Decision Tree Algorithm From Scratch In Python

by **Jason Brownlee** on November 9, 2016 in **Algorithms From Scratch**

6

159

Decision trees are a powerful prediction method and extremely popular.

They are popular because the final model is so easy to understand by practitioners and domain experts alike. The final decision tree can explain exactly why a specific prediction was made, making it very attractive for operational use.

Decision trees also provide the foundation for more advanced ensemble methods such as bagging, random forests and gradient boosting.

In this tutorial, you will discover how to implement the [Classification And Regression Tree algorithm](#) from scratch with Python.

After completing this tutorial, you will know:

- How to calculate and evaluate candidate split points in a data.
- How to arrange splits into a decision tree structure.
- How to apply the classification and regression tree algorithm to a real problem.

Let’s get started.

- **Update Jan/2017:** Changed the calculation of fold_size in cross_validation_split() to always be an integer. Fixes issues with Python 3.
- **Update Feb/2017:** Fixed a bug in build_tree.



How To Implement The Decision Tree Algorithm From Scratch In Python
Photo by [Martin Cathrae](#), some rights reserved.

Descriptions

This section provides a brief introduction to the Classification and Regression Tree algorithm and the Banknote dataset used in this tutorial.

Classification and Regression Trees

Classification and Regression Trees or CART for short is an acronym introduced by Leo Breiman to refer to Decision Tree algorithms that can be used for classification or regression predictive modeling problems.

We will focus on using CART for classification in this tutorial.

The representation of the CART model is a binary tree. This is the same binary tree from algorithms and data structures, nothing too fancy (each node can have zero, one or two child nodes).

A node represents a single input variable (X) and a split point on that variable, assuming the variable is numeric. The leaf nodes (also called terminal nodes) of the tree contain an output variable (y) which is used to make a prediction.

Once created, a tree can be navigated with a new row of data following each branch with the splits until a final prediction is made.

Creating a binary decision tree is actually a process of dividing up the input space. A greedy approach is used to divide the space called recursive binary splitting. This is a numerical procedure where all the values are lined up and different split points are tried and tested using a cost function.

The split with the best cost (lowest cost because we minimize cost) is selected. All input variables and all possible split points are evaluated and chosen in a greedy manner based on the cost function.

- **Regression:** The cost function that is minimized to choose split points is the sum squared error across all training samples that fall within the rectangle.
- **Classification:** The Gini cost function is used which provides an indication of how pure the nodes are, where node purity refers to how mixed the training data assigned to each node is.

Splitting continues until nodes contain a minimum number of training examples or a maximum tree depth is reached.

Banknote Dataset

The banknote dataset involves predicting whether a given banknote is authentic given a number of measures taken from a photograph.

The dataset contains 1,372 with 5 numeric variables. It is a classification problem with two classes (binary classification).

Below provides a list of the five variables in the dataset.

1. variance of Wavelet Transformed image (continuous).
2. skewness of Wavelet Transformed image (continuous).
3. kurtosis of Wavelet Transformed image (continuous).
4. entropy of image (continuous).
5. class (integer).

Below is a sample of the first 5 rows of the dataset

1	3.6216	8.6661	-2.8073	-0.44699	0
2	4.5459	8.1674	-2.4586	-1.4621	0
3	3.866	-2.6383	1.9242	0.10645	0
4	3.4566	9.5228	-4.0112	-3.5944	0
5	0.32924	-4.4552	4.5718	-0.9888	0
6	4.3684	9.6718	-3.9606	-3.1625	0

Using the Zero Rule Algorithm to predict the most common class value, the baseline accuracy on the problem is about 50%.

You can learn more and download the dataset from the [UCI Machine Learning Repository](#).

Download the dataset and place it in your current working directory with the filename **data_banknote_authentication.txt**.

Tutorial

This tutorial is broken down into 5 parts:

1. Gini Index.
2. Create Split.
3. Build a Tree.
4. Make a Prediction.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this*free* and *practical*email course.

START MY EMAIL COURSE

5. Banknote Case Study.

These steps will give you the foundation that you need to implement the CART algorithm from scratch and apply it to your own predictive modeling problems.

1. Gini Index

The Gini index is the name of the cost function used to evaluate splits in the dataset.

A split in the dataset involves one input attribute and one value for that attribute. It can be used to divide training patterns into two groups of rows.

A Gini score gives an idea of how good a split is by how mixed the classes are in the two groups created by the split. A perfect separation results in a Gini score of 0, whereas the worst case split that results in 50/50 classes in each group results in a Gini score of 1.0 (for a 2 class problem).

Calculating Gini is best demonstrated with an example.

We have two groups of data with 2 rows in each group. The rows in the first group all belong to class 0 and the rows in the second group belong to class 1, so it's a perfect split.

We first need to calculate the proportion of classes in each group.

```
1 proportion = count(class_value) / count(rows)
```

The proportions for this example would be:

```
1 group_1_class_0 = 2 / 2 = 1
2 group_1_class_1 = 0 / 2 = 0
3 group_2_class_0 = 0 / 2 = 0
4 group_2_class_1 = 2 / 2 = 1
```

Gini is then calculated as follows:

```
1 gini_index = sum(proportion * (1.0 - proportion))
```

Across all of the proportions calculated for each group and each class value. In our case, this would be calculated as:

```
1 gini_index = (group_1_class_0 * (1.0 - group_1_class_0)) +
2             (group_1_class_1 * (1.0 - group_1_class_1)) +
3             (group_2_class_0 * (1.0 - group_2_class_0)) +
4             (group_2_class_1 * (1.0 - group_2_class_1))
```

Or:

```
1 gini_index = 0 + 0 + 0 + 0 = 0
```

Below is a function named **gini_index()** the calculates the Gini index for a list of groups and a list of known class values.

You can see that there are some safety checks in there to avoid a divide by zero for an empty group.

```
1 # Calculate the Gini index for a split dataset
2 def gini_index(groups, class_values):
3     gini = 0.0
4     for class_value in class_values:
5         for group in groups:
6             size = len(group)
7             if size == 0:
8                 continue
9             proportion = [row[-1] for row in group].count(class_value) / float(size)
10            gini += (proportion * (1.0 - proportion))
11    return gini
```

We can test this function with our worked example above. We can also test it for the worst case of a 50/50 split in each group. The complete example is listed below.

```
1 # Calculate the Gini index for a split dataset
2 def gini_index(groups, class_values):
3     gini = 0.0
4     for class_value in class_values:
5         for group in groups:
6             size = len(group)
7             if size == 0:
8                 continue
9             proportion = [row[-1] for row in group].count(class_value) / float(size)
10            gini += (proportion * (1.0 - proportion))
11    return gini
12
13 # test Gini values
14 print(gini_index([[[1, 1], [1, 0]], [[1, 1], [1, 0]]], [0, 1]))
15 print(gini_index([[[1, 0], [1, 0]], [[1, 1], [1, 1]]], [0, 1]))
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this*free* and *practical*email course.

START MY EMAIL COURSE

Running the example prints the two Gini scores, first the score for the worst case at 1.0 followed by the score for the best case at 0.0.

```
1 1.0
2 0.0
```

Now that we know how to evaluate the results of a split, let’s look at creating splits.

2. Create Split

A split is comprised of an attribute in the dataset and a value.

We can summarize this as the index of an attribute to split and the value by which to split rows on that attribute. This is just a useful shorthand for indexing into rows of data.

Creating a split involves three parts, the first we have already looked at which is calculating the Gini score. The remaining two parts are:

- 1. Splitting a Dataset.
- 2. Evaluating All Splits.

Let’s take a look at each.

2.1. Splitting a Dataset

Splitting a dataset means separating a dataset into two lists of rows given the index of an attribute and a split value for that attribute.

Once we have the two groups, we can then use our Gini score above to evaluate the cost of the split.

Splitting a dataset involves iterating over each row, checking if the attribute value is below or above the split value and assigning it to the left or right group respectively.

Below is a function named **test_split()** that implements this procedure.

```
1 # Split a dataset based on an attribute and an attribute value
2 def test_split(index, value, dataset):
3     left, right = list(), list()
4     for row in dataset:
5         if row[index] < value:
6             left.append(row)
7         else:
8             right.append(row)
9     return left, right
```

Not much to it.

Note that the right group contains all rows with a value at the index above or equal to the split value.

2.2. Evaluating All Splits

With the Gini function above and the test split function we now have everything we need to evaluate splits.

Given a dataset, we must check every value on each attribute as a candidate split, evaluate the cost of the split and find the best possible split we could make.

Once the best split is found, we can use it as a node in our decision tree.

This is an exhaustive and greedy algorithm.

We will use a dictionary to represent a node in the decision tree as we can store data by name. When selecting the best split and using it as a new node for the tree we will store the index of the chosen attribute, the value of that attribute by which to split and the two groups of data split by the chosen split point.

Each group of data is its own small dataset of just those rows assigned to the left or right group. If we have more than two classes, we might split each group again, recursively as we build out our decision tree.

Below is a function named **get_split()** that implements this procedure. You can see that it iterates over each attribute, then each value for that attribute, splitting and evaluating splits as it goes.

The best split is recorded and then returned after all checks are complete.

```
1 # Select the best split point for a dataset
2 def get_split(dataset):
3     class_values = list(set(row[-1] for row in dataset))
4     b_index, b_value, b_score, b_groups = 999, 999, 999, None
5     for index in range(len(dataset[0])-1):
6         for row in dataset:
7             groups = test_split(index, row[index], dataset)
8             gini = gini_index(groups, class_values)
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.


START MY EMAIL COURSE


```
9         if gini < b_score:
10             b_index, b_value, b_score, b_groups = index, row[index], gini, groups
11     return {'index':b_index, 'value':b_value, 'groups':b_groups}
```

We can contrive a small dataset to test out this function and our whole dataset splitting process.

1	X1	X2	Y
2	2.771244718	1.784783929	0
3	1.728571309	1.169761413	0
4	3.678319846	2.81281357	0
5	3.961043357	2.61995032	0
6	2.999208922	2.209014212	0
7	7.497545867	3.162953546	1
8	9.00220326	3.339047188	1
9	7.444542326	0.476683375	1
10	10.12493903	3.234550982	1
11	6.642287351	3.319983761	1

We can plot this dataset using separate colors for each class. You can see that it would not be difficult to manually pick a value of X1 (x-axis on the plot) to split this dataset.



The example below puts all of this together.

```
1  # Split a dataset based on an attribute and an attribute value
2  def test_split(index, value, dataset):
3      left, right = list(), list()
4      for row in dataset:
5          if row[index] < value:
6              left.append(row)
7          else:
8              right.append(row)
9      return left, right
10
11 # Calculate the Gini index for a split dataset
12 def gini_index(groups, class_values):
13     gini = 0.0
14     for class_value in class_values:
15         for group in groups:
16             size = len(group)
17             if size == 0:
18                 continue
19             proportion = [row[-1] for row in group].count(class_value) / float(size)
20             gini += (proportion * (1.0 - proportion))
21     return gini
22
23 # Select the best split point for a dataset
24 def get_split(dataset):
25     class_values = list(set(row[-1] for row in dataset))
26     b_index, b_value, b_score, b_groups = 999, 999, 999, None
27     for index in range(len(dataset[0])-1):
28         for row in dataset:
29             groups = test_split(index, row[index], dataset)
30             gini = gini_index(groups, class_values)
31             print('X%d < %.3f Gini=%.3f' % ((index+1), row[index], gini))
32             if gini < b_score:
33                 b_index, b_value, b_score, b_groups = index, row[index], gini, groups
34     return {'index':b_index, 'value':b_value, 'groups':b_groups}
35
36 dataset = [[2.771244718,1.784783929,0],
37            [1.728571309,1.169761413,0],
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

```
38     [3.678319846,2.81281357,0],
39     [3.961043357,2.61995032,0],
40     [2.999208922,2.209014212,0],
41     [7.497545867,3.162953546,1],
42     [9.00220326,3.339047188,1],
43     [7.444542326,0.476683375,1],
44     [10.12493903,3.234550982,1],
45     [6.642287351,3.319983761,1]]
46 split = get_split(dataset)
47 print('Split: [X%d < %.3f]' % ((split['index']+1), split['value']))
```

The `get_split()` function was modified to print out each split point and it’s Gini index as it was evaluated.

Running the example prints all of the Gini scores and then prints the score of best split in the dataset of $X_1 < 6.642$ with a Gini Index of 0.0 or a perfect split.

```
1 X1 < 2.771 Gini=0.494
2 X1 < 1.729 Gini=0.500
3 X1 < 3.678 Gini=0.408
4 X1 < 3.961 Gini=0.278
5 X1 < 2.999 Gini=0.469
6 X1 < 7.498 Gini=0.408
7 X1 < 9.002 Gini=0.469
8 X1 < 7.445 Gini=0.278
9 X1 < 10.125 Gini=0.494
10 X1 < 6.642 Gini=0.000
11 X2 < 1.785 Gini=1.000
12 X2 < 1.170 Gini=0.494
13 X2 < 2.813 Gini=0.640
14 X2 < 2.620 Gini=0.819
15 X2 < 2.209 Gini=0.934
16 X2 < 3.163 Gini=0.278
17 X2 < 3.339 Gini=0.494
18 X2 < 0.477 Gini=0.500
19 X2 < 3.235 Gini=0.408
20 X2 < 3.320 Gini=0.469
21 Split: [X1 < 6.642]
```

Now that we know how to find the best split points in a dataset or list of rows, let’s see how we can use it to build out a decision tree.

3. Build a Tree

Creating the root node of the tree is easy.

We call the above `get_split()` function using the entire dataset.

Adding more nodes to our tree is more interesting.

Building a tree may be divided into 3 main parts:

1. Terminal Nodes.
2. Recursive Splitting.
3. Building a Tree.

3.1. Terminal Nodes

We need to decide when to stop growing a tree.

We can do that using the depth and the number of rows that the node is responsible for in the training dataset.

- **Maximum Tree Depth.** This is the maximum number of nodes from the root node of the tree. Once a maximum depth of the tree is met, we must stop splitting adding new nodes. Deeper trees are more complex and are more likely to overfit the training data.
- **Minimum Node Records.** This is the minimum number of training patterns that a given node is responsible for. Once at or below this minimum, we must stop splitting and adding new nodes. Nodes that account for too few training patterns are expected to be too specific and are likely to overfit the training data.

These two approaches will be user-specified arguments to our tree building procedure.

There is one more condition. It is possible to choose a split in which all rows belong to one splitting and adding child nodes as we will have no records to split on one side or another.

Now we have some ideas of when to stop growing the tree. When we do stop growing at a node, the node is used to make a final prediction.

This is done by taking the group of rows assigned to that node and selecting the most common class value to make predictions.

Below is a function named `to_terminal()` that will select a class value for a group of rows. It will return the most common class value for the rows.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

```
1 # Create a terminal node value
2 def to_terminal(group):
3     outcomes = [row[-1] for row in group]
4     return max(set(outcomes), key=outcomes.count)
```

3.2. Recursive Splitting

We know how and when to create terminal nodes, now we can build our tree.

Building a decision tree involves calling the above developed **get_split()** function over and over again on the groups created for each node.

New nodes added to an existing node are called child nodes. A node may have zero children (a terminal node), one child (one side makes a prediction directly) or two child nodes. We will refer to the child nodes as left and right in the dictionary representation of a given node.

Once a node is created, we can create child nodes recursively on each group of data from the split by calling the same function again.

Below is a function that implements this recursive procedure. It takes a node as an argument as well as the maximum depth, minimum number of patterns in a node and the current depth of a node.

You can imagine how this might be first called passing in the root node and the depth of 1. This function is best explained in steps:

1. Firstly, the two groups of data split by the node are extracted for use and deleted from the node. As we work on these groups the node no longer requires access to these data.
2. Next, we check if either left or right group of rows is empty and if so we create a terminal node using what records we do have.
3. We then check if we have reached our maximum depth and if so we create a terminal node.
4. We then process the left child, creating a terminal node if the group of rows is too small, otherwise creating and adding the left node in a depth first fashion until the bottom of the tree is reached on this branch.
5. The right side is then processed in the same manner, as we rise back up the constructed tree to the root.

```
1 # Create child splits for a node or make terminal
2 def split(node, max_depth, min_size, depth):
3     left, right = node['groups']
4     del(node['groups'])
5     # check for a no split
6     if not left or not right:
7         node['left'] = node['right'] = to_terminal(left + right)
8         return
9     # check for max depth
10    if depth >= max_depth:
11        node['left'], node['right'] = to_terminal(left), to_terminal(right)
12        return
13    # process left child
14    if len(left) <= min_size:
15        node['left'] = to_terminal(left)
16    else:
17        node['left'] = get_split(left)
18        split(node['left'], max_depth, min_size, depth+1)
19    # process right child
20    if len(right) <= min_size:
21        node['right'] = to_terminal(right)
22    else:
23        node['right'] = get_split(right)
24        split(node['right'], max_depth, min_size, depth+1)
```

3.3. Building a Tree

We can now put all of the pieces together.

Building the tree involves creating the root node and calling the **split()** function that then calls itself recursively to build out the whole tree.

Below is the small **build_tree()** function that implements this procedure.

```
1 # Build a decision tree
2 def build_tree(train, max_depth, min_size):
3     root = get_split(train)
4     split(root, max_depth, min_size, 1)
5     return root
```

We can test out this whole procedure using the small dataset we contrived above.

Below is the complete example.

Also included is a small **print_tree()** function that recursively prints out nodes of the decision tree. Striking as a real decision tree diagram, it gives an idea of the tree structure and decisions

```
1 # Split a dataset based on an attribute and an attribute value
2 def test_split(index, value, dataset):
3     left, right = list(), list()
4     for row in dataset:
5         if row[index] < value:
6             left.append(row)
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

```
7         else:
8             right.append(row)
9         return left, right
10
11 # Calculate the Gini index for a split dataset
12 def gini_index(groups, class_values):
13     gini = 0.0
14     for class_value in class_values:
15         for group in groups:
16             size = len(group)
17             if size == 0:
18                 continue
19             proportion = [row[-1] for row in group].count(class_value) / float(size)
20             gini += (proportion * (1.0 - proportion))
21     return gini
22
23 # Select the best split point for a dataset
24 def get_split(dataset):
25     class_values = list(set(row[-1] for row in dataset))
26     b_index, b_value, b_score, b_groups = 999, 999, 999, None
27     for index in range(len(dataset[0])-1):
28         for row in dataset:
29             groups = test_split(index, row[index], dataset)
30             gini = gini_index(groups, class_values)
31             if gini < b_score:
32                 b_index, b_value, b_score, b_groups = index, row[index], gini, groups
33     return {'index':b_index, 'value':b_value, 'groups':b_groups}
34
35 # Create a terminal node value
36 def to_terminal(group):
37     outcomes = [row[-1] for row in group]
38     return max(set(outcomes), key=outcomes.count)
39
40 # Create child splits for a node or make terminal
41 def split(node, max_depth, min_size, depth):
42     left, right = node['groups']
43     del(node['groups'])
44     # check for a no split
45     if not left or not right:
46         node['left'] = node['right'] = to_terminal(left + right)
47         return
48     # check for max depth
49     if depth >= max_depth:
50         node['left'], node['right'] = to_terminal(left), to_terminal(right)
51         return
52     # process left child
53     if len(left) <= min_size:
54         node['left'] = to_terminal(left)
55     else:
56         node['left'] = get_split(left)
57         split(node['left'], max_depth, min_size, depth+1)
58     # process right child
59     if len(right) <= min_size:
60         node['right'] = to_terminal(right)
61     else:
62         node['right'] = get_split(right)
63         split(node['right'], max_depth, min_size, depth+1)
64
65 # Build a decision tree
66 def build_tree(train, max_depth, min_size):
67     root = get_split(train)
68     split(root, max_depth, min_size, 1)
69     return root
70
71 # Print a decision tree
72 def print_tree(node, depth=0):
73     if isinstance(node, dict):
74         print('%s[X%d < %.3f]' % ((depth*' ', (node['index']+1), node['value'])))
75         print_tree(node['left'], depth+1)
76         print_tree(node['right'], depth+1)
77     else:
78         print('%s[%s]' % ((depth*' ', node)))
79
80 dataset = [[2.771244718,1.784783929,0],
81            [1.728571309,1.169761413,0],
82            [3.678319846,2.81281357,0],
83            [3.961043357,2.61995032,0],
84            [2.999208922,2.209014212,0],
85            [7.497545867,3.162953546,1],
86            [9.00220326,3.339047188,1],
87            [7.444542326,0.476683375,1],
88            [10.12493903,3.234550982,1],
89            [6.642287351,3.319983761,1]]
90 tree = build_tree(dataset, 1, 1)
91 print_tree(tree)
```

We can vary the maximum depth argument as we run this example and see the effect on the resulting decision tree.

With a maximum depth of 1 (the second parameter in the call to the **build_tree()** function), we discovered in the previous section. This is a tree with one node, also called a decision stump.

```
1 [X1 < 6.642]
2 [0]
3 [1]
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Increasing the maximum depth to 2, we are forcing the tree to make splits even when none are required. The **X1** attribute is then used again by both the left and right children of the root node to split up the already perfect mix of classes.

```
1 [X1 < 6.642]
2 [X1 < 2.771]
3 [0]
4 [0]
5 [X1 < 7.498]
6 [1]
7 [1]
```

Finally, and perversely, we can force one more level of splits with a maximum depth of 3.

```
1 [X1 < 6.642]
2 [X1 < 2.771]
3 [0]
4 [X1 < 2.771]
5 [0]
6 [0]
7 [X1 < 7.498]
8 [X1 < 7.445]
9 [1]
10 [1]
11 [X1 < 7.498]
12 [1]
13 [1]
```

These tests show that there is great opportunity to refine the implementation to avoid unnecessary splits. This is left as an extension.

Now that we can create a decision tree, let’s see how we can use it to make predictions on new data.

4. Make a Prediction

Making predictions with a decision tree involves navigating the tree with the specifically provided row of data.

Again, we can implement this using a recursive function, where the same prediction routine is called again with the left or the right child nodes, depending on how the split affects the provided data.

We must check if a child node is either a terminal value to be returned as the prediction, or if it is a dictionary node containing another level of the tree to be considered.

Below is the **predict()** function that implements this procedure. You can see how the index and value in a given node

You can see how the index and value in a given node is used to evaluate whether the row of provided data falls on the left or the right of the split.

```
1 # Make a prediction with a decision tree
2 def predict(node, row):
3     if row[node['index']] < node['value']:
4         if isinstance(node['left'], dict):
5             return predict(node['left'], row)
6         else:
7             return node['left']
8     else:
9         if isinstance(node['right'], dict):
10            return predict(node['right'], row)
11        else:
12            return node['right']
```

We can use our contrived dataset to test this function. Below is an example that uses a hard-coded decision tree with a single node that best splits the data (a decision stump).

The example makes a prediction for each row in the dataset.

```
1 # Make a prediction with a decision tree
2 def predict(node, row):
3     if row[node['index']] < node['value']:
4         if isinstance(node['left'], dict):
5             return predict(node['left'], row)
6         else:
7             return node['left']
8     else:
9         if isinstance(node['right'], dict):
10            return predict(node['right'], row)
11        else:
12            return node['right']
13
14 dataset = [[2.771244718,1.784783929,0],
15            [1.728571309,1.169761413,0],
16            [3.678319846,2.81281357,0],
17            [3.961043357,2.61995032,0],
18            [2.999208922,2.209014212,0],
19            [7.497545867,3.162953546,1],
20            [9.00220326,3.339047188,1],
21            [7.444542326,0.476683375,1],
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this*free* and *practical*email course.

START MY EMAIL COURSE

```
22     [10.12493903,3.234550982,1],
23     [6.642287351,3.319983761,1]]
24
25 # predict with a stump
26 stump = {'index': 0, 'right': 1, 'value': 6.642287351, 'left': 0}
27 for row in dataset:
28     prediction = predict(stump, row)
29     print('Expected=%d, Got=%d' % (row[-1], prediction))
```

Running the example prints the correct prediction for each row, as expected.

```
1 Expected=0, Got=0
2 Expected=0, Got=0
3 Expected=0, Got=0
4 Expected=0, Got=0
5 Expected=0, Got=0
6 Expected=1, Got=1
7 Expected=1, Got=1
8 Expected=1, Got=1
9 Expected=1, Got=1
10 Expected=1, Got=1
```

We now know how to create a decision tree and use it to make predictions. Now, let's apply it to a real dataset.

5. Banknote Case Study

This section applies the CART algorithm to the Bank Note dataset.

The first step is to load the dataset and convert the loaded data to numbers that we can use to calculate split points. For this we will use the helper function `load_csv()` to load the file and `str_column_to_float()` to convert string numbers to floats.

We will evaluate the algorithm using k-fold cross-validation with 5 folds. This means that $1372/5=274.4$ or just over 270 records will be used in each fold. We will use the helper functions `evaluate_algorithm()` to evaluate the algorithm with cross-validation and `accuracy_metric()` to calculate the accuracy of predictions.

A new function named `decision_tree()` was developed to manage the application of the CART algorithm, first creating the tree from the training dataset, then using the tree to make predictions on a test dataset.

The complete example is listed below.

```
1  # CART on the Bank Note dataset
2  from random import seed
3  from random import randrange
4  from csv import reader
5
6  # Load a CSV file
7  def load_csv(filename):
8      file = open(filename, "rb")
9      lines = reader(file)
10     dataset = list(lines)
11     return dataset
12
13 # Convert string column to float
14 def str_column_to_float(dataset, column):
15     for row in dataset:
16         row[column] = float(row[column].strip())
17
18 # Split a dataset into k folds
19 def cross_validation_split(dataset, n_folds):
20     dataset_split = list()
21     dataset_copy = list(dataset)
22     fold_size = int(len(dataset) / n_folds)
23     for i in range(n_folds):
24         fold = list()
25         while len(fold) < fold_size:
26             index = randrange(len(dataset_copy))
27             fold.append(dataset_copy.pop(index))
28         dataset_split.append(fold)
29     return dataset_split
30
31 # Calculate accuracy percentage
32 def accuracy_metric(actual, predicted):
33     correct = 0
34     for i in range(len(actual)):
35         if actual[i] == predicted[i]:
36             correct += 1
37     return correct / float(len(actual)) * 100.0
38
39 # Evaluate an algorithm using a cross validation split
40 def evaluate_algorithm(dataset, algorithm, n_folds, *args):
41     folds = cross_validation_split(dataset, n_folds)
42     scores = list()
43     for fold in folds:
44         train_set = list(folds)
45         train_set.remove(fold)
46         train_set = sum(train_set, [])
47         test_set = list()
48         for row in fold:
49             row_copy = list(row)
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

```
50         test_set.append(row_copy)
51         row_copy[-1] = None
52         predicted = algorithm(train_set, test_set, *args)
53         actual = [row[-1] for row in fold]
54         accuracy = accuracy_metric(actual, predicted)
55         scores.append(accuracy)
56     return scores
57
58 # Split a dataset based on an attribute and an attribute value
59 def test_split(index, value, dataset):
60     left, right = list(), list()
61     for row in dataset:
62         if row[index] < value:
63             left.append(row)
64         else:
65             right.append(row)
66     return left, right
67
68 # Calculate the Gini index for a split dataset
69 def gini_index(groups, class_values):
70     gini = 0.0
71     for class_value in class_values:
72         for group in groups:
73             size = len(group)
74             if size == 0:
75                 continue
76             proportion = [row[-1] for row in group].count(class_value) / float(size)
77             gini += (proportion * (1.0 - proportion))
78     return gini
79
80 # Select the best split point for a dataset
81 def get_split(dataset):
82     class_values = list(set(row[-1] for row in dataset))
83     b_index, b_value, b_score, b_groups = 999, 999, 999, None
84     for index in range(len(dataset[0])-1):
85         for row in dataset:
86             groups = test_split(index, row[index], dataset)
87             gini = gini_index(groups, class_values)
88             if gini < b_score:
89                 b_index, b_value, b_score, b_groups = index, row[index], gini, groups
90     return {'index':b_index, 'value':b_value, 'groups':b_groups}
91
92 # Create a terminal node value
93 def to_terminal(group):
94     outcomes = [row[-1] for row in group]
95     return max(set(outcomes), key=outcomes.count)
96
97 # Create child splits for a node or make terminal
98 def split(node, max_depth, min_size, depth):
99     left, right = node['groups']
100     del(node['groups'])
101     # check for a no split
102     if not left or not right:
103         node['left'] = node['right'] = to_terminal(left + right)
104         return
105     # check for max depth
106     if depth >= max_depth:
107         node['left'], node['right'] = to_terminal(left), to_terminal(right)
108         return
109     # process left child
110     if len(left) <= min_size:
111         node['left'] = to_terminal(left)
112     else:
113         node['left'] = get_split(left)
114         split(node['left'], max_depth, min_size, depth+1)
115     # process right child
116     if len(right) <= min_size:
117         node['right'] = to_terminal(right)
118     else:
119         node['right'] = get_split(right)
120         split(node['right'], max_depth, min_size, depth+1)
121
122 # Build a decision tree
123 def build_tree(train, max_depth, min_size):
124     root = get_split(train)
125     split(root, max_depth, min_size, 1)
126     return root
127
128 # Make a prediction with a decision tree
129 def predict(node, row):
130     if row[node['index']] < node['value']:
131         if isinstance(node['left'], dict):
132             return predict(node['left'], row)
133         else:
134             return node['left']
135     else:
136         if isinstance(node['right'], dict):
137             return predict(node['right'], row)
138         else:
139             return node['right']
140
141 # Classification and Regression Tree Algorithm
142 def decision_tree(train, test, max_depth, min_size):
143     tree = build_tree(train, max_depth, min_size)
144     predictions = list()
145     for row in test:
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

[START MY EMAIL COURSE](#)

```
146         prediction = predict(tree, row)
147         predictions.append(prediction)
148     return(predictions)
149
150 # Test CART on Bank Note dataset
151 seed(1)
152 # load and prepare data
153 filename = 'data_banknote_authentication.csv'
154 dataset = load_csv(filename)
155 # convert string attributes to integers
156 for i in range(len(dataset[0])):
157     str_column_to_float(dataset, i)
158 # evaluate algorithm
159 n_folds = 5
160 max_depth = 5
161 min_size = 10
162 scores = evaluate_algorithm(dataset, decision_tree, n_folds, max_depth, min_size)
163 print('Scores: %s' % scores)
164 print('Mean Accuracy: %.3f%%' % (sum(scores)/float(len(scores))))
```

The example uses the max tree depth of 5 layers and the minimum number of rows per node to 10. These parameters to CART were chosen with a little experimentation, but are by no means are they optimal.

Running the example prints the average classification accuracy on each fold as well as the average performance across all folds.

You can see that CART and the chosen configuration achieved a mean classification accuracy of about 83% which is dramatically better than the Zero Rule algorithm that achieved 50% accuracy.

```
1 Scores: [83.57664233576642, 82.84671532846716, 86.86131386861314, 79.92700729927007, 82.11678832116789]
2 Mean Accuracy: 83.066%
```

Extensions

This section lists extensions to this tutorial that you may wish to explore.

- **Algorithm Tuning.** The application of CART to the Bank Note dataset was not tuned. Experiment with different parameter values and see if you can achieve better performance.
- **Cross Entropy.** Another cost function for evaluating splits is cross entropy (logloss). You could implement and experiment with this alternative cost function.
- **Tree Pruning.** An important technique for reducing overfitting of the training dataset is to prune the trees. Investigate and implement tree pruning methods.
- **Categorical Dataset.** The example was designed for input data with numerical or ordinal input attributes, experiment with categorical input data and splits that may use equality instead of ranking.
- **Regression.** Adapt the tree for regression using a different cost function and method for creating terminal nodes.
- **More Datasets.** Apply the algorithm to more datasets on the UCI Machine Learning Repository.

Did you explore any of these extensions?
Share your experiences in the comments below.

Review

In this tutorial, you discovered how to implement the decision tree algorithm from scratch with Python.

Specifically, you learned:

- How to select and evaluate split points in a training dataset.
- How to recursively build a decision tree from multiple splits.
- How to apply the CART algorithm to a real world classification predictive modeling problem.

Do you have any questions?
Ask your questions in the comments below and I will do my best to answer them.

Want to Code Algorithms in Python

Code Your First Algorithm in Minutes

...with step-by-step tutorials on real-world datasets

Discover how in my new Ebook: [Machine Learning Algorithms](#)

It covers **18 tutorial lessons** with all the code for **12 top algorithms** including Linear Regression, k-Nearest Neighbors, Stochastic Gradient Descent and more.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE

Finally, Pull Back the Curtain on
Machine Learning Algorithms

Skip the Academics. Just Results.

[Click to learn more.](#)



About Jason Brownlee

Dr. Jason Brownlee is a husband, proud father, academic researcher, author, professional developer and a machine learning practitioner. He is dedicated to helping developers get started and get good at applied machine learning. [Learn more.](#)

[View all posts by Jason Brownlee](#) →

< How to Implement the Backpropagation Algorithm From Scratch In Python

How to Implement Bagging From Scratch With Python >

60 Responses to *How To Implement The Decision Tree Algorithm From Scratch In Python*



steve November 23, 2016 at 4:02 am <#>

REPLY ↩

Super good .. Thanks a lot for sharing



Jason Brownlee November 23, 2016 at 9:01 am <#>

REPLY ↩

I'm glad you found it useful steve.



jonathan November 27, 2016 at 9:22 am <#>

REPLY ↩

can this code be used for a multinomial Decision tree dataset?



Jason Brownlee November 27, 2016 at 10:22 am <#>

REPLY ↩

It can with some modification.



STORM RICK November 29, 2016 at 1:02 am <#>

REPLY ↩

What modifications would you recommend?



Jason Brownlee November 29, 2016 at 8:53 am <#>

REPLY ↩

Specifically the handling of evaluating and selecting nominal values at split points.



Mike December 24, 2016 at 2:48 pm <#>

Thanks for detailed description and code.

I tried to run and got 'ValueError: empty range for randrange()' in line 26:

```
index = randrange(len(dataset_copy))
```

if replace dataset_copy to list(dataset) and run this line manually it works.




Jason Brownlee December 26, 2016 at 7:39 am <#>

REPLY ↩

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



Sounds like a Python 3 issue Mike.

Replace

```
1 fold_size = len(dataset) / n_folds
```

With:

```
1 fold_size = int(len(dataset) / n_folds)
```



Jason Brownlee

January 3, 2017 at 9:53 am

#

REPLY



I have updated the cross_validation_split() function in the above example to address issues with Python 3.



Mohendra Roy

January 4, 2017 at 12:32 am

#

REPLY



How about to use of euclidian distance instead of calculating for each element in the dataset?



Jason Brownlee

January 4, 2017 at 8:55 am

#

REPLY



What do you mean exactly? Are you able to elaborate?



Selva Rani B

January 12, 2017 at 4:43 pm

#

REPLY



Thank you very much



Jason Brownlee


January 13, 2017 at 9:09 am

#

REPLY



You're welcome.



Sokrates

January 21, 2017 at 4:10 am

#

REPLY



Hi Jason,

Great tutorial on CART!

The results of decision trees are quite dependent on the training vs test data. With this in mind, how do I set the amount of training vs test data in the code right now to changes in the result? From what I can see, it looks like they are being set in the evaluate_algorithm method.

//Kind regards
Sokrates



Jason Brownlee

January 21, 2017 at 10:37 am

#

REPLY



That is correct Sokrates.

The example uses k-fold cross validation to evaluate the performance of the algorithm on the dataset.

You can change the number of folds by setting the “n_folds” variable.

You can use a different resampling method, like train/test splits, see this post:
<http://machinelearningmastery.com/implement-resampling-methods-scratch-python/>



Adeshina Alani

January 27, 2017 at 3:52 am

#

Nice Post. I will like to ask if i this implementation can be used for time series data wi



Jason Brownlee

January 27, 2017 at 12:13 pm

#

REPLY



Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this*free* and *practical*email course.

START MY EMAIL COURSE



Yes it could, but the time series data would have to be re-framed as a supervised learning problem.

See this post for more information:

<http://machinelearningmastery.com/time-series-forecasting-supervised-learning/>



vishal January 30, 2017 at 5:06 am #

REPLY ↩

Really helpful. Thanks a lot for sharing.



Jason Brownlee February 1, 2017 at 10:18 am #

REPLY ↩

I'm glad you found the post useful vishal.



elberiver February 3, 2017 at 6:02 pm #

REPLY ↩

Hi Jason,

there is a minor point in your code. Specifically, in the follwing procedure:

```
# Build a decision tree
def build_tree(train, max_depth, min_size):
    root = get_split(dataset)
    split(root, max_depth, min_size, 1)
    return root
```

I think it should be root = get_split(train), eventhough your code is still running correctly since dataset is the global variable.

Thank you for your nice posts.
I like your blog very much.



Jason Brownlee February 4, 2017 at 9:59 am #

REPLY ↩

I think you're right, nice catch!

I'll investigate and fix up the example.



from Thailand March 8, 2017 at 2:35 pm #

REPLY ↩

Thanks a lot Jason, really helpful



Jason Brownlee March 9, 2017 at 9:52 am #

REPLY ↩

I'm glad to hear that.



Amit Moondra April 2, 2017 at 6:31 am #

REPLY ↩

I'm slowly going through your code and I'm confused about a line in your get_split function

```
groups = test_split(index, row[index], dataset)
```

Doesn't this only return the left group? It seems we need both groups to calculate the gini_index

Thank you.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



Jason Brownlee April 2, 2017 at 6:34 am #

REPLY ↩

Hi Amit,

The `get_split()` function evaluates all possible split points and returns a dict of the best found split point, gini score, split data.



Amit Moondra April 2, 2017 at 12:15 pm #

REPLY ↩

After playing around with the code for a bit, I realized that function returns both groups (left and right) under one variable.



Amit Moondra April 2, 2017 at 9:59 am #

REPLY ↩

In the function `split`

```
if not left or not right:
node['left'] = node['right'] = to_terminal(left + right)
return
```

Why do you add `(left + right)`? Are you adding the two groups together into one group?

Thank you.



Jason Brownlee April 4, 2017 at 9:05 am #

REPLY ↩

Yes.



Amit Moondra April 2, 2017 at 12:30 pm #

REPLY ↩

Another question (line 132)

```
if isinstance(node['left'], dict):
return predict(node['left'], row)
```

`isinstance` is just checking if we have already created such a dictionary instance?

Thank you.



Jason Brownlee April 4, 2017 at 9:05 am #

REPLY ↩

It is checking if the type of the variable is a dict.



Ann April 3, 2017 at 9:25 am #

REPLY ↩

Hello,

I've been trying some stuff out with this code and I thought I was understanding what was going on but when I tried it on a dataset with binary values it doesn't seem to work and I can't figure out why. Could you help me out please?

Thanks.



Jason Brownlee April 4, 2017 at 9:11 am #

The example assumes real-valued inputs, binary or categorical inputs should be

I don't have an example at hand, sorry.



Dimple April 17, 2017 at 1:37 am #

Hi

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

REPLY ↩

START MY EMAIL COURSE

Could you tell me how decision trees are used for predicting an unknown function when a sample dataset is given. What i mean how it is used for regression?



Jason Brownlee April 17, 2017 at 5:15 am #

REPLY ↩

Good question, sorry, I don't have an example of decision trees for regression from scratch.



Dimple April 17, 2017 at 10:18 am #

REPLY ↩

How can we use weka for regression using decision trees?



Jason Brownlee April 18, 2017 at 8:28 am #

REPLY ↩

Consider using the search function of this blog.

See this post:

<http://machinelearningmastery.com/use-regression-machine-learning-algorithms-weka/>



Joe April 18, 2017 at 1:31 am #

REPLY ↩

Great article, this is exactly what I was looking for!



Jason Brownlee April 18, 2017 at 8:33 am #

REPLY ↩

I'm really glad to hear that Joe!



ansar April 19, 2017 at 3:13 am #

REPLY ↩

I am new to machine learning ... successfully ran the code with the given data set

Now I want to run it for my own data set ... will the algo always treat the last column as the column to classify?

thanks



Jason Brownlee April 19, 2017 at 7:54 am #

REPLY ↩

Yes, that is how it was coded.



Ansar April 20, 2017 at 2:53 am #

REPLY ↩

Thank you! It works beautifully



Jason Brownlee April 20, 2017 at 9:32 am #

Well done!



Ansar April 21, 2017 at 10:22 pm #

Apologies if I am taking too much time but I tried to run this algo on the below scenar

#

#https://www.youtube.com/watch?v=eKD5gxPPeY0&list=PLBv09BD7ez_4temBw7vLA19p3td

#

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree .

Find out how in this *free* and *practical* email course.

REPLY ↩

START MY EMAIL COURSE

```
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 3.000]
[X1 < 1.000]
[1.0]
[1.0]
[0.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
[X1 < 1.000]
[1.0]
[1.0]
Scores: [100.0, 100.0, 0.0, 100.0, 0.0, 100.0, 0.0, 0.0, 100.0, 100.0]
Mean Accuracy: 60.000%
```

Ensure that you have loaded your data correctly.

Yes, working fine now ☐

START MY EMAIL COURSE

Would love to get my hands on a script that would print the tree in a more graphical (readable) format. The current format helps but does get confusing at times.

Thanks a lot!



Greg May 6, 2017 at 10:15 am #

REPLY ↩

This will generate a graphviz dot file that you can use to generate a .png, jpeg etc.

e.g:

dot -Tpng graph1.dot > graph.png

Note it generates a new file each time it is called – graph1.dot ... graphN.dot

```
# code begin

def graph_node(f, node):
    if isinstance(node, dict):
        f.write(' %d [label=\\"X%d %d;\n' % ((id(node), id(node['left']))))
        f.write(' %d -> %d;\n' % ((id(node), id(node['right']))))
        graph_node(f, node['left'])
        graph_node(f, node['right'])
    else:
        f.write(' %d [label=\\"[%s]\n' % ((id(node), node)))

def graph_tree(node):
    if not hasattr(graph_tree, 'n'): graph_tree.n = 0
    graph_tree.n += 1
    fn = 'graph' + str(graph_tree.n) + '.dot'
    f = open(fn, 'w')
    f.write('digraph {\n')
    f.write(' node[shape=box;\n')
    graph_node(f, node)
    f.write('}\n')
```



katana April 28, 2017 at 1:27 am #

REPLY ↩

Thanks a lot for this, Dr. Brownlee!



Jason Brownlee April 28, 2017 at 7:47 am #

REPLY ↩

I'm glad you found it useful.



godavari May 4, 2017 at 11:08 pm #

REPLY ↩

excellent explanation



Jason Brownlee May 5, 2017 at 7:31 am #

REPLY ↩

I'm glad you found it useful.



King Deng May 14, 2017 at 7:15 am #

I'm implementing AdaBoost from scratch now, and I have a tough time understanding iteration to build the decision tree? I guess I should modify the gini index in this regard, but I'm some light? Thanks!




Jason Brownlee May 14, 2017 at 7:35 am #

REPLY ↩

Get Your Start in Machine Learning


You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE



I offer a step-by-step example in this book:
<https://machinelearningmastery.com/master-machine-learning-algorithms/>

I would also recommend this book for a great explanation:
<http://www-bcf.usc.edu/~gareth/ISL/>



Pavithra


May 19, 2017 at 7:10 pm #

REPLY ↩

Part of the code: predicted = algorithm(train_set, test_set, *args)

TypeError: 'int' object is not callable

Issue: I'm getting error like this. Please help me




Jason Brownlee

May 20, 2017 at 5:36 am #

REPLY ↩

I'm sorry to hear that.

Ensure that you have copied all of the code without any extra white space.



Luis Ilabaca

May 25, 2017 at 9:23 am #

REPLY ↩

hey jason

honestly dude stuff like this is no joke man.

I did BA in math and one year of MA in math
then MA in Statistical Computing and Data Mining
and then sas certifications and a lot of R and man let me tell you,
when I read your work and see how you have such a strong understanding of the unifications of all the different fields needed to be successful at
applying machine learning.

you my friend, are a killer.




Jason Brownlee

June 2, 2017 at 11:40 am #

REPLY ↩

Thanks.



Saurabh

May 25, 2017 at 7:16 pm #


REPLY ↩

Hello Sir!!
First of all Thank You for such a great tutorial.

I would like to make a suggestion for function get_split()-
In this function instead of calculating gini index considering every value of that attribute in data set , we can just use the mean of that attribute as
the split_value for test_split function.

This is just my idea please do correct me if this approach is wrong.

Thank You!!



Jason Brownlee

June 2, 2017 at 11:43 am #

Try it and see.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree .
Find out how in this*free* and *practical*email course.

START MY EMAIL COURSE



Habiba June 4, 2017 at 6:36 am #

REPLY ↩

Hello Sir,
I am a student and i need to develop an algorithm for both Decision Tree and Ensemble(Preferably,Random Forest) both using python and R. i really need the book that contains everything that is,the super bundle.

Thank you so very much for the post and the tutorials. They have been really helpful.



Jason Brownlee June 4, 2017 at 7:55 am #

REPLY ↩

You can grab the super bundle here:
<https://machinelearningmastery.com/super-bundle/>

Leave a Reply

Name (required)

Email (will not be published) (required)

Website

SUBMIT COMMENT

Welcome to Machine Learning Mastery



Hi, I'm Dr. Jason Brownlee.
My goal is to make practitioners like YOU awesome at applied machine learning.

[Read More](#)

Code Algorithms From Scratch in Python

Discover how to code top machine learning algorithms from first principles with Python.

[Code Machine Learning Algorithms From Scratch Today!](#)

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree .
Find out how in this*free* and *practical*email course.

START MY EMAIL COURSE



POPULAR



Time Series Prediction with LSTM Recurrent Neural Networks in Python with Keras
JULY 21, 2016



Your First Machine Learning Project in Python Step-By-Step
JUNE 10, 2016



Develop Your First Neural Network in Python With Keras Step-By-Step
MAY 24, 2016



Sequence Classification with LSTM Recurrent Neural Networks in Python with Keras
JULY 26, 2016



Multi-Class Classification Tutorial with the Keras Deep Learning Library
JUNE 2, 2016



How to Run Your First Classifier in Weka
FEBRUARY 17, 2014



Tutorial To Implement k-Nearest Neighbors in Python From Scratch
SEPTEMBER 12, 2014



A Tour of Machine Learning Algorithms
NOVEMBER 25, 2013



Regression Tutorial with the Keras Deep Learning Library in Python
JUNE 9, 2016



How to Implement the Backpropagation Algorithm From Scratch In Python
NOVEMBER 7, 2016

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree . Find out how in this *free* and *practical* email course.

START MY EMAIL COURSE