

Navigation



Start Here Blog Books About Contact

Search...

Q

Need help with LSTMs in Python? Take the FREE Mini-Course.

Data Preparation for Variable Length Input Sequences

by Jason Brownlee on June 19, 2017 in Long Short-Term Memory Networks









Deep learning libraries assume a vectorized representation of your data.

In the case of variable length sequence prediction problems, this requires that your data be transformed such that each sequence has the same length.


This vectorization allows code to efficiently perform the matrix operations in batch for your chosen deep learning algorithms.

In this tutorial, you will discover techniques that you can use to prepare your variable length sequence data for sequence prediction problems in Python with Keras.

After completing this tutorial, you will know:

- How to pad variable length sequences with dummy values.
- How to pad variable length sequences to a new longer desired length.
- How to truncate variable length sequences to a shorter desired length.

Let's get started.



Overview

This section is divided into 3 parts; they are:

- 1. Contrived Sequence Problem
- 2. Sequence Padding
- 3. Sequence Truncation

Environment

This tutorial assumes you have a Python SciPy environment installed. You can use either Python 2 or 3 with this example.

This tutorial assumes you have Keras (v2.0.4+) installed with either the TensorFlow (v1.1.0+) or Theano (v0.9+) backend.

This tutorial also assumes you have scikit-learn, Pandas, NumPy, and Matplotlib installed.

If you need help setting up your Python environment, see this post:

• How to Setup a Python Environment for Machine Learning and Deep Learning with Anaconda

Contrived Sequence Problem

We can contrive a simple sequence problem for the purposes of this tutorial.

The problem is defined as sequences of integers. There are three sequences with a length between

These can be defined as a list of lists in Python as follows (with spacing for readability):

1 sequences = [2 [1, 2, 3, 4], 3 [1, 2, 3], 4 [1] 5]

We will use these sequences as the basis for exploring sequence padding in this tutorial.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree.

Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE

Get Your Start in Machine Learning

X

Need help with LSTMs for Sequence Prediction?

Take my free 7-day email course and discover 6 different LSTM architectures (with sample code).

Click to sign-up and also get a free PDF Ebook version of the course.

Start Your FREE Mini-Course Now!

Sequence Padding

The pad_sequences() function in the Keras deep learning library can be used to pad variable length

The default padding value is 0.0, which is suitable for most applications, although this can be change argument. For example:

```
1 pad_sequences(..., value=99)
```

The padding to be applied to the beginning or the end of the sequence, called pre- or post-sequence argument, as follows.

Pre-Sequence Padding

Pre-sequence padding is the default (padding='pre')

The example below demonstrates pre-padding 3-input sequences with 0 values.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree.

Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE

```
7  ]
8  # pad sequence
9  padded = pad_sequences(sequences)
10 print(padded)
```

Running the example prints the 3 sequences pre-pended with zero values.

```
1 [[1 2 3 4]
2 [0 1 2 3]
3 [0 0 0 1]
```

Post-Sequence Padding

Padding can also be applied to the end of the sequences, which may be more appropriate for some problem domains.

Post-sequence padding can be specified by setting the "padding" argument to "post".

Running the example prints the same sequences with zero-values appended.

```
1 [[1 2 3 4]
2 [1 2 3 0]
3 [1 0 0 0]]
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree.

Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE

Pad Sequences To Length

The pad sequences() function can also be used to pad sequences to a preferred length that may be longer than any observed sequences.

This can be done by specifying the "maxlen" argument to the desired length. Padding will then be performed on all sequences to achieve the desired length, as follows.

Running the example pads each sequence to the desired length of 5 timesteps, even though the maximum length of an observed sequence is only 4 timesteps.

```
1 [[0 1 2 3 4]
2 [0 0 1 2 3]
3 [0 0 0 0 1]]
```

Sequence Truncation

The length of sequences can also be trimmed to a desired length.

The desired length for sequences can be specified as a number of timesteps with the "maxlen" argui

There are two ways that sequences can be truncated: by removing timesteps from the beginning or

Pre-Sequence Truncation

The default truncation method is to remove timesteps from the beginning of sequences. This is calle

The example below truncates sequences to a desired length of 2.

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree.

Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE

X

```
10 print(truncated)
```

Running the example removes the first two timesteps from the first sequence, the first timestep from the second sequence, and pads the final sequence.

```
1 [[3 4]
2 [2 3]
3 [0 1]]
```

Post-Sequence Truncation

Sequences can also be trimmed by removing timesteps from the end of the sequences.

This approach may be more desirable for some problem domains.

Post-sequence truncation can be configured by changing the "truncating" argument from the default

```
from keras.preprocessing.sequence import pad_sequences
define sequences
sequences = [
       [1, 2, 3, 4],
       [1, 2, 3],
       [1]
       ]
# truncate sequence
truncated= pad_sequences(sequences, maxlen=2, truncating='post')
print(truncated)
```

Running the example removes the last two timesteps from the first sequence, the last timestep from sequence.

```
1 [[1 2]
2 [1 2]
3 [0 1]]
```

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree.

Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE

Summary


In this tutorial, you discovered how to prepare variable length sequence data for use with sequence prediction problems in Python.

Specifically, you learned:

- How to pad variable length sequences with dummy values.
- How to pad out variable length sequences to a new desired length.
- How to truncate variable length sequences to a new desired length.

Do you have any questions about preparing variable length sequences? Ask your questions in the comments and I will do my best to answer.

Develop LSTMs for Sequence Prediction Today!



Develop Your Own LSTM models in Minutes

Discover how in my nev

...with just a few lines of p

Long Short-Term Memory Netw

It provides self-study tutorial

CNN LSTMs, Encoder-Decoder LSTMs, generative models, data

Finally Bring LSTM Recurrent Your Sequence Predicti

Skip the Academics. Jus

Click to learn mo

Get Your Start in Machine Learning

You can master applied Machine Learning without the math or fancy degree.

Find out how in this free and practical email course.

Email Address

START MY EMAIL COURSE









X



Dr. Jason Brownlee is a husband, proud father, academic researcher, author, professional developer and a machine learning practitioner. He is dedicated to helping developers get started and get good at applied machine learning. Learn more.

View all posts by Jason Brownlee →

< How to Develop a Bidirectional LSTM For Sequence Classification in Python with Keras

How to Handle Missing Timesteps in Sequence Prediction Problems with Python >

10 Responses to Data Preparation for Variable Length Input Sequences



Yuya June 19, 2017 at 6:46 am #

Are there alternative methods which doesn't make of use padding as a way to handle sequence




Jason Brownlee June 19, 2017 at 8:49 am #

Yes, some ideas:

- You could truncate sequences.
- You could concatenate sequences.
- You could write your own inefficient implementation of RNNs.

Get Your Start in Machine Learning



Find out how in this free and practical email course.

Email Address

START MY EMAIL COURSE



Tom June 19, 2017 at 10:54 am #

If you know the target length, you can try interpolation or warping, right? But they are more costly than just adding zeros.

Get Your Start in Machine Learning

REPLY 🦈



Jason Brownlee June 20, 2017 at 6:33 am #

REPLY <



Nice tip Tom!



Sudipta Kar June 23, 2017 at 7:57 am #



I am interested how does the padding affect the performance of models? Specifically when the dataset contains both long texts and very short texts. Lets assume, median length is 30 sentences, max length is 120 and minimum length is 10. how pre and post sequence padding affects the performance?



Rahul June 24, 2017 at 3:06 am #

I am not wrong you usually batch together inputs of similar length, so in this case you would lengths ranging from 30-120



Jason Brownlee June 24, 2017 at 7:52 am #

Padding and Masking is the best, little to no impact. I would recommend testing though.





You can master applied Machine Learning without the math or fancy degree.

Find out how in this free and practical email course.

Email Address

START MY EMAIL COURSE







Rahul June 24, 2017 at 3:06 am #

If* I



Patrick September 13, 2017 at 2:11 pm #



Thank you so much for writing these tutorials. They are remarkably effective in explaining concepts that other websites often gloss over. Thave a question about padding outputs in sequence-to-sequence classification problems. Let's say X has the shape (100, 50, 10), and y has the shape (100, 50, 3). X consists of 100 time series, 50 time steps per time series, and 10 features per time step. The y has three possible one-hot encoded classes per tilmestep. The samples of X have variable length so the shorter samples are pre-padded with 0 For the y labels corresponding to the pre-padded X time steps, should they be [0, 0, 0]? Or should a new fourth label, [0, 0, 0, 1], be created for the pre-padded time steps thus changing the shape of y to (100, 100, 4).



Jason Brownlee September 15, 2017 at 11:56 am #

REPLY 🦴

Thanks Patrick.

Why do you need to pad the output if each series is classified as one of 3 labels?

Leave a Reply	Learning
	You can master applied Machine Learning without the math or fancy degree. Find out how in this free and practical email course.
	Email Address
	START MY EMAIL COURSE
Name (required)	

Get Your Start in Machine Learning

Get Your Start in Machine

Website

Email (will not be published) (required)

SUBMIT COMMENT

Welcome to Machine Learning Mastery



Hi, I'm Dr. Jason Brownlee.

My goal is to make practitioners like YOU awesome at applied machine learning.


Read More

Deep Learning for Sequence Prediction

Cut through the math and research papers.

Discover 4 Models, 6 Architectures, and 14 Tutorials.

Get Started With LSTMs in Python Today!



Get Your Start in Machine Learning



You can master applied Machine Learning without the math or fancy degree.

Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE

POPULAR



Time Series Prediction with LSTM Recurrent Neural Networks in Python with Keras JULY 21, 2016



Your First Machine Learning Project in Python Step-By-Step JUNE 10, 2016



Develop Your First Neural Network in Python With Keras Step-By-Step MAY 24, 2016



Sequence Classification with LSTM Recurrent Neural Networks in Python with Keras JULY 26, 2016



How to Setup a Python Environment for Machine Learning and Deep Learning with Anaconda MARCH 13, 2017



Time Series Forecasting with the Long Short-Term Memory Network in Python APRIL 7, 2017



Multi-Class Classification Tutorial with the Keras Deep Learning Library JUNE 2, 2016



Regression Tutorial with the Keras Deep Learning Library in Python JUNE 9, 2016




Multivariate Time Series Forecasting with LSTMs in Keras AUGUST 14, 2017



How to Implement the Backpropagation Algorithm From Scratch In Python NOVEMBER 7, 2016

Get Your Start in Machine Learning



Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE

© 2017 Machine Learning Mastery. All Rights Reserved.

Privacy | Contact | About

Get Your Start in Machine Learning

×

You can master applied Machine Learning without the math or fancy degree.

Find out how in this *free* and *practical* email course.

Email Address

START MY EMAIL COURSE