## **UNIT 4: SOLVED EXERCISES (FILESYSTEM, PDF, MAIL)**

## **FPDF LIBRARY**

<?php

Basic pdf file:

require('fpdf/fpdf.php');

```
$pdf=new FPDF();
   $pdf->AddPage();
   $pdf->SetFont('Arial','B',16);
   $pdf->Cell(40,10,'My first page pdf with FPDF');
   $pdf->Output();
       Save in disk:
   $pdf->Output('prueba.pdf','F');
<?php
require('fpdf/fpdf.php');
$pdf=new FPDF();
$pdf->AddPage();
$pdf->SetFont('Arial','B',16);
$pdf->Cell(40,10,'My first page pdf with FPDF');
$pdf->Output('prueba.pdf','F');
?>
MAILS
       Simple mail
<?php
mail("m.gimenezgomez@edu.gva.es", "subject", "Text Body");
?>
       With format
<?php
$destinatario = "m.gimenezgomez@edu.gva.es";
$asunto = "Test missatge";
$cuerpo = '
```

```
<html>
<head>
 <title>Mail Test</title>
</head>
<body>
<h1>Hi friends!</h1>
>
<br/> <b>Welcome to my test email </b>. I am delighted to have so many readers. This body of the
message is from the PHP mailing article.
</body>
</html>

    HTML FORMAT MAIL:

//for sending in HTML format
$headers = "MIME-Version: 1.0\r\n";
$headers .= "Content-type: text/html; charset=iso-8859-1\r\n";
//sender address
$headers .= "From: studentpepe <pepestudent@hotmail.com>\r\n";
//reply address, if we want it to be different from the sender
$headers .= "Reply-To: pepe_personal@hotmail.com\r\n";
//Copy addresses. Several: separated by commas
$headers .= "Cc: enrique@hotmail.com\r\n";
mail("m.gimenezgomez@edu.gva.es","subject","How are you?",$headers);
FILES UPLOAD
```

1. Save a photo in the server. Select the photo in a form, upload it and show it.

```
page2.php
<html>
<head>
<title>Problem</title>
</head>
<body>
<?php
copy($_FILES['foto']['tmp_name'],$_FILES['foto']['name']);
echo "Photo uploaded.<br>";
$nom=$_FILES['foto']['name'];
echo "<img src=\"$nom\">";
?>
</body>
</html>
   2. Note: It's not possible to translate "Choose file" and "no file chosen" labels, as those are native
       browser elements and depend on browser's language.
I have create this table in "ies" database
CREATE TABLE user (
id smallint(5) unsigned NOT NULL auto_increment,
user varchar(10),
password longtext
name varchar(100) NOT NULL,
birthday date,
photo varchar(50) default NULL,
PRIMARY KEY (id)
);
I have this form to insert the information:
<form action="insert.php" method="POST" enctype="multipart/form-data">
  <label>user: </label><input type="text" name="user"/><br/>
  <label>name: </label><input type="text" name="name"/><br/><br/>
  <label>Password: </label><input type="password" name="password"/> <br/><br/>
  <label>Photo: </label><input type="file" name="file"/><br/><br/>
```

```
<input type="submit" name="button" value="Send"/>
</form>
insert.php
<?php
require_once 'login.php';
$conn = new mysqli($servername, $username, $password, $dbname);
if ($conn->connect_error) {
  die("Fatal Error: " . $conn->connect_error);
}
if (is_uploaded_file($_FILES['file']['tmp_name'])) {
  $photo= basename($_FILES['file']['name']);
  $dest = 'photos\\' . basename($_FILES['file']['name']);
  $file = $_FILES['file']['tmp_name'];
  $err = $_FILES['file']['error']; //checks the error code
  if($err == 0 && move_uploaded_file($file, $dest))
  echo 'File successfully uploaded';
} else {
  echo "Possible file upload attack: ";
  echo "filename "". $_FILES['file']['tmp_name'] . "".";
}
$user = $_POST["user"];
$name = $_POST["name"];
$pass = $_POST["password"];
$strongpass = password_hash($pass, PASSWORD_DEFAULT);
$sql = "INSERT INTO users values (null, '$user', '$strongpass', '$name', '$photo')";
if ($conn->query($sql)) { echo "Correct"; }
else { echo "Fail INSERT"; }
$conn->close();
?>
```