

IN5320 ExamPrep DHIS2

HTML - Hyper Text Markup Language

- **Doctype** .html / .htm files
- **Head** `<head>` element: metadata, title of page
- **Body** `<body>` element: document's main body
- **Heading** `<h1>My main title </h1>`
- **Subheadings** `<h2,3,4,5,6> </hnumber>`
- **Paragraph** `<p>paragraph </p>` Block level element
- **Image** `<img>` Void element, no closing tag
 - Use alternative text to describe img

```
HTML
1 - 
```

- **Link** `<a></a>`

```
HTML
1 <a
2   href="https://en.wikipedia.org/wiki/LLVM"
3   title="tooltip"
4   target="_blank"
5   rel="noreferrer">
6 Example hyperlink to the wikipedia page about LLVM
7 </a>
```

- **Lists**
 - `<ul> </ul>` Unordered list
 - `<ol> </ol>` Ordered list
 - `<li> </li>` List Element
- **Dividers** `<div> </div>`
 - `<div class="className"> </div>`
 - `<div id="idName"> </div>`
- **Buttons** `<button>Button text</button>`
- **Bold** `<strong> </strong>`
- **Cursive** `<em> </em>`
- **Inputs & Labels**

```
HTML
1 <label for="age">Age (years):</label>
2 <input type="number" name="age" id="age" required>
```

Age (years):

- **Checkbox**
 - Checked → Toggled on or off by default

HTML

```
1 <label for="displayEmptyColumns">Display empty columns:</label>
2 <input type="checkbox" name="displayEmptyColumns" id="displayEmptyColumns">
```

Display empty columns: ☒

- **Date**
 - Max / Min → latest/earliest acceptable date

HTML

```
1 <label for="startDate">Start date:</label>
2 <input type="date" name="startDate" id="startDate">
```

Start date:

dd/mm/yyyy 

- **File**
 - Accept / Multiple → Type / allow multiple

HTML

```
1 <label for="license">License:</label>
2 <input type="file" name="license" id="license"
3   accept="image/png, image/jpeg">
```

License: Choose file No file chosen

- **Number**
 - Min / max / step → minimum value / maximum value / step interval

HTML

```
1 <label for="sabers">Sabers (1-4):</label>
2 <input type="sabers" name="sabers" id="sabers"
3   min="1" max="4" value="1" required>
```

Sabers (1-4):

- **Password**
 - Maxlength / minlength

HTML

```
1 <label for="password">Password (8-64 characters):</label>
2 <input type="password" name="password" id="password"
3   minlength="8" maxlength="64" required>
```

Password (8-64 characters):

- **Radio**
 - Checked / value → on/off / pair with value when submitted

HTML

```
1 <div>
2   Please select preferred shipping method:
3   <label>
```

```

4 <input type="radio" name="shippingMethod"
5 value="dhl" checked>
6 DHL
7 </label>
8 <label>
9 <input type="radio" name="shippingMethod"
10 value="singapore-post">
11 Singapore Post
12 </label>
13 </div>

```

Please select preferred shipping method:

- ☒ DHL
- ☐ Singapore Post

- Text
 - Maxlength / minlength

```

HTML
1 <label for="name">Name (1-128 characters):</label>
2 <input type="text" name="name" id="name"
3 minlength="1" maxlength="128" required>

```

Name (1-128 characters):

HTML5 introduced **semantic elements** to replace many of those `<div>` s:

- `<header>` → for page or section headers
- `<nav>` → for navigation menus
- `<main>` → the unique main content of the page
- `<section>` → for grouping related content
- `<article>` → for standalone content pieces (e.g., blog posts, news articles)
- `<aside>` → for sidebars, ads, tangential content
- `<footer>` → for page or section footers
- `<figure>` and `<figcaption>` → for images, diagrams, code samples with captions
- `<div>` → **block-level element** (takes up the full width, starts on a new line).
- `<span>` → **inline element** (only takes up as much space as its content).