

Product Requirements Document – v2.0 (Refined)

Document Version: 2.0
Supersedes: v1.0 (draft)
Product Version: 0.1.0 (target)
Status: Ready for Architecture Phase
Purpose: SYNC HACK – Track 1
Primary Objective: Build a real product whose documented behavior can drift from its actual behavior, then use Thally to detect the drift and produce reviewable documentation updates.

0. Research Findings & Verification Status

Per the instruction to research before rewriting, here is what was verified and what was not, as of 2026-08-21.

0.1 SYNC HACK / Track 1 – NOT FOUND

No public, indexable source for an event called "SYNC HACK" with a "Track 1" documentation-synchronization challenge could be located. Several unrelated "Sync Hack" / "Syncs Hack" student hackathons exist (University of Sydney's annual event, various "Hack the Track" logistics hackathons) but none reference Thally or documentation synchronization.

Consequence: every "official requirement" implied by the original PRD (judging criteria, exact deliverable format, submission mechanics, restrictions on tooling, whether a live demo vs. a video is required, team size limits, time limits) is **ASSUMPTION – VERIFY BEFORE IMPLEMENTATION**. This document proceeds on the reasonable inferred goal stated in the original draft – *demonstrate that product changes can be traced to affected documentation and converted into reviewable documentation updates* – but you should get the actual rules doc from the organizers (Discord, email, info pack) and reconcile it against Sections 33–39 before build starts. If you have that brief, share it and this document can be corrected in one pass rather than guessed at repeatedly.

0.2 Thally – Verified from official docs (docs.thally.app)

Confirmed capabilities, in Thally's own words:

Capability	What it actually does	Source confidence
Docs-as-code publishing	Pages, navigation, OpenAPI files, and versioned settings live in Git; Thally publishes them (managed hosting at a <code>thally.app</code> address, or self-hosted open-source)	High – official docs
Multi-format serving	Same structured content is served as HTML, Markdown, JSON, JSON-LD, plus search, embeddings, and agent endpoints	High – official docs
Track (the change-sync feature)	Traces product changes to specific evidence, confirms which pages are affected, and can prepare a documentation pull request when a merged product change affects docs	High – official docs, but only landing-page depth. Exact trigger mechanism (webhook? poll? which repos? what counts as "evidence"?) is not yet confirmed – ASSUMPTION
OpenAPI → docs	Turns an OpenAPI spec into interactive endpoint pages	High
Pre-deploy checks	Catches content/config errors before deploying docs	High

Capability	What it actually does	Source confidence
Cloud-only add-ons	"Product Knowledge," analytics, and grounded AI answers are listed as cloud-service extras beyond the open-source core	Medium – named but not detailed on the landing page

Not verified / must confirm before architecture:

- Whether Track watches a *separate* application repo, or only the docs repo itself (i.e., does Thally need read access to `apps/api` and `apps/web` , or does it only reconcile docs against an OpenAPI file you regenerate and push?).
- What "evidence" means concretely – commit diffs? PR descriptions? OpenAPI diffs? test changes?
- Whether Track can be triggered on-demand (needed for a live demo) or only on merge-to-main (which would make the demo require pre-staged commits).
- Rate limits, auth model (GitHub App? PAT?), and whether self-hosted vs. managed changes any of the above.

Recommendation: before Phase 4 (Section 21 below), spend a fixed timebox (recommend ≤ 2 hours) doing a spike – connect a throwaway repo to Thally, make one trivial change, and observe exactly what Track produces. Everything in Section 15 (Thally Strategy) below is written to be **falsifiable by that spike** rather than assumed permanent.

0.3 Distinguishing official / inferred / recommended throughout this document

Every requirement below is implicitly one of:

- **[OFFICIAL]** – stated by the hackathon (currently: none found, so nothing in this document carries this tag with confidence)
- **[INFERRED]** – a reasonable reading of the stated Track 1 objective, carried over from the original draft
- **[RECOMMENDATION]** – this document's own addition, justified by hackathon-demo strength or engineering realism

Where a tag is omitted, treat it as **[RECOMMENDATION]**.

A. Critical Issues Found in Original PRD (summary – see full list in Section 24)

Before the expanded content, the headline problems with v1.0, so you can see what changed and why:

1. **No verification that "SYNC HACK Track 1" is real or that its requirements were correctly captured.** v1.0 stated things like team-size defaults and demo structure as if they were settled; none were traceable to a source. Now explicitly flagged as assumptions.
2. **Feature Requirements section was a skeleton, not a spec.** Each feature (AUTH-001, EVENT-001, etc.) had a one-line description with no actor/precondition/flow/failure-mode/acceptance-criteria structure – exactly the "manage teams" vagueness the meta-prompt warned against. Section 4 below rebuilds this properly for every feature.
3. **API Contract had no request/response bodies, no error cases per endpoint, no auth detail beyond a role list.** A backend dev could not implement from it. Section 8 fixes this.
4. **Data model listed fields with no types, constraints, or why the entity exists.** No indexing, no referential integrity rules. Section 7 fixes this.
5. **The Change Matrix (Section 33 in v1.0) had only 6 scenarios, and none covered a removed field, a feature addition/removal, or a schema change with public API implications** – 4 of the 10 categories the meta-prompt explicitly required were missing. Section 16 below adds them.
6. **RBAC was a single flat table with no permission matrix per resource, no ownership rules, no session/token strategy.** Section 9 fixes this.
7. **The product itself (a hackathon-judging platform) is defensible but under-argued** – see Section 1.5 for the case for and against, and why it's being kept.
8. **No UI/UX requirements at all** despite being asked for. Section 10 adds a screen inventory.
9. **No risk register, no phased plan with definitions of done, no observability spec.** All added (Sections 17–22).
10. **Demo design (v1.0 Sections 42–44) was a good skeleton but lacked the "expected unaffected documentation" and "proof of synchronization" fields the meta-prompt required per scenario.** Section 16 restructures this.

The full audit answering all 14 meta-prompt questions is in Section 24.

1. Product Overview

1.1 Product name

SyncFlow

1.2 Product concept

A hackathon/technical-event management platform (event creation → registration → team formation → project submission → judging) built specifically so that its own evolution — API renames, new required fields, business-rule changes, added/removed features, auth swaps — can be used as realistic fodder for demonstrating documentation-to-product synchronization via Thally.

1.3 Product vision

Documentation is treated as a queryable, versioned, evidence-backed layer of the product — not a folder of Markdown someone forgot to update.

1.4 Product mission

Ship a small but *real* multi-role web application, with a documentation set that is provably accurate at baseline, then deliberately evolve the product and use Thally to prove — with evidence, not vibes — exactly which pages went stale and why, while correctly leaving unaffected pages alone.

1.5 Problem statement

Software changes continuously; documentation does not change automatically with it. This produces silent drift between what a product does and what its docs claim it does — API consumers get wrong request shapes, business-rule descriptions go stale, and "no update needed" changes (internal refactors) get either ignored (fine) or over-documented (wasted effort). There is no default mechanism that traces a merged product change to the specific documentation pages it invalidates.

1.6 Target users (for the *demo*, not the *product*)

The real "users" of SyncFlow-the-artifact are Track 1 judges and the team itself. The *in-fiction* users are hackathon participants, organizers, judges, and admins (Section 3). Keep this distinction explicit in the pitch: SyncFlow is a vehicle, not the point.

1.7 Value proposition

- For the hackathon submission: a working product + working docs + working sync pipeline is a stronger demo than a docs-only prototype, because it proves Thally's value against a nontrivial, multi-actor system rather than a toy README.
- For a hypothetical real user: an event platform whose docs you can trust because they're mechanically checked against the product.

1.8 Differentiation

Not competing on event-management features. The differentiator is entirely the sync story — deliberately shallow on breadth (6 modules, capped scope, see Section 18) and deliberately deep on traceability (every business rule has an ID, every doc page has an ID, every change scenario has an explicit before/after and expected/unaffected doc list).

1.9 Why this product is suitable for Track 1

[RECOMMENDATION, argued explicitly since the original draft asserted this without argument]

For:

- Has genuine state machines (event, submission) whose transitions naturally generate API and business-rule documentation.
- Has a natural "internal refactor with no doc impact" control case (rename a service class) – important because Track 1 is explicitly *not* about "any commit → docs get rewritten."
- Multi-role RBAC gives you an authentic "which docs are role-scoped" dimension.

Against (raised honestly, not glossed over):

- Six CRUD-ish modules is a lot of surface area for a hackathon timebox; there's real risk the team spends its time on event/team/judging plumbing instead of the sync pipeline, which is the actual judged thing. See Section 18 (Scope Control) for the cut list that exists specifically to protect against this.
- None of the 6 modules is *inherently* more interesting to document-sync than a much smaller product would be. A team optimizing purely for demo strength could ship 2 modules (auth + one resource with a rich API) and get the same Track 1 story with a fraction of the build risk. This PRD keeps the 6-module scope because it was already a stated goal (G-001-G-005) and a team of 6 people, but you should treat Section 18's "cut-if-behind" list as a live decision, not a formality.

2. Goals and Non-Goals

2.1 Product goals

ID	Goal
PRD-G-001	Organizers can run the full lifecycle of one event: draft → publish → ongoing → completed
PRD-G-002	Participants can register, form/join a team, and submit one project per team
PRD-G-003	Judges can be assigned to submissions and record scored evaluations
PRD-G-004	Every business rule governing the above has a stable ID and is enforced server-side, not just documented
PRD-G-005	The documentation set describes the actual behavior of the running product at every checkpoint

2.2 User goals

ID	Goal
PRD-UG-001	A participant can go from "never seen this event" to "submission confirmed" without contacting a human
PRD-UG-002	An organizer can see, at a glance, registration/team/submission counts and any blocked states
PRD-UG-003	A judge can complete all assigned evaluations in one sitting without losing progress

2.3 Technical goals

ID	Goal
PRD-TG-001	Every state transition is validated server-side and rejected with a typed error code if invalid
PRD-TG-002	The API is described by a single OpenAPI 3.1 document that is the literal input to Thally's OpenAPI→docs feature
PRD-TG-003	Core business rules (BR-001-BR-010+) each have at least one automated test that fails if the rule is violated

2.4 Documentation goals

ID	Goal
PRD-DG-001	Baseline documentation is verified (manually, once) to match the shipped baseline product before any CHANGE scenario is introduced

ID	Goal
PRD-DG-002	Every documentation page has a declared set of upstream dependencies (API endpoints, business rules, examples) so "what could make this page stale" is answerable without re-reading the page
PRD-DG-003	At least one change scenario proves a negative — that an internal-only change does not trigger an unnecessary doc rewrite

2.5 Hackathon goals

ID	Goal	Source
PRD-HG-001	Demonstrate a real, working product, not a documentation-only mockup	[INFERRED]
PRD-HG-002	Demonstrate ≥ 3 meaningful product changes with distinct doc-impact shapes	[INFERRED]
PRD-HG-003	Demonstrate ≥ 1 "no update required" case	[INFERRED]
PRD-HG-004	Show the full loop live: change $\rightarrow$ evidence $\rightarrow$ affected pages $\rightarrow$ drafted update $\rightarrow$ human review $\rightarrow$ merged, synchronized state	[INFERRED]
PRD-HG-005	Do not claim any Thally capability that wasn't confirmed in Section 0.2	[RECOMMENDATION — protects against a judge asking "wait, does it actually do that?" and the team not having an answer]

2.6 Explicit non-goals

- Native mobile apps
 - Payments/sponsorship billing
 - Real-time chat or notifications
 - AI-assisted judging or scoring
 - Video hosting
 - Multi-event / multi-tenant support (single event per environment for MVP)
 - Marketplace or social-networking features
 - Building a general-purpose docs-sync engine — SyncFlow *uses* Thally, it does not reimplement it
-

3. User Research / Personas

3.1 Persona: Priya, the Participant

- **Role:** Final-year CS student, moderate technical skill
- **Context:** Discovers the event via a college WhatsApp group, registers solo, needs to find/form a team fast
- **Goals:** Register before the deadline, land on a team of the right size, submit before the cutoff without losing work
- **Pain points:** Ambiguous team-size rules, unclear whether her team is "full," fear of missing the submission deadline
- **Motivations:** Resume-building, prize money, learning
- **Behaviors:** Checks event page repeatedly near deadlines; likely on mobile at least once
- **Permissions:** PARTICIPANT
- **Primary workflows:** Register $\rightarrow$ create/join team $\rightarrow$ submit project $\rightarrow$ check status
- **Edge cases:** Registers after deadline (must be blocked with a clear error); tries to join a full team; tries to join two teams in the same event; team leader disappears before submission (no reassignment flow in MVP — documented as a known limitation, see Section 18)

3.2 Persona: Raj, the Organizer

- **Role:** Event lead for a college hackathon, runs the event solo or with 1-2 co-organizers
- **Context:** Needs the event configured correctly once, then mostly monitors
- **Goals:** Get accurate real-time counts, catch problems (e.g., team stuck at 1 member near the deadline) early, assign judges fairly
- **Pain points:** No way to bulk-communicate (out of scope — announcements are a stretch item, see Section 18), fear of a config change breaking existing registrations
- **Permissions:** ORGANIZER
- **Primary workflows:** Create event → configure → publish → monitor → assign judges → view results
- **Edge cases:** Edits `teamMaxSize` downward below the size of an existing team (must be blocked or explicitly allowed-with-warning — see BR-011 in Section 5); tries to publish an event missing required fields

3.3 Persona: Dr. Meera, the Judge

- **Role:** Industry mentor volunteering a few hours
- **Context:** Logs in once, wants to move through assigned submissions quickly, may not return
- **Goals:** Score fairly and quickly, leave useful feedback, not accidentally judge her own team
- **Pain points:** Losing an in-progress score if she navigates away; unclear rubric weighting
- **Permissions:** JUDGE
- **Primary workflows:** Login → view assigned submissions → score → submit
- **Edge cases:** Assigned to a submission from her own team (must be prevented at assignment time, BR-007); rubric changes (CHANGE-005) mid-judging — must not corrupt already-submitted evaluations

3.4 Persona: Admin (platform operator)

- **Role:** The team member running the demo/environment
- **Goals:** Fix stuck states, manage users if something goes wrong, have full visibility for the live demo
- **Permissions:** ADMIN (superset of all)
- **Primary workflows:** User management, event override, system activity review

3.5 User journeys, JTBD, success criteria

Journeys already captured in v1.0 Section 9 are retained; the "job to be done" framing adds precision:

Persona	Job to be done	Success criterion
Priya	"When I find an event I want to enter, help me get from zero to submitted without missing a deadline or getting stuck on team logistics"	Submission recorded with status <code>SUBMITTED</code> before deadline; no manual intervention required
Raj	"When I run an event, give me confidence the numbers I see are real and rules are enforced automatically"	Zero manual rule enforcement needed; dashboard counts match DB truth
Dr. Meera	"When I'm given work to judge, let me finish it in one sitting with no ambiguity about the rubric"	All assigned evaluations reach <code>EVALUATED</code> with no data loss

4. Feature Requirements

Consistent structure applied to every MVP feature. (Full detail given for representative features from each module; remaining features in each module follow the same template — abbreviated versions included for completeness.)

4.1 AUTH-001 – Register Account

- **Feature ID:** AUTH-001

- **Purpose:** Let a new person create a SyncFlow identity so they can act as a participant (or be promoted to organizer/judge/admin by an admin)
- **User story:** As a visitor, I want to create an account with my name, email, and password, so that I can register for events.
- **Actors:** Anonymous visitor
- **Preconditions:** No existing account with the given email
- **Main flow:**
 1. Visitor submits name, email, password
 2. Server validates input (Section 4.9)
 3. Server hashes password (bcrypt/argon2, never reversible)
 4. Server creates User with role= `PARTICIPANT` (default; cannot self-assign a higher role)
 5. Server returns a session token and the created user (without passwordHash)
- **Alternative flows:** None
- **Failure flows:**
 - Email already registered → `409 DUPLICATE_EMAIL`
 - Missing/invalid fields → `422 VALIDATION_FAILED` with per-field messages
 - Password below policy (min 8 chars) → `422 VALIDATION_FAILED`
- **Validation:** Email format (RFC 5322 subset), password ≥8 chars, name 1-120 chars
- **Business rules:** New accounts always start as `PARTICIPANT` (BR-012, new – see Section 5)
- **Permissions:** Public (unauthenticated) endpoint
- **State changes:** Creates User row
- **Inputs:** `{ name, email, password }`
- **Outputs:** `{ user: {...}, session token }`
- **Dependencies:** None
- **Edge cases:** Case-insensitive email uniqueness (`Foo@x.com == foo@x.com`); leading/trailing whitespace trimmed before uniqueness check
- **Acceptance criteria:**
 - AC1: Given a unique email and valid password, when registering, then a User is created with role `PARTICIPANT` and a session is issued
 - AC2: Given an email that already exists (any case), when registering, then the request fails with `409 DUPLICATE_EMAIL` and no row is created
 - AC3: Given a password under 8 characters, when registering, then the request fails with `422` and no row is created

4.2 AUTH-002 – Login

- **Feature ID:** AUTH-002
- **Purpose:** Authenticate a returning user
- **User story:** As a registered user, I want to log in with email and password, so I can access my role-scoped features.
- **Actors:** Registered, unauthenticated visitor
- **Preconditions:** Account exists
- **Main flow:** Submit email+password → server verifies hash → issues session
- **Failure flows:** Wrong password or unknown email → `401 INVALID_CREDENTIALS` (identical message for both, to avoid user enumeration)
- **Business rules:** BR-013 (new) – failed login attempts are rate-limited (5/15min per email+IP) to reduce credential-stuffing risk
- **Acceptance criteria:**
 - AC1: Correct credentials → `200` + session
 - AC2: Wrong password → `401`, message does not reveal whether the email exists
 - AC3: 6th failed attempt within 15 minutes for the same email → `429 RATE_LIMITED`, regardless of correctness

4.3 AUTH-003 / AUTH-004 – Session & Role (abbreviated)

- **Session:** server-side session table or signed JWT (decision needed – see Section 24.B Open Questions), expiry 7 days, refreshed on activity
- **Role:** immutable by the user themselves; only ADMIN can change another user's role (`PATCH /users/{userId}/role` , new endpoint – Section 8)

- Acceptance criteria: expired session → 401 SESSION_EXPIRED; role change by non-admin → 403 FORBIDDEN

4.4 EVENT-001 – Create Event

- **Feature ID:** EVENT-001
- **Purpose:** Let an organizer define a new event
- **User story:** As an organizer, I want to create an event with its dates, team-size bounds, and status, so participants have something to register for.
- **Actors:** ORGANIZER, ADMIN
- **Preconditions:** Authenticated as ORGANIZER or ADMIN
- **Main flow:** Submit event fields → validate → create with status= **DRAFT** → return event
- **Failure flows:**
 - `registrationDeadline` after `submissionDeadline` → 422 **INVALID_DATE_RANGE**
 - `teamMinSize` > `teamMaxSize` → 422 **INVALID_TEAM_SIZE_RANGE**
 - `slug` not unique → 409 **SLUG_TAKEN**
- **Validation:** All date fields ISO-8601; `slug` matches `^[a-z0-9-]{3,60}$`; `teamMinSize` ≥ 1, `teamMaxSize` ≥ `teamMinSize`
- **Business rules:** New events always start **DRAFT** (BR-014, new)
- **State changes:** Creates Event row, status=DRAFT
- **Acceptance criteria:**
 - AC1: Valid payload → 201, status DRAFT
 - AC2: `registrationDeadline` > `submissionDeadline` → 422, no row created
 - AC3: Duplicate slug → 409

4.5 EVENT-002 – Publish Event

- **User story:** As an organizer, I want to publish a DRAFT event, so participants can register.
- **Preconditions:** Event exists, status=DRAFT, caller owns the event or is ADMIN
- **Main flow:** Organizer triggers publish → server validates all required fields present and date logic still valid → status → PUBLISHED
- **Failure flows:** Missing required field → 422 **EVENT_INCOMPLETE** ; already published → 409 **ALREADY_PUBLISHED** ; wrong owner → 403 **FORBIDDEN**
- **Business rules:** BR-009 (only PUBLISHED events accept registrations – enforced here as the gate)
- **Acceptance criteria:**
 - AC1: Complete DRAFT event → publish succeeds, status PUBLISHED
 - AC2: Publishing an already-PUBLISHED event → 409
 - AC3: Registration attempt against a DRAFT event → 403 **EVENT_NOT_PUBLISHED** (tested via REG-001)

4.6 EVENT-003 / EVENT-004 (abbreviated)

- Update: allowed fields differ by status (e.g., `teamMaxSize` cannot be lowered below the largest existing team's current size – BR-011, new). Validated against existing Registration/Team rows before applying.
- Status enum and transition rules: see Section 6 (State Machines).

4.7 REG-001 – Register for Event

- **User story:** As an authenticated participant, I want to register for a published event, so I can form/join a team.
- **Preconditions:** Event status=PUBLISHED, now < registrationDeadline, no existing registration by this user for this event
- **Main flow:** Submit → validate deadline/status/duplicate → create Registration(status=CONFIRMED)
- **Failure flows:** Deadline passed → 403 **REGISTRATION_CLOSED** ; event not published → 403 **EVENT_NOT_PUBLISHED** ; duplicate → 409 **DUPLICATE_REGISTRATION**
- **Business rules:** BR-004, BR-009
- **Acceptance criteria:**
 - AC1: Valid, on-time registration → 201
 - AC2: Second registration attempt by same user/event → 409, only one row exists

- AC3: Attempt one second after deadline → 403

4.8 TEAM-001-005 (abbreviated, one deep example)

TEAM-003 – Team Capacity

- **User story:** As the system, I must reject a join attempt that would exceed `teamMaxSize`, so team-size business rules hold.
- **Preconditions:** Team exists, joining user is registered for the same event and not already on a team for that event
- **Main flow:** Join request → count current members → if count < teamMaxSize, add member; else reject
- **Failure flows:** Team full → 409 TEAM_FULL ; already on a team in this event → 409 ALREADY_IN_TEAM ; not registered for the event → 403 NOT_REGISTERED
- **Business rules:** BR-001, BR-002
- **Acceptance criteria:**
 - AC1: Joining a team at `teamMaxSize - 1` members → succeeds, count becomes `teamMaxSize`
 - AC2: Joining a team already at `teamMaxSize` → 409 TEAM_FULL
 - AC3: A user already on Team A in Event X attempting to join Team B in Event X → 409 ALREADY_IN_TEAM
 - AC4: The same user joining a team in a *different* event → succeeds (BR-002 is scoped per-event)

4.9 SUB-001-004 (abbreviated, one deep example)

SUB-002 – Submission Deadline

- **User story:** As the system, I must reject any create/update to a submission after the event's `submissionDeadline`, so late work is not scored.
- **Main flow:** On create/update, compare `now()` to `event.submissionDeadline`
- **Failure flows:** Past deadline → 403 SUBMISSION_CLOSED
- **Business rules:** BR-005
- **Edge case:** Server clock is authoritative, not client clock – prevents deadline gaming via client-side time manipulation
- **Acceptance criteria:**
 - AC1: Update one second before deadline → succeeds
 - AC2: Update one second after deadline → 403, existing submission unchanged

4.10 JUDGE-001-004 (abbreviated, one deep example)

JUDGE-004 – Conflict of Interest

- **User story:** As the system, I must prevent a judge from being assigned to, or scoring, a submission from their own team.
- **Main flow (assignment time):** Organizer assigns judge X to submission S → server checks whether judge X is a TeamMember of S.teamId → reject if so
- **Failure flows:** 409 JUDGE_CONFLICT
- **Business rules:** BR-007
- **Edge case:** A judge who is *also* a registered participant elsewhere (not disallowed) – conflict check is scoped to the specific submission's team, not "is this person a participant at all"
- **Acceptance criteria:**
 - AC1: Assigning a judge to a submission from a team they belong to → 409, no JudgeAssignment created
 - AC2: Assigning the same judge to a different team's submission → succeeds

5. Business Rules

Full authoritative list, expanded with reason/scope/affected-surfaces per the meta-prompt (this is the section that most directly feeds the Change Matrix in Section 16).

ID	Rule	Reason	Scope	Affected Feature	Affected API	Affected Data	Affected Docs
BR-001	Team must have 2-4 members (MVP default)	Prevents solo "teams" and oversized teams that dilute judging fairness	Per-event (bounds are configurable per event, defaulting 2/4)	TEAM-001, TEAM-003	POST <code>/teams/{id}/members</code>	Team, TeamMember	DOC-005, DOC-008, DOC-009
BR-002	A participant belongs to ≤1 team per event	Prevents double-counting/gaming judging	Per-event	TEAM-001, TEAM-002	TeamMember	DOC-005, DOC-008	
BR-003	Only the team leader can submit/update the submission	Single point of accountability per team	Per-team	SUB-001, SUB-004	Submission	DOC-006, DOC-008	
BR-004	No registration after <code>registrationDeadline</code>	Deadline integrity	Per-event	REG-002	Registration	DOC-004, DOC-008, DOC-009	
BR-005	No submission create/update after <code>submissionDeadline</code>	Deadline integrity	Per-event	SUB-002	Submission	DOC-006, DOC-008	
BR-006	A team has ≤1 active (non-withdrawn) submission	Simplifies judging model	Per-team	SUB-003	Submission	DOC-006	
BR-007	A judge cannot evaluate a submission from their own team	Conflict-of-interest integrity	Per-assignment	JUDGE-001, JUDGE-004	JudgeAssignment	DOC-007, DOC-008	
BR-008	Only ORGANIZER/ADMIN can configure judging criteria	Prevents tampering	Per-event	JUDGE rubric config	Rubric config endpoint	DOC-007, DOC-008	
BR-009	Only PUBLISHED events accept registrations	Lifecycle integrity	Per-event	EVENT-002, REG-001	Event, Registration	DOC-003, DOC-004	
BR-010	A CANCELLED event accepts no new registrations, teams, or submissions	Lifecycle integrity	Per-event	All write flows	Multiple	DOC-003	
BR-011 (new)	<code>teamMaxSize</code> cannot be lowered below the size of any existing team in that event	Prevents silently orphaning existing members	Per-event	EVENT-003	Event, Team	DOC-003, DOC-005	
BR-012 (new)	New accounts always default to role PARTICIPANT; elevation requires an ADMIN action	Prevents privilege self-escalation	Global	AUTH-001	User	DOC-002	
BR-013 (new)	Login attempts are rate-limited: 5 failures / 15 min / (email, IP) pair	Basic credential-stuffing mitigation	Global	AUTH-002	— (in-memory/redis counter)	DOC-002	
BR-014 (new)	New events always start in status DRAFT	Prevents accidental premature publication	Per-event	EVENT-001	Event	DOC-003	

6. State Machines

6.1 Event

```
stateDiagram-v2
    [*] --> DRAFT: EVENT-001 create
    DRAFT --> PUBLISHED: EVENT-002 publish (organizer/admin, requires complete fields)
    PUBLISHED --> ONGOING: system, at startDate
    ONGOING --> COMPLETED: system, at endDate
    PUBLISHED --> CANCELLED: organizer/admin
    ONGOING --> CANCELLED: organizer/admin
    DRAFT --> CANCELLED: organizer/admin
```

- **Allowed transitions:** as diagrammed above
- **Forbidden transitions:** DRAFT→ONGOING/COMPLETED (must pass through PUBLISHED); COMPLETED→anything (terminal); CANCELLED→anything (terminal)
- **Triggers:** DRAFT→PUBLISHED is user-triggered (organizer); PUBLISHED→ONGOING and ONGOING→COMPLETED are system-triggered (scheduled job comparing `now()` to `startDate / endDate`) — **[OPEN QUESTION: does MVP need a real scheduler, or is this transition computed on-read? Recommend on-read for hackathon scope — see Section 24.B]**
- **Side effects:** PUBLISHED enables registration; CANCELLED blocks all writes (BR-010)
- **Documentation implications:** DOC-003 (Event Management guide) must describe the diagram above; any transition rule change is a Change Matrix candidate

6.2 Registration

```
stateDiagram-v2
    [*] --> CONFIRMED: REG-001 register
    CONFIRMED --> WITHDRAWN: participant withdraws (new, minor feature)
```

- MVP note: v1.0 defined a `status` field on Registration but never enumerated its values. This is corrected here: `CONFIRMED | WITHDRAWN`.

6.3 Team

```
stateDiagram-v2
    [*] --> FORMING: TEAM-001 create (1 member: leader)
    FORMING --> FORMING: TEAM-002 join (while size < max)
    FORMING --> LOCKED: automatically, at event submissionDeadline OR on first submission
```

- **New concept vs. v1.0:** v1.0 had no team-level state at all, which left "can I still join a team after the team has submitted?" unanswered. LOCKED prevents new joins once the team has an active submission, closing that gap.

6.4 Submission

```
stateDiagram-v2
    [*] --> DRAFT: SUB-001 create
    DRAFT --> SUBMITTED: team leader finalizes (before deadline)
    SUBMITTED --> UNDER_REVIEW: JUDGE-001 first judge assignment
    UNDER_REVIEW --> EVALUATED: all assigned judges have submitted evaluations
```

- **Forbidden:** SUBMITTED→DRAFT (no un-submitting in MVP — reduces edge cases); EVALUATED→anything (terminal for MVP)
- **Correction vs. v1.0:** v1.0's SUB-004 said "team leader can update a submission until the deadline" but the state diagram implied SUBMITTED was already final. Resolved: DRAFT is editable freely before the deadline; SUBMITTED is the finalized/locked state entered explicitly, not implicitly at deadline. `POST /submissions/{id}/submit` (Section 8) is the DRAFT→SUBMITTED trigger.

6.5 Evaluation

- Single-shot: created via `POST /submissions/{id}/evaluation`, immutable once created (no PATCH in MVP — a judge who makes a mistake contacts an admin; documented as a known limitation).

7. Data Model

7.1 Why each entity exists

Entity	Purpose
User	Single identity across all roles; role is a field, not separate tables, to keep auth simple for MVP
Event	The root aggregate; almost everything else is scoped by <code>eventId</code>
Registration	Represents "this user is participating in this event" independent of team status (a user can be registered but teamless)
Team	The unit that submits; scoped to one event
TeamMember	Join table, but modeled as a first-class entity because <code>joinedAt</code> and future per-member metadata matter
Submission	The judged artifact; one-to-one with Team in MVP (BR-006)
JudgeAssignment	Explicit assignment record (not inferred), so "who is assigned to what" is queryable and conflict-checkable before an Evaluation exists
Evaluation	The scored result; immutable, one per (judge, submission) pair

7.2 Entities

User

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
name	varchar(120)	yes	—	1-120 chars
email	varchar(255)	yes	—	unique (case-insensitive), RFC 5322 subset
passwordHash	varchar(255)	yes	—	never returned in API responses
role	enum	yes	<code>PARTICIPANT</code>	<code>PARTICIPANT ORGANIZER JUDGE ADMIN</code>
createdAt	timestamp	yes	<code>now()</code>	—
updatedAt	timestamp	yes	<code>now()</code>	auto-updated

Security/privacy: email is PII; passwordHash never leaves the server boundary; consider hashed/salted lookup index for case-insensitive uniqueness (store a normalized `emailLower` column with a unique index).

Event

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
name	varchar(200)	yes	—	1-200
slug	varchar(60)	yes	—	unique, <code>^[a-z0-9-]{3,60}\$</code>
description	text	no	null	—
startDate	timestamp	yes	—	—
endDate	timestamp	yes	—	must be $\geq$ startDate

Field	Type	Required	Default	Constraints
registrationDeadline	timestamp	yes	—	must be $\leq$ submissionDeadline
teamMinSize	int	yes	2	≥ 1
teamMaxSize	int	yes	4	$\geq$ teamMinSize
submissionDeadline	timestamp	yes	—	must be $\leq$ endDate (recommended, not hard-enforced in v1.0 — gap closed here)
status	enum	yes	DRAFT	see Section 6.1
organizerId	UUID	yes	—	FK $\rightarrow$ User.id (missing in v1.0 — an event had no owner!)
createdAt / updatedAt	timestamp	yes	now()	—

Indexing: unique index on slug ; index on status (list/filter queries); index on organizerId .

Registration

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
userId	UUID	yes	—	FK $\rightarrow$ User.id
eventId	UUID	yes	—	FK $\rightarrow$ Event.id
status	enum	yes	CONFIRMED	CONFIRMED WITHDRAWN
registeredAt	timestamp	yes	now()	—

Constraint: unique (userId, eventId) — enforces BR-003 (no duplicate registration) at the DB layer, not just app logic.

Team

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
eventId	UUID	yes	—	FK $\rightarrow$ Event.id
name	varchar(120)	yes	—	unique per event
leaderId	UUID	yes	—	FK $\rightarrow$ User.id, must be a member
state	enum	yes	FORMING	see Section 6.3
createdAt / updatedAt	timestamp	yes	now()	—

TeamMember

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
teamId	UUID	yes	—	FK $\rightarrow$ Team.id
userId	UUID	yes	—	FK $\rightarrow$ User.id
joinedAt	timestamp	yes	now()	—

Constraint: unique (teamId, userId) ; application-layer check enforces BR-002 (one team per event per user) since it spans teams, not expressible as a simple DB unique constraint without a computed column.

Submission

Field	Type	Required	Default	Constraints
-------	------	----------	---------	-------------

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
teamId	UUID	yes	—	FK → Team.id, unique (enforces BR-006: one submission per team)
projectName	varchar(150)	yes	—	1–150
description	text	yes	—	1–5000 chars
repositoryUrl	varchar(500)	yes	—	valid URL
demoUrl	varchar(500)	no	null	valid URL if present
status	enum	yes	DRAFT	see Section 6.4
submittedAt	timestamp	no	null	set on DRAFT→SUBMITTED
updatedAt	timestamp	yes	now()	—

JudgeAssignment

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
judgId	UUID	yes	—	FK → User.id (role=JUDGE)
submissionId	UUID	yes	—	FK → Submission.id
assignedAt	timestamp	yes	now()	—

Constraint: unique (judgId, submissionId) ; app-layer BR-007 check at insert time.

Evaluation

Field	Type	Required	Default	Constraints
id	UUID	yes	generated	PK
submissionId	UUID	yes	—	FK → Submission.id
judgId	UUID	yes	—	FK → User.id
innovationScore	int	yes	—	0–10 (or 0–20 post CHANGE-005)
technicalScore	int	yes	—	0–10
designScore	int	yes	—	0–10
impactScore	int	yes	—	0–10
feedback	text	no	null	≤2000 chars
submittedAt	timestamp	yes	now()	immutable after insert

Constraint: unique (submissionId, judgId) — a judge scores a given submission exactly once.

7.3 ERD

```

erDiagram
    USER ||--o{ REGISTRATION : "makes"
    EVENT ||--o{ REGISTRATION : "receives"
    EVENT ||--o{ TEAM : "contains"
    USER ||--o{ TEAM_MEMBER : "joins"
    TEAM ||--o{ TEAM_MEMBER : "has"
    TEAM ||--|| SUBMISSION : "produces (0..1)"
    SUBMISSION ||--o{ JUDGE_ASSIGNMENT : "assigned"
  
```

```
USER ||--o{ JUDGE_ASSIGNMENT : "assigned as judge"
JUDGE_ASSIGNMENT ||--|| EVALUATION : "results in"
EVENT ||--o{ USER : "organized by (organizerId)"
```

7.4 Referential integrity rules

- Deleting an Event with any Registration/Team/Submission is **soft-blocked**: MVP does not support hard delete of an Event once it has left DRAFT (use CANCELLED instead)
 - `Team.leaderId` must always reference a row in `TeamMember` for that same team — enforced at the application layer on both team creation and leader-leaving (leader-leaving/reassignment is explicitly **out of scope for MVP**, see Section 18, and is a known limitation)
 - Cascade: deleting a Team (only possible while `FORMING` and empty) cascades to `TeamMember`; deleting anything else is not supported in MVP (soft states preferred over hard deletes)
-

8. API Specification

Base URL: `/api/v1`. Auth: Bearer session token in `Authorization` header unless marked public. All responses follow the envelope in Section 8.1.

8.1 Response envelope

Success:

```
{ "data": { }, "meta": { } }
```

Error:

```
{ "error": { "code": "TEAM_FULL", "message": "This team has reached its maximum size.", "field": n
```

8.2 Status codes

`200, 201, 204, 400, 401, 403, 404, 409, 422, 429, 500` — used per the semantics in Section 4/6/8.4.

8.3 Recommendation: OpenAPI as the contract of record

[RECOMMENDATION — directly feeds Thally strategy, Section 15]

Yes, maintain a single `openapi/openapi.yaml` (OpenAPI 3.1) as the literal source of truth for the API surface. Rationale:

- Thally has a confirmed capability to turn an OpenAPI spec into interactive docs pages — using OpenAPI as the contract means the "API Reference" documentation surface (DOC-008) can be regenerated rather than hand-maintained, which removes an entire category of drift (docs described one signature, code implemented another) *by construction*.
- It gives CHANGE-002 (endpoint rename) and CHANGE-003 (new required field) a clean, diffable artifact — the OpenAPI diff *is* the evidence Thally needs to trace to affected pages, whether or not Thally reads the diff directly (per Section 0.2, this needs confirming in the spike).
- Contract tests (Section 17) can validate the implementation against the OpenAPI spec directly (e.g., via Dredd, Schemathesis, or a Prism mock), catching drift between code and contract *before* it ever reaches documentation.

Every endpoint below carries an API ID for traceability into the Change Matrix (Section 16) and Documentation Dependency Matrix (Section 13).

8.4 Endpoints

API ID	Method	Path	Purpose	Auth	Success	Key errors
API-001	POST	<code>/auth/register</code>	Create account	Public	201	409 DUPLICATE_EMAIL, 422
API-002	POST	<code>/auth/login</code>	Authenticate	Public	200	401 INVALID_CREDENTIALS, 429 RATE_LIMITED
API-003	GET	<code>/auth/me</code>	Current user	Session	200	401 SESSION_EXPIRED
API-004	PATCH	<code>/users/{userId}/role</code>	Change a user's role	ADMIN	200	403 FORBIDDEN, 404
API-005	GET	<code>/events</code>	List published events	Public	200	—
API-006	GET	<code>/events/{eventId}</code>	Event detail	Public (DRAFT visible to owner/admin only)	200	404, 403 (draft, non-owner)
API-007	POST	<code>/events</code>	Create event	ORGANIZER, ADMIN	201	422 INVALID_DATE_RANGE, 422 INVALID_TEAM_SIZE_RANGE, 409 SLUG_TAKEN
API-008	PATCH	<code>/events/{eventId}</code>	Update event	Owner ORGANIZER, ADMIN	200	403, 422, 409 (BR-011 violation → <code>TEAM_SIZE_CONFLICT</code>)
API-009	POST	<code>/events/{eventId}/publish</code>	DRAFT→PUBLISHED	Owner ORGANIZER, ADMIN	200	422 EVENT_INCOMPLETE, 409 ALREADY_PUBLISHED
API-010	POST	<code>/events/{eventId}/registrations</code>	Register self	Session (PARTICIPANT)	201	403 EVENT_NOT_PUBLISHED, 403 REGISTRATION_CLOSED, 409 DUPLICATE_REGISTRATION
API-011	GET	<code>/events/{eventId}/registrations</code>	List registrations	Owner ORGANIZER, ADMIN	200	403
API-012	POST	<code>/events/{eventId}/teams</code>	Create team	Session, must be registered	201	403 NOT_REGISTERED, 409 ALREADY_IN_TEAM
API-013	POST	<code>/teams/{teamId}/members</code>	Join team	Session, must be registered for the team's event	201	409 TEAM_FULL, 409 ALREADY_IN_TEAM, 403 NOT_REGISTERED, 409 TEAM_LOCKED
API-014	GET	<code>/teams/{teamId}</code>	Team detail	Session	200	404
API-015	DELETE	<code>/teams/{teamId}/members/{userId}</code>	Remove member	Team leader, Owner ORGANIZER, ADMIN	204	403, 404, 409 CANNOT_REMOVE_LEADER
API-016	POST	<code>/teams/{teamId}/submission</code>	Create (DRAFT) submission	Team leader	201	403 FORBIDDEN (not leader), 409 ALREADY_SUBMITTED
API-017	GET	<code>/teams/{teamId}/submission</code>	Get submission	Team member, Owner ORGANIZER, ADMIN, assigned JUDGE	200	404
API-018	PATCH	<code>/submissions/{submissionId}</code>	Update DRAFT submission	Team leader	200	403 SUBMISSION_LOCKED, 403 SUBMISSION_CLOSED
API-019	POST	<code>/submissions/{submissionId}/submit</code>	DRAFT→SUBMITTED	Team leader	200	403 SUBMISSION_CLOSED, 422 (missing required fields)
API-020	POST	<code>/submissions/{submissionId}/evaluation</code>	Create evaluation	Assigned JUDGE	201	409 JUDGE_CONFLICT, 409 ALREADY_EVALUATED, 422 INVALID_SCORE

API ID	Method	Path	Purpose	Auth	Success	Key errors
API-021	GET	/submissions/{submissionId}/evaluations	List evaluations	Owner ORGANIZER, ADMIN	200	403
API-022	POST	/submissions/{submissionId}/assignments	Assign judge	Owner ORGANIZER, ADMIN	201	409 JUDGE_CONFLICT, 409 ALREADY_ASSIGNED

8.5 Detailed example – API-013 (representative of the full detail level expected for every endpoint at implementation time)

POST /teams/{teamId}/members

- Purpose: add the authenticated user to the given team
- Auth: session required; user must have a CONFIRMED Registration for the team's event
- Path params: `teamId` (UUID)
- Request body: none (acts on the authenticated user) – *design choice, documented explicitly because v1.0 was ambiguous about whether an organizer could add others*
- Success response `201` :

```
{
  "data": {
    "id": "tm_...",
    "teamId": "team_...",
    "userId": "user_...",
    "joinedAt": "2026-08-21T10:00:00Z"
  }
}
```

- Error responses: `403 NOT_REGISTERED`, `409 TEAM_FULL`, `409 ALREADY_IN_TEAM`, `409 TEAM_LOCKED`, `404 TEAM_NOT_FOUND`
- Business rules invoked: BR-001, BR-002
- Side effects: none beyond the TeamMember row (team `state` does not change on join, only on lock trigger)
- Related documentation: DOC-005 (Team Management guide), DOC-008 (API Reference → Teams), `examples/team-creation.md`

(Every other endpoint follows this exact template at implementation time; abbreviated to a table above for document length.)

9. Authentication & Authorization

9.1 Registration / Login / Logout

- Registration: AUTH-001 (Section 4.1)
- Login: AUTH-002 (Section 4.2)
- Logout: `POST /auth/logout` – invalidates the current session (server-side session store) or, if JWT is chosen, is a client-side no-op with a short-lived token + refresh strategy – **decision needed, see Section 24.B**

9.2 Session/token strategy

[OPEN QUESTION] Two viable options, both compatible with everything else in this document:

- **Option A – server sessions:** simplest to reason about, trivially revocable, requires a session store (DB table or Redis)
- **Option B – short-lived JWT + refresh token:** more moving parts, but stateless verification

- **Recommendation for a hackathon timebox:** Option A. Revocability matters more than the marginal scalability Option B buys, and Option A is faster to build correctly.

9.3 Password handling

bcrypt (cost factor 10–12) or argon2id; never log or return `passwordHash` ; SEC-001(unchanged from v1.0).

9.4 RBAC permission matrix

Resource / Action	PARTICIPANT	ORGANIZER (owner)	ORGANIZER (non-owner)	JUDGE (assigned)	ADMIN
View published event	✓	✓	✓	✓	✓
View DRAFT event	✗	✓	✗	✗	✓
Create event	✗	✓	✓	✗	✓
Update event	✗	✓	✗	✗	✓
Publish event	✗	✓	✗	✗	✓
Register self	✓	✗	✗	✗	✓
View registrations list	✗	✓	✗	✗	✓
Create/join team (self)	✓	✗	✗	✗	✓
Remove team member	Leader only	✓	✗	✗	✓
Create/update own submission	Leader only	✗	✗	✗	✓
View any submission	Own team only	✓	✗	Assigned only	✓
Assign judge	✗	✓	✗	✗	✓
Score submission	✗	✗	✗	Assigned, non-conflicted	✓
Change user role	✗	✗	✗	✗	✓

9.5 Resource ownership & security boundaries

- "Owner" for Event = `Event.organizerId` ; any write endpoint checks `caller.id == event.organizerId` OR `caller.role == ADMIN`
- Cross-tenant access (participant reading another team's submission they're not assigned to judge) → `403 FORBIDDEN` , not `404` , is a deliberate choice to keep, **but** flagged: returning 403 instead of 404 leaks existence of the resource. For MVP this is an accepted tradeoff (simplicity); document it as SEC-008 (new) — a known information-disclosure tradeoff, not a bug.

9.6 Error behavior

Unauthenticated on a protected route → `401 UNAUTHENTICATED` . Authenticated but wrong role/ownership → `403 FORBIDDEN` .
Never conflate the two.

9.7 Account lifecycle

No self-service account deletion in MVP (explicit non-goal); ADMIN can deactivate a user (`isActive` flag — **new field, add to User entity**, Section 7.2) which blocks login without deleting history.

10. Non-Functional Requirements

Category	Requirement	Measure
Performance	Standard API requests	p95 < 500ms under expected MVP load (~50 concurrent users)
Performance	Event list/detail (public, cacheable)	p95 < 200ms
Availability	Demo-day uptime	No target beyond "don't go down during the live demo" – this is a hackathon MVP, not a production SLA; stated honestly rather than inventing a number
Scalability	Not a design goal for MVP	Single-event, single-region deployment is acceptable
Security	See Section 27 (SEC-001-008)	All server-enforced, tested
Accessibility	WCAG 2.1 AA best-effort	Semantic HTML, keyboard nav, visible focus states, form labels, color contrast $\geq 4.5:1$
Reliability	Graceful degradation on downstream failure	5xx responses use the standard error envelope, never a raw stack trace
Maintainability	Clear module boundaries per Section 20	Enforced by repo structure, not just convention
Observability	See Section 19	Structured logs for every write operation
Logging	No PII in logs beyond user ID	email/name excluded from log lines
Backup/recovery	Out of scope for MVP	Explicit non-goal; noted so it isn't silently assumed
Deployment	Single environment (staging=prod for demo purposes)	Acceptable for hackathon; document as a known simplification
Configuration	Environment variables for all secrets (SEC-006)	<code>.env.example</code> committed, <code>.env</code> gitignored

11. UI / UX Requirements

11.1 Screen inventory

ID	Screen	Purpose	Primary user
UI-001	Event list	Browse published events	Public
UI-002	Event detail	See event info, register CTA	Public / Participant
UI-003	Register / Login	Auth entry points	Public
UI-004	Team dashboard	View/create/join team, see members	Participant
UI-005	Submission form	Create/edit/submit project	Team leader
UI-006	Submission status	Read-only view for non-leader team members	Participant
UI-007	Organizer: event create/edit	Configure event fields	Organizer
UI-008	Organizer: dashboard	Registration/team/submission counts, judge assignment	Organizer
UI-009	Judge: assignment list	Submissions assigned to this judge	Judge
UI-010	Judge: scoring form	Rubric input + feedback	Judge
UI-011	Admin: user management	Role changes, deactivation	Admin

11.2 Example detail – UI-005 Submission form

- **Purpose:** team leader creates/edits a DRAFT submission and finalizes it
- **User:** authenticated team leader
- **Entry point:** Team dashboard → "Submission" tab

- **Components:** project name field, description textarea, repository URL field, demo URL field (optional), "Save draft" button, "Submit" button (disabled until required fields valid and before deadline)
- **Data displayed:** current draft content, deadline countdown, current status badge
- **Actions:** save draft (PATCH), submit (POST .../submit)
- **Loading state:** skeleton form while fetching existing draft
- **Empty state:** no submission yet → blank form, "Save draft" only
- **Error state:** inline field errors from 422 responses; toast for 403 SUBMISSION_CLOSED
- **Success state:** confirmation banner + status badge flips to SUBMITTED, form becomes read-only
- **Permission behavior:** non-leader team members see UI-006 instead (read-only) – enforced both by routing and by API 403
- **Responsive behavior:** single-column form on mobile; countdown always visible (sticky) given deadline anxiety noted in Priya's persona (Section 3.1)

(Remaining screens follow the same structure at design time; abbreviated here for document length – this is exactly the kind of section a designer should be able to expand from the feature specs in Section 4 without asking what "the submission screen" means.)

11.3 Key user flows

Already captured as journeys in Section 3.5 / v1.0 Section 9 – retained without change, now traceable to the screen IDs above (e.g., Priya's journey = UI-003 → UI-002 → UI-004 → UI-005).

12. Documentation Architecture

Retained from v1.0 with IDs formalized and per-page dependency metadata added (this satisfies the meta-prompt's "for every documentation page define... what product changes could make it stale").

docs/		
├─	getting-started.md	DOC-001
├─	authentication.md	DOC-002
├─	architecture.md	DOC-012
├─	guides/	
	├─ creating-events.md	DOC-003
	├─ registering.md	DOC-004
	├─ teams.md	DOC-005
	├─ submissions.md	DOC-006
	└─ judging.md	DOC-007
├─	api/	DOC-008 (generated from openapi.yaml – see 8.3)
├─	examples/	
	├─ registration.md	
	├─ team-creation.md	
	└─ submission.md	
├─	faq.md	DOC-009
├─	changelog.md	DOC-010
└─	migrations/	DOC-011

12.1 Per-page dependency table

Doc ID	Purpose	Audience	API deps	Business-rule deps	Stale-if
DOC-001	Onboarding	All	API-001, API-002	BR-012	Auth flow changes
DOC-002	Auth guide	All	API-001-004	BR-012, BR-013	Auth mechanism, rate limits change
DOC-003	Event guide	Organizer	API-005-009	BR-009, BR-010, BR-011, BR-014	Status machine, required fields change

Doc ID	Purpose	Audience	API deps	Business-rule deps	Stale-if
DOC-004	Registration guide	Participant	API-010, 011	BR-004, BR-009	Deadline logic, endpoint shape changes
DOC-005	Team guide	Participant	API-012-015	BR-001, BR-002, BR-011	Team-size bounds, lock rule changes
DOC-006	Submission guide	Participant	API-016-019	BR-003, BR-005, BR-006	Deadline/state-machine changes
DOC-007	Judging guide	Judge, Organizer	API-020-022	BR-007, BR-008	Rubric weights, conflict rule changes
DOC-008	API reference	Developers	All	All	Any OpenAPI diff
DOC-009	FAQ	All	—	Any	Any user-facing behavior change
DOC-010	Changelog	All	—	—	Every merged change, by definition
DOC-011	Migration guides	Developers	—	—	Breaking changes only

12.2 Documentation dependency graph

```
graph LR
    BR001[BR-001 team size] --> DOC005[DOC-005 Team Guide]
    BR001 --> DOC009[DOC-009 FAQ]
    BR001 --> DOC008[DOC-008 API Ref]
    API010[API-010 register] --> DOC004[DOC-004 Registration]
    API010 --> DOC008
    API010 --> DOC001[DOC-001 Getting Started]
    AUTHMECH[Auth mechanism] --> DOC002[DOC-002 Auth Guide]
    AUTHMECH --> DOC001
    AUTHMECH --> DOC008
    AUTHMECH --> DOC011[DOC-011 Migration]
```

13. Source-of-Truth Model

Layer	Authoritative for
Running implementation	Actual behavior
<code>openapi.yaml</code>	Supported API contract (must match implementation — verified by contract tests, Section 17)
Business Rules (Section 5, IDs BR-xxx)	Intended behavior — the implementation is <i>supposed</i> to match these; a failing test means either the code or the rule doc is wrong
Documentation (<code>docs/</code>)	What is communicated to readers/agents; must match the implementation, mediated by Thally

13.1 Discrepancy resolution

When PRD says X, code does Y, and docs say Z:

- Code is the ground truth for "what currently happens."** A user hitting the API experiences the code, not the PRD.
- If code diverges from the PRD/business rules without a recorded decision, that is a bug** — fix the code, not the PRD, unless the divergence was an intentional unreviewed change (then update the PRD and BR table explicitly, with a changelog entry).
- Documentation must always converge to match the code**, via the Thally loop — documentation is never the tiebreaker source, it's the thing that gets corrected.

4. Any resolution that changes a Business Rule ID's definition must bump `CHANGELOG.md` and, if user-facing, `DOC-011` (migration guide).

14. Documentation Change Impact Matrix

See Section 16 for the full ten-scenario Track 1 Change Matrix – the meta-prompt's "Documentation Change Impact Matrix" and "Track 1 Change Matrix" asks are the same artifact for this project and are merged there to avoid duplicating ten near-identical tables.

15. Thally Strategy

Grounded strictly in Section 0.2's verified capabilities; anything beyond that is marked.

- What constitutes a product change?** A merged commit/PR to the application repo(s) and/or `openapi.yaml` that alters API shape, business-rule enforcement, or user-facing behavior. Pure refactors (Section 16, CHANGE-006) are commits that do *not* meet this bar – the control case.
- What types of changes are we testing?** The ten scenarios in Section 16: rename, add-required-field, remove-field, two business-rule changes, cross-cutting auth swap, feature addition, feature removal, schema change with public implications, UI-only behavior change, and one internal no-op refactor.
- Which source is monitored? [ASSUMPTION – confirm in spike]** Recommended setup: Thally watches the docs repo (or docs subfolder) where `openapi.yaml` lives, so an OpenAPI diff is the primary signal; if Thally's Track can also watch the application repo directly, add that as a second signal once confirmed.
- Which knowledge surfaces are monitored?** All pages under `docs/` (Section 12), keyed by the Doc IDs and dependency table in Section 12.1.
- How should affected documentation be identified?** Primary mechanism: Thally's Track evidence-tracing (confirmed capability). Secondary/manual cross-check for the demo: the dependency table in Section 12.1, used to verify Thally's output against our own prediction – this is also how we catch it if Track under- or over-reports.
- What evidence establishes staleness?** An OpenAPI diff touching a path/schema referenced by a page (for API docs), or a business-rule ID referenced in a page's frontmatter/metadata no longer matching the code's enforced value (for guides – this cross-check is **our own tooling**, not something claimed to be built into Thally, since that specific mechanism is unverified).
- How are updates reviewed?** Thally prepares a documentation PR (confirmed capability); a human (the team member playing "docs owner" in the demo) reviews and merges/edits it in GitHub, same as any PR.
- How is correctness verified after update?** Manual check against the changed product behavior + the documentation test suite (Section 17) run in CI on the docs PR.
- What happens when no documentation update is necessary?** CHANGE-006 (Section 16) exercises this: Thally should find no affected pages, or should report the change as evaluated-and-no-op – **[ASSUMPTION: confirm Thally actually surfaces a "checked, nothing to do" result rather than simply staying silent, since "silent because nothing happened" and "silent because it never looked" are indistinguishable to a demo audience unless Thally explicitly reports the former]**.
- How do we prevent unnecessary rewrites?** By scoping Track's evidence to the OpenAPI diff and business-rule enforcement, not raw commit volume – an internal rename touches neither, so it shouldn't surface as evidence.

15.1 Control boundaries

Controlled by	Responsibility
SyncFlow application	Enforces business rules, exposes the API described by <code>openapi.yaml</code>
GitHub	Hosts the repos, PR review UI, merge history
Thally	Evidence-tracing, affected-page identification, PR drafting for docs
Human reviewer	Approves/edits/rejects Thally's drafted PR before merge

16. Track 1 Change Matrix & Demonstration Design

Ten scenarios (meta-prompt required ≥10, covering the specific categories listed — all covered below), each doubling as a Track 1 demo candidate. Four are selected as the live demo (Section 16.2); all ten should exist as real commits in repo history so judges can inspect any of them.

16.1 Full Change Matrix

Change ID	Category	Product Change	Code	API	DB	UI	Business Rules	Docs Affected	Expected Action	Evidence
CHANGE-001	Business-rule change	<code>teamMaxSize</code> default 4→5	✓	—	—	✓	BR-001	DOC-005, DOC-008, DOC-009, DOC-010	Update guide + FAQ + changelog	Config/validation diff
CHANGE-002	API rename	<code>POST .../registrations</code> → <code>POST .../register</code>	✓	✓	—	✓	—	DOC-004, DOC-008, examples, DOC-001, DOC-010	Update all endpoint references	OpenAPI path diff
CHANGE-003	New required field	Registration gains required <code>college</code>	✓	✓	✓	✓	—	DOC-004, DOC-008, examples, DOC-009	Update request schema everywhere it's shown	OpenAPI schema diff
CHANGE-004	Removed field (new)	Submission's <code>demoUrl</code> becomes fully removed (not just optional)	✓	✓	✓	✓	—	DOC-006, DOC-008, examples, DOC-010, DOC-011 (migration)	Remove field from docs, add migration note for existing integrations	OpenAPI schema diff (field deleted)
CHANGE-005	Business-rule change	Judging rubric weights change (10/10/10/10 → 20/20/10/10)	✓	✓ (response shape unchanged, values change)	—	✓	rubric config	DOC-007, DOC-009, DOC-010	Update rubric table in judging guide	Config diff + evaluation max-score change
CHANGE-006	Auth mechanism (cross-cutting)	Email+password → Google OAuth	✓	✓	✓	✓	BR-012, BR-013 (rate-limit rule becomes moot)	DOC-001, DOC-002, DOC-008, examples, DOC-009, DOC-011, DOC-010	Full rewrite of auth guide + migration doc for existing password users	OpenAPI security-scheme diff + new endpoints
CHANGE-007	Feature addition (new)	Waitlist: registering after <code>teamMaxSize</code> -adjacent event capacity adds user to a WAITLISTED registration status instead of rejecting	✓	✓ (new status value, new endpoint <code>POST /registrations/{id}/promise</code>)	✓	✓	new BR-015	DOC-004, DOC-008, DOC-009, DOC-010, new guide page	Add new guide section + API page	OpenAPI new-path + new-enum-value diff
CHANGE-008	Feature removal (new)	Remove judge written-feedback field (<code>Evaluation.feedback</code>) entirely — scores only	✓	✓	✓	✓	—	DOC-007, DOC-008, examples, DOC-010, DOC-011	Remove field references, add migration note	OpenAPI schema diff (field deleted)

Change ID	Category	Product Change	Code	API	DB	UI	Business Rules	Docs Affected	Expected Action	Evidence
CHANGE-009	Schema change with public implications (<i>new</i>)	Split <code>User.name</code> into <code>firstName</code> + <code>lastName</code> , changing every API response that embeds a user summary	✓	✓ (breaking response shape change)	✓	✓	—	DOC-001, DOC-002, DOC-008, all example payloads referencing a user object, DOC-011	Widespread example-payload updates + migration guide	OpenAPI schema diff, propagates to every referenced schema
CHANGE-010	UI behavior change affecting docs (<i>new</i>)	Team joining changes from open "browse and join any team" to invite-code-only joining	✓	✓ (<code>POST /teams/{id}/members</code> now requires an <code>inviteCode</code> field)	✓	✓	new BR-016	DOC-005, DOC-008, DOC-009, examples, DOC-010	Update guide's join flow description, add invite-code concept	OpenAPI request-body diff (new required field) + UI copy change
CHANGE-011 (control)	Internal refactor — should NOT trigger doc updates	Rename <code>TeamService</code> → <code>TeamManagementService</code> internally	✓	— (no public surface touched)	—	—	—	None	No documentation PR should be generated	No OpenAPI diff, no business-rule diff — absence of evidence

(This intentionally exceeds the required 10 — CHANGE-011 is the critical negative-control case and should not be cut even under scope pressure; see Section 18.)

16.2 Selected live demo scenarios

Demo Scenario 1 — Simple change (CHANGE-001, team size)

- Initial state: baseline product + docs, verified synchronized (PRD-DG-001)
- Product change: `teamMaxSize` 4→5 in event config + validation
- Files changed: validation schema, one test, `openapi.yaml` (if size appears as a documented constraint, not just a runtime config value — **decide at build time whether team-size bounds are in the OpenAPI schema description or purely business-rule text; recommend documenting them in both for a stronger demo signal**)
- Expected affected docs: DOC-005, DOC-009, DOC-010
- Expected unaffected docs: DOC-002 (auth), DOC-007 (judging) — call this out explicitly on screen
- Thally workflow: commit → Track traces evidence → affected pages identified → PR drafted
- Human review: team member opens the PR, confirms wording, merges
- Final state: guide says 5, FAQ says 5, changelog has an entry
- Proof of sync: side-by-side screenshot of the config value and the rendered doc page showing "5" in both

Demo Scenario 2 — Cross-cutting change (CHANGE-006, auth swap)

- Initial state: post-Scenario-1 baseline
- Product change: replace password auth with Google OAuth
- Expected affected docs: DOC-001, DOC-002, DOC-008, DOC-009, DOC-011, DOC-010 (six surfaces — the point of picking this one)
- Expected unaffected docs: DOC-005 (team guide), DOC-007 (judging guide) — auth mechanism doesn't change team/judging behavior
- Thally workflow / human review / final state: same loop, larger diff
- Proof of sync: migration guide (DOC-011) exists and correctly tells an existing password user what to do

Demo Scenario 3 — Breaking change (CHANGE-009, schema split)

- Initial state: post-Scenario-2 baseline
- Product change: `name` → `firstName` / `lastName` across every response embedding a user
- Expected affected docs: every example payload site (deliberately chosen to show Thally handling a *propagating* change, not just a single endpoint)
- Expected unaffected docs: DOC-007 rubric-specific content (scores don't reference user name shape)

- Proof of sync: migration guide explains the breaking change with a clear before/after payload example

Demo Scenario 4 – "No update required" (CHANGE-011, internal refactor)

- Initial state: post-Scenario-3 baseline
- Product change: `TeamService` → `TeamManagementService` , no public behavior change
- Expected affected docs: **none**
- Expected unaffected docs: **all of them**
- Thally workflow: Track evaluates the change and reports no affected pages (or, per the confirmed capability description, does not draft a PR at all)
- Human review: none needed – the "review" step here is the team narrating why nothing happened, which is the actual point of the scenario
- Proof of sync: absence of a generated PR + a narrated explanation of why, referencing that the OpenAPI spec and business rules are byte-identical before/after

This ordering (simple → cross-cutting → breaking → no-op) tells a deliberate story: escalating complexity, then a clean negative control, which is the strongest structure for judges per the "smallest realistic product, strongest demonstration" goal.

17. Testing Strategy

Layer	Scope
Unit	Every BR-xxx rule (Section 5) individually testable in isolation from HTTP
Integration	Registration → Team → Submission; Submission → Judge Assignment → Evaluation
API/contract	Every endpoint in Section 8.4 validated against <code>openapi.yaml</code> (Schemathesis or Dredd) so code/contract drift is caught in CI, not discovered by Thally after the fact
E2E	Priya's journey (Section 3.5) end-to-end via Playwright; Raj's dashboard journey
Security	Auth boundary tests: every 401/403 case in Section 9.4 has a negative test
Documentation	See below
Regression	Full BR-xxx suite re-run on every PR, including docs PRs (a docs PR should never be able to merge if it silently references a business rule value that no longer matches the code – this is a recommended CI gate, not confirmed as a Thally-native feature)

17.1 Documentation synchronization test format

```
TEST-001
Given: baseline product + docs are verified synchronized (DOC-005 states teamMaxSize=4)
When: teamMaxSize is changed to 5 and merged
Then: Thally identifies DOC-005, DOC-009, DOC-010 as affected
Expected product state: teamMaxSize=5, enforced server-side (join attempt at 6th member rejected)
Expected documentation state: DOC-005 states 5; DOC-002/DOC-007 unchanged

TEST-011 (control)
Given: baseline product + docs are verified synchronized
When: TeamService is renamed to TeamManagementService and merged, with no OpenAPI or business-rule
Then: Thally reports zero affected pages / drafts no PR
Expected product state: identical external behavior (verify via existing E2E suite passing unchang
Expected documentation state: byte-identical to before the change
```

(TEST-002 through TEST-010 follow the same format for CHANGE-002 through CHANGE-010.)

18. Hackathon Scope Control

Must-have (M)

- AUTH (register/login/roles), EVENT (create/publish), REG-001, TEAM-001/002/003, SUB-001/002/004, JUDGE-001/002
- `openapi.yaml` as contract of record
- Baseline docs for DOC-001-DOC-010
- Thally connected and demonstrated on ≥ 1 real merged change
- CHANGE-001, CHANGE-002, CHANGE-011 (the negative control) – these three alone can carry the whole Track 1 story if time runs out

Should-have (S)

- CHANGE-003, CHANGE-005, CHANGE-006 as additional demo depth
- Waitlist (CHANGE-007) as a genuine feature-addition demo
- DOC-011 migration guides

Nice-to-have (N)

- CHANGE-004, CHANGE-008, CHANGE-009, CHANGE-010 as additional matrix entries (keep in the matrix even if not built – a well-reasoned *planned* scenario still demonstrates rigor)
- Admin UI (UI-011) beyond a minimal role-change endpoint
- Rate limiting (BR-013) as a real implementation vs. documented-only

Cut-if-behind

- Real-time anything
- Judge feedback field UI polish beyond a plain textarea
- Waitlist promotion automation (keep the WAITLISTED status, cut the auto-promote logic)
- Any UI screen beyond the minimum needed to generate real product-change evidence (remember: **the product is a vehicle for the sync demo, not the deliverable**)

Explicit recommendation: if the team is behind schedule, cut breadth in Section 4 (fewer polished screens, fewer roles fully fleshed out) before cutting anything in Section 16 (the change matrix / demo scenarios) or Section 17.1 (documentation sync tests). The judged artifact is the sync loop, not the event platform's UI polish.

19. Observability

Log (structured JSON) on every write operation:

- `actorId`, `action`, `resourceType`, `resourceId`, `result` (success/failure + error code), `timestamp`
- Documentation-synchronization events specifically: `changeCommitSha`, `affectedDocsPredicted` (our own dependency-table prediction, Section 12.1), `affectedDocsReportedByThally` (once confirmed what Thally exposes), `reviewDecision` (approved/edited/rejected), `publishedAt`

Visible in the final demo: a simple log/table view (even just a CLI `tail` or a Grafana-free flat table) showing predicted-vs-actual affected pages side by side for each CHANGE scenario – this is the single most convincing artifact for judges, since it makes the traceability claim inspectable rather than asserted.

20. Repository Structure

```
syncflow/
├─ apps/
│  └─ web/                # Next.js frontend
│     └─ api/             # API layer (may be Next.js API routes or separate service – decide in
├─ packages/
│  └─ database/           # Prisma schema + migrations
│     └─ validation/      # Shared Zod/Yup schemas used by both api and web
│        └─ types/        # Shared TS types generated from Prisma + OpenAPI
├─ docs/                  # Thally-published docs (Section 12)
├─ openapi/
│  └─ openapi.yaml        # Contract of record (Section 8.3)
├─ prd/
│  └─ syncflow-prd-v2.md  # This document
├─ tests/
│  └─ unit/
│     └─ integration/
│        └─ e2e/
│           └─ contract/  # OpenAPI-vs-implementation checks
├─ .github/workflows/    # CI: tests + contract checks + (if applicable) Thally trigger
├─ README.md
├─ CHANGELOG.md
└─ package.json
```

21. Development Strategy (Phased)

Phase	Deliverables	Dependencies	Definition of done	Key risks
0 – Research	Thally spike (Section 0.2), Track 1 rules confirmed or explicitly flagged unconfirmed	None	Spike notes committed to <code>docs/thally-spike.md</code>	Track 1 rules never surface – mitigated by proceeding on the inferred objective
1 – Product foundation	This PRD, Architecture doc, DB schema, OpenAPI skeleton	Phase 0	All four artifacts reviewed by the whole team	Scope creep back into v1.0's vagueness
2 – Core application	AUTH, EVENT, REG, TEAM, SUB, JUDGE modules per Section 18's Must-have list	Phase 1	All Must-have acceptance criteria (Section 4) pass	6-module scope eats the timebox – mitigated by Section 18's cut list
3 – Documentation	DOC-001-010 written and manually verified against the shipped baseline (PRD-DG-001)	Phase 2 complete	A second team member can follow the docs and successfully complete Priya's journey using only the docs	Docs written before product stabilizes → immediate drift before the demo even starts
4 – Thally integration	Repo connected, Track confirmed working on a trivial real change	Phase 3	One real merged change produces a real Thally-drafted PR	Auth/setup friction not budgeted – mitigated by Phase 0 spike
5 – Change simulations	CHANGE-001, 002, 011 minimum; 003/005/006/007 if time allows	Phase 4	Each implemented CHANGE has a passing TEST-xxx (Section 17.1)	Running out of time before the negative control (CHANGE-011) – protect this one specifically
6 – Testing	Full suite from Section 17 green	Rolling, alongside 2-5	CI green on main	Tests written after the fact / skipped under time pressure
7 – Demo hardening	Rehearsed run-through of Section 16.2's four scenarios, observability view (Section 19) working	Phase 5-6	Full demo run completes without manual DB edits	Demo depends on live Thally latency – have a recorded fallback

22. Risk Register

Risk	Probability	Impact	Mitigation	Owner	Trigger
Thally's Track doesn't behave as the landing page implies (Section 0.2 unknowns)	Medium	High	Phase 0 spike before any architecture is finalized	Whoever owns Thally integration	Spike reveals a gap
SYNC HACK Track 1's actual rules differ materially from the inferred objective	Medium	High	Get the real brief ASAP; keep this PRD's core loop (Section 16) generic enough to survive rule changes	Team lead	Official brief received
Documentation drift <i>before</i> the demo (docs written early, product changes underneath them)	High	Medium	PRD-DG-001 — verify baseline sync once, right before Phase 4 starts, not earlier	Docs owner	Any Phase 2 change after docs are drafted
Scope creep across 6 modules crowds out the actual judged deliverable (the sync loop)	High	High	Section 18's Must/Should/Nice/Cut list, enforced at each phase gate	Team lead	Any phase running >120% of planned time
API inconsistency between implementation and <code>openapi.yaml</code>	Medium	High	Contract tests in CI (Section 17)	Backend owner	CI failure
Demo-day live Thally call fails/is slow	Medium	Medium	Record a backup video of the four scenarios in advance	Demo owner	Rehearsal reveals latency
Overengineering the sync detection (building our own drift-detector instead of trusting Thally)	Medium	Medium	Explicitly scope our own tooling to <i>prediction/verification</i> (Section 19), never <i>replacement</i>	Team lead	Any PR that reimplements Track's job
Insufficient product complexity to generate a convincing cross-cutting change	Low	Medium	CHANGE-006 (auth swap) and CHANGE-009 (schema split) are specifically chosen to be genuinely cross-cutting	Team lead	Demo rehearsal feels thin
Deployment/infra breaks close to demo day	Low	High	Single environment, minimal moving parts (Section 10)	Whoever owns deploy	Any infra change in the final 48 hours

23. Success Metrics

Product

- All Must-have acceptance criteria (Section 4, Section 18) pass
- Zero business rule (Section 5) has a known enforcement gap at demo time

Technical implementation

- Contract tests green: 0 drift between `openapi.yaml` and implementation
- p95 latency targets (Section 10) met under a basic load test

Documentation

- 100% of DOC-001-010 manually verified against baseline before Phase 4 (PRD-DG-001)
- Every doc page has a populated dependency row in Section 12.1 — no orphaned pages

Synchronization

- ≥ 3 CHANGE scenarios produce a correct Thally-drafted PR (predicted-affected-pages == actually-affected-pages, per the observability view in Section 19)
- CHANGE-011 (negative control) produces zero unnecessary PR/pages touched

Hackathon demo

- All 4 selected scenarios (Section 16.2) run live or from a rehearsed recording without manual data fixes
- The team can answer "what does Thally actually do, concretely" without hedging — because Section 0.2 forced that clarity in advance

Avoided vanity metrics deliberately: no "lines of code," no "number of API endpoints," no "number of docs pages" as standalone success measures — these were the numbers that made v1.0 feel thorough without being rigorous. What's measured above is *correctness of traceability*, which is the actual Track 1 ask.

24. Final Quality Audit

1. **Can a developer build the MVP from this document?** Mostly yes for the Must-have list (Section 18) — Section 4/6/7/8 give actor/flow/failure/data/API detail. Two gaps remain open by design: session-vs-JWT (Section 9.2) and event-status-transition triggering (Section 6.1) — both flagged as open questions requiring a team decision, not oversights.
 2. **Are any requirements ambiguous?** The "leader leaves the team" scenario is explicitly out of scope rather than ambiguous — documented as a known limitation (Sections 3.1, 7.4) rather than left unaddressed.
 3. **Are any features unnecessary?** Section 18's Nice-to-have/Cut-if-behind lists directly answer this — nothing in Must-have is superfluous to either the product loop or the sync demo.
 4. **Are business rules complete?** 14 rules now (BR-001-014), each with reason/scope/affected-surface — up from 10 undecorated rules in v1.0.
 5. **Are API contracts sufficiently precise?** Yes for the representative deep example (Section 8.5); the table (8.4) gives every endpoint enough to implement, though full request/response bodies for all 22 endpoints should be written directly into `openapi.yaml` at Phase 1, not re-typed here.
 6. **Can database schema be derived from this?** Yes — Section 7 gives types, constraints, defaults, and indexing per entity.
 7. **Can UI screens be derived from this?** Yes for the 11 screens in Section 11.1; one fully-detailed example given, rest follow the template.
 8. **Can documentation structure be derived from this?** Yes — Section 12 plus the dependency table.
 9. **Can we intentionally create documentation drift?** Yes — 11 concrete, buildable scenarios (Section 16.1), covering all 10 required categories plus the critical control case.
 10. **Can we clearly demonstrate Thally solving that drift?** Conditionally yes — contingent on the Phase 0 spike confirming the specific unknowns in Section 0.2. This is the single biggest open risk in the whole plan and is treated as such (Section 22, top risk).
 11. **Do we have ≥ 3 excellent demo scenarios?** Yes — four selected (Section 16.2), escalating in complexity.
 12. **Do we have a convincing "no update required" scenario?** Yes — CHANGE-011, explicitly protected from being cut (Section 18) because it's the strongest evidence against "this just rewrites docs on every commit."
 13. **Is the project realistic for a hackathon?** Realistic if Section 18's scope discipline is actually honored — the honest risk (Section 1.9) is that 6 modules is more than the sync story strictly needs, and the mitigation is procedural (phase gates, cut list) rather than a scope reduction made here, since the 6-person team and existing goals (G-001-005) argue for keeping the fuller product.
 14. **Is there anything assumed about Thally without evidence?** Yes, explicitly enumerated in Section 0.2 and re-flagged inline at every point they matter (Sections 15, 16.2 Scenario 4, 17.1 TEST-011, Audit item 10) rather than buried in one place.
-

B. Open Questions (decide before Architecture doc)

1. Session strategy: server sessions vs. JWT+refresh (Section 9.2) — recommend server sessions
2. Event status auto-transition (PUBLISHED→ONGOING→COMPLETED): scheduled job vs. computed-on-read (Section 6.1) — recommend computed-on-read for hackathon scope
3. Does Thally's Track need access to the application repo(s) directly, or only `openapi.yaml` /docs repo? — resolve via Phase 0 spike
4. Is `apps/api` a separate service or Next.js API routes? (Section 20 leaves this open)
5. What is SYNC HACK Track 1's actual submission format — live demo, video, or both? (Section 0.1) — get the real brief
6. Should team-size bounds live in the OpenAPI schema description (stronger CHANGE-001 demo signal) or only in business-rule text? — recommend both
7. Leader-departure/reassignment: truly out of scope for MVP, or worth a minimal "reassign leader" endpoint given it's a real gap? — recommend leaving out of scope, document as known limitation only

C. Recommended Next Artifacts (in order)

1. Architecture + Technical Design Document (resolves Open Questions 1, 2, 4)
2. Database schema / Prisma schema (direct implementation of Section 7)

3. OpenAPI specification (`openapi.yaml` , direct implementation of Section 8)
4. Documentation architecture / actual page drafts (Section 12, gated on Phase 0 spike resolving Open Question 3 first, since it affects what docs need to look like for Thally to work against them)
5. UI specification / wireframes (Section 11)
6. GitHub repository structure + CI setup (Section 20)
7. Implementation plan / sprint breakdown (refines Section 21's phases into tickets)
8. Thally integration plan (only after Phase 0 spike – do not architect this from assumptions)
9. Test plan (refines Section 17 into an actual test-file layout)

D. Build Readiness Score

Dimension	Score /100	Why
Product clarity	92	Personas, journeys, goals all traceable to features; the 6-module-vs-2-module scope tension (1.9) is the only real ambiguity, and it's argued rather than hidden
Technical clarity	85	Feature specs are implementation-ready for Must-have items; two open questions (session strategy, status-transition trigger) are real gaps, not oversights, and are called out for a fast team decision
API clarity	88	Full endpoint table + one fully-detailed example is enough to write the rest into OpenAPI directly; would be 95+ once all 22 are actually in <code>openapi.yaml</code>
Data-model clarity	90	Types, constraints, indexing, and referential-integrity rules given per entity; missing only exact index strategy for high-cardinality queries, which is premature before real load data exists
UX clarity	78	Screen inventory and one deep example are enough to start design, but 10 of 11 screens are template-only, not fleshed out – acceptable for a hackathon MVP, not "build without asking a question" for every screen
Documentation clarity	91	Dependency table + doc IDs + dependency graph directly support the sync demo; the main remaining gap is that doc <i>content</i> doesn't exist yet (expected – that's Phase 3)
Thally readiness	55	This is intentionally the lowest score. Everything Thally-specific in this document is either confirmed-shallow (Section 0.2) or explicitly flagged as an assumption. It cannot honestly score higher until the Phase 0 spike happens – inflating this number would recreate exactly the problem the meta-prompt warned against ("do not invent Thally capabilities")
Hackathon readiness	80	Strong demo narrative (Section 16.2) and honest scope-control mechanism (Section 18), but real risk that "SYNC HACK Track 1" rules (never located) could require format/deliverable changes not anticipated here

Overall assessment: this PRD is ready to drive an Architecture document today, on the condition that the Phase 0 Thally spike (Section 0.2, Open Question 3) happens *before* Section 15's strategy is treated as final, and that the real Track 1 rules get sourced and reconciled against Sections 0.1, 16, and 18 as soon as available.