

CH-230-A

# **Programming in C and C++**

C/C++

## **Lecture 3**

Dr. Kinga Lipskoch

Fall 2020


## Multiple Choices: `switch`

- ▶ `switch` can be used when an expression should be compared with many values
- ▶ The same goal can be obtained with multiple `if`'s
- ▶ The expression must return an integer value

## switch: The Syntax

```
1 switch (expression) {  
2     case c1:  
3         statement1;  
4         break;  
5  
6     case c2:  
7         statement2;  
8         break;  
9  
10    ...  
11  
12    default:  
13        default_statement;  
14 }
```

## switch: Flow Chart



## switch: Example

```
1 #include <stdio.h>
2 int main() {
3     int c;
4     for (c = 0; c <= 3; c++) {
5         printf("c: %d\n", c);
6
7         switch (c) {
8             case 1:
9                 printf("Here is 1\n");
10                break;
11            case 2:
12                printf("Here is 2\n");
13                /* Fall through */
14            case 3:
15            case 4:
16                printf("Here is 3, 4\n");
17                break;
18            default:
19                printf("Here is default\n");
20        }
21    }
22    return 0;
23 }
```

# Iterations

- ▶ In many cases it is necessary to repeat a set of operations many times
- ▶ Example: compute the average grade of the exam
  - ▶ Read all the grades, and sum them
  - ▶ Divide the sum by the number of grades
- ▶ C provides three constructs


## Iterations: `while`

- ▶ General syntax:

```
1 while (condition) {  
2     statement;  
3 }
```

- ▶ Keep executing the statement as long as the condition is true

## while: Flow Chart





## Example:

### Compute the Sum of the First n Natural Numbers

```
1 #include <stdio.h>
2 int main() {
3     int idx, n, sum = 0;
4     printf("Enter a positive number ");
5     scanf("%d", &n);
6     idx = 1;
7     while (idx <= n) {
8         sum += idx;
9         idx++;
10    }
11    printf("The sum is %d\n", sum);
12    return 0;
13 }
```

# Iterations: for

► General syntax:


```
1 for (initial-statement; condition; iteration-  
    statement)  
2     statement;
```

► Example:

```
1 for (n = 0; n <= 10; n++)  
2     printf("%d\n", n);
```

► The `for` and `while` loops can be made interchangeable

## for: Flow Chart



## for: Example Revised

```
1 #include <stdio.h>
2 int main() {
3     int idx, n, sum = 0;
4     printf("Type a positive number ");
5     scanf("%d", &n);
6     for (idx = 1; idx <= n; idx++) {
7         printf("Processing %d..\n", idx);
8         sum += idx;
9     }
10    printf("The sum is %d\n", sum);
11    return 0;
12 }
```

## Boolean Operators and if

```
1  for (n = 0; n < 3; n++) {  
2      for (i = 0; i < 10; i++) {  
3          if (n < 1 && i == 0) {  
4              printf("n is < 1, i is 0\n");  
5          }  
6          if (n == 2 || i == 5) {  
7              printf("HERE n: %d i:%d\n", n, i);  
8          }  
9          else {  
10             printf("n:%d, i:%d\n", n, i);  
11         }  
12     }  
13 }
```

## Easier or Harder to Read?

```
1 for (n = 0; n < 3; n++)
2   for (i = 0; i < 10; i++) {
3     if (n < 1 && i == 0) {
4       printf("n is < 1, i is 0\n"); }
5     if (n == 2 || i == 5) {
6       printf("HERE n: %d i:%d\n", n, i); }
7     else {
8       printf("n:%d, i:%d\n", n, i); }}
```

## Iterations: `do ... while`


- ▶ General syntax:

```
1  do
2      statement;
3  while (condition);
```

```
1  do {
2      statement1;
3      statement2;
4  } while (condition);
```

- ▶ In this case the end condition is evaluated at the end
- ▶ The body is always executed at least once

## do ... while: Flow Chart





## do ... while: Example

```
1 #include <stdio.h>
2 int main() {
3     int n, sum = 0;
4     do {
5         printf("Enter number (<0 ends)");
6         scanf("%d", &n);
7         sum += n;
8     } while (n >= 0);
9     sum -= n; /* Remove last negative value */
10    printf("The sum is %d\n", sum);
11    return 0;
12 }
```

## Jumping Out of a Cycle: `break`

- ▶ The keyword `break` allows to jump out of a cycle when executed
- ▶ We have already seen this while discussing `switch`

```
1 int num, i = 0;
2 scanf("%d", &num);
3 while (i < 50) {
4     printf("%d\n", i);
5     i++;
6     if (i == num)
7         break;
8 }
```

## Jumping Out of a Cycle: `continue`

- ▶ `continue` jumps to the expression governing the cycle
- ▶ The expression is evaluated again and so on

```
1 char c;  
2 /* code assumes that the input is  
3    provided in one line like:  
4    "abf23cdef" followed by enter */  
5 while ((c = getchar()) != '\n') {  
6     // ignore the letter b  
7     if (c == 'b')  
8         continue;  
9     printf("%c", c);  
10 }
```

## Jumping Out of a Cycle

- ▶ Do not abuse `break` and `continue`
- ▶ You can always obtain the same result without using them
  - ▶ This at the price of longer coding
- ▶ By using them your code gets more difficult to read
- ▶ When you are experienced you will master their use
  - ▶ Meanwhile, learn the basics

## Iterations: General Comments

- ▶ Inside the body of the loop you must insert an instruction that can cause the condition to become false
- ▶ If you do not do that, your program will fall into an infinite loop and will be unable to stop (Press Ctrl-C to stop such a program)
- ▶ `do ... while` is far less used than `while` and `for`
- ▶ The same constructs are provided in the majority of other programming languages

# Arrays in C

- ▶ See first lecture for introduction
- ▶ In C you declare an array by specifying the size between square brackets
- ▶ Example: `int my_array[50];`
- ▶ The former is an array of 50 elements
- ▶ The first element is at position 0, the last one is at position 49

## Accessing an Array in C

- ▶ To write an element, you specify its position

```
1  my_array[2] = 34;  
2  my_array[0] = my_array[2];
```

- ▶ Pay attention: if you specify a position outside the limit, you will have unpredictable results segmentation fault, bus error, etc.
- ▶ And obviously wrong
- ▶ Note the different meaning of brackets
- ▶ Brackets in declaration describe the dimension, while in program they are the index operator

## Arrays with Initialization

- ▶ C allows also the following declarations:

```
1  int first_array[]    = {12, 45, 7, 34};  
2  int second_array[4] = {1, 4, 16, 64};  
3  int third_array[4]  = {0, 0};
```

- ▶ It is not possible to specify more values than the declared size of the array
- ▶ The following is wrong:

```
1  int wrong[3] = {1, 2, 3, 4};
```



# Typical Structure of a C Program

```
1 #include <stdio.h>
2 int rect_area(int length, int width);
3 float b_func(int a, int b);
4 int main() {
5     ...
6     c = rect_area(5, 7);
7     b_func(11, 6);
8     return 0;
9 }
10 int rect_area(int length, int width) {
11     ... /* do some operations */
12     return area;
13 }
14 float b_func(int a, int b) {
15     ... /* do some operations */
16     return c;
17 }
```

## Calling a Function

- ▶ To call a function you insert its name
  - ▶ Function call is a statement
- ▶ You have to provide suitable parameters
  - ▶ Number and type of parameters must match function declaration
- ▶ The result of a function can be ignored

## An Example

```
1 #include <math.h>
2 #include <stdio.h>
3 int main() {
4     double number, root;
5     scanf("%lf", &number);
6     if (number >= 0) {
7         root = sqrt(number);
8         printf("Square root is %f\n", root);
9         sqrt(number); /* useless but legal */
10        /* What can I print now? */
11    }
12    else
13        printf("Cannot calc square root\n");
14    return 0;
15 }
```

```
gcc -Wall -lm -o example example.c
```