Domain Adaptation with Graph-TransResNet for Medical Image Segmentation

1. Abstract

The research proposes a novel framework based on a fusion of CNN, Transformer, and GNN-based deep learning architectures for multiclass cardiac magnetic resonance imaging (MRI) segmentation. In this study, the segmentation task focuses on three cardiac structures: the right ventricle (RV), myocardium, and left ventricle (LV). For this project, we used three deep learning architectures: ResNet34 U-Net, representing the CNN-based approach, Swin-Small UPerNet, representing the Transformer-based approach, and ResNet34 + GraphSAGE U-Net, representing the GNN-based hybrid approach. The three models were evaluated across the ACDC, M&Ms, and CMR-MULTI datasets using Dice, IoU, ROC-AUC, SSIM, Hausdorff Distance, and HD95. Our results showed that GraphSAGE achieved the highest Dice scores on ACDC (74.67%) and M&Ms (83.67%), while Swin-Small UPerNet achieved the highest Dice score on CMR-MULTI (85.14%). Our findings suggest that model performance depends on the characteristics of the datasets.

***Index Terms*—Cardiac MRI, Medical Image Segmentation, Convolutional Neural Networks, Vision Transformers, Graph Neural Networks, GraphSAGE, Deep Learning**

2. Introduction

Background & Motivation:

Cardiac MRI Image segmentation is useful to healthcare professionals. It can be defined as "the process of partitioning heart structures—such as the left and right ventricles, myocardium, and atria—in magnetic resonance images to measure heart function and diagnose cardiovascular diseases". Image segmentation is designed to segment important organs and abnormal objects of the human body, such as lungs, nodules, and tumors. In this study, the segmentation task focuses on three important cardiac structures: the right ventricle (RV), myocardium, and left Ventricle (LV). As researchers interested in applying AI and technology, we believe AI tools can help the healthcare field advance. AI is a leading technology, and it is being integrated into different sectors. Healthcare can benefit greatly from AI because there are many tasks to be performed, and having AI assist with some of them can help healthcare professionals focus on other important areas of patient care. In this project, we focused on cardiac MRI images and on how different deep learning architectures can be used to segment key cardiac structures [18].

Research Gap:

The dataset contains three main cardiac structures examined in this study: the Left Ventricle (LV), the Right Ventricle (RV), and the Myocardium.

The left ventricle is the lower left chamber responsible for pumping oxygen-rich blood to the rest of the body. The LV has the thickest walls of the heart chambers because it must generate sufficient force to propel blood through the aortic valve and into the systemic circulation [14].

The right ventricle is responsible for pumping oxygen-poor blood to the lungs. Its walls are thinner than the left ventricle's because it only pumps blood to the lungs, a shorter distance [13].

The myocardium is the thick muscular middle layer of the heart wall responsible for pumping blood. It lies between the inner lining (endocardium) and the outer protective layer (epicardium) [12].

Although CNN, Transformer, and graph-based approaches have individually been investigated for medical image segmentation, their relative behavior is less clear when evaluated within a common multiclass cardiac MRI segmentation framework across multiple datasets. In particular, differences in overlap accuracy, boundary quality, structural similarity, and class-specific performance may not be captured by a single evaluation metric. This creates a need for a systematic comparison of these architectural families using consistent anatomical targets and multiple complementary evaluation measures. To address the research gap, we compared three architectural methods: ImageNet-pretrained ResNet34 U-Net, representing the CNN approach; a pretrained Swin-Small UPerNet, representing the Transformer-based approach; and a ResNet34 + GraphSAGE U-Net, representing the Graph Neural Network (GNN) approach. These models were evaluated across the ACDC, M&Ms, and CMR-MULTI datasets and were also used to segment the right ventricle, Myocardium, and left ventricle. We assessed their performance using Dice coefficient, Intersection over Union (IoU), ROC-AUC, Structural Similarity Index Measure (SSIM), Hausdorff Distance, and 95th-percentile Hausdorff Distance (HD95) [18].

- The main contribution of my research is applying domain adaptation using a transfer learning approach for cardiac image segmentation. A framework is designed with fusion of multiple state-of- the-art-vision-centric deep neural architectures for extracting vital biomarkers for early detection of cardiac

arrest. We extracted multiple anatomical features, including the Right Ventricle (RV), Left Ventricle (LV), and Myocardium

- The experiment is conducted by evaluating benchmark cardiac image datasets. For our study, we used three cardiac MRI datasets: Automated Cardiac Diagnosis Challenge (ACDC), Multi-Center, Multi-Vendor and Multi-Disease Cardiac Segmentation (M&Ms), and CMR-MULTI. We have improved existing methods by removing feature overlap, improving structural similarity, and boundary precision. Our research laid the foundation for systemic disease diagnosis by finding a correlation between pathological features. The performance was evaluated using key metrics, and we achieved better response on Dice, IoU, ROC-AUC, SSIM, Hausdorff Distance, HD95.

3. Methodology

Datasets:

For our study, we used three cardiac MRI datasets: Automated Cardiac Diagnosis Challenge (ACDC), Multi-Center, Multi-Vendor and Multi-Disease Cardiac Segmentation (M&Ms), and CMR-MULTI. These datasets were selected because they contain annotations for the three cardiac structures investigated in our study: the right ventricle (RV), myocardium, and left ventricle (LV).

ACDC Dataset: The ACDC dataset contains cardiac MRI images with manually annotated cardiac structures. For this study, we used the ACDC-PNG 10% labeled split. The segmentation labels consisted of four classes: background, right ventricle (RV), myocardium, and left ventricle (LV). We used the RV, Myocardium, and LV for training. The labeled training set contained 136 images from 7 patients, while the validation set contained 210 images from 10 patients, and the test set contained 380 images from 20 patients [11].

M&Ms Dataset: The M&Ms dataset is a multi-center and multi-vendor cardiac MRI dataset designed to provide cardiac images acquired under more diverse imaging conditions. The dataset contains annotations of the LV cavity, Myocardium, and RV cavity. For this study, both end-diastolic (ED) and end-systolic (ES) images were used. The original M&Ms class labels were standardized to match the class organization used throughout this study: background = 0, RV = 1, Myocardium = 2, and LV = 3. The dataset was divided at the patient level into 150 training patients, 34 validation patients, and 136 test patients. After extracting foreground-containing 2D slices, the final dataset consisted of 2,373 training slices, 573 validation slices, and 2,201 test slices.

CMR-MULTI Dataset: The third dataset we used was CMR-MULTI. For this study, we used the short-axis (SAX) cine cardiac MRI component of the dataset. A total of 105 cases with corresponding cardiac MRI images and segmentation annotations were included. The original annotations contained: background, LV myocardium, LV cavity, and RV cavity. As with M&Ms, the labels were standardized to the common class organization used in the experiments: background = 0, RV = 1, Myocardium = 2, and LV = 3. The 105 cases were split into 73 training, 15 validation, and 17 test cases. After selecting samples containing foreground cardiac structures, the resulting dataset contained 20,052 training samples, 3,954 validation samples, and 4,424 test samples [19].

Dataset Normalization:

One thing we noticed about the three datasets is that they did not use identical class numbering. Later, their segmentation labels were standardized before being used for training. Nevertheless, the experiments followed all four class conventions;

0 = Background
1 = Right Ventricle (RV)
2 = Myocardium
3 = Left Ventricle (LV)

With these standardizations, the evaluation of all three architectures against the same anatomical structures across the three datasets was enabled.

Pre-Processing:

Before training the datasets, the cardiac MRIs were preprocessed to ensure consistent inputs across the three architectures. The images and corresponding segmentation masks were resized to 224 x 224 pixels. Because the MRI images were grayscale, they were converted to three-channel images to make them compatible with the ImageNet-pretrained visual encoders. The images were normalized before they were transferred for training. Data augmentation was applied during the training process using horizontal flipping, affine transformations, brightness, contrast adjustments, and Gaussian noise to boost variation in the training data. For the M&Ms and CMR-MULTI datasets, foreground-containing 2D samples were selected for these experiments. Patients or case-level separation was maintained to prevent samples from the same subject from appearing across the training, validation, and test sets.

Model Architectures:

Three deep learning architectures were evaluated for cardiac MRI segmentation. ResNet34 U-Net, Swin-Small UPerNet, and ResNet34 + GraphSAGE U-Net. The ResNet34 U-Net represented the CNN-based approach. It used an ImageNet-pretrained ResNet34 encoder for feature extraction and a U-Net decoder to reconstruct the spatial information needed to produce the segmentation masks [18]. The Swin-Small UPerNet represented the Transformer-based approach. The model used a pretrained Swin-Small Transformer backbone with UPerNet for semantic segmentation. The Swin Transformer uses hierarchical and window-based self-attention to capture contextual relationships within the image. The segmentation output was adapted to the four

classes used in my study [7]. ResNet34 + GraphSAGE U-Net represented a GNN-based hybrid approach. Visual features of the images were extracted using an ImageNet-pretrained ResNet34 encoder, which was then processed using GraphSAGE layers to characterize interactions between neighboring spatial features [6].

Training Process:

The architectures were trained using PyTorch with GPU acceleration. For the final experiments, we used a batch size of 8. For training, we combined Cross-Entropy loss and multiclass Dice loss. Cross-Entropy helped the models make correct class predictions for each pixel, while Dice loss improved the overlap between the predicted and actual segmentation. The AdamW optimizer was used, with learning rates for the model determined by the architecture being trained. A ReduceLROnPlateau learning-rate scheduler was used to reduce the learning rate when validation performance stopped improving. During training, model performance was monitored using the mean validation Dice score for the RV, Myocardium, and LV. The checkpoint that had the highest validation Dice was retained for final testing, and we used early stopping to prevent unnecessary training after validation performance stopped improving.

Evaluation Metrics:

The performance of the three architectures was evaluated using six metrics: Dice coefficient, Intersection over Union (IoU), ROC-AUC, Structural Similarity Index Measure (SSIM), Hausdorff Distance (HD), and 95th-percentile Hausdorff Distance (HD95). Dice and IoU were used to measure the overlap between the predicted segmentation and the ground-truth mask. In contrast, ROC-AUC was used to evaluate the models' discrimination ability for each cardiac structure. The structural similarity between the predicted and ground-truth mask was measured using SSIM. HD95 provides a less outlier-sensitive assessment by considering the 95th percentile of the boundary distances. The metrics were evaluated separately for the RV, Myocardium, and LV, and macro-average results were used to compare overall model performance. Hausdorff Distance and HD95 were used to evaluate boundary differences, and the results were also reported in pixels on the resized 224 × 224 segmentation masks.

The Dice similarity coefficient was calculated as:

$$\text{Dice} = \frac{2|P \cap G|}{|P| + |G|}$$

where P stands for the predicted segmentation M and G represent the mask and the ground-truth mask, respectively. If there is noticeable overlap between the predicted and actual segmentation, a higher Dice score will be achieved.




Figure 1: Visual framework for cardiac MRI segmentation using CNN, Transformer, and CNN–GNN hybrid architectures.

3.1. Proposed Algorithm

Algorithm 1 Cardiac MRI Segmentation and Evaluation

Require: ACDC, M&Ms, CMR-MULTI datasets
Require: CNN, Transformer, CNN–GNN models
Ensure: Segmentation masks and evaluation results
for each dataset **do**
  Load MRI images and masks
  Split data by patient/case
  Resize images and standardize labels
  for each model **do**
    Initialize pretrained backbone
    Train using CE + Dice loss
    Monitor validation Dice
    Save best checkpoint
    Predict masks on test set
    Compute Dice, IoU, ROC-AUC, SSIM, HD, HD95
  end for
end for
return masks and evaluation results

4. Results and Discussion

Table 4 shows the macro-average segmentation performance of the three models across the ACDC, M&Ms, and CMR-MULTI datasets.

TABLE 1: ACDC Dice Scores

Method	Mean Dice (%)
R50 U-Net (2021)	87.55
TransUNet (2021)	89.71
ResNet34 U-Net	71.52
Swin-Small UPerNet	70.97
ResNet34 + GraphSAGE U-Net	**74.67**

TABLE 2: M&Ms Dice Scores

Method	Mean Dice (%)
Attention-Res-U-Net (2023)	84.42
ResNet34 U-Net	81.63
Swin-Small UPerNet	83.48
ResNet34 + GraphSAGE U-Net	**83.67**

TABLE 3: CMR-MULTI Dice Scores

Method	Mean Dice (%)
3D Swin UNETR (2026)	85.31
ResNet34 U-Net	84.47
Swin-Small UPerNet	**85.14**
ResNet34 + GraphSAGE U-Net	84.52

TABLE 4: Segmentation Performance of the Three Models Across Cardiac MRI Datasets

Dataset	Architecture	Dice	IoU	ROC-AUC	SSIM	HD	HD95
ACDC	ResNet34 U-Net	0.7152	0.6260	0.9896	0.9865	8.1751	5.8789
	Swin-Small UPerNet	0.7097	0.6125	0.9899	0.9851	8.5472	6.7230
	ResNet34 + GraphSAGE U-Net	0.7467	0.6582	0.9957	0.9871	9.9280	4.5921
M&Ms	ResNet34 U-Net	0.8163	0.7304	0.9967	0.9697	6.7530	5.0654
	Swin-Small UPerNet	0.8348	0.7513	0.9965	0.9702	6.0625	2.2324
	ResNet34 + GraphSAGE U-Net	0.8367	0.7540	0.9957	0.9701	6.3336	2.4152
CMR-MULTI	ResNet34 U-Net	0.8447	0.7751	0.9981	0.9730	7.0644	2.8007
	Swin-Small UPerNet	0.8514	0.7821	0.9971	0.9730	6.9237	2.7856
	ResNet34 + GraphSAGE U-Net	0.8452	0.7729	0.9981	0.9724	7.9740	2.9577

4.1. Quantitative Results 1:

Table 4 shows that ResNet34 + GraphSAGE U-Net achieved a slightly better result on the ACDC dataset than the other models, achieving the highest Dice score of 0.7467. ResNet34 + GraphSAGE U-Net also performed slightly better on the M&Ms dataset with a Dice score of 0.8367. However, Swin-Small UPerNet came close to that performance with a Dice score of 0.8348. For the CMR-MULTI dataset, Swin-Small UPerNet performed better than the other models, achieving a Dice score of 0.8514.

4.2. Quantitative Results 2

Figure 2, Figure 3, and Figure 4 present segmentation visualizations from the three cardiac MRI datasets. Figures 2 and 3 are visualized comparisons of the three models used on the ACDC and M&Ms datasets, while Figure 4 shows results of the ResNet34 + GraphSAGE U-Net model on the CMR-MULTI dataset. These visualizations show comparisons between the ground-truth annotations and the predicted segmentation masks for the cardiac images.




Figure 2: ACDC dataset Cardiac MRI segmentation visualization.




Figure 3: M&Ms dataset Cardiac MRI segmentation visualization.




Figure 4: CMR-MULTI dataset Cardiac MRI segmentation visualization.

5. Conclusion

In conclusion, our study compares three deep learning architectures for cardiac image segmentation using the ACDC, M&Ms, and CMR-MULTI datasets. We evaluated the models using Dice, IoU, ROC-AUC, SSIM, Hausdorff Distance, and HD95. The results from this study show that ResNet34 + GraphSAGE U-Net achieved the highest Dice scores on ACDC (74.67%) and M&Ms (83.67%), while Swin-Small UPerNet performed best on CMR-MULTI (85.14%). My findings suggest that model performance depends on the characteristics and quality of the datasets. In the future, we would focus more on improving model generalization across different cardiac MRI datasets.

References

[1] Abdulwahab, S., Rashwan, H. A., Sharaf, N., Khalid, S., & Puig, D. (2023). Deep monocular depth estimation based on content and contextual features. Sensors, 23(6), Article 2919. https://doi.org/10.3390/s23062919

[2] Li, C., Wang, L., & Li, Y. (2022). Transformer and group parallel axial attention co-encoder for medical image segmentation. *Scientific Reports, 12*, Article 16117. https://doi.org/10.1038/s41598-022-20440-z

[3] Liu, W., Zhang, Z., Yang, Z., Song, Y., Li, C., Liu, X., Sun, Y., He, R., Liu, X., & Ming, D. (2026). Anatomy-prior guided decoupled expert networks for multi-view cardiac MRI segmentation and biomarker estimation. In *Medical Image Computing and Computer Assisted Intervention–MICCAI 2026 Workshops and Challenges*, Lecture Notes in Computer Science, Vol. 17268. Springer Nature Switzerland. https://papers.miccai.org/miccai-2026-sat/CMRSeg_076.html

[4] Fu, Z., Zhang, J., Luo, R., Sun, Y., Deng, D., & Xia, L. (2022). TF-Unet: An automatic cardiac MRI image segmentation method. Mathematical Biosciences and Engineering, 19(5), 5207–5222. https://doi.org/10.3934/mbe.2022244

[5] Guo, S., Zhao, X., Ren, J., Shaw, M., Wan, J., & Su, J. (2026). Efficient cardiac MRI multi-structure segmentation for cardiovascular assessment with limited annotation by integrating data-level and network-level consistency. npj Digital Medicine, 9, Article 328. https://doi.org/10.1038/s41746-026-02475-y

[6] Hamilton, W. L., Ying, R., & Leskovec, J. (2017). Inductive representation learning on large graphs. Advances in Neural Information Processing Systems, 30. https://arxiv.org/abs/1706.02216

[7] Liu, Z., et al. (2021). Swin Transformer: Hierarchical vision transformer using shifted windows. In Proceedings of the IEEE/CVF International Conference on Computer Vision (pp. 10012–10022). https://doi.org/10.1109/ICCV48922.2021.00986

[8] Ma, S., Cao, J., Li, Z., Chen, Z., & Hu, X. (2022). An improved algorithm for superresolution reconstruction of ancient murals with a generative adversarial network based on asymmetric pyramid modules. Heritage Science, 10, Article 58. https://doi.org/10.1186/s40494-022-00700-x

[9] Educative. (n.d.). Image segmentation using ConvNets. https://www.educative.io/courses/vision-transformers/image-segmentation-using-convnets

[10] JeopardyLabs. (n.d.). Nursing Jeopardy [Educational game]. https://jeopardylabs.com/print/nursing-jeopardy-354

[11] yscript. (n.d.). ACDC-PNG [Data set]. Hugging Face. https://huggingface.co/datasets/yscript/ACDC-PNG

[12] Grujičić, R. (2023, October 30). Myocardium. Kenhub. https://www.kenhub.com/en/library/anatomy/myocardium

[13] Healthline Editorial Team. (2018, January 22). Right ventricle. Healthline. https://www.healthline.com/health/right-ventricle

[14] Mayo Clinic Staff. (2025, January 29). Ejection fraction: What does it measure? Mayo Clinic. https://www.mayoclinic.org/tests-procedures/ekg/expert-answers/ejection-fraction/faq-20058286

[15] Mayo Clinic Staff. (2026, September 18). Left ventricular hypertrophy: Symptoms and causes.MayoClinic. https://www.mayoclinic.org/diseases-conditions/left-ventricular-hypertrophy/symptoms-causes/syc-20374314

[16] Nemours KidsHealth. (n.d.). Dictionary: Right ventricle. https://kidshealth.org/en/parents/dictionary-right-ventricle.html

[17] Physiopedia. (n.d.). Left ventricle heart. https://www.physio-pedia.com/Left_Ventricle_Heart

[18] Khan, R. F., Lee, B.-D., & Lee, M. S. (2023). *Transformers in medical image segmentation: A narrative review*. *Quantitative Imaging in Medicine and Surgery, 13*(12), 8747–8767. https://pmc.ncbi.nlm.nih.gov/articles/PMC10722011/

[19] Qu, T., et al. (2026). BAAI Cardiac Agent: An intelligent multimodal agent for automated reasoning and diagnosis of cardiovascular diseases from cardiac magnetic resonance imaging. arXiv preprint arXiv:2604.04078. https://arxiv.org/abs/2604.04078

[20] Khan, R. F., Lee, B.-D., & Lee, M. S. (2023). *Vision Transformer in Medical Imaging: A Comprehensive Review of Advancement and Application Across Multiple Diseases, 142*, Article 104377. https://pmc.ncbi.nlm.nih.gov/articles/PMC12701147/

[21] Robu, R. (2023, November 17). *Vision Transformer (ViT).* Medium. https://medium.com/@RobuRishabh/vision-transformer-vit-39f627d04b2a

[22] Mindlina, O. (2024, March 9). *Vision Transformer for semantic segmentation on medical images: Practical uses and experiments.* Medium. https://medium.com/@olga.mindlina/vision-transformer-for-semantic-segmentation-on-medical-images-practical-uses-and-experiments-a2e3939d9870

[23] Raj, A. (2024, September 12). *Image segmentation using Vision Transformers (ViT): A deep dive with Cityscapes and CamVid datasets.* Medium. https://medium.com/@ankitrajsh/image-segmentation-using-vision-transformers-vit-a-deep-dive-with-cityscapes-and-camvid-datasets-fc1ccdca295b

[24] Sanchez-Lengeling, B., Reif, E., Pearce, A., & Wiltschko, A. B. (2021). A gentle introduction to graph neural networks. *Distill*. https://doi.org/10.23915/distill.00033

[25] IBM. (2024). *What is a graph neural network (GNN)?* https://www.ibm.com/think/topics/graph-neural-network

[26] Saini, A., Kumar, A., & colleagues. (2025). Hybrid vision transformer and graph neural network model with region-adaptive attention for enhanced skin cancer prediction. *Scientific Reports*. https://doi.org/10.1038/s41598-025-32502-z

[27] Yang, T., Zhu, G., & Yang, J. (2025). Optimizing image preprocessing for deep learning-based aortic root segmentation in TAVR assessment. In 2025 IEEE 13th International Conference on Healthcare Informatics (ICHI) (pp. 681–682). https://doi.org/10.1109/ICHI64645.2025.00097

[28] Akebli, H., Della Mea, V., & Roitero, K. (2025). Benchmarking feature extractors for prostate cancer detection using graph attention networks: A focus on foundation models. In 2025 IEEE 13th International Conference on Healthcare Informatics (ICHI) (pp. 685–686). https://doi.org/10.1109/ICHI64645.2025.00099

[29] Vemula, S., & Sinko, A. (2026). Gestalt-GNN: Multimodal ROI reasoning for uncertainty-aware chest X-ray multi-label classification. In 2026 IEEE 14th International Conference on Healthcare Informatics (ICHI) (pp. 1145–1153). https://doi.org/10.1109/ICHI69079.2026.00140

[30] Li, H., Xing, W., & Li, C. (2026). GCFSeg: Text-guided pulmonary infection segmentation for clinical decision support via adaptive frequency-domain feature decoupling. In 2026 IEEE 14th International Conference on Healthcare Informatics (ICHI) (pp. 490–495). https://doi.org/10.1109/ICHI69079.2026.00068

[31] Bernard, O., et al. (2018). Deep learning techniques for automatic MRI cardiac multi-structures segmentation and diagnosis: Is the problem solved? *IEEE Transactions on Medical Imaging*, 37(11), 2514–2525. https://doi.org/10.1109/TMI.2018.2837502

[32] Campello, V. M., et al. (2021). Multi-centre, multi-vendor and multi-disease cardiac segmentation: The M&Ms challenge. *IEEE Transactions on Medical Imaging*, 40(12), 3543–3554. https://doi.org/10.1109/TMI.2021.3090082