




Buttons







	e Selectab	
Interface	Signal EMAC_MDC_out EMAC_MDI_in	Pin
EMAC	EMAC_MDO_out EMAC_CRS_out EMAC_COL_out	Any GPIO
I2C	I2CEXTO_SCL_in I2CEXTO_SDA_in I2CEXT1_SCL_in I2CEXT1_SDA_in I2CEXTO_SCL_out I2CEXTO_SDA_out I2CEXT1_SCL_out I2CEXT1_SDA_out	Any GPIO
General Purpose SPI	HSPIQ_in/_out HSPID_In/_out HSPICLK_in/_out HSPICSO_in/_out HSPI_CS1_out HSPI_CS2_out VSPIQ_in/_out VSPID_in/_out VSPICLK_in/_out VSPICSO_in/_out VSPICSO_in/_out VSPICSO_in/_out VSPICSO_in/_out VSPICSO_in/_out VSPICSO_out	Any GPIO

		Voltage of Inter	nal LDO(VDD_SDIO)		
Pin	Default	3.3V	1.8V		
GPI012/MTDI	Pull-Down	0	1	Destatas Dias	
Booting Mode Bootstrapping P					
Pin	Default	SPI Flash Boot	Download Boot	Settings	
GPI00	Pull-Up	1	0		
GPI02	Pull-Down	Don't-care	0	<u> </u>	
		Debugging Log on	UOTXD During Booting		
Pin	Default	UOTXD Toggling	UOTXD Silent		
GPI015/MTD0	Pull-Up	1	0		
		Timing of	SDIO Slave		
Pin	Default	Falling-edge:Output	Falling-edge:Input Rising-edge:Output	Rising—edge:Input Falling—edge:Output	Rising—edge:Input Rising—edge:Outpu
GPI015/MTD0	Pull-Up	0	0	1	1
GPI05/PHY_PW	/RPull=lin	0	1	0	1

Internal Bootstra	pping Resistors
MTDI/GPI012:	Pull-Down
GPI00:	Pull-Up
GPI02:	Pull—Down
GP104:	Pull-Down
MTD0/GPI015:	Pull-Up
GPI05/PHY	_PWR?ull-Up

https://www.olimex.com	
OLIMEX LTD.	
Sheet: /	
File: ESP32-GATEWAY_Rev_D.sch	
Title: ESP32-GATEWAY	
Size: A2 Date: 2018-05-09	Rev: D
KiCad E.D.A. kicad (6.0.0-rc1-dev-1322-g1858b7dca)	ld: 1/1