Power Supply



ESP-WROOM-32 MODULE



Extension



Ethernet



SD/MMC Card



Buttons



LED

Mounting Holes



USB to UART



Software Selectable Pins

Interface	Signal	Pin
EMAC	EMAC_MDC_out EMAC_MDI_in EMAC_MDO_out EMAC_CRS_out EMAC_COL_out	Any GPIO
I2C	I2CEXT0_SCL_in I2CEXT0_SDA_in I2CEXT1_SCL_in I2CEXT1_SDA_in I2CEXT0_SCL_out I2CEXT0_SDA_out I2CEXT1_SCL_out I2CEXT1_SDA_out	Any GPIO
General Purpose SPI	HSPIQ_in/_out HSPID_in/_out HSPICLK_in/_out HSPI_CS0_in/_out HSPI_CS1_out HSPI_CS2_out VSPIQ_in/_out VSPID_in/_out VSPICLK_in/_out VSPI_CS0_in/_out VSPI_CS1_out VSPI_CS2_out	Any GPIO

For more information refer to esp_wroom_32_datasheet_en.pdf.

Bootstrapping Pins Settings

Voltage of Internal LDO(VDD_SDIO)			
Pin	Default	3.3V	1.8V
GPIO12/MTDI	Pull-Down	0	1
Booting Mode			
Pin	Default	SPI Flash Boot	Download Boot
GPIO0	Pull-Up	1	0
GPIO2	Pull-Down	Don't-care	0
Debugging Log on U0TXD During Booting			
Pin	Default	U0TXD Toggling	U0TXD Silent
GPIO15/MTDO	Pull-Up	1	0
Timing of SDIO Slave			
Pin	Default	Falling-edge:Output	Falling-edge:Input Rising-edge:Output	Rising-edge:Input Falling-edge:Output	Rising-edge:Input Rising-edge:Output
GPIO15/MTDO	Pull-Up	0	0	1	1
GPIO5/PHY_PWR	Pull-Up	0	1	0	1

Internal Bootstrapping Resistors

MTDI/GPIO12:	Pull-Down
GPIO0:	Pull-Up
GPIO2:	Pull-Down
GPIO4:	Pull-Down
MTDO/GPIO15:	Pull-Up
GPIO5/PHY_PWR:	Pull-Up

https://www.olimex.com
OLIMEX LTD.
Sheet: /
File: ESP32-GATEWAY_Rev_D.sch
Title: ESP32-GATEWAY
Size: A2 | Date: 2018-05-09 | **Rev: D**
KiCad E.D.A. kicad (6.0.0-rc1-dev-1322-g1858b7dca) | Id: 1/1