



Extension

GPIO6 TO GPIO11- DEBUG ONLY!
USED FOR INTERNAL FLASH MEMORY!





 Interface	Signal	Pin
EMAC	EMAC_MDC_out EMAC_MDL_in EMAC_MDO_out EMAC_CRS_out EMAC_COL_out	Any GPIO
I2C	I2CEXTO_SCL_in I2CEXTO_SDA_in I2CEXT1_SCL_in I2CEXT1_SDA_in I2CEXT0_SCL_out I2CEXT0_SDA_out I2CEXT1_SCL_out I2CEXT1_SCL_out	Any GPIO
General Purpose SPI	HSPIQ_in/_out HSPID_in/_out HSPID_in/_out HSPICSO_in/_out HSPL_CSS_out HSPL_CSS_out VSPIQ_in/_out VSPID_in/_out VSPID_in/_out VSPIC_SO_in/_out VSPLCSS_out VSPLCSS_out VSPLCSS_out	Any GPIO

	<b>,</b>	Voltage of Inter	nal LDO(VDD_SDIO)			
Pin	Default	3.3V	1.8V			
GPI012/MTDI	Pull-Down	0	1	Dooboboo	i Di	
		Bootin	ng Mode		pping Pins	
Pin	Default	SPI Flash Boot	Download Boot	iii Sett	Settings	
GPI00	Pull-Up	1	0			
GPI02	Pull-Down	Don't-care	0			
		Debugging Log on	UOTXD During Booting			
Pin	Default	UOTXD Toggling	UOTXD Silent			
GPI015/MTD0	Pull-Up	1	0			
		Timing of	SDIO Slave			
Pin	Default	Falling-edge:Output	Falling-edge:Input Rising-edge:Output	Rising—edge:Input Falling—edge:Output	Rising-edge:Input Rising-edge:Output	
GPI015/MTD0	Pull-Up	0	0	1	1	
GPI05	Pull-Up	0	1	0	1	

Internal Bootstra	pping Resistors
MTDI/GPI012:	Pull-Down
GPI00:	Pull-Up
GP102:	Pull-Down
GP104:	Pull-Down
MTDO/GPI015:	Pull-Up
GPI05:	Pull-Up

https://www.olimex.com	
OLIMEX LTD.	
Sheet: / File: ESP32-GATEWAY_Rev_C.sch	
Title: ESP32-GATEWAY_Rev_C	
Size: A2 Date:	Rev:
KiCad E.D.A. kicad 6.0.0-rc1-unknown-0cca1c665ubuntu16.04.1	ld: 1/1