

Data Manipulation

Module 6

Andrew Jaffe

June 16, 2015

Manipulating Data

So far, we've covered how to read in data, and select specific rows and columns.

All of these steps help you set up your analysis or data exploration.

Now we are going to cover manipulating your data and summarizing it using basic statistics and visualizations.

Sorting and ordering

`sort(x, decreasing=FALSE)`: 'sort (or order) a vector or factor (partially) into ascending or descending order.' Note that this returns an object that has been sorted/ordered

`order(...,decreasing=FALSE)`: 'returns a permutation which rearranges its first argument into ascending or descending order, breaking ties by further arguments.' Note that this returns the indices corresponding to the sorted data.

Sorting and ordering

```
x = c(1,4,7,6,4,12,9,3)
sort(x)
```

```
## [1]  1  3  4  4  6  7  9 12
```

```
order(x)
```

```
## [1] 1 8 2 5 4 3 7 6
```

Note you would have to assign the sorted variable to a new variable to retain it

Sorting and ordering

```
circ = read.csv("../data/charmcirc_reduced.csv", header=TRUE,as.is=TRUE)
circ2 = circ[,c("day", "date", "orangeAverage", "purpleAverage",
               "greenAverage", "bannerAverage", "daily")]
head(order(circ2$daily,decreasing=TRUE))
```

```
## [1] 888 887 886 971 880 866
```

```
head(sort(circ2$daily,decreasing=TRUE))
```

```
## [1] 22074.5 21951.0 17580.0 16714.0 16366.5 16149.5
```

The first indicates the rows of `circ2` ordered by daily average ridership. The second displays the actual sorted values of daily average ridership.

Sorting and ordering

```
circSorted = circ2[order(circ2$daily,decreasing=TRUE),]  
circSorted[1:5,]
```

```
##           day           date orangeAverage purpleAverage greenAverage  
## 888 Saturday 06/16/2012         6322.0         7797.0         3338.5  
## 887  Friday 06/15/2012         6926.5         8089.5         3485.0  
## 886 Thursday 06/14/2012         5617.5         6521.0         2769.5  
## 971  Friday 09/07/2012         5717.5         7007.0         2688.5  
## 880  Friday 06/08/2012         5782.5         6881.5         2858.0  
## bannerAverage  daily  
## 888           4617.0 22074.5  
## 887           3450.0 21951.0  
## 886           2672.0 17580.0  
## 971           1301.0 16714.0  
## 880            844.5 16366.5
```

Sorting and ordering

Note that the row names refer to their previous values. You can do something like this to fix:

```
rownames(circSorted)=NULL  
circSorted[1:5,]
```

```
##           day           date orangeAverage purpleAverage greenAverage  
## 1 Saturday 06/16/2012         6322.0         7797.0         3338.5  
## 2  Friday 06/15/2012         6926.5         8089.5         3485.0  
## 3 Thursday 06/14/2012         5617.5         6521.0         2769.5  
## 4  Friday 09/07/2012         5717.5         7007.0         2688.5  
## 5  Friday 06/08/2012         5782.5         6881.5         2858.0  
## bannerAverage  daily  
## 1           4617.0 22074.5  
## 2           3450.0 21951.0  
## 3           2672.0 17580.0  
## 4           1301.0 16714.0  
## 5            844.5 16366.5
```

Creating categorical variables

the `rep()` [“repeat”] function is useful for creating new variables

```
bg = rep(c("boy", "girl"), each=50)
head(bg)
```

```
## [1] "boy" "boy" "boy" "boy" "boy" "boy"
```

```
bg2 = rep(c("boy", "girl"), times=50)
head(bg2)
```

```
## [1] "boy" "girl" "boy" "girl" "boy" "girl"
```

```
length(bg)==length(bg2)
```

```
## [1] TRUE
```

Creating categorical variables

One frequently-used tool is creating categorical variables out of continuous variables, like generating quantiles of a specific continuously measured variable.

A general function for creating new variables based on existing variables is the `ifelse()` function, which “returns a value with the same shape as test which is filled with elements selected from either yes or no depending on whether the element of test is TRUE or FALSE.”

```
ifelse(test, yes, no)

# test: an object which can be coerced
#       to logical mode.
# yes: return values for true elements of test.
# no: return values for false elements of test.
```

Creating categorical variables

For example, we can create a new variable that records whether daily ridership on the Circulator was above 10,000.

```
hi_rider = ifelse(circ$daily > 10000, 1, 0)
head(hi_rider)
```

```
## [1] 0 0 0 0 0 0
```

```
table(hi_rider)
```

```
## hi_rider
##    0    1
## 740 282
```

Creating categorical variables

You can also nest `ifelse()` within itself to create 3 levels of a variable.

```
riderLevels = ifelse(circ$daily < 10000, "low",
                    ifelse(circ$daily > 20000,
                          "high", "med"))
head(riderLevels)
```

```
## [1] "low" "low" "low" "low" "low" "low"
```

```
table(riderLevels)
```

```
## riderLevels
## high low med
##      2 740 280
```

Creating categorical variables

However, it's much easier to use `cut()` to create categorical variables from continuous variables.

'`cut` divides the range of `x` into intervals and codes the values in `x` according to which interval they fall. The leftmost interval corresponds to level one, the next leftmost to level two and so on.'

```
cut(x, breaks, labels = NULL, include.lowest = FALSE,
    right = TRUE, dig.lab = 3,
    ordered_result = FALSE, ...)
```

Creating categorical variables

x: a numeric vector which is to be converted to a factor by cutting.

breaks: either a numeric vector of two or more unique cut points or a single number (greater than or equal to 2) giving the number of intervals into which `x` is to be cut.

labels: labels for the levels of the resulting category. By default, labels are constructed using "(a,b]" interval notation. If `labels = FALSE`, simple integer codes are returned instead of a factor.

Factors

Factors are used to represent categorical data, and can also be used for ordinal data (ie categories have an intrinsic ordering)

Note that R reads in character strings as factors by default in functions like `read.table()`

'The function `factor` is used to encode a vector as a factor (the terms 'category' and 'enumerated type' are also used for factors). If argument `ordered` is `TRUE`, the factor levels are assumed to be ordered.'

```
factor(x = character(), levels, labels = levels,
       exclude = NA, ordered = is.ordered(x))
```

Factors

Suppose we have a vector of case-control status

```
cc = factor(c("case","case","case",
             "control","control","control"))
cc
```

```
## [1] case    case    case    control control control
## Levels: case control
```

```
levels(cc) = c("control","case")
cc
```

```
## [1] control control control case    case    case
## Levels: control case
```

Factors

Note that the levels are alphabetically ordered by default. We can also specify the levels within the factor call

```
factor(c("case","case","case","control",
         "control","control"),
       levels =c("control","case") )
```

```
## [1] case    case    case    control control control
## Levels: control case
```

```
factor(c("case","case","case","control",
         "control","control"),
       levels =c("control","case"), ordered=TRUE)
```

```
## [1] case    case    case    control control control
## Levels: control < case
```

Factors

Factors can be converted to `numeric` or `character` very easily

```
x = factor(c("case","case","case","control",
             "control","control"),
           levels =c("control","case") )
as.character(x)
```

```
## [1] "case"    "case"    "case"    "control" "control" "control"
```

```
as.numeric(x)
```

```
## [1] 2 2 2 1 1 1
```

Cut

Now that we know more about factors, `cut()` will make more sense:

```
x = 1:100
cx = cut(x, breaks=c(0,10,25,50,100))
head(cx)
```

```
## [1] (0,10] (0,10] (0,10] (0,10] (0,10] (0,10]
## Levels: (0,10] (10,25] (25,50] (50,100]
```

```
table(cx)
```

```
## cx
##   (0,10]  (10,25]  (25,50]  (50,100]
##      10      15      25      50
```

We can also leave off the labels

```
cx = cut(x, breaks=c(0,10,25,50,100), labels=FALSE)
head(cx)
```

```
## [1] 1 1 1 1 1 1
```

```
table(cx)
```

```
## cx
##  1  2  3  4
## 10 15 25 50
```

Note that you have to specify the endpoints of the data, otherwise some of the categories will not be created

```
cx = cut(x, breaks=c(10,25,50), labels=FALSE)
head(cx)
```

```
## [1] NA NA NA NA NA NA
```

```
table(cx)
```

```
## cx
##  1  2
## 15 25
```

```
table(cx,useNA="ifany")
```

```
## cx
##   1    2 <NA>
##  15   25   60
```

Adding to data frames

```

circ2$riderLevels = cut(circ2$daily,
  breaks = c(0,10000,20000,100000))
circ2[1:2,]

```

```

##      day      date orangeAverage purpleAverage greenAverage
## 1 Monday 01/11/2010          952             NA             NA
## 2 Tuesday 01/12/2010         796             NA             NA
## bannerAverage daily riderLevels
## 1             NA    952  (0,1e+04]
## 2             NA    796  (0,1e+04]

```

```

table(circ2$riderLevels, useNA="always")

```

```

##
##      (0,1e+04] (1e+04,2e+04] (2e+04,1e+05]      <NA>
##             731             280             2             133

```

Adding rows and columns

```

m1 = matrix(1:9, nrow = 3,
  ncol = 3, byrow = FALSE)
m1

```

```

##      [,1] [,2] [,3]
## [1,]    1    4    7
## [2,]    2    5    8
## [3,]    3    6    9

```

```

m2 = matrix(1:9, nrow = 3,
  ncol = 3, byrow = TRUE)
m2

```

```

##      [,1] [,2] [,3]
## [1,]    1    2    3
## [2,]    4    5    6
## [3,]    7    8    9

```

Adding rows and columns

More generally, you can add columns (or another matrix/data frame) to a data frame or matrix using `cbind()` ('column bind'). You can also add rows (or another matrix/data frame) using `rbind()` ('row bind').

Note that the vector you are adding has to have the same length as the number of rows (for `cbind()`) or the number of columns (`rbind()`)

When binding two matrices, they must have either the same number of rows or columns

```
cbind(m1,m2)
```

```
##      [,1] [,2] [,3] [,4] [,5] [,6]
## [1,]    1    4    7    1    2    3
## [2,]    2    5    8    4    5    6
## [3,]    3    6    9    7    8    9
```

Adding rows and columns

```
rbind(m1,m2)
```

```
##      [,1] [,2] [,3]
## [1,]    1    4    7
## [2,]    2    5    8
## [3,]    3    6    9
## [4,]    1    2    3
## [5,]    4    5    6
## [6,]    7    8    9
```

Adding columns manually

```
circ2$riderLevels = NULL
rider = cut(circ2$daily, breaks = c(0,10000,20000,100000))
circ2 = cbind(circ2,rider)
circ2[1:2,]
```

```
##      day      date orangeAverage purpleAverage greenAverage
## 1 Monday 01/11/2010          952             NA             NA
## 2 Tuesday 01/12/2010          796             NA             NA
##  bannerAverage daily      rider
## 1              NA    952 (0,1e+04]
## 2              NA    796 (0,1e+04]
```

Other manipulations

- `abs(x)`: absolute value
- `sqrt(x)`: square root
- `ceiling(x)`: `ceiling(3.475)` is 4
- `floor(x)`: `floor(3.475)` is 3
- `trunc(x)`: `trunc(5.99)` is 5
- `round(x, digits=n)`: `round(3.475, digits=2)` is 3.48
- `signif(x, digits=n)`: `signif(3.475, digits=2)` is 3.5
- `log(x)`: natural logarithm
- `log10(x)`: common logarithm
- `exp(x)`: e^x

(via: <http://statmethods.net/management/functions.html>)