



Note:
1.Material:
1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
1.2 Contact: copper alloy,t=0.15mm
1.3 Shell: copper alloy,t=0.30mm
2.Specification:
2.1 Current rating: 1 A Max.
2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
2.3 Contact resistance: 50 mW Max.
2.4 Insulation resistance: 100 MW Min.
2.5 Total mating force: 3.57 Kgf Max.
2.6 Total unmating force: 1.0 Kgf Min.0.81~2.05 Kgf Min.
2.7 Temperature range: -30°C~80°C

A 01 S B 7 4 1 B 1-267

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

- ① 产品代号 A:成品
- ② 产品系列 01:micro usb 5pin
- ③ 产品类别 S:母座
- ④ 产品类型 B:B TYPE
- ⑤ 外壳材质 1:C2680R-H
- ⑥ 端子材质 4:05191R-EH
- ⑦ 主体材质 1:LCP
- ⑧ 主体颜色 B:黑色
- ⑨ 下板类型 1:DIP
- ⑩ 细节流水 267:MIRCO USB 5S B TYPE 四脚全插(牛角型)短针无导位

PART NO: A01SB741B1-267		MATERIAL: SEE NOTE		TITLE: MIRCO USB 5S B TYPE 四脚全插(牛角型)短针无导位			
MODEL NO: XX		FINSH: SEE NOTE					
UNIT: MM	SIZE: A4	COLOR: SEE NOTE					
TOLERANCE UNSPECIFIED .x 0.15 .xx 0.10 .xxx 0.05 Ang. 1°		DR: xiaoyouhong		DWG NO: A267		REV: A	
		CHK:					
		APP:		SCALE: 5:1		DATE: 2012.05.02	