

# Recommended PCB Pad Layouts for 8 Land USON & WSON Packages

### 1.0 Introduction

This application note specifies the recommended Printed Circuit Board pad layouts for the following 8-USON and 8-WSON packages.

2x3mm USON 8L	
4x4mm USON 8L	
6x5mm WSON 8L	
8x6mm WSON 8L	

### 2.0 2x3mm USON 8L




Figure-1: PCB Pad Layout for 2x3mm 8-USON

#### Notes:

- 1. Solid lines indicate the package outline.
- 2. Blue shaded areas indicate metal pad locations. The use of a solder mask between metal pads on the PCB is recommended.
- 3. The exposed metal center pad is not needed for heat dissipation.

Please leave a keep-out area underneath the exposed metal center pad and avoid placing vias or traces in the keep-out area. This is to prevent the exposed metal pad from accidentally shorting to a via or trace.

Another option is to put a pad underneath the exposed center metal pad, but leave the pad floating.

On some devices, the exposed metal center pad can be connected to the same ground as the GND pin of the package, but please check device datasheet package information to confirm that this option is allowable.

P/N: AN0159 1 Ver.3, Mar. 31, 2016



# Recommended PCB Pad Layouts for 8 Land USON & WSON Packages

### 3.0 4x4mm USON 8L




Figure-2: PCB pad layout 4x4mm 8-USON

#### Notes:

- 1. Solid lines indicate the package outline.
- 2. Blue shaded areas indicate metal pad locations. The use of a solder mask between metal pads on the PCB is recommended.
- 3. The exposed metal center pad is not needed for heat dissipation.

Please leave a keep-out area underneath the exposed metal center pad and avoid placing vias or traces in the keep-out area. This is to prevent the exposed metal pad from accidentally shorting to a via or trace.

Another option is to put a pad underneath the exposed center metal pad, but leave the pad floating.

On some devices, the exposed metal center pad can be connected to the same ground as the GND pin of the package, but please check device datasheet package information to confirm that this option is allowable.

P/N: AN0159 2 Ver.3, Mar. 31, 2016



## Recommended PCB Pad Layouts for 8 Land USON & WSON Packages

### 4.0 6x5mm WSON 8L




Figure-3: PCB pad layout for 6x5mm 8-WSON

#### Notes.

- 1. Solid lines indicate the package outline.
- 2. Blue shaded areas indicate metal pad locations. The use of a solder mask between metal pads on the PCB is recommended.
- 3. The exposed metal center pad is not needed for heat dissipation.

Please leave a keep-out area underneath the exposed metal center pad and avoid placing vias or traces in the keep-out area. This is to prevent the exposed metal pad from accidentally shorting to a via or trace.

Another option is to put a pad underneath the exposed center metal pad, but leave the pad floating.

On some devices, the exposed metal center pad can be connected to the same ground as the GND pin of the package, but please check device datasheet package information to confirm that this option is allowable.

P/N: AN0159 3 Ver.3, Mar. 31, 2016



### Recommended PCB Pad Layouts for 8 Land USON & WSON Packages

### 5.0 8x6mm WSON 8L




Figure-4: PCB pad layout for 8x6mm 8-WSON

#### Notes:

- 1. Solid lines indicate the package outline.
- 2. Blue shaded areas indicate metal pad locations. The use of a solder mask between metal pads on the PCB is recommended.
- 3. The exposed metal center pad is not needed for heat dissipation.

Please leave a keep-out area underneath the exposed metal center pad and avoid placing vias or traces in the keep-out area. This is to prevent the exposed metal pad from accidentally shorting to a via or trace.

Another option is to put a pad underneath the exposed center metal pad, but leave the pad floating.

On some devices, the exposed metal center pad can be connected to the same ground as the GND pin of the package, but please check device datasheet package information to confirm that this option is allowable.

## 6. Revision History

Revision	Description	Date
2.0	Initial Release	May 15, 2012
3.0	Modify PCB Pad Size to match component typical dimensions instead of min/max dimensions.	Mar. 31, 2016

P/N: AN0159 4 Ver.3, Mar. 31, 2016



## Recommended PCB Pad Layouts for 8 Land USON & WSON Packages

Except for customized products which have been expressly identified in the applicable agreement, Macronix's products are designed, developed, and/or manufactured for ordinary business, industrial, personal, and/or household applications only, and not for use in any applications which may, directly or indirectly, cause death, personal injury, or severe property damages. In the event Macronix products are used in contradicted to their target usage above, the buyer shall take any and all actions to ensure said Macronix's product qualified for its actual use in accordance with the applicable laws and regulations; and Macronix as well as it's suppliers and/or distributors shall be released from any and all liability arisen therefrom.

Copyright© Macronix International Co., Ltd. 2016. All rights reserved, including the trademarks and tradename thereof, such as Macronix, MXIC, MXIC Logo, MX Logo, Integrated Solutions Provider, NBit, Nbit, NBiit, Macronix NBit, eLiteFlash, HybridNVM, HybridFlash, XtraROM, Phines, KH Logo, BE-SONOS, KSMC, Kingtech, MXSMIO, Macronix vEE, Macronix MAP, Rich Au-dio, Rich Book, Rich TV, and FitCAM. The names and brands of third party referred thereto (if any) are for identification purposes only.

For the contact and order information, please visit Macronix's Web site at: http://www.macronix.com

P/N: AN0159 5 Ver.3, Mar. 31, 2016