CHIPONE
集创北方

ICN2027

(16-Channel Constant Current LED Sink Driver)

Description

The ICN2027 is a 16-channel constant current sink output LED driver. All 16-channels constant current can be set by a single external resistor, which provides users flexibility in controlling the light intensity of LEDs.

The ICN2027 contains 16-bit shift registers and latches which convert serial input data into parallel output format，therefore，the ON or OFF of LED can be controlled by an external enable signal $\overline{OE}$. And ICN2027 exploits current precision controlling technology，which makes error between ICs less than ±2.5%, and error between channels less than ±1.3%. At ICN2027 output stage， 16-regulated output ports are designed to provide uniform and constant current sinks for driving LEDs within a large range of forward voltage(V_F) variations. The high clock frequency, 30MHz, also satisfies the system requirements of high volume data transmission.

ICN2027

Features

- ✧ 16 channel constant-current output
- ✧ Output current setting range：
  3~65mA×16@V_{DD}=5V constant current output
  3~30mA×16@V_{DD}=3.3V constant current output
- ✧ Current accuracy
  Between channel :< ±1.3%
  Between ICs :< ± 2.5%
- ✧ Fast response of output current,
  $\overline{OE}$ (min):40ns@V_{DD}=5V
- ✧ 16 channels maximum voltage 17V
- ✧ I/O: Schmitt trigger input
- ✧ Data transfer frequency:f_{MAX}=30MHz(Max)
- ✧ Power supply voltage: V_{DD}=3.3～5V
- ✧ Operating Temperature: –40°C to +85°C
- ✧ Pre-Charge for Ghosting Reduction

Pin Configuration



ICN2027

Pin Description

Pin Name	Function
GND	Power Ground
SIN	Serial data input for driver control
CLK	Clock input terminal for data shift on rising edge
LE	Edge triggered latch. LE high level, serial data is transferred to the output latch; LE low level, the data is latched
$\overline{OUT0}\sim\overline{OUT15}$	Constant current output
$\overline{OE}$	Output enable terminal, $\overline{OE}$ high level, all output drivers are enabled; OE low level, all output drivers are turned OFF
SOUT	Serial-data output to the following IC.
R-EXT	Constant-current value setting .Connection to an external resistor to GND.
VDD	Power-supply voltage

Block Diagram



I/O Equivalent Circuits

1. CLK, SIN



2. $\overline{OE}$



3. LE



4. SOUT



Timing Diagram



Note 1: Keep the LE pin is set to L to enable the latch circuit to hold data. When the LE pin is set to H, the latch circuit does not hold data. The data will instead pass onto output. When the $\overline{OE}$ pin is set to L, the $\overline{OUT0}$ to $\overline{OUT15}$ output pins will go ON and OFF in response to the data. In addtion, when the $\overline{OE}$ pin is set to H all the output pins will be forced OFF regardless of the data.

Truth Table

CLK	LE	$\overline{OE}$	SIN	$\overline{OUT0}$ ··· $\overline{OUT7}$ ··· $\overline{OUT15}$	SOUT
↑	H	L	D_n	D_n ··· D_{n-7} ··· D_{n-15}	D_{n-15}
↑	L	L	D_{n+1}	No Change	D_{n-14}
↑	H	L	D_{n+2}	D_{n+2} ··· D_{n-5} ··· D_{n-13}	D_{n-13}
↓	×	L	D_{n+3}	D_{n+2} ··· D_{n-5} ··· D_{n-13}	D_{n-13}
↓	×	H	D_{n+3}	OFF	D_{n-13}

Maximum Ratings (T_a =25℃)

Characteristics		Symbol	Rating	Unit
Supply Voltage		V_{DD}	0~7.0	V
Output Current		I_O	65	mA
Input Voltage		V_{IN}	−0.4~V_{DD}+0.4	V
Output voltage		V_{OUT}	11V	
Clock Frequency		F_{CLK}	30	MHz
GND Terminal Current		I_{GND}	+1000	mA
Power Dissipation (On PCB，25℃)	DN-type	P_D	3.19	W
Thermal Resistance	DN-type	$R_{th(j-a)}$	39.15	℃/W
Operating Temperature		T_{opr}	−50 ~ 85	℃
Storage Temperature		T_{stg}	−55 ~ 150	℃

DC Items (Unless otherwise specified, T_a =-40℃~85℃)

Characteristics	Symbol	Test Conditions	Min	Typ	Max	Unit
Power Supply Voltage	V_{DD}	−	3.3	5	6.0	V
Output Voltage when ON	$V_{O(ON)}$	$\overline{OUTn}$	0.6	−	4	V
High level logic input voltage	V_{IH}	−	0.7*V_{DD}	−	V_{DD}	V
High level logic input voltage	V_{IL}	−	GND	−	0.3*V_{DD}	V
SOUT high level output Current	I_{OH}	V_{DD}=5V	−	−	−1	mA
SOUT low level output Current	I_{OL}	V_{DD}=5V	−	−	1	mA
Constant current output	I_O	$\overline{OUTn}$	0.5	−	65	mA

Transition Items (Unless otherwise specified, V_{DD}=4.5~5.5V，T_a =-40℃~85℃)

Characteristics	Symbol	Test circuit	Test Conditions	Min	Typ	Max	Unit
Serial data transfer frequency	F_{CLK}	6	-	-	-	35	MHz
Clock pulse width	t_{wCLK}	6	SCK=H or L	20	-	-	ns
Latch pulse width	t_{wLE}	6	LE=H	20	-	-	ns
Enable pulse width	t_{wOE}	6	$\overline{OE}$ =H or L, R_{EXT}=890Ω	40	-	-	ns
Hold time	t_{HOLD1}	6	-	5	-	-	ns
	t_{HOLD2}	6	-	5	-	-	ns
Setup time	t_{SETUP1}	6	-	5	-	-	ns
	t_{SETUP2}	6	-	5	-	-	ns
Maximum clock rise time	t_r	6		-	-	500	ns
Maximum clock fall time	t_f	6		-	-	500	ns

Electrical Characteristics (Unless otherwise specified, V_{DD} =4.5~5.5V，T_a =25℃)

Characteristics	Symbol	Test circuit	Test Conditions	Min	Typ	Max	Unit
High level logic output voltage	V_{OH}	1	I_{OH}=-1mA, SOUT	V_{DD}-0.4	-	V_{DD}	V
Low level logic output voltage	V_{OL}	1	I_{OH}=+1mA, SOUT	-	-	0.4	V
High level logic input current	I_{IH}	2	V_{IN}=V_{DD}, $\overline{OE}$, SIN, CLK	-	-	1	μA
Low level logic input circuit	I_{IL}	3	V_{IN}=GND, LE, SIN, CLK	-	-	-1	μA
Power supply current	I_{DD1}	4	Rext=open, OUT off	-	2.5	5.0	mA
	I_{DD2}	4	Rext=1.24kΩ, OUT off	-	4.5	7.0	mA
	I_{DD3}	4	Rext=620Ω, OUT off	-	6	9.0	mA
	I_{DD4}	4	Rext=1.24kΩ, OUT on	-	5.2	8.5	mA
	I_{DD5}	4	Rext=620Ω, OUT on	-	6.5	9.5	mA
Constant current output	I_{O1}	5	V_{DD}=5.0V, V_O=1.0V, R_{EXT}=1.23kΩ	-	15	-	mA
	I_{O2}	5	V_{DD}=5.0V, V_O=1.0V, R_{EXT}=615Ω	-	30	-	mA
Constant current error	ΔI_O	5	V_{DD}=5.0V, V_O=1.0V, R_{EXT}=1.23kΩ, $\overline{OUT0}$~$\overline{OUT15}$	-	± 0.15	± 0.37	mA
Constant current power supply voltage regulation	$\%V_{DD}$	5	V_{DD}=4.5~5.5V, V_O=1.0V, R_{EXT}=1.24kΩ, $\overline{OUT0}$~$\overline{OUT15}$	-	±0.2	-	%/V
Constant current output voltage regulation	$\%V_{OUT}$	5	V_{DD}=5.0V, V_O=1.0~3.0V, R_{EXT}=1.24kΩ, $\overline{OUT0}$~$\overline{OUT15}$	-	±0.1		%/V
Pull-up resistor	R_{UP}	3	$\overline{OE}$	250	500	800	kΩ
Pull-down resistor	R_{DOWN}	2	LE	250	500	800	kΩ

Switching Characteristics (Unless otherwise specified, T_a =25℃， V_{DD} =5.0V)

Characteristics		Symbol	Test circuit	Test conditions	Min	Typ	Max	Unit
Propagation delay time	CLK-$\overline{OUT0}$	t_{pLH1}	6	LE=H, $\overline{OE}$ =L	–	35	45	ns
	LE-$\overline{OUT0}$	t_{pLH2}	6	$\overline{OE}$ =L	–	32	42	
	$\overline{OE}$-$\overline{OUT0}$	t_{pLH3}	6	LE=H	–	30	40	
	CLK-$\overline{OUT1}$	t_{pHL1}	6	LE=H, $\overline{OE}$ =L	–	44	54	
	LE-$\overline{OUT1}$	t_{pHL2}	6	$\overline{OE}$ =L	–	41	51	
	$\overline{OE}$-$\overline{OUT1}$	t_{pHL3}	6	LE=H	–	39	49	
	CLK-SOUT	t_{pHL}	6	–	–	20	25	
	CLK-$\overline{OUT0}$	t_{pLH1}	6	LE=H, $\overline{OE}$ =L	–	35	45	
Output rise time		t_{or}	6	10~90% of voltage waveform	–	35	41	ns
Output fall time		t_{of}	6	90~10% voltage waveform	–	40	52	ns

Test Circuit

Test Circuit1: High level logic input voltage/Low level logic input voltage



Test Circuit2: High level logic input current/Pull-down resistor



Test Circuit3：Low level logic input current/Pull-up resistor



Test Circuit4: Power supply current



Test Circuit5: Constant current output/Output OFF leak current/Constant current error

Constant current power supply voltage regulation/Constant current output voltage regulation



Test Circuit6: Switching Characteristics



Timing Waveforms

1. CLK, SIN, SOUT



2. CLK, SIN, LE, $\overline{OE}$, $\overline{OUT0}$



3. $\overline{OUT0}$



Application Information

ICN2027 exploits current precision controlling technology，and provides nearly no current variations from channel to channel and from IC to IC.

1) The maximum current variation between channels is less than ±1.3%，and that between ICs<±2.5%.

2) The current characteristic of output stage is flat, and can be kept constant regardless of the variations of LED forward voltages.



Setting Output Current

The output current (I_{out}) of ICN2027 is set by an external resistor, R_{ext}. The relationship between I_{out} and R_{ext} is

$$Iout=(V_{R\text{-}EXT}/ R_{ext})*15 \qquad V_{R\text{-}EXT}=1.24V;$$



Package Outline

SSOP24 (150mil) PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	**Max**	**Min**	**Max**
A	——	1.750	——	0.069
A1	0.100	0.250	0.004	0.010
A2	1.250	——	0.049	——
b	0.203	0.305	0.008	0.012
c	0.102	0.254	0.004	0.010
D	8.450	8.850	0.333	0.348
E1	3.800	4.000	0.150	0.157
E	5.800	6.200	0.228	0.244
e	0.635(BSC)		0.025(BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

IC Top-mark Information



Product Ordering Information

Product number	Package （Pb-Free）	Weight（g）
ICN2027BP	SSOP24-0.635	0.13

Important information

Chipone Technology (Beijing) Co., Ltd. (Chipone) reserves the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

Chipone warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with Chipone's standard warranty. Testing and other quality control techniques are utilized to the extent Chipone deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). CHIPONE SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF CHIPONE PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

Chipone assumes no liability for applications assistance or customer product design. Chipone does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of Chipone covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. Chipone's publication of information regarding any third party's products or services does not constitute Chipone's approval, warranty or endorsement thereof.