1 Assignment 1: Tabular Reinforcement Learning

1.1 Motvation

In this assignment, you will study a range of basic principles in tabular, value-based reinforcement learning. They serve as a primer for the rest of the course. In particular, we will study the following topics:

- **Dynamic Programming** (DP) (Part 1.4):
  We first focus on dynamic programming, which is a bridging method between planning and reinforcement learning. DP assumes full access to a model of the environment, i.e., we can get $p(s'|s,a)$ and $r(s,a,s')$ for any state s and action a. DP is guaranteed to find the optimal solution, but it 1) requires a model (which is not always available) and 2) suffers from the curse of dimensionality (which all tabular methods actually do, and to which we get back later in the course).

- **Model-free RL**: We next switch to the reinforcement learning setting, where we do not have access to a model, but can only permanently execute actions from a state, and have to continue from the resulting next state.

  - **Exploration** (Part 1.5) The first issue this brings up is exploration versus exploitation: we need to sometimes try novel things, but at some point also exploit what we know works well. We will compare two simple ways to ensure exploration: ϵ-greedy and a softmax/Boltzmann policy.

  - **Back-up**: The second main aspect of any RL algorithm is the back-up. We acquired new information, and want to construct a new estimate of the value of a certain state-action pair s, a. There are two important considerations when constructing this back-up:

    * **Off-policy versus on-policy** (Part 1.6): This difference is best illustrated for one-step back-ups, for which we will compare Q-learning (off-policy) to SARSA (on-policy).

    * **Depth** (Part 1.7): We can also compute deeper back-ups, where we sum more rewards in a trace. We will compare 1-step back-ups, n-step back-ups, and Monte Carlo back-ups.

1.2 Environment

You will study these methods on the *Stochastic Windy Gridworld*, an adapted version of Example 6.5 (page 130) in *Reinforcement Learning: An Introduction* (second edition) by Sutton and Barto (see figure).



The environment consists of a 10x7 grid, where at each cell we can move up, down, left or right. We start at location (0,3) (we start indexing at 0, as is done in Python as well), indicated in the figure by 'S'. Our goal is to move to location (7,3), indicated by 'G'. However, a special feature of the environment is that there is a vertical wind. In columns 3, 4, 5 and 8, we are pushed one additional step up, while in columns 6 and 7, we move up two additional steps. The wind does not always blow, but is randomly present on 90% of the occasions (which makes the environment stochastic!). The reward of the agent at each step is -1, while reaching the goal gives a reward of +100, and terminates the episode.

1.3 Preparation

Python You need to install Python 3, the packages `Numpy`, `Matplotlib`, `SciPy` and an IDE of your choice.

Files You are provided with the following Python files:

- `Environment.py`: This file generates the environment. Run the file to see a demonstration of the environment with randomly selected actions. Inspect the class methods and make sure you understand them. With `render()` you can interactively visualize the environment during execution. If you provide `Q_sa` (a Q-value table), the environment will also display the Q-value estimates for each action in each state, while toggling `plot_optimal_policy` will also show arrows for the optimal policy. Play around with these settings, and make sure you understand them.
- `Dynamic_Programming.py`: This file contains placeholder classes and functions for your Dynamic Programming experiments (Part 1.4). Your goal is to complete these classes and functions.
- `Agent.py`: This file contains the Agent baseclass, in which you will implement the exploration methods (`select_action`) and you are provided with an `evaluate` method to run greedy evaluation episodes throughout training. The `update` method needs to be overwritten in each specific back-up method (files below).
- `Q-learning.py`: This file contains placeholder classes and functions for your Q-learning implementation.

- `SARSA.py`: This file contains placeholder classes and functions for your SARSA implementation.
- `MonteCarlo.py`: This file contains placeholder classes and functions for your Monte Carlo RL implementation.
- `Nstep.py`: This file contains placeholder classes and functions for your n-step Q-learning implementation.
- `Experiments.py`: In this file you will write all your code for the reinforcement learning experiments (Part 1.5, 1.6 and 1.7).
- `Helper.py`: This file contains some helper classes for plotting and smoothing. You can choose to use them, but are of course free to write your own code for plotting and smoothing as well. Inspect the code and run the file to verify that you understand what the functions do.

Matplotlib rendering Depending on your local software setup and the way you run your code (e.g., from the command line, or within an IDE), you may need to change the Matplotlib backend to allow for interactive rendering. For example, when your code does not give interactive rendering in PyCharm, you may add the following two lines to the top of `Environment.py`:

```
import matplotlib
matplotlib.use('Qt5Agg') # or TkAgg
```

Depending on you own software setup, play around with the backend settings until you find the plot being interactively updated (or run it from the command line, outside of your IDE).

1.4 Dynamic Programming

Bram

You first study Dynamic Programming, in particular the Q-value iteration algorithm (Alg. 1). In this algorithm you sweep through all state-action pairs, each time updating the estimate of a state-action value based on the following equation:

$$Q(s,a) \leftarrow \sum_{s'} \Big[p(s'|s,a) \cdot \big(r(s,a,s') + \gamma \cdot \max_{a'} Q(s',a') \big) \Big] \tag{1}$$

In DP, you have access to the full model of the environment dynamics. Therefore, you may use the `StochasticWindyGridworld.model()` function in your experiments.

You proceed with the following steps:

a) **Implement**:

- Correctly complete the class `QValueIterationAgent()` in the file `DynamicProgramming.py`.
  - In `init()`, initialize a table with means $Q(s,a)$ to 0.
  - In `select_action()`, implement the greedy policy: $\pi(s) = \arg\max_a Q(s,a)$.
  - In `update()`, implement the Q-iteration update, shown in Eq. 1. Make sure you print the maximum absolute error after each full sweep (i.e., each time after you visited each state-action pair once).
- Correctly complete the function `Q_value_iteration()` in the file `DynamicProgramming.py`. This function should execute Q-value iteration, as shown in Algorithm 1. It first initializes an agent, and then sweeps through the state space, each time calling the model and then updating the agent, until convergence.

b) **Experiment**: Verify that your code works by running the file. You should see a visualization of all the Q-value estimates during execution of the algorithm. **Closely inspect the values, how they change, and how they converge**. (You may need to increase the value of `step_pause` to make plotting slower). Do you understand the final values in each cell, and can you interpret them?

c) **Write**: Write a section of you report, in which you:

- Explain your method (with equations/algorithm boxes).
- Show a picture with the progression of Q-value iteration during execution, e.g., the estimates at each state-action at the beginning, midway, and at convergence. Explain the final values you observe, working backwards from the goal.
- Compute $V^\star(s = 3)$ at the start state ($s = 3$, `location=(0,3)`), i.e., the converged optimal value at the start. Explain what it means.
- Compute the average reward per timestep under the optimal policy. Explain your answer. (Hint: You must use i) the optimal value at the start state, ii) the magnitude of the final reward, iii) the magnitude of the reward on every other step. First try to compute the average number of steps the agent needs to take to reach the goal based on these quantities. Use this number to derive the average reward per step, again using the optimal value at the start state.)
- The goal state in the environment ($s = 52$) is terminal. Explain how your implementation of dynamic programming deals with this issue, i.e., why does it still converge? (Hint: check the code in `Environment.py`). Could you think of another way to solve this issue?

- The goal state is currently located at (x,y) location `[7,3]`, defined in initialization function of the environment. Briefly change the location tot `[6,2]`, run your DP algorithm again, and observe how the agent now behaves under the optimal policy. Is there a noticeable difference. Explain your answer.

Algorithm 1: Tabular Q-value iteration (Dynamic Programming)

Input: Threshold $\eta \in R^+$.
Result: The optimal value function $Q^\star(s,a)$ and/or associated optimal policy $\pi^\star(s)$.
Initialization: A state-action value table $\hat{Q}(s,a) = 0 \quad \forall s \in \mathcal{S}, a \in \mathcal{A}$
repeat
  $\Delta \leftarrow 0$
  for *each* $s \in \mathcal{S}$ **do**
    for *each* $a \in \mathcal{A}$ **do**
      $x \leftarrow Q(s,a)$ `/* Store current estimate */`
      $\hat{Q}(s,a) \leftarrow \sum_{s'} \Big[p(s'|s,a) \cdot \big(r(s,a,s') + \gamma \cdot \max_{a'} Q(s',a')\big)\Big]$ `/* Eq. 1 */`
      $\Delta \leftarrow \max(\Delta, |x - \hat{Q}(s,a)|)$ `/* Update max error */`
    end
  end
until $\Delta < \eta$;
$Q^\star(s,a) = \hat{Q}(s,a)$ `/* Converged at optimal value function */`
$\pi^\star(s) = \arg\max_a Q^\star(s,a) \quad \forall s \in \mathcal{S}$ `/* Optimal policy is greedy */`
Return $Q^\star(s,a)$ and/or $\pi^\star(s)$.

1.5 Exploration Ali

You will now switch to the (model-free) reinforcement learning setting. In this case, you no longer have access to the model (like the real world, where executing an action permanently brings you to the next state). You therefore no longer have access to the `StochasticWindyGridworld.model()` function, and you can no longer sweep through all states. **Instead, you have to move forward from the current state, where you use the `StochasticWindyGridworld.step()` function**.

Since you cannot sweep through all states anymore, you will proceed in episodes from the start state. Compared to sweeping through the state space, you are now no longer guaranteed to visit all states under a greedy policy. You therefore need to introduce *exploration* into your action selection, to sometimes try something novel.

1. This first crucial step of any RL algorithm is the **action selection**. You decide to compare two types of policies:

   - The **ϵ-greedy policy**:

   $$\pi(a|s) = \begin{cases} 1.0 - \epsilon \cdot \frac{|\mathcal{A}|-1}{|\mathcal{A}|}, & \text{if } a = \arg\max_{b \in \mathcal{A}} \hat{Q}(s,b) \\ \epsilon/(|\mathcal{A}|), & \text{otherwise} \end{cases} \tag{2}$$

   In words, we select with small probability ϵ a random action, which ensures exploration, and otherwise take the greedy action. The parameter ϵ allows you to scale the amount of exploration ($\epsilon = 0$ gives a greedy policy, $\epsilon = 1$ gives a uniform/random policy).

   - The **Boltzmann policy**:

   $$\pi(a|s) = \frac{e^{\hat{Q}(s,a)/\tau}}{\sum_{b \in \mathcal{A}} e^{\hat{Q}(s,b)/\tau}} \tag{3}$$

   where $\tau \in (0, \infty)$ denotes a temperature parameter. This approach gives a higher probability to actions with a higher current value estimate, but still ensures exploration of other actions than the greedy one. The temperature τ allows you to scale the amount of exploration: for $\tau \to \infty$ the policy becomes uniform/random (why?), and for $\tau \to 0$ the policy becomes greedy.

2. The second crucial step of an RL algorithm is the **update**. After executing an action, the environment gives you new data, in the form of the observed reward and next state. Therefore, after timestep t you have observed data $\langle s_t, a_t, r_t, s_{t+1} \rangle$. In the next part of the assignment we will compare different ways to use this data to compute a new estimate for the state-action value at s_t, a_t, but in this assignment we will use the 1-step Q-learning update. We first compute the new **back-up estimate/target** G_t as

   $$G_t = r_t + \gamma \cdot \max_{a'} \hat{Q}(s_{t+1}, a') \tag{4}$$

   and then apply the **tabular learning update**

   $$\hat{Q}(s_t, a_t) \leftarrow \hat{Q}(s_t, a_t) + \alpha \cdot [G_t - \hat{Q}(s_t, a_t)] \tag{5}$$

   where $\alpha \in (0, 1]$ denotes the learning rate. For $\alpha \to 0$ learning is slow but stable, while $\alpha \to 1$ makes learning fast but less stable. The optimal learning rate typically lies somewhere

in between. The learning rate is an important parameter in any learning experiment, and typically needs to be tuned extensively.

You proceed with your experiments as follows:

a) **Implement**:

- Correctly complete the class `Agent()` in the file `Agent.py`.
  - In `init()`, initialize a table with means $Q(s, a)$ to 0.
  - In `select_action()`, implement the above ϵ-greedy policy and softmax policy. Note: we already provided `argmax()` and `softmax()` functions for you in `Helper.py`, which are already imported into the file.
- Correct complete the class `QLearningAgent()` in the file `Q_learning.py`.
  - In `update()`, implement the Q-learning update shown above.
- Correctly complete the function `q_learning()` in the file `Q_learning.py`. This function should execute Q-learning, as shown in Algorithm 2. Make sure you run independent evaluation episodes (through the `evaluate()` method of the base agent) after every `eval_interval` steps. The function should return the mean return of the greedy policy at these evaluation moments, and the timesteps of evaluation.
- Verify that your code works by running `Q_learning.py`. Observe how the agent explores and learns. Plots the value estimates during execution, and observe how they change.

b) **Experiment**: You decide to perform a more systematic experiment, comparing ϵ-greedy and Boltzmann policies with different settings for the exploration parameters (respectively ϵ and temperature parameter τ).

- Write your experiment code in `Experiment.py`, using the `q_learning()` function you wrote above.
- Try ϵ-greedy with `epsilon = [0.03,0.1,0.3]` and softmax with `temps = [0.01,0.1,1.0]`.
- **Use runs of `n_timesteps = 50001` where you evaluate every `eval_interval = 1000`. For each setting, average the results over 20 repetitions. Smooth your learning curves if necessary**. Plot the learning curves for each setting in the same graph. Add a clear legend!

c) **Write**:

- Explain your method (with equations/algorithm boxes).
- Show a picture which compares both exploration methods for different values of ϵ and τ.
- Interpret your results. Which method do you prefer? Does RL achieve the optimal performance you found from Dynamic Programming? Explain why it does or doesn't.

d) **Multiple goals**: Finally, add a second goal to the environment definition, for example at location (3,2), with a reward of +5. You can adjust this in the environment definition, where you can alter `self.goal_locations` and `self.goal_rewards`, which specify the locations and associated rewards of the terminal goal states in this task. Briefly report on:

- Does this affect overall performance?

- How does it affect the exploration-exploitation trade-off?
- Does the optimal exploration parameter change?

Algorithm 2: Tabular Q-learning.

Input: Exploration parameter, learning rate $\alpha \in (0, 1]$, discount parameter $\gamma \in [0, 1]$, total *budget*.

```
Q̂(s,a) ← 0,  ∀s ∈ S, a ∈ A.                    /* Initialize Q-value table */
s ~ p_0(s)                                      /* Sample initial state */
while budget do
    a ~ π(a|s)                                  /* Sample action, e.g., ε-greedy, softmax */
    r, s' ~ p(r, s'|s, a)                       /* Simulate environment */
    Q̂(s,a) ← Q̂(s,a) + α · [r + γ · max_a' Q̂(s',a') − Q̂(s,a)]   /* Q update */
    if s' is terminal then
        s ~ p_0(s)                              /* Reset environment */
    else
        s ← s'
    end
end
Return: Q̂(s,a)
```

1.6 Back-up: On-policy versus off-policy target Judith

The second important part of any RL algorithm is the way we back-up information. A major distinction is between off-policy back-ups (like Q-learning) and on-policy back-ups (like SARSA). We will first focus on the one-step case. The back-up equation for Q-learning was already implemented in the previous assignment:

$$G_t = r_t + \gamma \cdot \max_{a'} \hat{Q}(s_{t+1}, a') \tag{6}$$

$$\hat{Q}(s_t, a_t) \leftarrow \hat{Q}(s_t, a_t) + \alpha \cdot [G_t - \hat{Q}(s_t, a_t)] \tag{7}$$

The back-up equation for SARSA, given observations $\langle s_t, a_t, r_t, s_{t+1}, a_{t+1} \rangle$ is

$$G_t = r_t + \gamma \cdot \hat{Q}(s_{t+1}, a_{t+1}) \tag{8}$$

$$\hat{Q}(s_t, a_t) \leftarrow \hat{Q}(s_t, a_t) + \alpha \cdot [G_t - \hat{Q}(s_t, a_t)] \tag{9}$$

The major difference between these two is the value they bootstrap at the next state. Q-learning plugs in the value of the *best possible action at the next state*, and thereby attempts to learn the value of the optimal policy. SARSA backs up the value of the action we actually take (which may be exploratory and not the one with the currently optimal estimate). SARSA therefore learns the value function of the policy we actually execute (which includes exploration). Both approaches have their benefits and problems (see the textbook). Look closely at both above equations to understand this difference.

a) **Implement**:

- Correctly complete the class `SarsaAgent()` in the file `SARSA.py`.
  - In `update()`, implement the SARSA update shown above.
- Correctly complete the function `sarsa()` in the file `SARSA.py`. This function should execute SARSA, as shown in Algorithm 3. Make sure you run independent evaluation episodes (through the `evaluate()` method of the base agent) after every `eval_interval` steps. The function should return the mean return of the greedy policy at these evaluation moments, and the timesteps of evaluation.
- Run `SARSA.py` to verify that your implementation works. Plots the value estimates during execution, and observe how they change.

b) **Experiment**: You decide to perform a more systematic experiment, where you compare Q-learning and SARSA for different learning rates.

- Write your experiment code in `Experiment.py`, using the `q_learning()` and `sarsa()` functions you wrote above.
- Try both methods for `learning_rates = [0.03,0.1,0.3]`.
- **For each setting, average your results over 20 repetitions. Smooth your learning curves if necessary**. Plot the learning curves for all settings (Q-learning and SARSA for each of the above learning rates) in the same graph. Add a clear legend!

c) **Write**:

- Explain your method (with equations/algorithm boxes).
- Show a picture which compares both types of back-ups for different learning rates.
- Interpret your results. Which method do you prefer? Could you think of a situation in which you would prefer the other method?

Algorithm 3: Tabular SARSA.

Input: Exploration parameter, learning rate $\alpha \in (0, 1]$, discount parameter $\gamma \in [0, 1]$, total *budget*.

```
Q̂(s,a) ← 0, ∀s ∈ S, a ∈ A.                    /* Initialize Q-value table */
s ~ p_0(s)                                     /* Sample initial state */
a ~ π(a|s)                                     /* Sample action, e.g., ε-greedy or softmax */
while budget do
    r, s' ~ p(r, s'|s, a)                      /* Simulate environment */
    a' ~ π(a'|s')                              /* Sample action, e.g., ε-greedy */
    Q̂(s,a) ← Q̂(s,a) + α · [r + γ · Q̂(s',a') − Q̂(s,a)]   /* SARSA */
    if s' is terminal then
        s ~ p_0(s)                             /* Reset environment */
        a ~ π(a|s)
    else
        s ← s'
        a ← a'
    end
end
Return: Q̂(s,a)
```

1.7 Back-up: Depth of target

The other important aspect of the back-up is its depth. So far, we have only looked at 1-step method, which directly bootstrap a value estimate after one transition. Instead, we can also sum multiple rewards in a trace before we bootstrap, which leads to *n-step methods* (n-step Q-learning or n-step SARSA, depending on the way you bootstrap). You will use n-step Q-learning, which computes the following target:

$$G_t = \sum_{i=0}^{n-1} (\gamma)^i \cdot r_{t+i} + (\gamma)^n \max_a Q(s_{t+n}, a) \tag{10}$$

and again standard tabular update

$$\hat{Q}(s_t, a_t) \leftarrow \hat{Q}(s_t, a_t) + \alpha \cdot [G_t - \hat{Q}(s_t, a_t)] \tag{11}$$

Not that, although it is called n-step Q-learning (due to the maximization over the last action), it is not a full off-policy method, since the first n reward are of course sampled from the current policy (and the target therefore mostly follows our behavioral policy).

On the other extreme, we can also omit bootstrapping altogether, and simply sum all rewards up to the end of the episode (or up to some maximum timestep after which we terminate the episode). The gives a *Monte Carlo update*:

$$G_t = \sum_{i=0}^{\infty} (\gamma)^i \cdot r_{t+i} \tag{12}$$

$$\hat{Q}(s_t, a_t) \leftarrow \hat{Q}(s_t, a_t) + \alpha \cdot [G_t - \hat{Q}(s_t, a_t)] \tag{13}$$

You will run experiments to compare different depths of the back-up target, from one-step up to Monte Carlo targets.

a) **Implement**:

- Correctly complete the class `NstepQLearningAgent()` in the file `Nstep.py`.
  - In `update()`, implement the n-step Q-learning update for each state-action pair in `states` and `actions`.
- Correctly complete the function `n_step_Q()` in the file `Nstep.py`. This function should execute n-step Q-learning, as shown in Algorithm 4. Make sure you run independent evaluation episodes (through the `evaluate()` method of the base agent) after every `eval_interval` steps. The function should return the mean return of the greedy policy at these evaluation moments, and the timesteps of evaluation.
- Run `Nstep.py` to verify that your method works. Observe the agent learning.
- Correctly complete the class `MonteCarloAgent()` in the file `MonteCarlo.py`.
  - In `update()`, implement the Monte Carlo update for each state-action pair in `states` and `actions`.
- Correctly complete the function `monte_carlo()` in the file `MonteCarlo.py`. This function should execute Monte Carlo RL as shown in Algorithm 5. Make sure you run independent evaluation episodes (through the `evaluate()` method of the base agent) after every `eval_interval` steps. The function should return the mean return of the greedy policy at these evaluation moments, and the timesteps of evaluation.

Run `MonteCarlo.py` to verify that your method works. Observe the agent learning, while you plot the value estimates and optimal policy. Do you see a difference with the previous RL methods?

b) **Experiment**: You decide to perform a more systematic experiment, comparing different back-up depths.

- Write your experiment code in `Experiment.py`, using the `n_step_Q()` and `monte_carlo()` functions you wrote above.
- For `n_step_Q()`, try different back-up depths: `ns = [1,3,10]`. Also run the Monte Carlo method.
- Plot the learning curves for each setting in the same graph. **For each setting, average your results over** 20 **repetitions. Smooth your learning curves if necessary**. Add a clear legend!

c) **Write**:

- Explain your method (with equations/algorithm boxes).
- Show a picture with the relevant comparisons.
- Interpret your results. Which method learns faster initially? Which method has better final performance? Give possible explanations for these observations.
- Do you notice a difference in performance between your Q-learning implementation, and your n-step Q-learning implementation with $n = 1$. Did something change in the way the algorithm got implemented? Explain you answer.

Algorithm 4: Tabular n-step Q-learning

Input: Exploration parameter $\epsilon \in (0, 1]$, learning rate $\alpha \in (0, 1]$, discount parameter $\gamma \in [0, 1]$, maximum episode length T, target depth n.

```
Q̂(s, a) ← 0, ∀s ∈ S, a ∈ A.                          /* Initialize Q-value table */
while budget do
    s_0 ~ p_0(s)                                      /* Sample initial state */
    /// Collect episode
    for t = 0...(T − 1) do
        a_t ~ π(a|s_t)                                /* Sample action, e.g., ε-greedy */
        r_t, s_{t+1} ~ p(r, s'|s_t, a_t)              /* Simulate environment */
        if s_{t+1} is terminal then
            break                                     /* Episode terminates */
        end
    end
    T_ep ← t + 1                                      /* T_ep stores episode length */
    /// Compute n-step targets and update
    for t = 0...(T_ep − 1) do
        m = min(n, T_ep − t)                          /* m is number of rewards left to sum */
        if s_{t+m} is terminal then
            G_t ← Σ_{i=0}^{m−1} (γ)^i · r_{t+i}       /* n-step target without bootstrap */
        else
            G_t ← Σ_{i=0}^{m−1} (γ)^i · r_{t+i} + (γ)^m · max_a Q̂(s_{t+m}, a)   /* n-step target */
        end
        Q̂(s_t, a_t) ← Q̂(s_t, a_t) + α · [G_t − Q̂(s_t, a_t)]   /* Update Q-table */
    end
end
Return: Q̂(s, a)
```

Algorithm 5: Tabular Monte Carlo reinforcement learning.

Input: Exploration parameter $\epsilon \in (0, 1]$, learning rate $\alpha \in (0, 1]$, discount parameter $\gamma \in [0, 1]$, maximum episode length T.

```
Q̂(s,a) ← 0, ∀s ∈ S, a ∈ A.                    /* Initialize Q-value table */
while budget do
    s_0 ~ p_0(s)                                /* Sample initial state */
    for t = 0...(T − 1) do
        a_t ~ π(a|s_t)                          /* Sample action, e.g., ε-greedy */
        r_t, s_{t+1} ~ p(r, s'|s_t, a_t)        /* Simulate environment */
        if s_{t+1} is terminal then
            break                               /* Episode terminates */
        end
    end
    G_{t+1} ← 0                                 /* Start reward summation from 0 */
    for i = t...0 do
        G_i ← r_i + γ · G_{i+1}                 /* Compute Monte Carlo target at each step */
        Q̂(s_i, a_i) ← Q̂(s_i, a_i) + α · [G_i − Q̂(s_i, a_i)]   /* Update Q-table */
    end
end
Return: Q̂(s,a)
```

1.8 Reflection

You did a lot of experiments with Dynamic Programming and various aspects of tabular model-free RL algorithms. Write a reflection/discussion of your experiments, which discusses the following topics:

- **DP versus RL**: What is a strength of Dynamic Programming compared to RL? And what is a potential weakness?
- **Exploration**: Which exploration method do you prefer: ϵ-greedy of softmax exploration? Could you think of a better way to explore?
- **Exploration 2**: Each step currently has a default reward of -1, while all value estimates are initialized at 0. Do you think this affects exploration performance? Try changing the default reward per step to 0 (in the environment definition), and see how this affects performance. Can you explain what's going on?
- **Discount factor**: John decides he indeed prefers the default reward per step to be 0, since he does not like the idea of penalizing the agent for taking an action (a case of anthropomorphism). He runs two new experiments, one with discount factor (`gamma`) at 1.0, and the other one with the discount factor at 0.99. Will any of these approaches find the shortest path to the goal? If so, indicate which one(s).
- **Back-up, on-policy versus off-policy**: What are the benefits and problems of on-policy (SARSA) or off-policy (Q-learning) updates? Explain their difference. Is n-step Q-learning an on-policy or off-policy method? Explain your answer.
- **Back-up, target depth**: What are the benefits and problems of one-step, n-step and MC methods? Explain the bias-variance trade-off. Which method do you prefer for this task? Which method propagates information faster? Which method may converge on the optimal policy?
- **Curse of dimensionality**: You extensively studied tabular RL algorithms. What is their benefit? And when will they run into trouble? Explain the curse of dimensionality. How may machine learning methods, like deep learning, help to overcome this issue?

1.9 Task Checklist

- Answer questions 1.4 a) - c)
- Answer questions 1.5 a) - d)
- Answer questions 1.7 a) - c)
- Answer questions 1.6 a) - c)
- Write your reflection 1.8

1.10 Submission

Make sure to nicely document everything that you do. Your final submission consists of:

1. Your source code, together with a requirements file and a README with instructions that allows us to easily (single command per experiment / sub task) rerun your experiments on a university machine booted into Linux (DSLab or computer lab). To generate a requirements file boot up a terminal, activate your virtual/conda environment (if you used one), navigate to the folder in which you want to generate the file and run the following command: `python -m pip freeze > requirements.txt`.
2. You have to use the ICML Latex template for your Report. (Obtainable here)
3. Chapter Structure: Abstract (at most quarter of a page), Introduction, Theory (Theory only, around one page), Background/Theory, Experiments (setup & results; explaining environment should take at most quarter of a page), Discussion (discussion of results & weaknesses), Conclusion (reflect own work & outline future work).
4. A self-contained scientific pdf report of 4 (see also template on brightspace) pages with figures etc. This report contains an explanation of the techniques, your experimental design, results (performance statistics, other measurements,...), and overall conclusions, in which you briefly summarize the goal of your experiments, what you have done, and what you have observed/learned.

If you have any questions about this assignment, please visit our lab sessions on Friday where we can help you out. In case you cannot make it, you can post questions about the contents of the course on the Brightspace discussion forums, where other students can also read and reply to your questions.

1.11 Deadline

March 9, 23:59:59, EST+1