




avast

COMPILE TIME REGULAR EXPRESSIONS WITH A DETERMINISTIC FINITE AUTOMATON

HANA DUSÍKOVÁ



HANA DUSÍKOVÁ

HANA DUSÍKOVÁ

- Researcher in Avast
 - Improving things
 - High-performance code

HANA DUSÍKOVÁ

- Researcher in Avast
 - Improving things
 - High-performance code
- Avast Prague C++ Meetup

HANA DUSÍKOVÁ

- Researcher in Avast
 - Improving things
 - High-performance code
- Avast Prague C++ Meetup
- Czech National Body in WG21

HANA DUSÍKOVÁ

- Researcher in Avast
 - Improving things
 - High-performance code
- Avast Prague C++ Meetup
- Czech National Body in WG21
- Occasional hiker

HANA DUSÍKOVÁ

- Researcher in Avast
 - Improving things
 - High-performance code
- Avast Prague C++ Meetup
- Czech National Body in WG21
- Occasional hiker
- Enthusiastic photographer

HANA DUSÍKOVÁ

- Researcher in Avast
 - Improving things
 - High-performance code
- Avast Prague C++ Meetup
- Czech National Body in WG21
- Occasional hiker
- Enthusiastic photographer
- Fast book reader



@HANKADUSIKOVA

#CTRE #CPPNOW

*"And if thou gaze long at a finite automaton,
a finite automaton also gazes into thee."*

– Friedrich Nietzsche

(after taking a computer science class)

**THE
COMPILE TIME REGULAR EXPRESSIONS
LIBRARY**

EXAMPLE: BASIC USAGE

```
1 bool is_a_date(std::string_view input) noexcept {  
2     return ctre::match<"[0-9]{4}/[0-9]{2}/[0-9]{2}">(input);  
3 }
```

EXAMPLE: BASIC USAGE

```
1 bool is_a_date(std::string_view input) noexcept {  
2     return ctre::match<"[0-9]{4}/[0-9]{2}/[0-9]{2}">(input);  
3 }
```

EXAMPLE: BASIC USAGE

```
1 bool is_a_date(std::string_view input) noexcept {  
2     return ctre::match<"[0-9]{4}/[0-9]{2}/[0-9]{2}">(input);  
3 }
```

EXAMPLE: BASIC USAGE

```
1 bool is_a_date(std::string_view input) noexcept {  
2     return ctre::match<"[0-9]{4}/[0-9]{2}/[0-9]{2}">(input);  
3 }
```


EXAMPLE: BASIC USAGE

```
1 bool is_a_date(std::string_view input) noexcept {  
2     return ctre::match<"[0-9]{4}/[0-9]{2}/[0-9]{2}">(input);  
3 }
```

EXAMPLE: EXTRACTING A VALUE

```
1 std::optional<std::string_view> extract_sha256(std::string_view input) noexcept {
2     if (auto r = ctre::match<"[a-fA-F0-9]{64}">(input)) {
3         return r;
4     } else {
5         return std::nullopt;
6     }
7 }
```

EXAMPLE: EXTRACTING A VALUE

```
1 std::optional<std::string_view> extract_sha256(std::string_view input) noexcept {
2     if (auto r = ctre::match<"[a-fA-F0-9]{64}">(input)) {
3         return r;
4     } else {
5         return std::nullopt;
6     }
7 }
```

EXAMPLE: EXTRACTING A VALUE

```
1 std::optional<std::string_view> extract_sha256(std::string_view input) noexcept {
2     if (auto r = ctre::match<"[a-fA-F0-9]{64}">(input)) {
3         return r;
4     } else {
5         return std::nullopt;
6     }
7 }
```

EXAMPLE: EXTRACTING A VALUE

```
1 std::optional<std::string_view> extract_sha256(std::string_view input) noexcept {
2     if (auto r = ctre::match<"[a-fA-F0-9]{64}">(input)) {
3         return r;
4     } else {
5         return std::nullopt;
6     }
7 }
```

EXAMPLE: EXTRACTING A VALUE

```
1 std::optional<std::string_view> extract_sha256(std::string_view input) noexcept {
2     if (auto r = ctcre::match<"[a-fA-F0-9]{64}">(input)) {
3         return r;
4     } else {
5         return std::nullopt;
6     }
7 }
```

EXAMPLE: EXTRACTING A VALUE

```
1 std::optional<std::string_view> extract_sha256(std::string_view input) noexcept {
2     if (auto r = ctcre::match<"[a-fA-F0-9]{64}">(input)) {
3         return r;
4     } else {
5         return std::nullopt;
6     }
7 }
```

EXAMPLE: EXTRACTING A VALUE

```
1 std::optional<std::string_view> extract_sha256(std::string_view input) noexcept {
2     if (auto r = ctre::match<"[a-fA-F0-9]{64}">(input)) {
3         return r;
4     } else {
5         return std::nullopt;
6     }
7 }
```


FEATURES OF CTRE

FEATURES OF CTRE

- PCRE2 compatible dialect

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible
- `constexpr`

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible
- `constexpr`
 - compile time constructing

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible
- `constexpr`
 - compile time constructing
 - `constexpr` & runtime matching

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible
- `constexpr`
 - compile time constructing
 - `constexpr` & runtime matching
 - doesn't support runtime defined patterns

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible
- `constexpr`
 - compile time constructing
 - `constexpr` & runtime matching
 - doesn't support runtime defined patterns
- quick regex matching/searching

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible
- `constexpr`
 - compile time constructing
 - `constexpr` & runtime matching
 - doesn't support runtime defined patterns
- quick regex matching/searching
 - structured-bindings for extracting captures

FEATURES OF CTRE

- PCRE2 compatible dialect
 - basic unicode support
 - optimizing greedy cycles into possessive if possible
- `constexpr`
 - compile time constructing
 - `constexpr` & runtime matching
 - doesn't support runtime defined patterns
- quick regex matching/searching
 - structured-bindings for extracting captures
 - generates compact assembly

TECHNICAL DETAILS OF CTRE

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)
- supports all major compilers

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)
- supports all major compilers
 - clang 6.0

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)
- supports all major compilers
 - clang 6.0
 - gcc 7.4

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)
- supports all major compilers
 - clang 6.0
 - gcc 7.4
 - msvc 15.8.8+

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)
- supports all major compilers
 - clang 6.0
 - gcc 7.4
 - msvc 15.8.8+
- open-source

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)
- supports all major compilers
 - clang 6.0
 - gcc 7.4
 - msvc 15.8.8+
- open-source
 - apache-2.0 license

TECHNICAL DETAILS OF CTRE

- small, header only C++17/20 library (8k LoC)
- supports all major compilers
 - clang 6.0
 - gcc 7.4
 - msvc 15.8.8+
- open-source
 - apache-2.0 license
 - available on github.com

BASIC API

```
1 namespace ctre {
2
3     template <fixed_string Pattern>
4     constexpr auto match(const Range auto &) noexcept;
5
6     template <fixed_string Pattern>
7     constexpr auto match(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;
8
9     template <fixed_string Pattern>
10    constexpr auto search(const Range auto &) noexcept;
11
12    template <fixed_string Pattern>
13    constexpr auto search(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;
14
15 }
```

BASIC API

```
1 namespace ctre {  
2  
3     template <fixed_string Pattern>  
4     constexpr auto match(const Range auto &) noexcept;  
5  
6     template <fixed_string Pattern>  
7     constexpr auto match(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;  
8  
9     template <fixed_string Pattern>  
10    constexpr auto search(const Range auto &) noexcept;  
11  
12    template <fixed_string Pattern>  
13    constexpr auto search(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;  
14  
15 }
```

BASIC API

```
1 namespace ctre {
2
3     template <fixed_string Pattern>
4     constexpr auto match(const Range auto &) noexcept;
5
6     template <fixed_string Pattern>
7     constexpr auto match(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;
8
9     template <fixed_string Pattern>
10    constexpr auto search(const Range auto &) noexcept;
11
12    template <fixed_string Pattern>
13    constexpr auto search(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;
14
15 }
```

BASIC API

```
1 namespace ctre {
2
3     template <fixed_string Pattern>
4     constexpr auto match(const Range auto &) noexcept;
5
6     template <fixed_string Pattern>
7     constexpr auto match(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;
8
9     template <fixed_string Pattern>
10    constexpr auto search(const Range auto &) noexcept;
11
12    template <fixed_string Pattern>
13    constexpr auto search(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;
14
15 }
```


BASIC API

```
1 namespace ctre {  
2  
3     template <fixed_string Pattern>  
4     constexpr auto match(const Range auto &) noexcept;  
5  
6     template <fixed_string Pattern>  
7     constexpr auto match(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;  
8  
9     template <fixed_string Pattern>  
10    constexpr auto search(const Range auto &) noexcept;  
11  
12    template <fixed_string Pattern>  
13    constexpr auto search(ForwardIterable auto &&, ForwardIterable auto &&) noexcept;  
14  
15 }
```

DFA BASED API

```
1 namespace ctre {
2
3     template <fixed_string Pattern>
4     constexpr bool fast_match(const Range auto &) noexcept;
5
6     template <fixed_string Pattern>
7     constexpr bool fast_match(ForwardIterable auto &&, ForwardIterable auto &&) no
8
9     template <fixed_string Pattern>
10    constexpr bool fast_search(const Range auto &) noexcept;
11
12    template <fixed_string Pattern>
13    constexpr bool fast_search(ForwardIterable auto &&, ForwardIterable auto &&) r
14
15 }
```

DFA BASED API

```
1 namespace ctre {
2
3     template <fixed_string Pattern>
4     constexpr bool fast_match(const Range auto &) noexcept;
5
6     template <fixed_string Pattern>
7     constexpr bool fast_match(ForwardIterable auto &&, ForwardIterable auto &&) n
8
9     template <fixed_string Pattern>
10    constexpr bool fast_search(const Range auto &) noexcept;
11
12    template <fixed_string Pattern>
13    constexpr bool fast_search(ForwardIterable auto &&, ForwardIterable auto &&) r
14
15 }
```

DFA BASED API

```
1 namespace ctre {
2
3     template <fixed_string Pattern>
4     constexpr bool fast_match(const Range auto &) noexcept;
5
6     template <fixed_string Pattern>
7     constexpr bool fast_match(ForwardIterable auto &&, ForwardIterable auto &&) no
8
9     template <fixed_string Pattern>
10    constexpr bool fast_search(const Range auto &) noexcept;
11
12    template <fixed_string Pattern>
13    constexpr bool fast_search(ForwardIterable auto &&, ForwardIterable auto &&) r
14
15 }
```

DFA BASED API

```
1 namespace ctre {
2
3     template <fixed_string Pattern>
4     constexpr bool fast_match(const Range auto &) noexcept;
5
6     template <fixed_string Pattern>
7     constexpr bool fast_match(ForwardIterable auto &&, ForwardIterable auto &&) n
8
9     template <fixed_string Pattern>
10    constexpr bool fast_search(const Range auto &) noexcept;
11
12    template <fixed_string Pattern>
13    constexpr bool fast_search(ForwardIterable auto &&, ForwardIterable auto &&) r
14
15 }
```

RETURN TYPE OF THE BASIC API

```
1 namespace ctre {  
2  
3     template <impl-spec> struct regex_results {  
4         constexpr operator bool() const noexcept;  
5  
6         constexpr operator basic_string_view<char_type>() const noexcept;  
7         constexpr explicit operator basic_string<char_type>() const noexcept;  
8  
9         constexpr auto begin() const noexcept;  
10        constexpr auto end() const noexcept;  
11  
12        // number of captures  
13        constexpr static size_t size() const noexcept;  
14  
15        // returns object similar to regex_results (without 'get' method)
```

RETURN TYPE OF THE BASIC API

```
1 namespace ctre {
2
3     template <impl-spec> struct regex_results {
4         constexpr operator bool() const noexcept;
5
6         constexpr operator basic_string_view<char_type>() const noexcept;
7         constexpr explicit operator basic_string<char_type>() const noexcept;
8
9         constexpr auto begin() const noexcept;
10        constexpr auto end() const noexcept;
11
12        // number of captures
13        constexpr static size_t size() const noexcept;
14
15        // returns object similar to regex_results (without 'get' method)
```

RETURN TYPE OF THE BASIC API

```
1 namespace ctre {
2
3     template <impl-spec> struct regex_results {
4         constexpr operator bool() const noexcept;
5
6         constexpr operator basic_string_view<char_type>() const noexcept;
7         constexpr explicit operator basic_string<char_type>() const noexcept;
8
9         constexpr auto begin() const noexcept;
10        constexpr auto end() const noexcept;
11
12        // number of captures
13        constexpr static size_t size() const noexcept;
14
15        // returns object similar to regex_results (without 'get' method)
```


RETURN TYPE OF THE BASIC API

```
1 namespace ctre {
2
3     template <impl-spec> struct regex_results {
4         constexpr operator bool() const noexcept;
5
6         constexpr operator basic_string_view<char_type>() const noexcept;
7         constexpr explicit operator basic_string<char_type>() const noexcept;
8
9         constexpr auto begin() const noexcept;
10        constexpr auto end() const noexcept;
11
12        // number of captures
13        constexpr static size_t size() const noexcept;
14
15        // returns object similar to regex_results (without 'get' method)
```

RETURN TYPE OF THE BASIC API

```
1 namespace ctre {  
2  
3     template <impl-spec> struct regex_results {  
4         constexpr operator bool() const noexcept;  
5  
6         constexpr operator basic_string_view<char_type>() const noexcept;  
7         constexpr explicit operator basic_string<char_type>() const noexcept;  
8  
9         constexpr auto begin() const noexcept;  
10        constexpr auto end() const noexcept;  
11  
12        // number of captures  
13        constexpr static size_t size() const noexcept;  
14  
15        // returns object similar to regex_results (without 'get' method)
```

RETURN TYPE OF THE BASIC API

```
1 namespace ctre {
2
3     template <impl-spec> struct regex_results {
4         constexpr operator bool() const noexcept;
5
6         constexpr operator basic_string_view<char_type>() const noexcept;
7         constexpr explicit operator basic_string<char_type>() const noexcept;
8
9         constexpr auto begin() const noexcept;
10        constexpr auto end() const noexcept;
11
12        // number of captures
13        constexpr static size_t size() const noexcept;
14
15        // returns object similar to regex_results (without 'get' method)
```

RETURN TYPE OF THE BASIC API

```
1 namespace ctre {  
2  
3     template <impl-spec> struct regex_results {  
4         constexpr operator bool() const noexcept;  
5  
6         constexpr operator basic_string_view<char_type>() const noexcept;  
7         constexpr explicit operator basic_string<char_type>() const noexcept;  
8  
9         constexpr auto begin() const noexcept;  
10        constexpr auto end() const noexcept;  
11  
12        // number of captures  
13        constexpr static size_t size() const noexcept;  
14  
15        // returns object similar to regex_results (without 'get' method)
```

RETURN TYPE OF THE BASIC API

```
1 namespace ctre {
2
3     template <impl-spec> struct regex_results {
4         constexpr operator bool() const noexcept;
5
6         constexpr operator basic_string_view<char_type>() const noexcept;
7         constexpr explicit operator basic_string<char_type>() const noexcept;
8
9         constexpr auto begin() const noexcept;
10        constexpr auto end() const noexcept;
11
12        // number of captures
13        constexpr static size_t size() const noexcept;
14
15        // returns object similar to regex_results (without 'get' method)
```

EXAMPLE: STRUCTURED BINDING

```
1 // .get<0> is an implicit capture of whole pattern
2 auto [r, year, month, day] = ctre::match<"([0-9]{4})/([0-9]{2})/([0-9]{2})">(input);
3
4 if (r) {
5     // do something with successful match
6 }
```

EXAMPLE: STRUCTURED BINDING

```
1 // .get<0> is an implicit capture of whole pattern
2 auto [r, year, month, day] = ctreg::match<"([0-9]{4})/([0-9]{2})/([0-9]{2})">(input);
3
4 if (r) {
5     // do something with successful match
6 }
```

EXAMPLE: STRUCTURED BINDING

```
1 // .get<0> is an implicit capture of whole pattern
2 auto [r, year, month, day] = ctreg::match<"([0-9]{4})/([0-9]{2})/([0-9]{2})">(input);
3
4 if (r) {
5     // do something with successful match
6 }
```


EXAMPLE: STRUCTURED BINDING

```
1 // .get<0> is an implicit capture of whole pattern
2 auto [r, year, month, day] = ctreg::match<"([0-9]{4})/([0-9]{2})/([0-9]{2})">(input);
3
4 if (r) {
5     // do something with successful match
6 }
```

EXAMPLE: STRUCTURED BINDING

```
1 // .get<0> is an implicit capture of whole pattern
2 auto [r, year, month, day] = ctreg::match<"([0-9]{4})/([0-9]{2})/([0-9]{2})">(input);
3
4 if (r) {
5     // do something with successful match
6 }
```

EXAMPLE: STRUCTURED BINDING

```
1 // .get<0> is an implicit capture of whole pattern
2 auto [r, year, month, day] = ctre::match<"([0-9]{4})/([0-9]{2})/([0-9]{2})">(input);
3
4 if (r) {
5     // do something with successful match
6 }
```

EXAMPLE: ITERATE OVER CONCATENATED SEQUENCE OF NUMBERS

```
1 int sum(std::string_view input) {  
2     int output = 0;  
3     for (const auto & capt: ctre::range<"^,?([0-9]+)">(input))  
4         output += to_integer(capt.get<1>());  
5     return output;  
6 }
```

EXAMPLE: ITERATE OVER CONCATENATED SEQUENCE OF NUMBERS

```
1 int sum(std::string_view input) {  
2     int output = 0;  
3     for (const auto & capt: ctre::range<"^,?([0-9]+)">(input))  
4         output += to_integer(capt.get<1>());  
5     return output;  
6 }
```

EXAMPLE: ITERATE OVER CONCATENATED SEQUENCE OF NUMBERS

```
1 int sum(std::string_view input) {  
2     int output = 0;  
3     for (const auto & capt: ctre::range<"^,?([0-9]+)">(input))  
4         output += to_integer(capt.get<1>());  
5     return output;  
6 }
```

EXAMPLE: ITERATE OVER CONCATENATED SEQUENCE OF NUMBERS

```
1 int sum(std::string_view input) {  
2     int output = 0;  
3     for (const auto & capt: ctre::range<"^,?([0-9]+)">(input))  
4         output += to_integer(capt.get<1>());  
5     return output;  
6 }
```

EXAMPLE: ITERATE OVER CONCATENATED SEQUENCE OF NUMBERS

```
1 int sum(std::string_view input) {  
2     int output = 0;  
3     for (const auto & capt: ctre::range<"^,?([0-9]+)">(input))  
4         output += to_integer(capt.get<1>());  
5     return output;  
6 }
```


EXAMPLE: ITERATE OVER CONCATENATED SEQUENCE OF NUMBERS

```
1 int sum(std::string_view input) {  
2     int output = 0;  
3     for (const auto & capt: ctre::range<"^,?([0-9]+)">(input))  
4         output += to_integer(capt.get<1>());  
5     return output;  
6 }
```

ITERABLE API

```
1 namespace ctre {  
2  
3     template <fixed_string Pattern>  
4     constexpr auto range(const Range auto &) noexcept;  
5  
6     template <fixed_string Pattern>  
7     constexpr auto range(ForwardIterable auto &&, ForwardIterable auto &&) noexcept  
8  
9 }
```

ITERABLE API

```
1 namespace ctre {  
2  
3     template <fixed_string Pattern>  
4     constexpr auto range(const Range auto &) noexcept;  
5  
6     template <fixed_string Pattern>  
7     constexpr auto range(ForwardIterable auto &&, ForwardIterable auto &&) noexcept  
8  
9 }
```

EXAMPLE: 🥰🦄

```
1 constexpr bool is_emoji_only(std::u32string_view input) noexcept {  
2     return ctre::match<>"\\p{emoji}+">(input);  
3 }
```

EXAMPLE: 🥰🦄

```
1 constexpr bool is_emoji_only(std::u32string_view input) noexcept {  
2     return ctre::match<>"\\p{emoji}+">(input);  
3 }
```

EXAMPLE: 🥰🦄

```
1 constexpr bool is_emoji_only(std::u32string_view input) noexcept {  
2     return ctre::match<"\p{emoji}+">(input);  
3 }
```

EXAMPLE: 🥰🦄

```
1 constexpr bool is_emoji_only(std::u32string_view input) noexcept {
2     return ctre::match<"\p{emoji}+">(input);
3 }

static_assert( is_emoji_only(U"🥰🤖😄") );
```

EXAMPLE: 🥰🦄

```
1 constexpr bool is_emoji_only(std::u32string_view input) noexcept {  
2     return ctre::match<>"\\p{emoji}+">(input);  
3 }
```

```
static_assert( is_emoji_only(U"🥰🦄😄" ));  
static_assert(!is_emoji_only(U"no!😡" ));
```


EXAMPLE: 🥰🦄

```
1 constexpr bool is_emoji_only(std::u32string_view input) noexcept {  
2     return ctre::match<>"\\p{emoji}+">(input);  
3 }
```

```
static_assert( is_emoji_only(U"🥰🦄😄" ));  
static_assert(!is_emoji_only(U"no!😡" ));
```

*unicode support is not yet fully merged

EXAMPLE: 🥰🦄

```
1 constexpr bool is_emoji_only(std::u32string_view input) noexcept {  
2     return ctre::match<>"\\p{emoji}+">(input);  
3 }
```

```
static_assert( is_emoji_only(U"🥰🦄😏" ));  
static_assert(!is_emoji_only(U"no!😡" ));
```

*unicode support is not yet fully merged

**thanks to Corentin Jabot for providing constexpr unicode tables ❤️

```
1 #include <ctre.hpp>
2
3 bool match(std::string_view input) {
4     return ctre::match<"aloha|[a-z]+">(input);
5 }
```

```
1
```

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha|[a-z]+`
input:

CAVEATS OF A BACKTRACKING ENGINE

pattern: **a**loha | [a-z]⁺

input: **a**

a

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z]+`
input: `al`

`al`

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z]+`

input: `alo`

`alo`

CAVEATS OF A BACKTRACKING ENGINE

pattern: aloha | [a-z] +

input: aloh

aloh

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`
input: `aloha`

`aloha`

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`
input: `alohah`

`aloha` (fail, backtrack)

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`

input: `alohah`

`aloha (fail, backtrack) a`

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`

input: `alohah`

`aloha (fail, backtrack) al`

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`

input: alohah

aloha (fail, backtrack) alo

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`

input: alohah

aloha (fail, backtrack) aloh

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`

input: alohah

`aloha` (fail, backtrack) `aloha`

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`

input: alohah

`aloha` (fail, backtrack) `alohah`

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha | [a-z] +`

input: alohaha

`aloha` (fail, backtrack) `alohaha`

CAVEATS OF A BACKTRACKING ENGINE

pattern: `aloha` | `[a-z]`+

input: alohaha

`aloha` (fail, backtrack) `alohaha` (accepts)

BACK-TRACKING

A common problem of many regular expression engines.

HOW CAN WE AVOID IT?

HOW CAN WE AVOID IT?

We need to talk (a little bit) about theory.

REGULAR EXPRESSIONS

`hello|aloha|guten tag|dobrý den|bonjour`

`[a-z]+[0-9]+`

A REGULAR EXPRESSION IS (FORMALLY)

A REGULAR EXPRESSION IS (FORMALLY)

- the empty set (\emptyset or $\{\}$),

A REGULAR EXPRESSION IS (FORMALLY)

- the empty set (\emptyset or $\{\}$),
- an empty string (ϵ or $\{""\}$),

A REGULAR EXPRESSION IS (FORMALLY)

- the empty set (\emptyset or $\{\}$),
- an empty string (ϵ or $\{\text{" "}\}$),
- a literal character (e.g. a or $\{\text{"a"}\}$),

A REGULAR EXPRESSION IS (FORMALLY)

- the empty set (\emptyset or $\{\}$),
- an empty string (ϵ or $\{""\}$),
- a literal character (e.g. a or $\{a\}$),
- the concatenation of two REs ($A \cdot B$),

A REGULAR EXPRESSION IS (FORMALLY)

- the empty set (\emptyset or $\{\}$),
- an empty string (ϵ or $\{\text{" "}\}$),
- a literal character (e.g. a or $\{\text{"a"}\}$),
- the concatenation of two REs ($A \cdot B$),
- the alternation of two REs ($A|B$),

A REGULAR EXPRESSION IS (FORMALLY)

- the empty set (\emptyset or $\{\}$),
- an empty string (ϵ or $\{\text{" "}\}$),
- a literal character (e.g. a or $\{\text{"a"}\}$),
- the concatenation of two REs ($A \cdot B$),
- the alternation of two REs ($A|B$),
- or repetitions (Kleene star) (A^*)

NON-FORMAL SYNTAX CONSTRUCTS

NON-FORMAL SYNTAX CONSTRUCTS

- Optional A ($A?$ is $\epsilon|A$)

NON-FORMAL SYNTAX CONSTRUCTS

- Optional A ($A?$ is $\epsilon|A$)
- Plus repetition of A ($A \cdot A^*$)

NON-FORMAL SYNTAX CONSTRUCTS

- Optional A ($A?$ is $\epsilon|A$)
- Plus repetition of A ($A \cdot A^*$)
- Back-reference

NON-FORMAL SYNTAX CONSTRUCTS

- Optional A ($A?$ is $\epsilon|A$)
- Plus repetition of A ($A \cdot A^*$)
- ~~Back-reference~~

NON-FORMAL SYNTAX CONSTRUCTS

- Optional A ($A?$ is $\epsilon|A$)
- Plus repetition of A ($A \cdot A^*$)
- ~~Back-reference~~

not all features of a "regular expression"
implementation is technically a regular expression

EXAMPLE: NON-FORMAL SYNTAX CONSTRUCTS

We are all used to a pattern like this:

`(ct)?re|[a-f]+`

The pattern is equivalent to:

`(ε|ct)re|(a|b|c|d|e|f)(a|b|c|d|e|f)*`

EXAMPLE: NON-FORMAL SYNTAX CONSTRUCTS

We are all used to a pattern like this:

$(ct)?re|[a-f]^+$


The pattern is equivalent to:

$(\epsilon|ct)re|(a|b|c|d|e|f)(a|b|c|d|e|f)^*$

Every pattern can be converted into a formal form.

A REGULAR EXPRESSION CAN BE DESCRIBED AS AN ABSTRACT SYNTAX TREE

$(ct)?re \mid [a-f]^+$



**HOW TO STORE THE AST
IN C++ COMPILE-TIME EVALUATED CODE?**

HOW TO STORE THE AST IN C++ COMPILE-TIME EVALUATED CODE?

- tree-like (allocated) data structure

HOW TO STORE THE AST IN C++ COMPILE-TIME EVALUATED CODE?

- ~~tree-like (allocated) data structure~~ (we can't allocate in constexpr, yet)

HOW TO STORE THE AST IN C++ COMPILE-TIME EVALUATED CODE?

- ~~tree-like (allocated) data structure~~ (we can't allocate in constexpr, yet)
- type based expression
 - expression templates (like boost::xpressive)
 - tuple-like empty types

TYPES AS THE BUILDING BLOCKS

```
1 // building blocks
2 struct epsilon { };
3 template <Character auto C> struct ch { };
4
5 // operations
6 template <typename...> struct concat { };
7 template <typename...> struct alt { };
8 template <typename> struct star { };
9
10 // for convenient usage
11 template <typename E> using opt = alternation<E, epsilon>;
12 template <typename E> using plus = concat<E, star<E>>;
```

EXAMPLE: A REGEX TYPE

```
(ct)?re
```

CONVERTING A PATTERN INTO AN AST: PARSING

HOW TO CONVERT THE PATTERN?

HOW TO CONVERT THE PATTERN?

- Use a generic LL(1) parser for converting a pattern into a type.

HOW TO CONVERT THE PATTERN?

- Use a generic **LL(1)** parser for converting a pattern into a type.
- The parser uses a provided **PCRE** compatible grammar.

HOW TO CONVERT THE PATTERN?

- Use a generic **LL(1)** parser for converting a pattern into a type.
- The parser uses a provided **PCRE** compatible grammar.
- Output type is the **AST**.

HOW DOES AN LL(1) PARSER WORK?

HOW DOES AN LL(1) PARSER WORK?

- Starts with a start symbol on the stack.

HOW DOES AN LL(1) PARSER WORK?

- Starts with a start symbol on the stack.
- On every step it pops one symbol from the stack and checks the current character at the input.

HOW DOES AN LL(1) PARSER WORK?

- Starts with a start symbol on the stack.
- On every step it pops one symbol from the stack and checks the current character at the input.
- Based on the pair of symbol and character it decides to:

HOW DOES AN LL(1) PARSER WORK?

- Starts with a start symbol on the stack.
- On every step it pops one symbol from the stack and checks the current character at the input.
- Based on the pair of symbol and character it decides to:
 - push a string of symbols to the stack,

HOW DOES AN LL(1) PARSER WORK?

- Starts with a start symbol on the stack.
- On every step it pops one symbol from the stack and checks the current character at the input.
- Based on the pair of symbol and character it decides to:
 - push a string of symbols to the stack,
 - pop a character from the input,

HOW DOES AN LL(1) PARSER WORK?

- Starts with a start symbol on the stack.
- On every step it pops one symbol from the stack and checks the current character at the input.
- Based on the pair of symbol and character it decides to:
 - push a string of symbols to the stack,
 - pop a character from the input,
 - or reject.

HOW DOES AN LL(1) PARSER WORK?

- Starts with a start symbol on the stack.
- On every step it pops one symbol from the stack and checks the current character at the input.
- Based on the pair of symbol and character it decides to:
 - push a string of symbols to the stack,
 - pop a character from the input,
 - or reject.
- Repeat until the stack and input are empty then accept.

WHAT DOES THE GRAMMAR LOOK LIKE?

f(symbol,char) →

[illegible]

WHAT DOES THE GRAMMAR LOOK LIKE?

f(symbol,char) →

[illegible]

WHAT DOES THE GRAMMAR LOOK LIKE?

f(symbol, char) →

[illegible]

WHAT DOES THE GRAMMAR LOOK LIKE?

$f(\text{symbol}, \text{char}) \rightarrow (\dots)$

[illegible]

WHAT DOES THE GRAMMAR LOOK LIKE?

$$f(\text{symbol}, \text{char}) \rightarrow \epsilon$$
[illegible]

WHAT DOES THE GRAMMAR LOOK LIKE?

f(symbol,char) → pop input

[illegible]

WHAT DOES THE GRAMMAR LOOK LIKE?

f(symbol,char) → reject

	()	*	+	?		other	ϵ
$\rightarrow S$	$(alt0) \text{ mod seq alt}$						other mod seq alt	$\underline{\epsilon}$
$alt0$	$(alt0) \text{ mod seq alt}$						other mod seq alt	
alt		$\underline{\epsilon}$				$ \text{ seq0 alt}$		$\underline{\epsilon}$
mod	$\underline{\epsilon}$	$\underline{\epsilon}$	*	+	?	$\underline{\epsilon}$	$\underline{\epsilon}$	$\underline{\epsilon}$
$seq0$	$(alt0) \text{ mod seq}$						other mod seq	
seq	$(alt0) \text{ mod seq}$	$\underline{\epsilon}$				$\underline{\epsilon}$	other mod seq	$\underline{\epsilon}$
(\underline{pop}							
)		\underline{pop}						
*			\underline{pop}					
+				\underline{pop}				
?					\underline{pop}			
						\underline{pop}		
other							\underline{pop}	
z_0								\underline{accept}

WHAT DOES THE GRAMMAR LOOK LIKE?

f(symbol,char) → **accept**

[illegible]

HOW DOES AN LL1 PARSER WORK?

input: **a***b* ϵ step: 0

stack:

S

	()	*	+	?		other	ϵ
$\rightarrow S$	(<i>alt0</i>) <i>mod seq alt</i>						other <i>mod seq alt</i>	ϵ
<i>alt0</i>	(<i>alt0</i>) <i>mod seq alt</i>						other <i>mod seq alt</i>	
<i>alt</i>		ϵ				<i>seq0 alt</i>		ϵ
<i>mod</i>	ϵ	ϵ	*	+	?	ϵ	ϵ	ϵ
<i>seq0</i>	(<i>alt0</i>) <i>mod seq</i>						other <i>mod seq</i>	
<i>seq</i>	(<i>alt0</i>) <i>mod seq</i>	ϵ				ϵ	other <i>mod seq</i>	ϵ
terminal	pop	pop	pop	pop	pop	pop	pop	
Z ₀								<u>accept</u>

reset

a*b*

HOW CAN WE REPRESENT THE SYMBOLS IN C++?

```
1 struct S {};  
2 struct alt0 {};  
3 struct alt {};  
4 struct mod {};  
5 struct seq0 {};  
6 struct seq {};  
7  
8 using start_symbol = S;
```

HOW CAN WE REPRESENT THE SYMBOLS IN C++?

```
1 struct S {};  
2 struct alt0 {};  
3 struct alt {};  
4 struct mod {};  
5 struct seq0 {};  
6 struct seq {};  
7  
8 using start_symbol = S;
```

HOW CAN WE REPRESENT AN LL(1) TABLE IN C++?

```
1 // f (symbol, char) → (...)
2
3
4 // f (symbol, symbol) → pop input
5
6
7 // f (symbol, char) → reject
8
9
10 // f (Z0, ε) → accept
11
```

HOW CAN WE REPRESENT AN LL(1) TABLE IN C++?

```
1 // f (symbol, char) → (...)
2 auto f(symbol, term<'c'>) -> list{...};
3
4 // f (symbol, symbol) → pop input
5
6
7 // f (symbol, char) → reject
8
9
10 // f (Z0, ε) → accept
11
```

HOW CAN WE REPRESENT AN LL(1) TABLE IN C++?

```
1 // f (symbol, char) → (...)
2 auto f(symbol, term<'c'>) -> list{...};
3
4 // f (symbol, symbol) → pop input
5 template <auto S> auto f(term<S>, term<S>) -> pop_input;
6
7 // f (symbol, char) → reject
8
9
10 // f (Z0, ε) → accept
11
```

HOW CAN WE REPRESENT AN LL(1) TABLE IN C++?

```
1 // f (symbol, char) → (...)
2 auto f(symbol, term<'c'>) -> list{...};
3
4 // f (symbol, symbol) → pop input
5 template <auto S> auto f(term<S>, term<S>) -> pop_input;
6
7 // f (symbol, char) → reject
8 auto f(...) -> reject;
9
10 // f (Z0, ε) → accept
11
```


HOW CAN WE REPRESENT AN LL(1) TABLE IN C++?

```
1 // f (symbol, char) → (...)
2 auto f(symbol, term<'c'>) -> list{...};
3
4 // f (symbol, symbol) → pop input
5 template <auto S> auto f(term<S>, term<S>) -> pop_input;
6
7 // f (symbol, char) → reject
8 auto f(...) -> reject;
9
10 // f (Z0, ε) → accept
11 auto f(empty_stack, epsilon) -> accept;
```

HOW CAN WE PASS THE GRAMMAR INTO THE PARSER?

```
1
2 struct S {};
3 struct alt0 {};
4 struct alt {};
5 // ...
6
7 using start_symbol = S;
8
9 auto f(...) -> reject;
10 // ...
11
```

HOW CAN WE PASS THE GRAMMAR INTO THE PARSER?

```
1 struct pcre {  
2     struct S {};  
3     struct alt0 {};  
4     struct alt {};  
5     // ...  
6  
7     using start_symbol = S;  
8  
9     auto f(...) -> reject;  
10    // ...  
11 }
```

HOW IS THE PARSER USED?

```
constexpr bool ok = parser<pcr, "a+b+">::correct;
```

HOW IS THE PARSER IMPLEMENTED?

```
1 template <typename Grammar, ...> struct parser {  
2     //...  
3     auto next_move = Grammar::f(top_of_stack, current_term);  
4     //...  
5 }
```

HOW IS THE PARSER IMPLEMENTED?

```
1 template <typename Grammar, ...> struct parser {  
2     //...  
3     auto next_move = Grammar::f(top_of_stack, current_term);  
4     //...  
5 }
```

HOW IS THE PARSER IMPLEMENTED?

```
1 template <typename Grammar, ...> struct parser {  
2     //...  
3     auto next_move = Grammar::f(top_of_stack, current_term);  
4     //...  
5 }
```

HOW IS THE PARSER IMPLEMENTED?

```
1 template <typename Grammar, ...> struct parser {  
2     //...  
3     auto next_move = Grammar::f(top_of_stack, current_term);  
4     //...  
5 }
```


HOW DO WE IMPLEMENT THE INPUT STRING?

```
1  template <typename CharT, size_t N> struct fixed_string {
2      CharT data[N+1];
3      // constexpr constructor from const char[N]
4      constexpr auto operator[](size_t i) const noexcept { return data[i]; }
5      constexpr size_t size() const noexcept { return N; }
6      constexpr auto operator<=>(const fixed_string &) = default;
7  };
8
9  template <typename CharT, size_t N>
10     fixed_string(const CharT[N]) -> fixed_string<CharT, N>;
11  // more info about class NTP in p0732 by Jeff Snyder and Louis Dionne
```

HOW DO WE IMPLEMENT THE INPUT STRING?

```
1  template <typename CharT, size_t N> struct fixed_string {
2      CharT data[N+1];
3      // constexpr constructor from const char[N]
4      constexpr auto operator[](size_t i) const noexcept { return data[i]; }
5      constexpr size_t size() const noexcept { return N; }
6      constexpr auto operator<=>(const fixed_string &) = default;
7  };
8
9  template <typename CharT, size_t N>
10     fixed_string(const CharT[N]) -> fixed_string<CharT, N>;
11  // more info about class NTPP in p0732 by Jeff Snyder and Louis Dionne
```

HOW DO WE IMPLEMENT THE INPUT STRING?

```
1  template <typename CharT, size_t N> struct fixed_string {
2      CharT data[N+1];
3      // constexpr constructor from const char[N]
4      constexpr auto operator[](size_t i) const noexcept { return data[i]; }
5      constexpr size_t size() const noexcept { return N; }
6      constexpr auto operator<=>(const fixed_string &) = default;
7  };
8
9  template <typename CharT, size_t N>
10     fixed_string(const CharT[N]) -> fixed_string<CharT, N>;
11  // more info about class NTP in p0732 by Jeff Snyder and Louis Dionne
```

HOW DO WE IMPLEMENT THE STACK?

```
1  template <typename... Ts> struct list { };
2
3  template <typename... Ts, typename... As>
4    constexpr auto push(list<Ts...>, As...) -> list<As..., Ts...>;
5
6  template <typename T, typename... As>
7    constexpr auto pop(list<T, Ts...>) -> list<Ts...>;
8
9  template <typename T, typename... Ts>
10   constexpr auto top(list<T, Ts...>) -> T;
11
12  struct empty { };
13  constexpr auto top(list<>) -> empty;
```

HOW DO WE IMPLEMENT THE STACK?

```
1  template <typename... Ts> struct list { };
2
3  template <typename... Ts, typename... As>
4    constexpr auto push(list<Ts...>, As...) -> list<As..., Ts...>;
5
6  template <typename T, typename... As>
7    constexpr auto pop(list<T, Ts...>) -> list<Ts...>;
8
9  template <typename T, typename... Ts>
10   constexpr auto top(list<T, Ts...>) -> T;
11
12  struct empty { };
13  constexpr auto top(list<>) -> empty;
```

HOW DO WE IMPLEMENT THE STACK?

```
1  template <typename... Ts> struct list { };
2
3  template <typename... Ts, typename... As>
4  constexpr auto push(list<Ts...>, As...) -> list<As..., Ts...>;
5
6  template <typename T, typename... As>
7  constexpr auto pop(list<T, Ts...>) -> list<Ts...>;
8
9  template <typename T, typename... Ts>
10 constexpr auto top(list<T, Ts...>) -> T;
11
12 struct empty { };
13 constexpr auto top(list<>) -> empty;
```

HOW DO WE IMPLEMENT THE STACK?

```
1  template <typename... Ts> struct list { };
2
3  template <typename... Ts, typename... As>
4    constexpr auto push(list<Ts...>, As...) -> list<As..., Ts...>;
5
6  template <typename T, typename... As>
7    constexpr auto pop(list<T, Ts...>) -> list<Ts...>;
8
9  template <typename T, typename... Ts>
10    constexpr auto top(list<T, Ts...>) -> T;
11
12  struct empty { };
13  constexpr auto top(list<>) -> empty;
```

HOW DO WE IMPLEMENT THE STACK?

```
1  template <typename... Ts> struct list { };
2
3  template <typename... Ts, typename... As>
4    constexpr auto push(list<Ts...>, As...) -> list<As..., Ts...>;
5
6  template <typename T, typename... As>
7    constexpr auto pop(list<T, Ts...>) -> list<Ts...>;
8
9  template <typename T, typename... Ts>
10   constexpr auto top(list<T, Ts...>) -> T;
11
12  struct empty { };
13  constexpr auto top(list<>) -> empty;
```


HOW DO WE IMPLEMENT THE STACK?

```
1  template <typename... Ts> struct list { };
2
3  template <typename... Ts, typename... As>
4    constexpr auto push(list<Ts...>, As...) -> list<As..., Ts...>;
5
6  template <typename T, typename... As>
7    constexpr auto pop(list<T, Ts...>) -> list<Ts...>;
8
9  template <typename T, typename... Ts>
10   constexpr auto top(list<T, Ts...>) -> T;
11
12  struct empty { };
13  constexpr auto top(list<>) -> empty;
```

HOW DOES IT FIT TOGETHER?

```
constexpr bool ok = parser<pcr, "a*b*">::correct;
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1  template <typename Grammar, fixed_string Str> struct parser {
2
3      static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5      // return current term
6      template <size_t Pos> constexpr auto get_character() const {
7          if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8          else return epsilon{};
9      }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```


LL1 CONSTEXPR PARSER

```
1  template <typename Grammar, fixed_string Str> struct parser {
2
3      static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5      // return current term
6      template <size_t Pos> constexpr auto get_character() const {
7          if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8          else return epsilon{};
9      }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11    // prepare each step and move to next
12    template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14        auto symbol = top(stack);
15        auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1  template <typename Grammar, fixed_string Str> struct parser {
2
3      static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5      // return current term
6      template <size_t Pos> constexpr auto get_character() const {
7          if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8          else return epsilon{};
9      }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```


LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```


LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5     // return current term
6     template <size_t Pos> constexpr auto get_character() const {
7         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8         else return epsilon{};
9     }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

LL1 CONSTEXPR PARSER

```
1  template <typename Grammar, fixed_string Str> struct parser {
2
3      static constexpr bool correct = parse(list<Grammar::start_symbol>{});
4
5      // return current term
6      template <size_t Pos> constexpr auto get_character() const {
7          if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
8          else return epsilon{};
9      }
10
11     // prepare each step and move to next
12     template <size_t Pos = 0, typename S> static constexpr bool parse(S stack) {
13
14         auto symbol = top(stack);
15         auto current_term = get_character<Pos>();
```

**WE NEED MORE THAN
JUST RETURNING A BOOLEAN.**

**A PATTERN TO THE AST:
LET THERE BE A TYPE**

HOW CAN WE BUILD A TYPE FROM A STRING?

WHERE ARE THE SEMANTIC ACTIONS PLACED?

[illegible]

WHERE ARE THE SEMANTIC ACTIONS PLACED?

[illegible]

WHAT DO THE SEMANTIC ACTION SYMBOLS LOOK LIKE?

```
1 struct pcre {  
2     struct _char: action {};  
3     struct alpha: action {};  
4     struct digit: action {};  
5     struct seq: action {};  
6     struct star: action {};  
7     struct plus: action {};  
8     struct opt: action {};  
9     // ...  
10 }
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{});
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```


WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1  template <typename Grammar, fixed_string Str> struct parser {
2
3      template <typename Subject>
4      static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6      // return current term
7      template <size_t Pos> constexpr auto get_character() const {
8          if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9          else return epsilon{};
10     }
11
12     // prepare each step and move to next
13     template <size_t Pos = 0, typename S, typename T>
14     static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```


WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1  template <typename Grammar, fixed_string Str> struct parser {
2
3      template <typename Subject>
4      static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6      // return current term
7      template <size_t Pos> constexpr auto get_character() const {
8          if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9          else return epsilon{};
10     }
11
12     // prepare each step and move to next
13     template <size_t Pos = 0, typename S, typename T>
14     static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```


WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT ARE THE CHANGES TO THE PARSER?

```
1 template <typename Grammar, fixed_string Str> struct parser {
2
3     template <typename Subject>
4     static constexpr auto output = parse(list<Grammar::start_symbol>{}, Subject{})
5
6     // return current term
7     template <size_t Pos> constexpr auto get_character() const {
8         if constexpr (Pos < Str.size()) return term<Str[Pos]>{};
9         else return epsilon{};
10    }
11
12    // prepare each step and move to next
13    template <size_t Pos = 0, typename S, typename T>
14    static constexpr auto parse(S stack, T subject) {
15
```

WHAT DOES BUILDING FROM A STRING LOOK LIKE?

a^*b^*

WHAT ABOUT THE MODIFY FUNCTION?

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```


BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```


BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```


BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

BUILDING THE AST ON A STACK

```
1 // pushing a character
2 template <Character auto C, typename... Ts>
3   auto modify(pcre::_char, term<C>, list<Ts...>)
4     -> list<ch<C>, Ts...>;
5
6 // concatenating a sequence (notice the switched order of A & B on the stack)
7 template <Character auto C, typename A, typename B, typename... Ts>
8   auto modify(pcre::seq, term<C>, list<B, A, Ts...>)
9     -> list<concat<A, B>, Ts...>;
10
11 // adding to a concatenated sequence
12 template <Character auto C, typename... As, typename B, typename... Ts>
13   auto modify(pcre::seq, term<C>, list<B, concat<As...>, Ts...>)
14     -> list<concat<As..., B>, Ts...>;
15
```

WE HAVE THE AST!

```
static_assert(std::is_same_v<
    '
    decltype( top(parser<pcre, ">::type) )
>);
```

WE HAVE THE AST!

```
static_assert(std::is_same_v<
    '
    decltype( top(parser<pcre, ">::type) )
>);
```

WE HAVE THE AST!


```
static_assert(std::is_same_v<
    '
    decltype( top(parser<pcr, " " >::type) )
>);
```

WE HAVE THE AST!

```
static_assert(std::is_same_v<  
    '  
    decltype( top(parser<pcr, ">::type) )  
>);
```

**HOW DO WE MATCH
A REGULAR EXPRESSION
IN THE FORM OF AN AST?**

FINITE AUTOMATON



WHAT'S A FINITE AUTOMATON?

$(Q, \Sigma, \delta, q_0, F)$

WHAT'S A FINITE AUTOMATON?

$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of **states** Q

WHAT'S A FINITE AUTOMATON?

$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of **states** Q
- a finite set of input symbols (the **alphabet**) Σ

WHAT'S A FINITE AUTOMATON?

$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of **states** Q
- a finite set of input symbols (the **alphabet**) Σ
- a **transition function** $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA)
 - Q (deterministic FA)

WHAT'S A FINITE AUTOMATON?

$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of **states** Q
- a finite set of input symbols (the **alphabet**) Σ
- a **transition function** $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA)
 - Q (deterministic FA)
- a **start state** $q_0 \in Q$

WHAT'S A FINITE AUTOMATON?

$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of **states** Q
- a finite set of input symbols (the **alphabet**) Σ
- a **transition function** $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA)
 - Q (deterministic FA)
- a **start state** $q_0 \in Q$
- a set of **accept (final) states** $F \subseteq Q$

WHAT'S A FINITE AUTOMATON?



$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of **states** Q
- a finite set of input symbols (the **alphabet**) Σ
- a **transition function** $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA)
 - Q (deterministic FA)
- a **start state** $q_0 \in Q$
- a set of **accept (final) states** $F \subseteq Q$

A finite automaton accepts exactly the same class of languages as a regular expression.



EXAMPLE: INTEGRAL NUMBERS

[0-9]+





EXAMPLE: INTEGRAL NUMBERS

[0-9]⁺





EXAMPLE: INTEGRAL NUMBERS

[0-9]+




EXAMPLE: INTEGRAL NUMBERS

[0-9]+





**HOW DO YOU CONVERT
A REGEX INTO AN FA?**



\emptyset (EMPTY SET)





\emptyset (EMPTY SET)





\emptyset (EMPTY SET)





\emptyset (EMPTY SET)





\emptyset (EMPTY SET)





\emptyset (EMPTY SET)





\emptyset (EMPTY SET)





\emptyset (EMPTY SET)





\emptyset (EMPTY SET)




\emptyset (EMPTY SET)



\emptyset (EMPTY SET)



\emptyset (EMPTY SET)



**THERE IS A DIRECT MAPPING BETWEEN
THE RE DEFINITION AND OPERATIONS OVER THE FAs.**

**THERE IS A DIRECT MAPPING BETWEEN
THE RE DEFINITION AND OPERATIONS OVER THE FAs.**

And we need to map it onto C++ code.

HOW TO REPRESENT AN FA IN C++?

$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of states Q
- a finite set of input symbols (the alphabet) Σ
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA)
 - Q (deterministic FA)
- a start state $q_0 \in Q$
- a set of accept (final) states $F \subseteq Q$

HOW TO REPRESENT AN FA IN C++?

$$(Q, \Sigma, \delta, q_0, F)$$

- a finite set of states Q – `set<int>`
- a finite set of input symbols (the alphabet) Σ
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA)
 - Q (deterministic FA)
- a start state $q_0 \in Q$
- a set of accept (final) states $F \subseteq Q$

HOW TO REPRESENT AN FA IN C++?

$(Q, \Sigma, \delta, q_0, F)$

- a finite set of states Q – `set<int>`
- a finite set of input symbols (the alphabet) Σ – `char32_t`
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA)
 - Q (deterministic FA)
- a start state $q_0 \in Q$
- a set of accept (final) states $F \subseteq Q$

HOW TO REPRESENT AN FA IN C++?

$(Q, \Sigma, \delta, q_0, F)$

- a finite set of states Q – `set<int>`
- a finite set of input symbols (the alphabet) Σ – `char32_t`
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA) – `set<tuple<int, int, char32_t>>`
 - Q (deterministic FA)
- a start state $q_0 \in Q$
- a set of accept (final) states $F \subseteq Q$

HOW TO REPRESENT AN FA IN C++?

$(Q, \Sigma, \delta, q_0, F)$

- a finite set of states Q – `set<int>`
- a finite set of input symbols (the alphabet) Σ – `char32_t`
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA) – `set<tuple<int, int, char32_t>>`
 - Q (deterministic FA)
- a start state $q_0 \in Q$ – `int(0)`
- a set of accept (final) states $F \subseteq Q$

HOW TO REPRESENT AN FA IN C++?

$(Q, \Sigma, \delta, q_0, F)$

- a finite set of states Q – `set<int>`
- a finite set of input symbols (the alphabet) Σ – `char32_t`
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA) – `set<tuple<int, int, char32_t>>`
 - Q (deterministic FA)
- a start state $q_0 \in Q$ – `int(0)`
- a set of accept (final) states $F \subseteq Q$ – `set<int>`

HOW TO REPRESENT AN FA IN C++?

$(Q, \Sigma, \delta, q_0, F)$

- a finite set of states Q – ~~set<int>~~
- a finite set of input symbols (the alphabet) Σ – `char32_t`
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA) – `set<tuple<int, int, char32_t>>`
 - Q (deterministic FA)
- a start state $q_0 \in Q$ – `int(0)`
- a set of accept (final) states $F \subseteq Q$ – `set<int>`

HOW TO REPRESENT AN FA IN C++?

$(Q, \Sigma, \delta, q_0, F)$

- a finite set of states Q – ~~set<int>~~ `int` (implicit)
- a finite set of input symbols (the alphabet) Σ – `char32_t`
- a transition function $\delta: Q \times \Sigma \rightarrow$
 - $P(Q)$ (nondeterministic FA) – `set<tuple<int, int, char32_t>>`
 - Q (deterministic FA)
- a start state $q_0 \in Q$ – `int(0)`
- a set of accept (final) states $F \subseteq Q$ – `set<int>`

CONSTEXPR IMPLEMENTATION OF A FA

"There is no such thing as a zero-cost abstraction."

– Chandler Carruth

CONSTEXPR PROBLEMS

CONSTEXPR PROBLEMS

- every operation counts

CONSTEXPR PROBLEMS

- every operation counts
 - there are limits

CONSTEXPR PROBLEMS

- every operation counts
 - there are limits (and different in every compiler)

CONSTEXPR PROBLEMS

- every operation counts
 - there are limits (and different in every compiler)
- move semantics don't matter

CONSTEXPR PROBLEMS

- every operation counts
 - there are limits (and different in every compiler)
- move semantics don't matter
- problematic error handling & debugging

CONSTEXPR PROBLEMS

- every operation counts
 - there are limits (and different in every compiler)
- move semantics don't matter
- problematic error handling & debugging
 - use a conditional UB or throw-statement as form of an assert

CONSTEXPR PROBLEMS

- every operation counts
 - there are limits (and different in every compiler)
- move semantics don't matter
- problematic error handling & debugging
 - use a conditional UB or throw-statement as form of an assert
 - printf styled debugging

```
template <typename T> struct identify_type;
```

THE CONSTEXPR PROBLEM

THE CONSTEXPR PROBLEM

sloooooooooooooow

THE CONSTEXPR PROBLEM

sloooooooooooooow

2 minutes

(NFA determinization)

THE CONSTEXPR PROBLEM

sloooooooooooooow

2 minutes (gcc 9.1)

(NFA determinization)

THE CONSTEXPR PROBLEM

sloooooooooooooow

2 minutes (gcc 9.1)

40 seconds

(NFA determinization)

THE CONSTEXPR PROBLEM

sloooooooooooooow

2 minutes (gcc 9.1)
40 seconds (clang 8)

(NFA determinization)

THE CONSTEXPR PROBLEM

sloooooooooooooow

2 minutes (gcc 9.1)

40 seconds (clang 8)

< 5 second

(NFA determinization)

THE CONSTEXPR PROBLEM

sloooooooooooooow

2 minutes (gcc 9.1)

40 seconds (clang 8)

< 5 second (php 7.1)

(NFA determinization)

CONSTEXPR set

```
1  template <typename T> class set {  
2  
3  public:  
4      constexpr auto begin();  
5      constexpr auto end();  
6      constexpr auto begin() const;  
7      constexpr auto end() const;  
8  
9      constexpr size_t size() const;  
10     constexpr auto & operator[](size_t);  
11     constexpr const auto & operator[](size_t) const;  
12  
13     constexpr auto insert(T);  
14  
15     template <typename K> constexpr auto erase(K);
```

CONSTEXPR set

```
1  template <typename T> class set {  
2  
3  public:  
4      constexpr auto begin();  
5      constexpr auto end();  
6      constexpr auto begin() const;  
7      constexpr auto end() const;  
8  
9      constexpr size_t size() const;  
10     constexpr auto & operator[](size_t);  
11     constexpr const auto & operator[](size_t) const;  
12  
13     constexpr auto insert(T);  
14  
15     template <typename K> constexpr auto erase(K);
```

CONSTEXPR set

```
1  template <typename T> class set {
2
3  public:
4      constexpr auto begin();
5      constexpr auto end();
6      constexpr auto begin() const;
7      constexpr auto end() const;
8
9      constexpr size_t size() const;
10     constexpr auto & operator[](size_t);
11     constexpr const auto & operator[](size_t) const;
12
13     constexpr auto insert(T);
14
15     template <typename K> constexpr auto erase(K);
```

CONSTEXPR set

```
1  template <typename T> class set {  
2  
3  public:  
4      constexpr auto begin();  
5      constexpr auto end();  
6      constexpr auto begin() const;  
7      constexpr auto end() const;  
8  
9      constexpr size_t size() const;  
10     constexpr auto & operator[](size_t);  
11     constexpr const auto & operator[](size_t) const;  
12  
13     constexpr auto insert(T);  
14  
15     template <typename K> constexpr auto erase(K);
```

CONSTEXPR set

```
1  template <typename T> class set {  
2  
3  public:  
4      constexpr auto begin();  
5      constexpr auto end();  
6      constexpr auto begin() const;  
7      constexpr auto end() const;  
8  
9      constexpr size_t size() const;  
10     constexpr auto & operator[](size_t);  
11     constexpr const auto & operator[](size_t) const;  
12  
13     constexpr auto insert(T);  
14  
15     template <typename K> constexpr auto erase(K);
```


CONSTEXPR set

```
1  template <typename T> class set {  
2  
3  public:  
4      constexpr auto begin();  
5      constexpr auto end();  
6      constexpr auto begin() const;  
7      constexpr auto end() const;  
8  
9      constexpr size_t size() const;  
10     constexpr auto & operator[](size_t);  
11     constexpr const auto & operator[](size_t) const;  
12  
13     constexpr auto insert(T);  
14  
15     template <typename K> constexpr auto erase(K);
```

CONSTEXPR set

```
1  template <typename T> class set {  
2  
3  public:  
4      constexpr auto begin();  
5      constexpr auto end();  
6      constexpr auto begin() const;  
7      constexpr auto end() const;  
8  
9      constexpr size_t size() const;  
10     constexpr auto & operator[](size_t);  
11     constexpr const auto & operator[](size_t) const;  
12  
13     constexpr auto insert(T);  
14  
15     template <typename K> constexpr auto erase(K);
```

CONSTEXPR `fixed_set`

```
1 template <size_t Sz, typename T> class fixed_set {
2     T data[Sz];
3 public:
4     constexpr auto begin();
5     constexpr auto end();
6     constexpr auto begin() const;
7     constexpr auto end() const;
8
9     constexpr size_t size() const;
10    constexpr auto & operator[](size_t);
11    constexpr const auto & operator[](size_t) const;
12
13    constexpr auto insert(T);
14
15    template <typename K> constexpr auto erase(K);
```

CONSTEXPR `finite_automaton`

```
1 struct transition {
2     int source;
3     int target;
4     char32_t term;
5
6     constexpr transition(int, int, char32_t);
7     constexpr bool match(char32_t c) const;
8     // comparable with int against source
9 };
10
11 template <size_t Tr, size_t FSz> struct finite_automaton {
12     fixed_set<Tr, transition> transitions;
13     fixed_set<FSz, int> final_states;
14
15     // normal constructor / copy constructor ...
```

CONSTEXPR `finite_automaton`

```
1 struct transition {
2     int source;
3     int target;
4     char32_t term;
5
6     constexpr transition(int, int, char32_t);
7     constexpr bool match(char32_t c) const;
8     // comparable with int against source
9 };
10
11 template <size_t Tr, size_t FSz> struct finite_automaton {
12     fixed_set<Tr, transition> transitions;
13     fixed_set<FSz, int> final_states;
14
15     // normal constructor / copy constructor ...
```

CONSTEXPR `finite_automaton`

```
1 struct transition {
2     int source;
3     int target;
4     char32_t term;
5
6     constexpr transition(int, int, char32_t);
7     constexpr bool match(char32_t c) const;
8     // comparable with int against source
9 };
10
11 template <size_t Tr, size_t FSz> struct finite_automaton {
12     fixed_set<Tr, transition> transitions;
13     fixed_set<FSz, int> final_states;
14
15     // normal constructor / copy constructor ...
```

CONSTEXPR `finite_automaton`

```
1 struct transition {
2     int source;
3     int target;
4     char32_t term;
5
6     constexpr transition(int, int, char32_t);
7     constexpr bool match(char32_t c) const;
8     // comparable with int against source
9 };
10
11 template <size_t Tr, size_t FSz> struct finite_automaton {
12     fixed_set<Tr, transition> transitions;
13     fixed_set<FSz, int> final_states;
14
15     // normal constructor / copy constructor ...
```

CONSTEXPR `finite_automaton`

```
1 struct transition {
2     int source;
3     int target;
4     char32_t term;
5
6     constexpr transition(int, int, char32_t);
7     constexpr bool match(char32_t c) const;
8     // comparable with int against source
9 };
10
11 template <size_t Tr, size_t FSz> struct finite_automaton {
12     fixed_set<Tr, transition> transitions;
13     fixed_set<FSz, int> final_states;
14
15     // normal constructor / copy constructor ...
```


CONSTEXPR `finite_automaton`

```
1 struct transition {
2     int source;
3     int target;
4     char32_t term;
5
6     constexpr transition(int, int, char32_t);
7     constexpr bool match(char32_t c) const;
8     // comparable with int against source
9 };
10
11 template <size_t Tr, size_t FSz> struct finite_automaton {
12     fixed_set<Tr, transition> transitions;
13     fixed_set<FSz, int> final_states;
14
15     // normal constructor / copy constructor ...
```

BASIC BUILDING BLOCKS

```
1 static constexpr auto empty = finite_automaton<0,0>{};
2
3 static constexpr auto epsilon = finite_automaton<0,1>{{}, {0}};
4
5 template <char32_t C> static constexpr auto one_char = finite_automaton<1,1>{
6     {transition(0, 1, C)},
7     {1}
8 };
```

BASIC BUILDING BLOCKS

```
1 static constexpr auto empty = finite_automaton<0,0>{};
2
3 static constexpr auto epsilon = finite_automaton<0,1>{{}, {0}};
4
5 template <char32_t C> static constexpr auto one_char = finite_automaton<1,1>{
6     {transition(0, 1, C)},
7     {1}
8 };
```

BASIC BUILDING BLOCKS

```
1 static constexpr auto empty = finite_automaton<0,0>{};
2
3 static constexpr auto epsilon = finite_automaton<0,1>{{}, {0}};
4
5 template <char32_t C> static constexpr auto one_char = finite_automaton<1,1>{
6     {transition(0, 1, C)},
7     {1}
8 };
```

BASIC BUILDING BLOCKS

```
1 static constexpr auto empty = finite_automaton<0,0>{};
2
3 static constexpr auto epsilon = finite_automaton<0,1>{{}, {0}};
4
5 template <char32_t C> static constexpr auto one_char = finite_automaton<1,1>{
6     {transition(0, 1, C)},
7     {1}
8 };
```

BASIC MANIPULATION

```
1 auto operator>>(const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs) {
2
3 auto operator|(const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs) {
4
5 auto star(const FiniteAutomaton auto & lhs);
```

BASIC MANIPULATION

```
1 auto operator>> (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
2  
3 auto operator| (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
4  
5 auto star(const FiniteAutomaton auto & lhs);
```

BASIC MANIPULATION

```
1 auto operator>> (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
2  
3 auto operator| (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
4  
5 auto star(const FiniteAutomaton auto & lhs);
```


BASIC MANIPULATION




```
1 auto operator>> (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
2  
3 auto operator| (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
4  
5 auto star (const FiniteAutomaton auto & lhs);
```

BASIC MANIPULATION




```
1 auto operator>> (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
2  
3 auto operator| (const FiniteAutomaton auto & lhs, const FiniteAutomaton auto & rhs)  
4  
5 auto star (const FiniteAutomaton auto & lhs);
```

Result of operation is dependent
not just on a input type but also on a input value.




CONCATENATION ALGORITHM






CONCATENATION ALGORITHM



CONCATENATION ALGORITHM



CONCATENATION ALGORITHM



CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1 template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3     constexpr static auto calculate() {
4         constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5         constexpr size_t tr_start = Rhs.count_transitions(0);
6
7         constexpr int prefix = Lhs.get_max_state() + 1;
8
9         finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```


CONCATENATION ALGORITHM

```
1 template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3     constexpr static auto calculate() {
4         constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5         constexpr size_t tr_start = Rhs.count_transitions(0);
6
7         constexpr int prefix = Lhs.get_max_state() + 1;
8
9         finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1 template <finite_automaton Lhs, finite_automaton Rh> struct concat_two {
2
3     constexpr static auto calculate() {
4         constexpr size_t tr_count = Lhs.transitions.size() + Rh.transitions.size();
5         constexpr size_t tr_start = Rh.count_transitions(0);
6
7         constexpr int prefix = Lhs.get_max_state() + 1;
8
9         finite_automaton<(tr_count + tr_start), Rh.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rh.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```


CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

CONCATENATION ALGORITHM

```
1  template <finite_automaton Lhs, finite_automaton Rhs> struct concat_two {
2
3      constexpr static auto calculate() {
4          constexpr size_t tr_count = Lhs.transitions.size() + Rhs.transitions.size();
5          constexpr size_t tr_start = Rhs.count_transitions(0);
6
7          constexpr int prefix = Lhs.get_max_state() + 1;
8
9          finite_automaton<(tr_count + tr_start), Rhs.final_states.count()> out;
10
11         copy(Lhs.transitions.begin(), Lhs.transitions.end(), out.transitions.begin())
12
13         for (int f: Lhs.final_states) {
14             Rhs.foreach_transition_from(0, [&](transition t){
15                 t.source = f;
```

OTHER ALGORITHMS

OTHER ALGORITHMS

- alternation

OTHER ALGORITHMS

- alternation
- repeating (Kleene star)

OTHER ALGORITHMS

- alternation
- repeating (Kleene star)

Both other algorithms work the same,
pre-calculate the size and then populate the content.

TEMPLATE STYLE MANIPULATION

```
1 template <finite_automaton... Fas>
2 static constexpr auto concat =
3
4 template <finite_automaton... Fas>
5 static constexpr auto alternation =
6
7 template <finite_automaton... Fas>
8 static constexpr auto star =
```

TEMPLATE STYLE MANIPULATION

```
1 template <finite_automaton... Fas>
2 static constexpr auto concat = multi_helper<concat_two, Fas...>::value;
3
4 template <finite_automaton... Fas>
5 static constexpr auto alternation = multi_helper<alternation_two, Fas...>::value;
6
7 template <finite_automaton... Fas>
8 static constexpr auto star = star_one<concat<Fas...>>::value;
```

TEMPLATE STYLE MANIPULATION

```
1 template <finite_automaton... Fas>
2 static constexpr auto concat = multi_helper<concat_two, Fas...>::value;
3
4 template <finite_automaton... Fas>
5 static constexpr auto alternation = multi_helper<alternation_two, Fas...>::value;
6
7 template <finite_automaton... Fas>
8 static constexpr auto star = star_one<concat<Fas...>>::value;
```

TEMPLATE STYLE MANIPULATION

```
1 template <finite_automaton... Fas>
2 static constexpr auto concat = multi_helper<concat_two, Fas...>::value;
3
4 template <finite_automaton... Fas>
5 static constexpr auto alternation = multi_helper<alternation_two, Fas...>::value;
6
7 template <finite_automaton... Fas>
8 static constexpr auto star = star_one<concat<Fas...>>::value;
```

TEMPLATE STYLE MANIPULATION

```
1 template <finite_automaton... Fas>
2 static constexpr auto concat = multi_helper<concat_two, Fas...>::value;
3
4 template <finite_automaton... Fas>
5 static constexpr auto alternation = multi_helper<alternation_two, Fas...>::value;
6
7 template <finite_automaton... Fas>
8 static constexpr auto star = star_one<concat<Fas...>>::value;
```


RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```


RECURSIVE APPLICATION OF A BINARY FUNCTION

```
1  template <
2      template <finite_automaton, finite_automaton> Op,
3      finite_automaton... Arg
4  >
5  struct multi_helper;
6
7
8
9  // specialization for 2+
10 template <
11     template <finite_automaton, finite_automaton> Op,
12     finite_automaton A,
13     finite_automaton B,
14     finite_automaton... Tail
15 >
```

**WE HAVE A CLASS-VALUE BASED
TEMPLATE META-PROGRAMMING!**

WE HAVE A CLASS-VALUE BASED TEMPLATE META-PROGRAMMING!

And if you use `const auto &` it's C++17 compatible!

```
constexpr auto fa = concat<one_char<'a'>, one_char<'b'>>;
```

```
constexpr auto fa = concat<one_char<'a'>, one_char<'b'>>;
```

- I called it a "compile time" function with compile-time arguments.

```
constexpr auto fa = concat<one_char<'a'>, one_char<'b'>>;
```

- I called it a "compile time" function with compile-time arguments.
- Unlike a constexpr function, it can take constexpr variables as arguments and maintain their "constexpr-bility".

```
constexpr auto fa = concat<one_char<'a'>, one_char<'b'>>;
```

- I called it a "compile time" function with compile-time arguments.
- Unlike a constexpr function, it can take constexpr variables as arguments and maintain their "constexpr-bility".
- It makes sure the value is cached.



```
constexpr auto fa = concat<one_char<'a'>, one_char<'b'>>;
```

- I called it a "compile time" function with compile-time arguments.
- Unlike a constexpr function, it can take constexpr variables as arguments and maintain their "constexpr-bility".
- It makes sure the value is cached.
- It looks nice :)



MINIMIZATION

Remove unnecessary states and links by merging the same states.

MINIMIZATION ALGORITHM





MINIMIZATION ALGORITHM





DETERMINIZATION

Remove nondeterministic transitions, can generate 2^n new states.



DETERMINIZATION ALGORITHM



DETERMINIZATION ALGORITHM



DETERMINIZATION ALGORITHM



DETERMINIZATION

Remove nondeterministic transitions, can generate 2^n new states.

DETERMINIZATION

Remove nondeterministic transitions, can generate 2^n new states.

Constexpr implementation must be iterative,
as the whole output can't be calculated in one step.

DETERMINIZATION

Remove nondeterministic transitions, can generate 2^n new states.

Constexpr implementation must be iterative,
as the whole output can't be calculated in one step.

It's useful to minimize the FA after the determinization.

**WE HAVE A DETERMINISTIC
FINITE AUTOMATON**

MATCHING

A REGULAR EXPRESSION

`"hello" =~ /aloha|[a-z]+/`

MATCHING AND SEARCHING

```
ctre::match<"aloha|[a-z]+">( "aloha"sv );  
  
// search(x) is actually match(.*x.*)  
ctre::search<"aloha|[a-z]+">( "...aloha..."sv );
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```


DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

CONVERTING A RE'S AST INTO AN FA

```
1 namespace fa {  
2     static constexpr auto empty = finite_automaton<0, 0>{};  
3 }  
4  
5 template <typename RE>  
6 static constexpr auto nfa_from = convert(fa::empty, list<RE>{});
```

RE is a type, `finite_automaton` is a value.

CONVERTING A RE'S AST INTO AN FA

```
1 namespace fa {  
2     static constexpr auto empty = finite_automaton<0, 0>{};  
3 }  
4  
5 template <typename RE>  
6 static constexpr auto nfa_from = convert(fa::empty, list<RE>{});
```

RE is a type, finite_automaton is a value.

CONVERTING A RE'S AST INTO AN FA

```
1 namespace fa {  
2     static constexpr auto empty = finite_automaton<0, 0>{};  
3 }  
4  
5 template <typename RE>  
6 static constexpr auto nfa_from = convert(fa::empty, list<RE>{});
```

RE is a type, finite_automaton is a value.

CONVERTING A RE'S AST INTO AN FA

```
1 namespace fa {  
2     static constexpr auto empty = finite_automaton<0, 0>{};  
3 }  
4  
5 template <typename RE>  
6 static constexpr auto nfa_from = convert(fa::empty, list<RE>{});
```

RE is a type, finite_automaton is a value.

CONVERTING A RE'S AST INTO AN FA

```
1 namespace fa {  
2     static constexpr auto empty = finite_automaton<0, 0>{};  
3 }  
4  
5 template <typename RE>  
6 static constexpr auto nfa_from = convert(fa::empty, list<RE>{});
```

RE is a type, finite_automaton is a value.

CONVERTING A RE'S AST INTO AN FA

```
1 namespace fa {  
2     static constexpr auto empty = finite_automaton<0, 0>{};  
3 }  
4  
5 template <typename RE>  
6 static constexpr auto nfa_from = convert(fa::empty, list<RE>{});
```

RE is a type, `finite_automaton` is a value.

CONVERTING A RE'S AST INTO AN FA

```
1 namespace fa {  
2     static constexpr auto empty = finite_automaton<0, 0>{};  
3 }  
4  
5 template <typename RE>  
6 static constexpr auto nfa_from = convert(fa::empty, list<RE>{});
```

RE is a type, finite_automaton is a value.

CONVERTING THE EMPTY RE

```
1 auto convert(const FinAutomaton auto seed, list<>) {  
2     // for an empty RE seed is empty FA  
3  
4     return seed;  
5  
6 }
```

CONVERTING THE EMPTY RE

```
1 auto convert(const FinAutomaton auto seed, list<>) {  
2     // for an empty RE seed is empty FA  
3  
4     return seed;  
5  
6 }
```

CONVERTING THE EMPTY RE

```
1 auto convert(const FinAutomaton auto seed, list<>) {  
2     // for an empty RE seed is empty FA  
3  
4     return seed;  
5  
6 }
```


CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{ }, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{});
10
11 }
```

CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{ }, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{});
10
11 }
```

CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{}, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{});
10
11 }
```

CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{ }, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{});
10
11 }
```

CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{}, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{});
10
11 }
```

CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{ }, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{});
10
11 }
```

CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{ }, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{{ });
10
11 }
```

CONVERTING EPSILON (EMPTY STRING)

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     static constexpr auto epsilon = finite_automaton<0, 1>{{{}, {0}}};
4 }
5
6 template <typename... Ts>
7 auto convert(const FinAutomaton auto lhs, list<epsilon, Ts...>) {
8
9     return convert(fa::concat<lhs, fa::epsilon>, list<Ts...>{});
10
11 }
```


CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs, fa::character<Term>>, list<Ts...>{});
11
12 }
```

CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs, fa::character<Term>>, list<Ts...>{});
11
12 }
```

CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs>, fa::character<Term>, list<Ts...>{});
11
12 }
```

CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs, fa::character<Term>>, list<Ts...>{});
11
12 }
```

CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs, fa::character<Term>>, list<Ts...>{});
11
12 }
```

CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs, fa::character<Term>>, list<Ts...>{});
11
12 }
```

CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs, fa::character<Term>>, list<Ts...>{});
11
12 }
```

CONVERTING A CHARACTER

```
1 namespace fa {
2     // epsilon is FA with a start state final
3     template <char32_t Term> static constexpr auto
4     character = finite_automaton<0, 1>{{transition{0, 1, Term}}, {1}};
5 }
6
7 template <char32_t Term, typename... Ts>
8 auto convert(const FinAutomaton auto lhs, list<character<Term>, Ts...>) {
9
10     return convert(fa::concat<lhs, fa::character<Term>>, list<Ts...>{});
11
12 }
```


CONVERTING A CONCAT SEQUENCE

```
1 template <typename... Content, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<concat<Content...>, Ts...>) {
3
4     return convert(lhs, list<Content..., Ts...>{});
5
6 }
```

CONVERTING A CONCAT SEQUENCE

```
1 template <typename... Content, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<concat<Content...>, Ts...>) {
3
4     return convert(lhs, list<Content..., Ts...>{});
5
6 }
```

CONVERTING A CONCAT SEQUENCE

```
1 template <typename... Content, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<concat<Content...>, Ts...>) {
3
4     return convert(lhs, list<Content..., Ts...>{});
5
6 }
```

CONVERTING A CONCAT SEQUENCE

```
1 template <typename... Content, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<concat<Content...>, Ts...>) {
3
4     return convert(lhs, list<Content..., Ts...>{});
5
6 }
```

CONVERTING A CONCAT SEQUENCE

```
1 template <typename... Content, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<concat<Content...>, Ts...>) {
3
4     return convert(lhs, list<Content..., Ts...>{});
5
6 }
```

CONVERTING A CONCAT SEQUENCE

```
1 template <typename... Content, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<concat<Content...>, Ts...>) {
3
4     return convert(lhs, list<Content..., Ts...>{});
5
6 }
```

CONVERTING AN ALTERNATION

```
1 template <typename... Options, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<alt<Options...>, Ts...>) {
3
4     constexpr auto inner = fa::alternative<convert(fa::empty, Options)...>;
5
6     return convert(fa::concat<lhs, inner>, list<Ts...>{});
7
8 }
```

CONVERTING AN ALTERNATION

```
1 template <typename... Options, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<alt<Options...>, Ts...>) {
3
4     constexpr auto inner = fa::alternative<convert(fa::empty, Options)...>;
5
6     return convert(fa::concat<lhs, inner>, list<Ts...>{});
7
8 }
```


CONVERTING AN ALTERNATION

```
1 template <typename... Options, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<alt<Options...>, Ts...>) {
3
4     constexpr auto inner = fa::alternative<convert(fa::empty, Options)...>;
5
6     return convert(fa::concat<lhs, inner>, list<Ts...>{});
7
8 }
```

CONVERTING AN ALTERNATION

```
1 template <typename... Options, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<alt<Options...>, Ts...>) {
3
4     constexpr auto inner = fa::alternative<convert(fa::empty, Options)...>;
5
6     return convert(fa::concat<lhs, inner>, list<Ts...>{});
7
8 }
```

CONVERTING AN ALTERNATION

```
1 template <typename... Options, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<alt<Options...>, Ts...>) {
3
4     constexpr auto inner = fa::alternative<convert(fa::empty, Options)...>;
5
6     return convert(fa::concat<lhs, inner>, list<Ts...>{});
7
8 }
```

CONVERTING AN ALTERNATION

```
1 template <typename... Options, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<alt<Options...>, Ts...>) {
3
4     constexpr auto inner = fa::alternative<convert(fa::empty, Options)...>;
5
6     return convert(fa::concat<lhs, inner>, list<Ts...>{});
7
8 }
```

CONVERTING AN ALTERNATION

```
1 template <typename... Options, typename... Ts>
2 auto convert(const FinAutomaton auto lhs, list<alt<Options...>, Ts...>) {
3
4     constexpr auto inner = fa::alternative<convert(fa::empty, Options)...>;
5
6     return convert(fa::concat<lhs, inner>, list<Ts...>{});
7
8 }
```

CONVERTING A KLEENE STAR (CYCLE)

```
1 template <typename Content, typename Ts...>
2 auto convert(const FinAutomaton auto seed, list<star<Content>, Ts...>) {
3
4     return convert(fa::concat<lhs, fa::star<Content>>, list<Ts...>{});
5
6 }
```

CONVERTING A KLEENE STAR (CYCLE)

```
1 template <typename Content, typename Ts...>
2 auto convert(const FinAutomaton auto seed, list<star<Content>, Ts...>) {
3
4     return convert(fa::concat<lhs, fa::star<Content>>, list<Ts...>{});
5
6 }
```

CONVERTING A KLEENE STAR (CYCLE)

```
1 template <typename Content, typename Ts...>
2 auto convert(const FinAutomaton auto seed, list<star<Content>, Ts...>) {
3
4     return convert(fa::concat<lhs, fa::star<Content>>, list<Ts...>{});
5
6 }
```


CONVERTING A KLEENE STAR (CYCLE)

```
1 template <typename Content, typename Ts...>
2 auto convert(const FinAutomaton auto seed, list<star<Content>, Ts...>) {
3
4     return convert(fa::concat<lhs, fa::star<Content>>, list<Ts...>{});
5
6 }
```

CONVERTING A KLEENE STAR (CYCLE)

```
1 template <typename Content, typename Ts...>
2 auto convert(const FinAutomaton auto seed, list<star<Content>, Ts...>) {
3
4     return convert(fa::concat<lhs, fa::star<Content>>, list<Ts...>{});
5
6 }
```

**WE HAVE A FINITE AUTOMATON,
NOW WE NEED TO DO THE MATCHING.**

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```

DETERMINISTIC MATCH WRAPPER

```
1 template <fixed_string re> bool fast_match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     constexpr auto dfa = fa::minimize<fa::determinize<nfa_from<RE>>>>;  
6  
7     return match_state<dfa>(rng.begin(), rng.end());  
8 }
```


MATCHING A STATE

```
1  template <finite_automaton DFA, int State = 0, typename Iterator>
2  constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4      // we can end correctly only if this state is final
5      if constexpr (DFA.is_final(State)) {
6          if (end == it) return true;
7      } else {
8          if (end == it) return false;
9      }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1 template <finite_automaton DFA, int State = 0, typename Iterator>
2 constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4     // we can end correctly only if this state is final
5     if constexpr (DFA.is_final(State)) {
6         if (end == it) return true;
7     } else {
8         if (end == it) return false;
9     }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1  template <finite_automaton DFA, int State = 0, typename Iterator>
2  constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4      // we can end correctly only if this state is final
5      if constexpr (DFA.is_final(State)) {
6          if (end == it) return true;
7      } else {
8          if (end == it) return false;
9      }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1  template <finite_automaton DFA, int State = 0, typename Iterator>
2  constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4      // we can end correctly only if this state is final
5      if constexpr (DFA.is_final(State)) {
6          if (end == it) return true;
7      } else {
8          if (end == it) return false;
9      }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1  template <finite_automaton DFA, int State = 0, typename Iterator>
2  constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4      // we can end correctly only if this state is final
5      if constexpr (DFA.is_final(State)) {
6          if (end == it) return true;
7      } else {
8          if (end == it) return false;
9      }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1  template <finite_automaton DFA, int State = 0, typename Iterator>
2  constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4      // we can end correctly only if this state is final
5      if constexpr (DFA.is_final(State)) {
6          if (end == it) return true;
7      } else {
8          if (end == it) return false;
9      }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1  template <finite_automaton DFA, int State = 0, typename Iterator>
2  constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4      // we can end correctly only if this state is final
5      if constexpr (DFA.is_final(State)) {
6          if (end == it) return true;
7      } else {
8          if (end == it) return false;
9      }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1  template <finite_automaton DFA, int State = 0, typename Iterator>
2  constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4      // we can end correctly only if this state is final
5      if constexpr (DFA.is_final(State)) {
6          if (end == it) return true;
7      } else {
8          if (end == it) return false;
9      }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```


MATCHING A STATE

```
1 template <finite_automaton DFA, int State = 0, typename Iterator>
2 constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4     // we can end correctly only if this state is final
5     if constexpr (DFA.is_final(State)) {
6         if (end == it) return true;
7     } else {
8         if (end == it) return false;
9     }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A STATE

```
1 template <finite_automaton DFA, int State = 0, typename Iterator>
2 constexpr bool match_state(Iterator it, Iterator end) noexcept {
3
4     // we can end correctly only if this state is final
5     if constexpr (DFA.is_final(State)) {
6         if (end == it) return true;
7     } else {
8         if (end == it) return false;
9     }
10
11     // transitions are sorted by source state
12     constexpr auto index = DFA.first_transition_index_of(State);
13
14     // tail-recursion
15     return choose_transition<DFA, index, State>(it, end);
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```


MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1  template <finite_automaton DFA, int Index, int State, typename Iterator>
2  constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3      // check if we are still in same state
4      if constexpr (Index >= DFA.transitions.size()
5          || DFA.transitions[Index].source != State) {
6
7          return false;
8      }
9
10     if (DFA.transitions[Index].match(*it)) {
11         // this transition is the one, go to next state (tail recursion)
12         return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13     }
14
15     // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```


MATCHING A TRANSITION

```
1 template <finite_automaton DFA, int Index, int State, typename Iterator>
2 constexpr bool choose_transition(Iterator it, const Iterator end) noexcept {
3     // check if we are still in same state
4     if constexpr (Index >= DFA.transitions.size()
5         || DFA.transitions[Index].source != State) {
6
7         return false;
8     }
9
10    if (DFA.transitions[Index].match(*it)) {
11        // this transition is the one, go to next state (tail recursion)
12        return match_state<DFA, DFA.transitions[Index].target>(std::next(it), end);
13    }
14
15    // try next one (also tail recursion)
```

THE DETERMINISTIC MATCHING

- $O(n * t)$ time complexity
- $O(1)$ dynamic memory complexity

n = length of the input, t = average number of transitions per state

THE DETERMINISTIC MATCHING

- $O(n * t)$ time complexity
- $O(1)$ dynamic memory complexity

n = length of the input, t = average number of transitions per state

- doesn't support capture tracking

THE DETERMINISTIC MATCHING

- $O(n * t)$ time complexity
- $O(1)$ dynamic memory complexity

n = length of the input, t = average number of transitions per state

- doesn't support capture tracking
- theoretically the quickest approach

THE DETERMINISTIC MATCHING

- $O(n * t)$ time complexity
- $O(1)$ dynamic memory complexity

n = length of the input, t = average number of transitions per state

- doesn't support capture tracking
- theoretically the quickest approach
- allows streamed data

BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```

BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```

BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```


BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```

BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```

BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```

BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```

BACKTRACKING MATCH WRAPPER

```
1 template <fixed_string re> bool match(const Range auto & rng) {  
2     static_assert(parser<pcre, re>::correct);  
3     using RE = parser<pcre, re>::type;  
4  
5     auto out = evaluate(rng.begin(), rng.end(), list<RE>{});  
6  
7     return out.success && out.it == rng.end();  
8 }
```

RETURN TYPE OF EVALUATE(...)

```
1 template <ForwardIterator It> struct result {  
2     bool success;  
3     ForwardIterator it;  
4 };
```

RETURN TYPE OF EVALUATE(...)

```
1 template <ForwardIterator It> struct result {  
2     bool success;  
3     ForwardIterator it;  
4 };
```

RETURN TYPE OF EVALUATE(...)

```
1 template <ForwardIterator It> struct result {  
2     bool success;  
3     ForwardIterator it;  
4 };
```


MATCHING EPSILON (EMPTY STRING)

```
1 template <ForwardIterator It, typename... Ts>
2 result<It> evaluate(It it, It end, list<epsilon, Ts...>) {
3     // tail-recursion => no backtracking
4     return evaluate(it, end, list<Ts...>{});
5 }
```

MATCHING EPSILON (EMPTY STRING)

```
1 template <ForwardIterator It, typename... Ts>
2 result<It> evaluate(It it, It end, list<epsilon, Ts...>) {
3     // tail-recursion => no backtracking
4     return evaluate(it, end, list<Ts...>{});
5 }
```

MATCHING EPSILON (EMPTY STRING)

```
1 template <ForwardIterator It, typename... Ts>
2 result<It> evaluate(It it, It end, list<epsilon, Ts...>) {
3     // tail-recursion => no backtracking
4     return evaluate(it, end, list<Ts...>{});
5 }
```

MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```

MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```

MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```

MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```

MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```


MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```

MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```

MATCHING A CHARACTER

```
1 template <ForwardIterator It, auto C, typename... Ts>
2 result<It> evaluate(It it, It end, list<ch<C>, Ts...>) {
3
4     if (it == end) return {it, false};
5     if (*it != C) return {it, false};
6
7     // tail-recursion => no backtracking
8     return evaluate(std::next(it), end, list<Ts...>{});
9 }
```

MATCHING A CONCATENATED SEQUENCE

```
1 template <ForwardIterator It, typename... Seq, typename... Ts>
2 result<It> evaluate(It it, It end, list<concat<Seq...>, Ts...>) {
3
4     // tail-recursion => no backtracking
5     return evaluate(it, end, list<Seq..., Ts...>{});
6
7 }
```

MATCHING A CONCATENATED SEQUENCE

```
1 template <ForwardIterator It, typename... Seq, typename... Ts>
2 result<It> evaluate(It it, It end, list<concat<Seq...>, Ts...>) {
3
4     // tail-recursion => no backtracking
5     return evaluate(it, end, list<Seq..., Ts...>{});
6
7 }
```

MATCHING A CONCATENATED SEQUENCE

```
1 template <ForwardIterator It, typename... Seq, typename... Ts>
2 result<It> evaluate(It it, It end, list<concat<Seq...>, Ts...>) {
3
4     // tail-recursion => no backtracking
5     return evaluate(it, end, list<Seq..., Ts...>{});
6
7 }
```

MATCHING A CONCATENATED SEQUENCE

```
1 template <ForwardIterator It, typename... Seq, typename... Ts>
2 result<It> evaluate(It it, It end, list<concat<Seq...>, Ts...>) {
3
4     // tail-recursion => no backtracking
5     return evaluate(it, end, list<Seq..., Ts...>{});
6
7 }
```

MATCHING AN ALTERNATE

```
1  template <ForwardIterator It, typename Head, typename... Tail, typename... Ts>
2  result<It> evaluate(It it, It end, list<alt<Head, Tail...>, Ts...>) {
3
4      // recursion => backtracking point
5      if (auto out = evaluate(it, end, list<Head, Ts...>{})) {
6          return out;
7      } else {
8          // tail-recursion => no backtracking
9          return evaluate(it, end, list<alt<Tail...>, Ts...>{}));
10     }
11 }
12
13 template <ForwardIterator It, typename... Ts>
14 result<It> evaluate(It it, It end, list<alt<>, Ts...>) {
15     // no option was successful
```


MATCHING AN ALTERNATE

```
1  template <ForwardIterator It, typename Head, typename... Tail, typename... Ts>
2  result<It> evaluate(It it, It end, list<alt<Head, Tail...>, Ts...>) {
3
4      // recursion => backtracking point
5      if (auto out = evaluate(it, end, list<Head, Ts...>{})) {
6          return out;
7      } else {
8          // tail-recursion => no backtracking
9          return evaluate(it, end, list<alt<Tail...>, Ts...>{}));
10     }
11 }
12
13 template <ForwardIterator It, typename... Ts>
14 result<It> evaluate(It it, It end, list<alt<>, Ts...>) {
15     // no option was successful
```

MATCHING AN ALTERNATE

```
1  template <ForwardIterator It, typename Head, typename... Tail, typename... Ts>
2  result<It> evaluate(It it, It end, list<alt<Head, Tail...>, Ts...>) {
3
4      // recursion => backtracking point
5      if (auto out = evaluate(it, end, list<Head, Ts...>{})) {
6          return out;
7      } else {
8          // tail-recursion => no backtracking
9          return evaluate(it, end, list<alt<Tail...>, Ts...>{}));
10     }
11 }
12
13 template <ForwardIterator It, typename... Ts>
14 result<It> evaluate(It it, It end, list<alt<>, Ts...>) {
15     // no option was successful
```

MATCHING AN ALTERNATE

```
1 template <ForwardIterator It, typename Head, typename... Tail, typename... Ts>
2 result<It> evaluate(It it, It end, list<alt<Head, Tail...>, Ts...>) {
3
4     // recursion => backtracking point
5     if (auto out = evaluate(it, end, list<Head, Ts...>{})) {
6         return out;
7     } else {
8         // tail-recursion => no backtracking
9         return evaluate(it, end, list<alt<Tail...>, Ts...>{}));
10    }
11 }
12
13 template <ForwardIterator It, typename... Ts>
14 result<It> evaluate(It it, It end, list<alt<>, Ts...>) {
15     // no option was successful
```

MATCHING AN ALTERNATE

```
1  template <ForwardIterator It, typename Head, typename... Tail, typename... Ts>
2  result<It> evaluate(It it, It end, list<alt<Head, Tail...>, Ts...>) {
3
4      // recursion => backtracking point
5      if (auto out = evaluate(it, end, list<Head, Ts...>{})) {
6          return out;
7      } else {
8          // tail-recursion => no backtracking
9          return evaluate(it, end, list<alt<Tail...>, Ts...>{}));
10     }
11 }
12
13 template <ForwardIterator It, typename... Ts>
14 result<It> evaluate(It it, It end, list<alt<>, Ts...>) {
15     // no option was successful
```

MATCHING AN ALTERNATE

```
1  template <ForwardIterator It, typename Head, typename... Tail, typename... Ts>
2  result<It> evaluate(It it, It end, list<alt<Head, Tail...>, Ts...>) {
3
4      // recursion => backtracking point
5      if (auto out = evaluate(it, end, list<Head, Ts...>{})) {
6          return out;
7      } else {
8          // tail-recursion => no backtracking
9          return evaluate(it, end, list<alt<Tail...>, Ts...>{}));
10     }
11 }
12
13 template <ForwardIterator It, typename... Ts>
14 result<It> evaluate(It it, It end, list<alt<>, Ts...>) {
15     // no option was successful
```

MATCHING AN ALTERNATE

```
1  template <ForwardIterator It, typename Head, typename... Tail, typename... Ts>
2  result<It> evaluate(It it, It end, list<alt<Head, Tail...>, Ts...>) {
3
4      // recursion => backtracking point
5      if (auto out = evaluate(it, end, list<Head, Ts...>{})) {
6          return out;
7      } else {
8          // tail-recursion => no backtracking
9          return evaluate(it, end, list<alt<Tail...>, Ts...>{}));
10     }
11 }
12
13 template <ForwardIterator It, typename... Ts>
14 result<It> evaluate(It it, It end, list<alt<>, Ts...>) {
15     // no option was successful
```

MATCHING A KLEENE STAR (CYCLE)

```
1 template <ForwardIterator It, typename Star, typename... Ts>
2 result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4     for (;;) {
5         // recursion => backtracking point
6         if (auto out = match(it, end, list<Ts...>{})) {
7             return out;
8         }
9
10        // recursion => backtracking point
11        if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12            it = inner.it;
13        } else {
14            // inner cycle failed and outer too => whole cycle fail
15            return {it, false};
```

MATCHING A KLEENE STAR (CYCLE)

```
1 template <ForwardIterator It, typename Star, typename... Ts>
2 result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4     for (;;) {
5         // recursion => backtracking point
6         if (auto out = match(it, end, list<Ts...>{})) {
7             return out;
8         }
9
10        // recursion => backtracking point
11        if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12            it = inner.it;
13        } else {
14            // inner cycle failed and outer too => whole cycle fail
15            return {it, false};
```


MATCHING A KLEENE STAR (CYCLE)

```
1 template <ForwardIterator It, typename Star, typename... Ts>
2 result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4     for (;;) {
5         // recursion => backtracking point
6         if (auto out = match(it, end, list<Ts...>{})) {
7             return out;
8         }
9
10        // recursion => backtracking point
11        if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12            it = inner.it;
13        } else {
14            // inner cycle failed and outer too => whole cycle fail
15            return {it, false};
```

MATCHING A KLEENE STAR (CYCLE)

```
1 template <ForwardIterator It, typename Star, typename... Ts>
2 result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4     for (;;) {
5         // recursion => backtracking point
6         if (auto out = match(it, end, list<Ts...>{})) {
7             return out;
8         }
9
10        // recursion => backtracking point
11        if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12            it = inner.it;
13        } else {
14            // inner cycle failed and outer too => whole cycle fail
15            return {it, false};
```

MATCHING A KLEENE STAR (CYCLE)

```
1 template <ForwardIterator It, typename Star, typename... Ts>
2 result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4     for (;;) {
5         // recursion => backtracking point
6         if (auto out = match(it, end, list<Ts...>{})) {
7             return out;
8         }
9
10        // recursion => backtracking point
11        if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12            it = inner.it;
13        } else {
14            // inner cycle failed and outer too => whole cycle fail
15            return {it, false};
```

MATCHING A KLEENE STAR (CYCLE)

```
1 template <ForwardIterator It, typename Star, typename... Ts>
2 result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4     for (;;) {
5         // recursion => backtracking point
6         if (auto out = match(it, end, list<Ts...>{})) {
7             return out;
8         }
9
10        // recursion => backtracking point
11        if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12            it = inner.it;
13        } else {
14            // inner cycle failed and outer too => whole cycle fail
15            return {it, false};
```

MATCHING A KLEENE STAR (CYCLE)

```
1 template <ForwardIterator It, typename Star, typename... Ts>
2 result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4     for (;;) {
5         // recursion => backtracking point
6         if (auto out = match(it, end, list<Ts...>{})) {
7             return out;
8         }
9
10        // recursion => backtracking point
11        if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12            it = inner.it;
13        } else {
14            // inner cycle failed and outer too => whole cycle fail
15            return {it, false};
```

MATCHING A KLEENE STAR (CYCLE)

```
1  template <ForwardIterator It, typename Star, typename... Ts>
2  result<It> match(It it, It end, list<star<Star>, Ts...>) {
3
4      for (;;) {
5          // recursion => backtracking point
6          if (auto out = match(it, end, list<Ts...>{})) {
7              return out;
8          }
9
10         // recursion => backtracking point
11         if (auto inner = match(it, end, list<Star..., end_of_cycle>{})) {
12             it = inner.it;
13         } else {
14             // inner cycle failed and outer too => whole cycle fail
15             return {it, false};
```

THE BACKTRACKING MATCHING

- $O(n * 2^b)$ time complexity
- $O(b)$ dynamic memory complexity

b = number of backtracking points, n = length of the input

THE BACKTRACKING MATCHING

- $O(n * 2^b)$ time complexity
- $O(b)$ dynamic memory complexity

b = number of backtracking points, n = length of the input

- easiest to implement

THE BACKTRACKING MATCHING

- $O(n * 2^b)$ time complexity
- $O(b)$ dynamic memory complexity

b = number of backtracking points, n = length of the input

- easiest to implement
- supports capture tracking

THE BACKTRACKING MATCHING

- $O(n * 2^b)$ time complexity
- $O(b)$ dynamic memory complexity

b = number of backtracking points, n = length of the input

- easiest to implement
- supports capture tracking
- slow worst case scenario

THE BACKTRACKING MATCHING

- $O(n * 2^b)$ time complexity
- $O(b)$ dynamic memory complexity

b = number of backtracking points, n = length of the input

- easiest to implement
- supports capture tracking
- slow worst case scenario
- doesn't allow streamed data

NFA WITHOUT BACKTRACKING

NFA WITHOUT BACKTRACKING

- supports capture tracking

NFA WITHOUT BACKTRACKING

- supports capture tracking
- slower to match, but much quicker to build (than DFA)

NFA WITHOUT BACKTRACKING

- supports capture tracking
- slower to match, but much quicker to build (than DFA)
- allows streamed data

NFA WITHOUT BACKTRACKING

- supports capture tracking
- slower to match, but much quicker to build (than DFA)
- allows streamed data

But I haven't implemented it yet

NFA WITHOUT BACKTRACKING

- supports capture tracking
- slower to match, but much quicker to build (than DFA)
- allows streamed data

But I haven't implemented it yet (some future talk maybe)

COMPARISON

LET'S READ SOME ASSEMBLY :)

```
1 #include <regex>
2 #include <string_view>
3
4 static std::regex re("[a-z0-9]+abc[0-9]");
5
6 bool match(std::string_view line) {
7     return std::regex_match(line.begin(), line.end(), re);
8 }
```

1



```
1 #include <boost/regex.hpp>
2 #include <string_view>
3
4 static boost::regex re("[a-z0-9]+abc[0-9]");
5
6 bool match(std::string_view line) {
7     return boost::regex_match(line.begin(), line.end(), re)
8 }
```



1

A

Save/Load

+ Add new...

CppInsights

C++

1#include <boost/xpressive/xpressive.hpp>

2

3using svregex = boost::xpressive::basic_regex<std::string_v

4

5static svregex re

6= (+boost::xpressive::alnum)

7>> 'a' >> 'b' >> 'c'

8>> boost::xpressive::digit;

9

10bool match(std::string_view line) {

11return bool(boost::xpressive::regex_search(line, re));

12}

GCC 9.1

-Os -std=c++2a

A

☐ 11010

☒ .LX0:

☒ .text

☒ //

☒ \s+

☒ Intel

☒ Demangle


+

1

Edit on Compiler Explorer

```
1 #include <ctre.hpp>
2
3 bool match(std::string_view line) {
4     return ctre::match<"[a-z0-9]+abc[0-9]">(line);
5 }
```

A ▾ ☐ 11010 ☒ .LX0: ☒ .text ☒ // ☒ \s+ ☒ Intel ☒ Demangle

 Libraries ▾ + Add new... ▾ ⚙ Add tool... ▾

1

BENCHMARKS

MEASURED CODE (GREP-LIKE UTILITY)

```
int main(int argc, char ** argv) {  
    auto re = PREPARE("PATTERN");  
    auto lines = load_file_by_lines(argv[1]);  
  
    size_t count = 0;  
  
    // some warm-up  
  
    auto start = steady_clock::now();  
    for (string_view line: lines) {  
        if (re.SEARCH(line)) count++;  
    }  
    auto end = steady_clock::now();  
  
    cout << count << "\n";  
}
```


MEASURED CODE (GREP-LIKE UTILITY)

```
int main(int argc, char ** argv) {  
    auto re = PREPARE("PATTERN");  
    auto lines = load_file_by_lines(argv[1]);  
  
    size_t count = 0;  
  
    // some warm-up  
  
    auto start = steady_clock::now();  
    for (string_view line: lines) {  
        if (re.SEARCH(line)) count++;  
    }  
    auto end = steady_clock::now();  
  
    cout << count << "\n";  
}
```

MEASURED CODE (GREP-LIKE UTILITY)

```
int main(int argc, char ** argv) {  
    auto re = PREPARE("PATTERN");  
    auto lines = load_file_by_lines(argv[1]);  
  
    size_t count = 0;  
  
    // some warm-up  
  
    auto start = steady_clock::now();  
    for (string_view line: lines) {  
        if (re.SEARCH(line)) count++;  
    }  
    auto end = steady_clock::now();  
  
    cout << count << "\n";  
}
```

MEASURED CODE (GREP-LIKE UTILITY)

```
int main(int argc, char ** argv) {  
    auto re = PREPARE("PATTERN");  
    auto lines = load_file_by_lines(argv[1]);  
  
    size_t count = 0;  
  
    // some warm-up  
  
    auto start = steady_clock::now();  
    for (string_view line: lines) {  
        if (re.SEARCH(line)) count++;  
    }  
    auto end = steady_clock::now();  
  
    cout << count << "\n";  
}
```

MEASURED CODE (GREP-LIKE UTILITY)

```
int main(int argc, char ** argv) {  
    auto re = PREPARE("PATTERN");  
    auto lines = load_file_by_lines(argv[1]);  
  
    size_t count = 0;  
  
    // some warm-up  
  
    auto start = steady_clock::now();  
    for (string_view line: lines) {  
        if (re.SEARCH(line)) count++;  
    }  
    auto end = steady_clock::now();  
  
    cout << count << "\n";  
}
```

MEASURED CODE (GREP-LIKE UTILITY)

```
int main(int argc, char ** argv) {  
    auto re = PREPARE("PATTERN");  
    auto lines = load_file_by_lines(argv[1]);  
  
    size_t count = 0;  
  
    // some warm-up  
  
    auto start = steady_clock::now();  
    for (string_view line: lines) {  
        if (re.SEARCH(line)) count++;  
    }  
    auto end = steady_clock::now();  
  
    cout << count << "\n";  
}
```


MEASURED CODE (GREP-LIKE UTILITY)

```
int main(int argc, char ** argv) {  
    auto re = PREPARE("PATTERN");  
    auto lines = load_file_by_lines(argv[1]);  
  
    size_t count = 0;  
  
    // some warm-up  
  
    auto start = steady_clock::now();  
    for (string_view line: lines) {  
        if (re.SEARCH(line)) count++;  
    }  
    auto end = steady_clock::now();  
  
    cout << count << "\n";  
}
```


MEASUREMENT METHODOLOGY

- CSV file (1.3GiB) with 6.5 MLoC
- Median of 3 measurements
- MacBook Pro 13" 2016 i7 3.3Ghz
- GCC 9.1 & clang 8 (-std=2a -O3)


RUNTIME SEARCHING (CLANG 8): [a-z0-9]+abc[0-9]




RUNTIME SEARCHING (GCC 9): [a-z0-9]+abc[0-9]




COMPILATION (CLANG 8): `[a-z0-9]+?abc[0-9]`




COMPILATION (GCC 9): `[a-z0-9]+?abc[0-9]`




RUNTIME SEARCHING (CLANG 8): `ABCDE-[0-9]+`




RUNTIME SEARCHING (GCC 9): **ABCDE-[0-9]+**



COMPILATION (CLANG 8): **ABCDE-[0-9]+**



COMPILATION (GCC 9): **ABCDE-[0-9]+**



SIX THINGS I SHOWED YOU...

SIX THINGS I SHOWED YOU...

- How regular expression engines work.

SIX THINGS I SHOWED YOU...

- How regular expression engines work.
- Connection between theory and code.

SIX THINGS I SHOWED YOU...

- How regular expression engines work.
- Connection between theory and code.
- Parsing of a pattern during compilation.

SIX THINGS I SHOWED YOU...

- How regular expression engines work.
- Connection between theory and code.
- Parsing of a pattern during compilation.
- Building of a finite automaton.

SIX THINGS I SHOWED YOU...

- How regular expression engines work.
- Connection between theory and code.
- Parsing of a pattern during compilation.
- Building of a finite automaton.
- Matching a regex with various algorithms.

SIX THINGS I SHOWED YOU...

- How regular expression engines work.
- Connection between theory and code.
- Parsing of a pattern during compilation.
- Building of a finite automaton.
- Matching a regex with various algorithms.
- Comparison between different regex implementations.

AND FOUR THINGS YOU SHOULD REMEMBER...

AND FOUR THINGS YOU SHOULD REMEMBER...

- Compilers can optimize your code, if you help them.

AND FOUR THINGS YOU SHOULD REMEMBER...

- Compilers can optimize your code, if you help them.
- Combining TMP and constexpr code can help you express more things more precisely.

AND FOUR THINGS YOU SHOULD REMEMBER...

- Compilers can optimize your code, if you help them.
- Combining TMP and constexpr code can help you express more things more precisely.
- Stop pretending that constexpr C++ is a compiled language.

AND FOUR THINGS YOU SHOULD REMEMBER...

- Compilers can optimize your code, if you help them.
- Combining TMP and constexpr code can help you express more things more precisely.
- Stop pretending that constexpr C++ is a compiled language.
- Try the CTRE library

AND FOUR THINGS YOU SHOULD REMEMBER...

- Compilers can optimize your code, if you help them.
- Combining TMP and constexpr code can help you express more things more precisely.
- Stop pretending that constexpr C++ is a compiled language.
- Try the CTRE library, not just for speed but for code clarity.

THANK YOU!

You can find slides & code at compile-time.re