

# THE ROUGH ROAD TOWARDS UPGRADING TO C++ MODULES

**RICHÁRD SZALAY** @Whisperity,  
ZOLTÁN PORKOLÁB

EÖTVÖS LORÁND UNIVERSITY  
FACULTY OF INFORMATICS  
DEPT. OF PROG. LANG. & COMPILERS

2019. 05. 10.

Research effort supported by the ÚNKP-18-2 “New National Excellence Program” of the Ministry of Human Capacities.  
Publication supported by the European Union, co-financed by the European Social Fund in project EFOP-3.6.3-VEKOP-16-2017-00002.



EMBERI ERŐFORRÁSOK  
MINISZTERIUMA

SZÉCHENYI 2020



MAGYARORSZÁG  
KORMÁNYA

Európai Unió  
Európai Szociális  
Alap



BEFEKTETÉS A JÖVŐBE

# USING THIRD-PARTY SOLUTIONS IN OUR CODE

After some download & build configuration...

- Java: **import** org.apache.hadoop.\*;
- Python: **import** networkx **as** nx
- Fortran ( $\geq 90$ ): **use** opengl\_gl

# USING THIRD-PARTY SOLUTIONS IN OUR CODE

After some download & build configuration...

- Java: **import** org.apache.hadoop.\*;
- Python: **import** networkx **as** nx
- Fortran ( $\geq 90$ ): **use** opengl\_gl
- C++:  

```
#include <boost/fiber/bounded_channel.hpp>  
#include <boost/filesystem/path.h>  
#include <complex>
```

# USING THIRD-PARTY SOLUTIONS IN OUR CODE

After some download & build configuration...

- Java: **import** org.apache.hadoop.\*;
- Python: **import** networkx **as** nx
- Fortran ( $\geq 90$ ): **use** opengl\_gl

- C++:

```
#include <boost/fiber/bounded_channel.hpp>
#include <boost/filesystem/path.h>
#include <complex>
```

- ▶ and also:

```
g++ a.o -lboost_filesystem@1.58.0 -o a.out
```

# USING THIRD-PARTY SOLUTIONS IN OUR CODE

After some download & build configuration...

- Java: **import** org.apache.hadoop.\*;
- Python: **import** networkx **as** nx
- Fortran ( $\geq 90$ ): **use** opengl\_gl

■ C++:


```
#include <boost/fiber/bounded_channel.hpp>
#include <boost/filesystem/path.h>
#include <complex>
```

► and also:

```
g++ a.o -lboost_filesystem@1.58.0 -o a.out
```

## USING THIRD-PARTY SOLUTIONS IN OUR CODE

Assuming a set environment, good build configuration and IDE...




The screenshot shows a code editor with a list of files on the left: `riting.cpp`, `tion.cpp`, `ing.cpp`, `ticDeclaration`, `cpp`, and `o`. The main editor displays C++ code with line numbers 4 through 12. A tooltip is visible over the `ASTUnit` identifier on line 10. The code is as follows:

```
4  #include <utility>
5
6  namespace /* anonymous */
7  {
8      void f()
9      {
10         ASTUnit
11         # LLVM_CLANG_FRONTEND_ASTUNIT_H
12         Press Ctrl+Space again for not-imported symbols >>
```

## USING THIRD-PARTY SOLUTIONS IN OUR CODE

Assuming a set environment, good build configuration and IDE...



The screenshot shows a code editor with a dark theme. On the left, a file explorer lists 'riting.cpp' and 'tion.cpp'. The main editor area shows C++ code with line numbers 4 through 12. Line 4: `#include <utility>`. Line 6: `namespace /* anonymous */`. Line 7: `{`. Line 10: `clang::ASTUnit` (highlighted in red). Line 11: `}`. Line 12: `} // end namespace anonymous`. A blue tooltip box is overlaid on the code, containing the text: `?class 'clang::ASTUnit' from <clang/Frontend/ASTUnit.h>? Alt+Enter`. The tooltip has a small question mark icon on the left and a pointer at the bottom.

```
4      #include <utility>
5
6      namespace /* anonymous */
7      {
8
9      }
10     clang::ASTUnit
11 }
12 } // end namespace anonymous
```

?class 'clang::ASTUnit' from <clang/Frontend/ASTUnit.h>? Alt+Enter

## USING THIRD-PARTY SOLUTIONS IN OUR CODE

Assuming a set environment, good build configuration and IDE...

```
4      #include <utility>
5      #include <clang/Frontend/ASTUnit.h>
6
7      namespace /* anonymous */
8      {
9          void f()
10         {
11             clang::ASTUnit FooUnit;
12         }
```



# USING THIRD-PARTY SOLUTIONS IN OUR CODE

Did I subtly break something?

```
4      #include <utility>
5      #include <clang/Frontend/ASTUnit.h>
6
7      namespace /* anonymous */
8      {
9          void f()
10         {
11             clang::ASTUnit FooUnit;
12         }
```

# OUTLINE OF THIS TALK

- 1 C++'s Compilation Model
  - Software technology issues
  - Performance drawbacks and possible solutions
- 2 C++ Modules
  - “How it should work?”
  - Traps and pitfalls (even) with Modules
- 3 The Wish for Automatic Modularisation
  - Formal overview
  - Case study — Apache Xerces
  - Evaluation of findings
  - Requirements for upgrading to Modules
- 4 Summary


# COMPILATION MODEL

1. Compiler invoked with a **single** source file.




# COMPILATION MODEL

1. Compiler invoked with a **single** source file.
2. Source file preprocessed, directives such as `#define`, `#include` executed




# COMPILATION MODEL

1. Compiler invoked with a **single** source file.
2. Source file preprocessed, directives such as `#define`, `#include` executed
3. Included headers located




# COMPILATION MODEL

1. Compiler invoked with a **single** source file.
2. Source file preprocessed, directives such as `#define`, `#include` executed
3. Included headers located
4. Included headers transitively preprocessed




# COMPILATION MODEL

1. Compiler invoked with a **single** source file.
2. Source file preprocessed, directives such as `#define`, `#include` executed
3. Included headers located
4. Included headers transitively preprocessed
5. The input buffer is complete.



# COMPILATION MODEL


1. Compiler invoked with a **single** source file.
2. Source file preprocessed, directives such as `#define`, `#include` executed
3. Included headers located
4. Included headers transitively preprocessed
5. The input buffer is complete.
6. Template instantiation, code generation





# COMPILATION MODEL

1. Compiler invoked with a **single** source file.
2. Source file preprocessed, directives such as `#define`, `#include` executed
3. Included headers located
4. Included headers transitively preprocessed
5. The input buffer is complete.
6. Template instantiation, code generation
7. Generated objects linked into binary



# “FACES”, “METRICS” AND “GOALS” AROUND DEVELOPMENT

- Good (?) code
- Often easily written
- Almost always well readable
- Good run-time performance
- Stable behaviour, tested, ...
- Good tooling:
  - ▶ Build (and package?) management
  - ▶ Static analysis, coverage
  - ▶ Code comprehension
- Solid releases, nightlies
- Easy, fast incremental development

# “FACES”, “METRICS” AND “GOALS” AROUND DEVELOPMENT

- Good (?) code
- Often easily written
- Almost always well readable
- Good run-time performance
- Stable behaviour, tested, ...
- Good tooling:
  - ▶ Build (and package?) management
  - ▶ Static analysis, coverage
  - ▶ Code comprehension
- ~~Solid releases, nightlies~~
- ~~Easy, fast incremental development~~

# ISSUES WITH TOKEN LEAK

header.hpp

```
#define APP_DATE __DATE__          /* Build date */
```

main.cpp

```
int main() { std::cout << APP_DATE << std::endl; }
```

# ISSUES WITH TOKEN LEAK

header.hpp

```
#define APP_DATE __DATE__          /* Build date */
```

main.cpp

```
int main() { std::cout << APP_DATE << std::endl; }
```

lib.hpp

```
#define APP_DATE "2017. Oct. 20." /* Licensing date */
```

lib.cpp

```
const char* LicenseStartDate() { return APP_DATE; }
```

# ISSUES WITH TOKEN LEAK/SINGLE INPUT BUFFER

header.hpp

```
#define APP_DATE __DATE__          /* Build date */
```

lib.hpp

```
#define APP_DATE "2017. Oct. 20." /* Licensing date */
```

main.cpp

```
#include "header.hpp"
#include "lib.hpp"
int main() {
    std::cout << LicenseStartDate() << '/'
               << APP_DATE << std::endl;
}
```

# ISSUES WITH NAME LEAK

header1.hpp

```
namespace A {  
namespace {  
    inline int detail() { return 1; }  
}  
    class X { /* ... */ };  
}
```

header2.hpp

```
namespace A {  
namespace {  
    inline int detail() { return 2; }  
}  
    class Y { /* ... */ };  
}
```

# ISSUES WITH SUBTLE BREAKING CHANGES

client.cpp

```
struct B, D;
```

```
int f(const void* vp) { return 1; }
```

```
int f(const B* bp) { return 0; }
```

```
int test(D* dp) [[ensures t: t == 1]]  
{  
    return f(dp); // resolved as 'f(const void*)'  
}
```

---

Source: [google.github.io/styleguide/cppguide.html#Forward\\_Declarations](https://google.github.io/styleguide/cppguide.html#Forward_Declarations)



# ISSUES WITH SUBTLE BREAKING CHANGES

types.hpp

```
struct B      { /* ... */ };  
struct D : B { /* ... */ };
```

client.cpp

```
#include "types.hpp"  
  
int f(const void* vp) { return 1; }  
int f(const B* bp) { return 0; }  
  
int test(D* dp) [[ensures t: t == 1]]  
{ return f(dp); }
```

---

Source: [google.github.io/styleguide/cppguide.html#Forward\\_Declarations](https://google.github.io/styleguide/cppguide.html#Forward_Declarations)

# ISSUES WITH SUBTLE BREAKING CHANGES

types.hpp

```
struct B      { /* ... */ };  
struct D : B { /* ... */ };
```

client.cpp

```
#include "types.hpp"  
  
int f(const void* vp) { return 1; }  
int f(const B* bp) { return 0; }  
  
int test(D* dp) [[ensures t: t == 1]]  
{ return f(dp); } // resolved as 'f(const B*)'
```

---

Source: [google.github.io/styleguide/cppguide.html#Forward\\_Declarations](https://google.github.io/styleguide/cppguide.html#Forward_Declarations)

# ISSUES WITH LACK OF HIDING DETAILS

Symbol in input buffer → it's there forever

```
__throw_underflow_error(const char *) void
f __use_alloc(const _Alloc &&) void
f _Exit(int __status) void
f _Fnv_hash_bytes(const void *__ptr, size_t __len, ... size_t
f _Hash_bytes(const void *__ptr, size_t __len, size... size_t
f _Rb_tree_black_count(const _Rb_tree_node_ba... unsigned int
s _Rb_tree
// f _Rb_tree_decrement(_Rb_tree_no... std::_Rb_tree_node_base *
fo f _Rb_tree_increment(_Rb_tree_no... std::_Rb_tree_node_base *
f _Rb_tree_insert_and_rebalance(const bool __insert_l... void
// f _Rb_tree_rebalance_for_erase(_... std::_Rb_tree_node_base *
Th f abort(void) void
Press Ctrl+Space again for not-imported symbols >> π
std::
```

# ISSUES WITH LACK OF HIDING DETAILS

Symbol in input buffer → it's there forever

```
1 __throw_underflow_error(const char *) void
f __use_alloc(const _Alloc &&) void
f _Exit(int __status) void
f _Fnv_hash_bytes(const void *__ptr, size_t __len, ... size_t
f _Hash_bytes(const void *__ptr, size_t __len, size... size_t
f _Rb_tree_black_count(const _Rb_tree_node_ba... unsigned int
s _Rb_tree
// f _Rb_tree_decrement(_Rb_tree_no... std::_Rb_tree_node_base *
fo f _Rb_tree_increment(_Rb_tree_no... std::_Rb_tree_node_base *
f _Rb_tree_insert_and_rebalance(const bool __insert_l... void
// f _Rb_tree_rebalance_for_erase(_... std::_Rb_tree_node_base *
Th f abort(void) void
Press Ctrl+Space again for not-imported symbols >> π
std::
```

Hide with **static** (or anonymous **namespace**)?

# ISSUES WITH LACK OF HIDING DETAILS

For templates, *internal linkage* isn't a solution...

```
template <class T>
class X
{
    private:
        T foo(T t);
};
```

# ISSUES WITH LACK OF HIDING DETAILS

For templates, *internal linkage* isn't a solution...


```
template <class T>
class X
{
    private:
        T foo(T t);
};
```

- Is `X<int>{}.foo` a valid naming?
- Can I actually call the function?

# ISSUES WITH LACK OF HIDING DETAILS

For templates, *internal linkage* isn't a solution...



```
template <class T>
class X
{
    private:
        T foo(T t);
};
```

- Is `X<int>{}.foo` a valid naming?  **Yes!**
- Can I actually call the function?

# ISSUES WITH LACK OF HIDING DETAILS

For templates, *internal linkage* isn't a solution...

```
template <class T>
class X
{
    private:
        T foo(T t);
};
```



- Is `X<int>{}.foo` a valid naming?  **Yes!**
- Can I actually call the function?  **No!**



# ISSUES WITH LACK OF HIDING DETAILS

For templates, *internal linkage* isn't a solution...

```
template <class T>
class X
{
    private:
        T foo(T t);
};
```

- Is `X<int>{}.foo` a valid naming?  **Yes!**
- Can I actually call the function?  **Maybe...**<sup>1</sup>

---

<sup>1</sup>Márton and Porkoláb, “Unit Testing in C++ with Compiler Instrumentation and friends”.

## ISSUES WITH LACK OF HIDING DETAILS

### detail namespace

```
static boost::regex rCppFiles("\\.cpp\b");  
  
/* ... */  
  
std::string sFilenameArgs("/tmp/foo.cpp");  
boost::re_detail::matcher mBuf(  
    sFilename.begin(), sFilename.end(),  
    /* ... */,  
    &rCppFiles);  
  
// Inner detail through mBuf instead of documented API
```

## ISSUES WITH LACK OF HIDING DETAILS

```
boost::re_detail::matcher mBuf(/* ... */);
```

## ISSUES WITH LACK OF HIDING DETAILS

```
boost::re_detail::matcher mBuf(/* ... */);
```

Compiler errors only go so long...

## ISSUES WITH LACK OF HIDING DETAILS

```
boost::re_detail::matcher mBuf(/* ... */);
```

Compiler errors only go so long...

Linters and other analysis tools only go so long...

# ISSUES WITH LACK OF HIDING DETAILS

```
boost::re_detail::matcher mBuf(/* ... */);
```

Compiler errors only go so long...

Linters and other analysis tools only go so long...

**Users go further.**


# “FACES”, “METRICS” AND “GOALS” AROUND DEVELOPMENT

- Good (?) code
- Often easily written
- Almost always well readable
- Good run-time performance
- Stable behaviour, tested, ...
- Good tooling:
  - ▶ Build (and package?) management
  - ▶ Static analysis, coverage
  - ▶ Code comprehension
- **Solid releases, nightlies**
- **Easy, fast incremental development**

# NOT JUST COMPILATION MODEL

Remember this?

We only do this for all translation units **once** per (re-)build, right?






# NOT JUST COMPILATION MODEL

Remember this?


We only do this for all translation units **once** per (re-)build, right?

 **Wrong!**




# NOT JUST COMPILATION MODEL

## ■ *Compiler*




# NOT JUST COMPILATION MODEL

- *Compiler*
- Static analysis




# NOT JUST COMPILATION MODEL

- *Compiler*
- Static analysis
- Code comprehension, indexing




# NOT JUST COMPILATION MODEL

- *Compiler*
- Static analysis
- Code comprehension, indexing
- Formatting




# NOT JUST COMPILATION MODEL

- *Compiler*
- Static analysis
- Code comprehension, indexing
- Formatting
- Automatic refactoring




# NOT JUST COMPILATION MODEL

- *Compiler*
- Static analysis
- Code comprehension, indexing
- Formatting
- Automatic refactoring
- Metrics



# NOT JUST COMPILATION MODEL

- *Compiler*
- Static analysis
- Code comprehension, indexing
- Formatting
- Automatic refactoring
- Metrics
- ...





# PERFORMANCE CONCERNS

*Personal story...*

*Personal story...*

Working on an algorithm in *CodeCompass*<sup>2</sup>.

- TU depends on: STL, Boost, LLVM, ODB (database), ...
- 24-core system, plenty of RAM
- Incremental rebuild 1 TU:  $\sim 6$  minutes

---

<sup>2</sup><http://github.com/Ericsson/CodeCompass>

*Personal story...*

Working on an algorithm in *CodeCompass*<sup>2</sup>.

- TU depends on: STL, Boost, LLVM, ODB (database), ...
- 24-core system, plenty of RAM
- Incremental rebuild 1 TU:  $\sim 6$  minutes
- 1. Move sources and build to memory.  $\sim 2.5 - 3$  minutes

---

<sup>2</sup><http://github.com/Ericsson/CodeCompass>

*Personal story...*

Working on an algorithm in *CodeCompass*<sup>2</sup>.

- TU depends on: STL, Boost, LLVM, ODB (database), ...
- 24-core system, plenty of RAM
- Incremental rebuild 1 TU:  $\sim 6$  minutes
  1. Move sources and build to memory.  $\sim 2.5 - 3$  minutes
  2. Cut down on includes.  $\sim 1$  minute 40 seconds

---

<sup>2</sup><http://github.com/Ericsson/CodeCompass>

## PERFORMANCE CONCERNS

Because of *separate compilation*, many times:

- `#include` files read from “storage”

# PERFORMANCE CONCERNS

Because of *separate compilation*, many times:

- `#include` files read from “storage”
- Big chunk of the input buffer is copy-paste:

Library	original LOC	preproc. LOC	preproc. impact	impact ratio
OpenSceneGraph	91205	16366213	17944%	} 4.90%
OpenSceneGraph unity		802053	879%	
wxWidgets	357642	40550041	11338%	} 3.85%
wxWidgets unity		1562461	437%	
Xerces	122396	2398884	1960%	} 9.87%
Xerces unity		236810	193%	

**Figure:** Impact on input buffer LoC by preprocessing.<sup>3</sup>

---

<sup>3</sup>Mihalicza, “How `#includes` Affect Build Time in Large Systems”.

# PERFORMANCE CONCERNS

Because of *separate compilation*, many times:

- `#include` files read from “storage”
- Big chunk of the input buffer is copy-paste:

Library	original LOC	preproc. LOC	preproc. impact	impact ratio
OpenSceneGraph	91205	16366213	17944%	} 4.90%
OpenSceneGraph unity		802053	879%	
wxWidgets	357642	40550041	11338%	} 3.85%
wxWidgets unity		1562461	437%	
Xerces	122396	2398884	1960%	} 9.87%
Xerces unity		236810	193%	

**Figure:** Impact on input buffer LoC by preprocessing.<sup>3</sup>

- Template generation – even worse than preprocessor

---

<sup>3</sup>Mihalicza, “How `#includes` Affect Build Time in Large Systems”.

# PERFORMANCE CONCERNS

Because of *separate compilation*, many times:

- `#include` files read from “storage”
- Big chunk of the input buffer is copy-paste:

Library	original LOC	preproc. LOC	preproc. impact	impact ratio
OpenSceneGraph	91205	16366213	17944%	} 4.90%
OpenSceneGraph unity		802053	879%	
wxWidgets	357642	40550041	11338%	} 3.85%
wxWidgets unity		1562461	437%	
Xerces	122396	2398884	1960%	} 9.87%
Xerces unity		236810	193%	

**Figure:** Impact on input buffer LoC by preprocessing.<sup>3</sup>

- Template generation – even worse than preprocessor
- Weak references thrown away at linking

<sup>3</sup>Mihalicza, “How `#includes` Affect Build Time in Large Systems”.



## POSSIBLE SOLUTIONS TO PERFORMANCE

- Boosting build process

- Boosting build process: ccache, distcc, *Bazel*, ...

- Boosting build process: `ccache`, `distcc`, *Bazel*, ...
- **Precompiled headers** (PCH)
  - + Save and reuse compiler representation (e.g. AST) into a file

- Boosting build process: `ccache`, `distcc`, *Bazel*, ...
- **Precompiled headers** (PCH)
  - + Save and reuse compiler representation (e.g. AST) into a file
  - *PCHs* require build system support

## POSSIBLE *SOLUTIONS* WORKAROUNDS

- Boosting build process: `ccache`, `distcc`, *Bazel*, ...
- **Precompiled headers** (PCH)
  - + Save and reuse compiler representation (e.g. AST) into a file
  - *PCHs* require build system support
- HP's `aCC` compiler<sup>4</sup>

---

<sup>4</sup>Krishnaswamy, "Automatic Precompiled Headers: Speeding up C++ Application Build Times".

## POSSIBLE *SOLUTIONS* WORKAROUNDS

- Boosting build process: `ccache`, `distcc`, *Bazel*, ...
- **Precompiled headers** (PCH)
  - + Save and reuse compiler representation (e.g. AST) into a file
  - PCHs require build system support
- HP's aCC compiler<sup>4</sup>
  - ▶ PCH for TU's "preamble"

---

<sup>4</sup>Krishnaswamy, "Automatic Precompiled Headers: Speeding up C++ Application Build Times".

## POSSIBLE *SOLUTIONS* WORKAROUNDS

- Boosting build process: `ccache`, `distcc`, *Bazel*, ...
- **Precompiled headers** (PCH)
  - + Save and reuse compiler representation (e.g. AST) into a file
  - *PCHs* require build system support
- HP's `aCC` compiler<sup>4</sup>
  - ▶ PCH for TU's "preamble"
- C++ Modules?

---

<sup>4</sup>Krishnaswamy, "Automatic Precompiled Headers: Speeding up C++ Application Build Times".

- 1 C++'s Compilation Model
  - Software technology issues
  - Performance drawbacks and possible solutions


- 2 C++ Modules
  - “How it should work?”
  - Traps and pitfalls (even) with Modules

- 3 The Wish for Automatic Modularisation
  - Formal overview
  - Case study — Apache Xerces
  - Evaluation of findings
  - Requirements for upgrading to Modules



- 4 Summary



# PCHs vs. C++ MODULES



# PCHs vs. C++ MODULES



PCM extension for something like the “binary module interface” is Modules for Clang, is a beefed up PCH under the hood.

# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.

# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**
- Officially part of C++20 feature set

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.

# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**
- Officially part of C++20 feature set
- + Header mechanics → logical packaging

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.

# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**
- Officially part of C++20 feature set
- + Header mechanics → logical packaging
- One module is still a (bunch of) translation units

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.

# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**
- Officially part of C++20 feature set
- + Header mechanics → logical packaging
- One module is still a (bunch of) translation units
- How to use? **import** M;

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.

# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**
- Officially part of C++20 feature set
  - + Header mechanics → logical packaging
- One module is still a (bunch of) translation units
- How to use? **import** M;
  - + No preprocessor effect between TUs

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.



# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**
- Officially part of C++20 feature set
  - + Header mechanics → logical packaging
- One module is still a (bunch of) translation units
- How to use? **import** M;
  - + No preprocessor effect between TUs
- Name not part of FQN: ~~M::std::vector~~

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.

# C++ MODULES (AS OF P1103R3<sup>5</sup>)

- Original form first proposed in **2004**
- Officially part of C++20 feature set
- + Header mechanics → logical packaging
- One module is still a (bunch of) translation units
- How to use? **import** M;
- + No preprocessor effect between TUs
- Name not part of FQN: ~~M::std::vector~~
- ? Wording of standard proposal is rather flexible to allow compiler optimisations?

---

<sup>5</sup>Smith, P1103R3: *Merging Modules*.

# “HELLO MODULES!”

# “HELLO MODULES!”

## Module file

```
export module MyModule;
```

```
int four() { return 4; }
```

```
int six() { return four() + 2; }
```

# “HELLO MODULES!”

## Module file

```
export module MyModule;  
  
    int four() { return 4; }  
    int  six() { return four() + 2; }
```

## Client code

```
import MyModule;  
int main() {  
    int s;  
    int f;  
  
}
```

# “HELLO MODULES!”

## Module file

```
export module MyModule;  
  
    int four() { return 4; }  
export int six() { return four() + 2; }
```

## Client code

```
import MyModule;  
int main() {  
    int s = six();  
    int f = four();  
  
}
```

# “HELLO MODULES!”

## Module file

```
export module MyModule;  
  
    int four() { return 4; }  
export int six() { return four() + 2; }
```

## Client code

```
import MyModule;  
int main() {  
    int s = six();  
    int f = four(); // <- Compile error:  
                    // no function named four().  
}
```

```
export module M;
```

```
int const export foo() noexcept { /* ... */ }
```



```
export module M;
```

```
int const export foo() noexcept { /* ... */ }
```

```
east-export.cpp:3:11:
```

```
    error: expected unqualified-id
```

```
int const export foo() { return 2; }
```

```
    ^
```

```
1 error generated.
```

## HOW IT SHOULD WORK?

- 6 When a *module-import-declaration* imports a translation unit  $T$ , it also imports all translation units imported by exported *module-import-declarations* in  $T$ ; such translation units are said to be *exported* by  $T$ . When a *module-import-declaration* in a module unit imports another module unit of the same module, it also imports all translation units imported by all *module-import-declarations* in that module unit. These rules may in turn lead to the importation of yet more translation units.

# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")


CMake

x.cpp


M.cpppm

y.cpp


# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")



# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")







# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")




# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")



# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")



# HOW IT SHOULD WORK? (VERSION 1, "PREVENTIVE")






# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")

CMake


x.cpp

y.cpp


# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")



# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")







# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")



# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")




# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")





# HOW IT SHOULD WORK? (VERSION 2, "ON-DEMAND")



# WHAT HAS MODULES EVER DONE FOR US?

- Token leak solved — PP shouldn't affect client
- Hiding true detail!
- Better explained interfaces

## What is in the library?

library.hpp

```
/* Precondition: a greater or equal to b! */  
int fun(int a, int b);
```

secret\_library\_code.cpp

```
int fun(int a, int b)  
{  
    if (a < b)  
        throw std::domain_error{  
            "first argument must be bigger!";  
        };  
    /* ... */  
}
```

What do the user (and tools) see?

```
library.hpp
```

```
/* Precondition: a greater or equal to b! */  
int fun(int a, int b);
```

```
secret_library_code.cpp
```

library.cppm

```
export int fun(int a, int b)  
    [[expects P: a >= b]];
```

library\_secret.cppm

# WHAT HAS MODULES EVER DONE FOR US?

- Token leak solved — PP shouldn't affect client
- Hiding true detail!
- Better explained interfaces

# WHAT HAS MODULES EVER DONE FOR US?

- Token leak solved — PP shouldn't affect client
- Hiding true detail!
- Better explained interfaces
- Fix some burden on developers: which header to use?!

# WHAT HAS MODULES EVER DONE FOR US?

- Token leak solved — PP shouldn't affect client
- Hiding true detail!
- Better explained interfaces
- Fix some burden on developers: which header to use?!

So all problems discussed before?



## SO THEN... WHAT MODULES **DOES NOT** SOLVE?

- Increase burden on build system
- Library vendors might need an extra step
- Some new ways to shoot yourself in the foot

# NEW WAYS TOO MESS IT UP

module.cppm

```
export module M;  
struct S  
{  
    S(int i)      : m(i) {}  
    S(const S&) = delete;  
    S(S&&)       = default;  
  
    int m;  
};  
export S make_s() { return S{0}; }
```

---

Source:

<https://vector-of-bool.github.io/2019/03/31/modules-2.html>

# NEW WAYS TOO MESS IT UP

```
module.cppm
```

```
export module M;  
struct S                                // Not exported!  
{                                       // But reachable.  
    S(int i)      : m(i) {}  
    S(const S&) = delete;  
    S(S&&)      = default;  
  
    int m;  
};  
export S make_s() { return S{0}; }
```

---

Source:

<https://vector-of-bool.github.io/2019/03/31/modules-2.html>

# NEW WAYS TOO MESS IT UP

module.cppm

```
export module M;  
/* not exported */ struct S { /* ... */ };  
export S make_s() { return S{0}; }
```

main.cpp

```
import M;  
int main() {  
    S s{1};  
  
}
```

---

Source:

<https://vector-of-bool.github.io/2019/03/31/modules-2.html>

# NEW WAYS TOO MESS IT UP

## module.cppm

```
export module M;  
/* not exported */ struct S { /* ... */ };  
export S make_s() { return S{0}; }
```

## main.cpp

```
import M;  
int main() {  
    S s{1};  
    //! ^ error: no type name 'S' in current scope.  
}
```

---

Source:

<https://vector-of-bool.github.io/2019/03/31/modules-2.html>

# NEW WAYS TOO MESS IT UP

module.cppm

```
export module M;  
/* not exported */ struct S { /* ... */ };  
    export      S make_s() { return S{0}; }
```

main.cpp

```
import M;  
int main() {  
    auto s = make_s();  
  
}
```

---

Source:

<https://vector-of-bool.github.io/2019/03/31/modules-2.html>

# NEW WAYS TOO MESS IT UP

## module.cppm

```
export module M;  
/* not exported */ struct S { /* ... */ };  
    export      S make_s() { return S{0}; }
```

## main.cpp

```
import M;  
int main() {  
    auto s = make_s();  
  
}
```

---

Source:

<https://vector-of-bool.github.io/2019/03/31/modules-2.html>

# NEW WAYS TOO MESS IT UP

## module.cppm

```
export module M;  
/* not exported */ struct S { /* ... */ };  
    export      S make_s() { return S{0}; }
```

## main.cpp

```
import M;  
int main() {  
    auto s = make_s();  
    s.m = 1;  
}
```

---

Source:

<https://vector-of-bool.github.io/2019/03/31/modules-2.html>



## SO THEN... WHAT MODULES **DOES NOT** SOLVE?

- Increase burden on build system
- Library vendors might need an extra step
- Some new ways to shoot yourself in the foot

## SO THEN... WHAT MODULES **DOES NOT** SOLVE?

- Increase burden on build system
- Library vendors might need an extra step
- Some new ways to shoot yourself in the foot
- Some new implementation-defined behaviour

## SO THEN... WHAT MODULES **DOES NOT** SOLVE?

- Increase burden on build system
- Library vendors might need an extra step
- Some new ways to shoot yourself in the foot
- Some new implementation-defined behaviour
- **Performance concerns!**

# PERFORMANCE ISSUES

main.cpp

```
import containers;
int main()
{
    std::vector V {1, 2, 3};
    return V.size() - 3;
}
```

```
$ objdump -t main.o | grep vector | grep size
```

```
0000000000000000 w      F .text._ZNKSt6vectorIiSaIiEE4sizeEv
// std::vector<int, std::allocator<int> >::size() const
```



Source: <https://migrainearts.deviantart.com/art/Long-Live-the-King-The-Lion-King-740054413>

# PREPROCESSOR $\longrightarrow$ ASTReader/ASTImporter

*Almost personal story...*

$\Sigma$  TU size for LLVM/Clang:  $\sim 65$  GiB

# PREPROCESSOR → ASTReader/ASTImporter

*Almost personal story...*

$\Sigma$  TU size for LLVM/Clang:  $\sim 65$  GiB

For Cross-TU analysis<sup>6</sup>:

- High disk I/O
- Often 40–50 TU loaded
- up to 10 GiB RAM usage **per thread**

---

<sup>6</sup>Horváth et al., “Implementation and Evaluation of Cross Translation Unit Symbolic Execution for C Family Languages”.

# PREPROCESSOR → ASTReader/ASTImporter

*Almost personal story...*

$\Sigma$  TU size for LLVM/Clang:  $\sim 65$  GiB

For Cross-TU analysis<sup>6</sup>:

- High disk I/O
- Often 40–50 TU loaded
- up to 10 GiB RAM usage **per thread**
- Arbitrary 8 TU cap, meaning *10-thread* analysis stays just under 30 GiB

---

<sup>6</sup>Horváth et al., “Implementation and Evaluation of Cross Translation Unit Symbolic Execution for C Family Languages”.



## SO THEN... WHAT MODULES **DOES NOT** SOLVE?

- Increase burden on build system
- Library vendors might need an extra step
- Some new ways to shoot yourself in the foot
- Some new implementation-defined behaviour
- **Performance concerns!**

## SO THEN... WHAT MODULES **DOES NOT** SOLVE?

- Increase burden on build system
- Library vendors might need an extra step
- Some new ways to shoot yourself in the foot
- Some new implementation-defined behaviour
- **Performance concerns!**

*But wait, there's more!...*

# THE BIG PROBLEM?

100 000 000 000

## THE BIG PROBLEM?

$$10^9 - 10^{11}$$

## THE BIG PROBLEM?

$$10^9 - 10^{11} \text{ LoC}$$

- 1 C++'s Compilation Model
  - Software technology issues
  - Performance drawbacks and possible solutions

- 2 C++ Modules
  - “How it should work?”
  - Traps and pitfalls (even) with Modules

- 3 The Wish for Automatic Modularisation
  - Formal overview
  - Case study — Apache Xerces
  - Evaluation of findings
  - Requirements for upgrading to Modules

- 4 Summary

# AUTOMATIC MODULARISATION: GOALS

## Goal

Break existing project up into modules.

# AUTOMATIC MODULARISATION: GOALS

## Goal

Break existing project up into modules.

## Input

- Initial mapping, usually from pure physical layout
- The source code, and conventional (“translation unit-based”) configuration metadata
- **The input contains no domain knowledge.**



# AUTOMATIC MODULARISATION: GOALS

## Goal

Break existing project up into modules.

## Input

- Initial mapping, usually from pure physical layout
- The source code, and conventional (“translation unit-based”) configuration metadata
- **The input contains no domain knowledge.**

## Output

Refined mapping which is sensible.

# AUTOMATIC MODULARISATION: GOALS

## Goal

Break existing project up into modules.

## Input

- Initial mapping, usually from pure physical layout
- The source code, and conventional (“translation unit-based”) configuration metadata
- **The input contains no domain knowledge.**

## Output

Refined mapping which is sensible compiles.

# AUTOMATIC MODULARISATION: OVERVIEW


1. Deep fact extraction from the source code

# AUTOMATIC MODULARISATION: OVERVIEW

1. Deep fact extraction from the source code
2. Build a dependency graph purpose-tailored


# AUTOMATIC MODULARISATION: OVERVIEW

1. Deep fact extraction from the source code
2. Build a dependency graph purpose-tailored
3. Cuts isolate acyclic *interface dependencies* — using commodity flow algorithms



# AUTOMATIC MODULARISATION: OVERVIEW


1. Deep fact extraction from the source code
2. Build a dependency graph purpose-tailored
3. Cuts isolate acyclic *interface dependencies* — using commodity flow algorithms



- #### 4. Move implementation to interface due to ownership

# AUTOMATIC MODULARISATION: OVERVIEW


1. Deep fact extraction from the source code
2. Build a dependency graph purpose-tailored
3. Cuts isolate acyclic *interface dependencies* — using commodity flow algorithms



4. Move implementation to interface due to ownership
5. Fix graph so modules compile without (re-)introducing cycles — using path search

# AUTOMATIC MODULARISATION: OVERVIEW

1. Deep fact extraction from the source code
2. Build a dependency graph purpose-tailored
3. Cuts isolate acyclic *interface dependencies* — using commodity flow algorithms



4. Move implementation to interface due to ownership
5. Fix graph so modules compile without (re-)introducing cycles — using path search

Result: modules  $\sim$  “*unity build*” for synthesised components.



## STEP 1 — FACT EXTRACTION

Using LLVM/Clang AST matchers, visitors.

Driver infrastructure and graph algorithms in Python.<sup>7</sup>

Find, emit, organise:

- `#includes`<sup>8</sup>
- usage dependencies (true symbol usage)

---

<sup>7</sup>[github.com/whisperity/buildtooling/tree/module-making](https://github.com/whisperity/buildtooling/tree/module-making)

<sup>8</sup>Eventually could turn this over to clang-scan-deps:  
[lists.llvm.org/pipermail/cfe-dev/2018-October/059831.html](https://lists.llvm.org/pipermail/cfe-dev/2018-October/059831.html)

## STEP 1 — FACT EXTRACTION

Using LLVM/Clang AST matchers, visitors.

Driver infrastructure and graph algorithms in Python.<sup>7</sup>

Find, emit, organise:

- `#includes`<sup>8</sup>
- usage dependencies (true symbol usage)
- “problematic” names, unification breakers<sup>9</sup>:
  - ▶ TU-internal names
  - ▶ (defined macros that bleed out)

---

<sup>7</sup>[github.com/whisperity/buildtooling/tree/module-making](https://github.com/whisperity/buildtooling/tree/module-making)

<sup>8</sup>Eventually could turn this over to clang-scan-deps:  
[lists.llvm.org/pipermail/cfe-dev/2018-October/059831.html](https://lists.llvm.org/pipermail/cfe-dev/2018-October/059831.html)

<sup>9</sup>Mihalicza, “How `#includes` Affect Build Time in Large Systems”.

## STEP 1 — FACT EXTRACTION

Using LLVM/Clang AST matchers, visitors.

Driver infrastructure and graph algorithms in Python.<sup>7</sup>

Find, emit, organise:

- `#includes`<sup>8</sup>
- usage dependencies (true symbol usage)
- “problematic” names, unification breakers<sup>9</sup>:
  - ▶ TU-internal names
  - ▶ (defined macros that bleed out)
- forward declarations
  - ▶ herald true usage
  - ▶ (might cause name collisions)

---

<sup>7</sup>[github.com/whisperity/buildtooling/tree/module-making](https://github.com/whisperity/buildtooling/tree/module-making)

<sup>8</sup>Eventually could turn this over to clang-scan-deps:

[lists.llvm.org/pipermail/cfe-dev/2018-October/059831.html](https://lists.llvm.org/pipermail/cfe-dev/2018-October/059831.html)

<sup>9</sup>Mihalicza, “How `#includes` Affect Build Time in Large Systems”.

# FORWARD DECLARATIONS

M1.cppm

```
export module M1;
```

```
class Fwd;
```

```
export void open(Fwd* fptr) { /* ... */ };
```

M2.cppm

```
export module M2;
```

```
export class Fwd { /* ... */ };
```

```
export void close(Fwd f) { /* ... */ }
```

# FORWARD DECLARATIONS

M1.cppm

```
export module M1;  
  
class Fwd;  
export void open(Fwd* fptr) { /* ... */ };
```

M2.cppm

```
export module M2;  
import M1;  
  
export class Fwd { /* ... */ };  
export void close(Fwd f) { /* ... */ }
```

# FORWARD DECLARATIONS

**M1  $\cup$  M2.cppm**

**export module** M;

**export class** Fwd { /\* ... \*/ };

**export void** open (Fwd\* fptr) { /\* ... \*/ };

**export void** close(Fwd f) { /\* ... \*/ };

# FORWARD DECLARATIONS

$M_1 \cup M_2$ .cppm

```
export module M;
```

```
export class Fwd { /* ... */ };
```

```
export void open (Fwd* fptr) { /* ... */ };
```

```
export void close(Fwd f) { /* ... */ };
```

How about **Module Partitions**?

# FORWARD DECLARATIONS

$M1 \cup M2$ .cppm

```
export module M;
```

```
export class Fwd { /* ... */ };
```

```
export void open (Fwd* fptr) { /* ... */ };
```

```
export void close(Fwd f) { /* ... */ };
```

How about **Module Partitions**?




- Partitions are “just” module-internal fluff
- Don't change the client's view




## STEP 2 — BUILD DEPENDENCY GRAPH



# STEP 3 — PERFORM CUTS ON CYCLES




## STEP 3 — PERFORM CUTS ON CYCLES



## STEP 3 — PERFORM CUTS ON CYCLES

```
Module__autogen_aa68844cecf -> XercesUtil -> Module__autogen_f02a9dad0 -> Module__autogen_aa68844cecf
```



## STEP 4 — MOVE IMPLEMENTATION TO INTERFACE

```
import MODULE_NAME_Module_07899b6_XMemory;  
/* ... */  
export module FULL_NAME_Module_e77754b;  
  
#include "xercesc/util/XMLUri.hpp"  
#include "xercesc/framework/XMLErrorCodes.hpp"  
#include "xercesc/xinclude/XIncludeUtils.hpp"  
#include "xercesc/util/TransService.hpp"  
  
#include "xercesc/util/TransService.cpp"  
#include "xercesc/util/XMLUri.cpp"  
#include "xercesc/xinclude/XIncludeUtils.cpp"
```

## STEP 4 — MOVE IMPLEMENTATION TO INTERFACE

```
import MODULE_NAME_Module_07899b6_XMemory;  
/* ... */  
export module FULL_NAME_Module_e77754b;  
  
#include "xercesc/util/XMLUri.hpp"  
#include "xercesc/framework/XMLErrorCodes.hpp"  
#include "xercesc/xinclude/XIncludeUtils.hpp"  
#include "xercesc/util/TransService.hpp"  
  
#include "xercesc/util/TransService.cpp"  
#include "xercesc/util/XMLUri.cpp"  
#include "xercesc/xinclude/XIncludeUtils.cpp"
```

What about *module partitions*?

## STEP 4 — MOVE IMPLEMENTATION TO INTERFACE

```
import MODULE_NAME_Module_07899b6_XMemory;  
/* ... */  
export module FULL_NAME_Module_e77754b;  
  
#include "xercesc/util/XMLUri.hpp"  
#include "xercesc/framework/XMLErrorCodes.hpp"  
#include "xercesc/xinclude/XIncludeUtils.hpp"  
#include "xercesc/util/TransService.hpp"  
  
#include "xercesc/util/TransService.cpp"  
#include "xercesc/util/XMLUri.cpp"  
#include "xercesc/xinclude/XIncludeUtils.cpp"
```

What about *module partitions*? 🤔

## STEP 5 — JOIN CYCLES

```
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor
import MODULE_NAME_Module_0ba0532_DOMErrorHandl
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesUtil;

#define MODULE_EXPORT
export module FULL_NAME_Module_e77754b;

#include "xercesc/util/XMLUri.hpp"
#include "xercesc/framework/XMLErrorCodes.hpp"
```

```
import MODULE_NAME_Module_05d3784;
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor
import MODULE_NAME_Module_0ba0532_DOMErrorHandl
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_2a7dc8f;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_408d3e9;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_Module_ff362e6_DOM;
import MODULE_NAME_XercesFramework;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesInternal;
import MODULE_NAME_XercesSAX;
import MODULE_NAME_XercesUtil;
```



## STEP 5 — JOIN CYCLES

```
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor
import MODULE_NAME_Module_0ba0532_DOMErrorHandl
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesUtil;

#define MODULE_EXPORT
export module FULL_NAME_Module_e7754b;

#include "xercesc/util/XMLUri.hpp"
#include "xercesc/framework/XMLErrorCodes.hpp"
```

```
import MODULE_NAME_Module_05d3784;
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor
import MODULE_NAME_Module_0ba0532_DOMErrorHandl
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_2a7dc8f;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_408d3e9;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_Module_ff362e6_DOM;
import MODULE_NAME_XercesFramework;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesInternal;
import MODULE_NAME_XercesSAX;
import MODULE_NAME_XercesUtil;
```

New dependencies → potential new cycles.

## STEP 5 — JOIN CYCLES

The diagram illustrates dependencies between two code snippets. The left snippet contains various module imports and a definition. The right snippet contains a series of module imports. Arrows point from the right snippet to the left snippet, indicating that the right snippet depends on the modules defined in the left snippet.

```
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor;
import MODULE_NAME_Module_0ba0532_DOMErrorHandl;
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesUtil;

#define MODULE_EXPORT
export module FULL_NAME_Module_e77754b;

#include "xercesc/util/XMLUri.hpp"
#include "xercesc/framework/XMLErrorCodes.hpp"
```

```
import MODULE_NAME_Module_05d3784;
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor;
import MODULE_NAME_Module_0ba0532_DOMErrorHandl;
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_2a7dc8f;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_408d3e9;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_Module_ff362e6_DOM;
import MODULE_NAME_XercesFramework;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesInternal;
import MODULE_NAME_XercesSAX;
import MODULE_NAME_XercesUtil;
```

New dependencies → potential new cycles.

■ Analyse the paths

## STEP 5 — JOIN CYCLES

The diagram illustrates the process of joining two modules. On the left, a code block contains several `import` statements for modules like `MODULE_NAME_Module_07899b6_XMemory`, `MODULE_NAME_Module_09e21a3_XMLErrorRepor`, `MODULE_NAME_Module_0ba0532_DOMErrorHandl`, `MODULE_NAME_Module_10a7b6a_DOMError`, `MODULE_NAME_Module_3581466`, `MODULE_NAME_Module_4960365`, `MODULE_NAME_Module_725bdc7_XMLString`, `MODULE_NAME_Module_91ca685_XMLBuffer`, `MODULE_NAME_Module_99060c0`, `MODULE_NAME_Module_d01cd88`, `MODULE_NAME_Module_d9f280c_DOMNode`, `MODULE_NAME_Module_e2c79c7_DOMDocument`, `MODULE_NAME_Module_fc50e1f_XMLException`, `MODULE_NAME_XercesFrameworkXML`, and `MODULE_NAME_XercesUtil`. It also defines `MODULE_EXPORT` and exports `FULL_NAME_Module_e77754b`. At the bottom, it includes `"xercesc/util/XMLUri.hpp"` and `"xercesc/framework/XMLErrorCodes.hpp"`. On the right, another code block contains `import` statements for `MODULE_NAME_Module_05d3784`, `MODULE_NAME_Module_07899b6_XMemory`, `MODULE_NAME_Module_09e21a3_XMLErrorRepor`, `MODULE_NAME_Module_0ba0532_DOMErrorHandl`, `MODULE_NAME_Module_10a7b6a_DOMError`, `MODULE_NAME_Module_2a7dc8f`, `MODULE_NAME_Module_3581466`, `MODULE_NAME_Module_408d3e9`, `MODULE_NAME_Module_4960365`, `MODULE_NAME_Module_725bdc7_XMLString`, `MODULE_NAME_Module_91ca685_XMLBuffer`, `MODULE_NAME_Module_99060c0`, `MODULE_NAME_Module_d01cd88`, `MODULE_NAME_Module_d9f280c_DOMNode`, `MODULE_NAME_Module_e2c79c7_DOMDocument`, `MODULE_NAME_Module_fc50e1f_XMLException`, `MODULE_NAME_Module_ff362e6_DOM`, `MODULE_NAME_XercesFramework`, `MODULE_NAME_XercesFrameworkXML`, `MODULE_NAME_XercesInternal`, `MODULE_NAME_XercesSAX`, and `MODULE_NAME_XercesUtil`. Green arrows connect the `import` statements in the right block to the corresponding `import` statements in the left block, indicating that the right block's dependencies are being resolved by the left block's imports.

```
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor;
import MODULE_NAME_Module_0ba0532_DOMErrorHandl;
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesUtil;

#define MODULE_EXPORT
export module FULL_NAME_Module_e77754b;

#include "xercesc/util/XMLUri.hpp"
#include "xercesc/framework/XMLErrorCodes.hpp"
```

```
import MODULE_NAME_Module_05d3784;
import MODULE_NAME_Module_07899b6_XMemory;
import MODULE_NAME_Module_09e21a3_XMLErrorRepor;
import MODULE_NAME_Module_0ba0532_DOMErrorHandl;
import MODULE_NAME_Module_10a7b6a_DOMError;
import MODULE_NAME_Module_2a7dc8f;
import MODULE_NAME_Module_3581466;
import MODULE_NAME_Module_408d3e9;
import MODULE_NAME_Module_4960365;
import MODULE_NAME_Module_725bdc7_XMLString;
import MODULE_NAME_Module_91ca685_XMLBuffer;
import MODULE_NAME_Module_99060c0;
import MODULE_NAME_Module_d01cd88;
import MODULE_NAME_Module_d9f280c_DOMNode;
import MODULE_NAME_Module_e2c79c7_DOMDocument;
import MODULE_NAME_Module_fc50e1f_XMLException;
import MODULE_NAME_Module_ff362e6_DOM;
import MODULE_NAME_XercesFramework;
import MODULE_NAME_XercesFrameworkXML;
import MODULE_NAME_XercesInternal;
import MODULE_NAME_XercesSAX;
import MODULE_NAME_XercesUtil;
```


New dependencies → potential new cycles.

- Analyse the paths
- Merge the cycle into a bigger module

# INITIAL INPUT

Test bed: Apache Xerces<sup>10</sup>.

~ 800 source files, roughly 40% : 60% (cpp : hpp) ratio.



<sup>10</sup><http://github.com/whisperity/xerces-c-modules>

- Headers implemented in multiple files, across initial modules

## BROKEN CODE?

- Headers implemented in multiple files, across initial modules
- Header used macro from config but didn't include config file

# BROKEN CODE?

- Headers implemented in multiple files, across initial modules
- Header used macro from config but didn't include config file
- Missing forward declaration in header using the symbol

# BROKEN CODE?

- Headers implemented in multiple files, across initial modules
- Header used macro from config but didn't include config file
- Missing forward declaration in header using the symbol
- Missing header guard



# THE PROGRESS...

14 initial “modules”.

## THE PROGRESS...

14 initial “modules”.

After step 3 *cycle-breaking*, 67 “modules”.

## THE PROGRESS...

14 initial “modules”.

After step 3 *cycle-breaking*, 67 “modules”.

Without handling forward declarations, after step 4:  
 $692 + 11 + 2 + 1 + 1 + 1 + 1 + 1 + 1$ .

# THE PROGRESS...

14 initial “modules”.

After step 3 *cycle-breaking*, 67 “modules”.

Without handling forward declarations, after step 4:  
 $692 + 11 + 2 + 1 + 1 + 1 + 1 + 1 + 1$ .

With handling...

## “END RESULT”

Step merging modules on fwddecl codedependencies:

```
Module_09e21a3_XMLErrorReporter,  
Module_0ba0532_DOMErrorHandler,  
Module_10a7b6a_DOMError,  
Module_1a62989_MemoryManager,  
Module_3b94cf2,  
Module_9544d86,  
Module_ba6ca70,  
Module_d9f280c_DOMNode.
```

- Final file # after forwards -

```
Module Module_23efd64: 710  
Module Module_55b5fc8_PSVIDefs: 1
```

## “END RESULT”

- Final file # after forwards -
  - Module Module\_23efd64: 710
  - Module Module\_55b5fc8\_PSVIDefs: 1

## “END RESULT”

```
- Final file # after forwards -  
  Module Module_23efd64: 710  
  Module Module_55b5fc8_PSVIDefs: 1
```

Original number of input files: 711.

## “END RESULT”

- Final file # after forwards -  
Module Module\_23efd64: 710  
Module Module\_55b5fc8\_PSVIDefs: 1

Original number of input files: 711.

1 *almost* true unity build + a lone **enum**.



# PSVIDefs

```
22  #if !defined(XERCESC_INCLUDE_GUARD_PSVIDEFS_HPP)
23  #define XERCESC_INCLUDE_GUARD_PSVIDEFS_HPP
24
25  #include <xercesc/util/XercesDefs.hpp> // CHANGE4AUTOMODULES: Missing include!
26
27  XERCES_CPP_NAMESPACE_BEGIN
28
29  class VALIDATORS_EXPORT PSVIDefs
30  {
31  public:
32      enum PSVIScope
33      {
34          SCP_ABSENT    // declared in group/attribute group
35          , SCP_GLOBAL  // global declaration or ref
36          , SCP_LOCAL   // local declaration
37      };
38  };
39
40  XERCES_CPP_NAMESPACE_END
41
42  #endif
```

# PERFORMANCE DIFFERENCE WITH *MODULES*

Conventional style: `-Ilib/xerces ...fix.cpp ...-lxerces`

```
#include <string>
#include <xerces/util/XMLString.hpp>

char* fix(const char* S)
{
    char* R = new char[std::strlen(S) * 2];
    XMLString::fixURI(S, R);
    return R;
}
```

# PERFORMANCE DIFFERENCE WITH *MODULES*

Conventional style: `-Ilib/xerces ...fix.cpp ...-lxerces`

```
#include <string>
#include <xerces/util/XMLString.hpp>

char* fix(const char* S)
{
    char* R = new char[std::strlen(S) * 2];
    XMLString::fixURI(S, R);
    return R;
}
```

```
import Xerces;

char* fix(const char* S)
{
    /* ... same as above ... */
}
```

- Theoretical time complexity:  $\mathcal{O}(\text{build time} + |\text{files}|^9)$ .
  - ▶ Empirical: for *Apache Xerces*, 4 min. build, 25 sec. algorithm execution.

- Theoretical time complexity:  $\mathcal{O}(\text{build time} + |\text{files}|^9)$ .
  - ▶ Empirical: for *Apache Xerces*, 4 min. build, 25 sec. algorithm execution.
- Modules made from existing code without touching it

- Theoretical time complexity:  $\mathcal{O}(\text{build time} + |\text{files}|^9)$ .
  - ▶ Empirical: for *Apache Xerces*, 4 min. build, 25 sec. algorithm execution.
- Modules made from existing code without touching it
- Not really feasible, it seems...

- Theoretical time complexity:  $\mathcal{O}(\text{build time} + |\text{files}|^9)$ .
  - ▶ Empirical: for *Apache Xerces*, 4 min. build, 25 sec. algorithm execution.
- Modules made from existing code without touching it
- Not really feasible, it seems...
- “TU semantics” approach  $\rightarrow$  coupling seems to break it
  - ▶ Collapse to **very few** modules per binary – almost *unity build*

- Theoretical time complexity:  $\mathcal{O}(\text{build time} + |\text{files}|^9)$ .
  - ▶ Empirical: for *Apache Xerces*, 4 min. build, 25 sec. algorithm execution.
- Modules made from existing code without touching it
- Not really feasible, it seems...
- “TU semantics” approach  $\rightarrow$  coupling seems to break it
  - ▶ Collapse to **very few** modules per binary – almost *unity build*
  - ▶ ...or cross-binary modules



# REQUIREMENTS FOR “TRUE MODULARISATION”

*“The only solution here we can think of is actually to make people split up libraries.” (Manuel Klimek<sup>11</sup>)*

---

<sup>11</sup>CppCon 2016 talk, [youtube.com/watch?v=dHFNpBfemDI&t=38m48s](https://www.youtube.com/watch?v=dHFNpBfemDI&t=38m48s)

# REQUIREMENTS FOR “TRUE MODULARISATION”


*“The only solution here we can think of is actually to make people split up libraries.” (Manuel Klimek<sup>11</sup>)*

 *What if the results ARE right?...*

---

<sup>11</sup>CppCon 2016 talk, [youtube.com/watch?v=dHFNpBfemDI&t=38m48s](https://www.youtube.com/watch?v=dHFNpBfemDI&t=38m48s)





## REQUIREMENTS FOR UPGRADING TO MODULES

In any case if upgrading to modules happens:

# REQUIREMENTS FOR UPGRADING TO MODULES

In any case if upgrading to modules happens:

- Either libs/modules end up staying same “size”/composition
  - Cue performance concerns...

# REQUIREMENTS FOR UPGRADING TO MODULES

In any case if upgrading to modules happens:

- Either libs/modules end up staying same “size”/composition
  - Cue performance concerns...
- Or we'll have to break API...

# REQUIREMENTS FOR UPGRADING TO MODULES

In any case if upgrading to modules happens:

- Either libs/modules end up staying same “size”/composition
  - Cue performance concerns...
- Or we'll have to break API...
- ...and put in actual work





- 1 C++'s Compilation Model
  - Software technology issues
  - Performance drawbacks and possible solutions

- 2 C++ Modules
  - “How it should work?”
  - Traps and pitfalls (even) with Modules





- 3 The Wish for Automatic Modularisation
  - Formal overview
  - Case study — Apache Xerces
  - Evaluation of findings
  - Requirements for upgrading to Modules

- 4 Summary

## REFERENCES I


-  Gábor Horváth et al. “Implementation and Evaluation of Cross Translation Unit Symbolic Execution for C Family Languages”. In: *Proceedings of the 40th International Conference on Software Engineering: Companion Proceedings*. ICSE '18. Gothenburg, Sweden: ACM, May 2018, pp. 428–428. ISBN: 978-1-4503-5663-3. DOI: 10.1145/3183440.3195041.
-  Tara Krishnaswamy. “Automatic Precompiled Headers: Speeding up C++ Application Build Times”. In: *Proceedings of the First Workshop on Industrial Experiences with Systems Software, WIESS 2000, October 22, 2000, San Diego, CA, USA*. Ed. by Dejan S. Milojevic. USENIX, Jan. 2000, pp. 57–66. ISBN: 1-880446-15-4.

## REFERENCES II

-  Gábor Márton and Zoltán Porkoláb. “Unit Testing in C++ with Compiler Instrumentation and friends”. In: *Acta Cybernetica* 23.2 (Jan. 2017), pp. 659–686. DOI: 10.14232/actacyb.23.2.2017.14.
-  József Mihalicza. “How #includes Affect Build Time in Large Systems”. In: *Proceedings of the 8th International Conference on Applied Informatics (ICAI)*. Ed. by Attila Egri-Nagy et al. Vol. 2. 8. Eszterházy Károly College. BVB Nyomda és Kiadó Kft., Eger, Hungary, Jan. 2010, pp. 343–350. ISBN: 978-963-9894-72-3.
-  Richard Smith. P1103R3: *Merging Modules*. Tech. rep. 3. JTC1/SC22/WG21 - Papers Mailing List, Feb. 2019.
-  Zachary Turner. *Host is now dependency free*. `lldb-dev` mailing list. (accessed 20 Mar. 2019). Mar. 2019.


## CONCLUSION

## ■ Modules – Good? Bad?




## CONCLUSION

- Automatic modularisation findings could be useful – for metrics?



## CONCLUSION

- **Modules – Good? Bad?**
- **Automatic modularisation findings could be useful – for metrics?**
- **“Real” modularisation *is* effort from everyone involved.**




# CONCLUSION

## ■ Modules – Good? Bad?

## ■ Automatic modularisation findings could be useful – for metrics?

## ■ “Real” modularisation **is** effort from everyone involved.

## ■ Maybe don't expect *The True* solution soon?



# CONCLUSION

## ■ Modules – Good? Bad?

## ■ Automatic modularisation findings could be useful – for metrics?

## ■ “Real” modularisation is effort from everyone involved.

## ■ Maybe don't expect *The True* solution soon?

Side note: *LLDB* started breaking up some parts of their project<sup>12</sup> parallel to this research.

<sup>12</sup>Turner, *Host is now dependency free*.



# CONCLUSION

## ■ Modules – Good? Bad?

## ■ Automatic modularisation findings could be useful – for metrics?

## ■ “Real” modularisation is effort from everyone involved.

## ■ Maybe don't expect *The True* solution soon?

Side note: *LLDB* started breaking up some parts of their project<sup>12</sup> parallel to this research.

See you in the pure module world in 10...20...30 years?

<sup>12</sup>Turner, *Host is now dependency free*.