

Presentation patterns for web applications with Play! Framework

Alberto García García
< *agg180@alu.ua.es* >



May 13, 2014

TABLE OF CONTENTS

INTRODUCTION

PLAY! FRAMEWORK

PATTERNS IN PLAY!

CONCLUSIONS

INTRODUCTION

OUTLINE

INTRODUCTION

- Trends

- Challenges

- Addressing the challenges

TRENDS

- ▶ Enterprises's needs lead the market.
- ▶ Offering services: SOA wins.
- ▶ The web changes the status quo.
- ▶ SOA is not web compliant.
- ▶ Exposing services through the web requires extra effort.
- ▶ The game changes: new possibilities and challenges.

CHALLENGES

- ▶ Real time data has to be pushed.
- ▶ Huge amounts of data.
- ▶ Need for scalability and integration.
- ▶ Easy integration and accessibility.
- ▶ Interoperability.

ADDRESSING THE CHALLENGES

- ▶ Embrace the internet.
 - ▶ HTTP Protocol
 - ▶ HTML5
 - ▶ XML/JSON
 - ▶ Javascript
 - ▶ CSS
- ▶ Paradigm shift: client-side.
- ▶ Simplicity.
- ▶ A framework to rule them all.
- ▶ **Patterns for enterprise applications.**

PLAY! FRAMEWORK

OUTLINE

PLAY! FRAMEWORK

What is Play! Framework?

RESTful Architecture

Project layout

WHAT IS PLAY! FRAMEWORK?

- ▶ A web framework focused on:
 - ▶ Simplicity.
 - ▶ Productivity.
 - ▶ Scalability.
 - ▶ Designed for the modern web.
 - ▶ Concentrate on server-side.
 - ▶ Delegate AMAP to the client.
 - ▶ Embrace internet standards.
 - ▶ Java and Scala.
 - ▶ RESTful architecture web applications.
 - ▶ Model-View-Controller.

RESTFUL ARCHITECTURE

- ▶ Implemented using HTTP and REST principles.
- ▶ Representational state transfer (REST) principles:
 - ▶ Uniform interface.
 - ▶ Stateless.
 - ▶ Caching.
 - ▶ Layers.
 - ▶ Code on demand.
- ▶ Goals:
 - ▶ Performance.
 - ▶ Scalability.
 - ▶ Portability.
 - ▶ Reliability.
 - ▶ SIMPLICITY.

PROJECT LAYOUT

app	→ Application sources
└ assets	→ Compiled asset sources
└ stylesheets	→ Typically LESS CSS sources
└ javascripts	→ Typically CoffeeScript sources
└ controllers	→ Application controllers
└ models	→ Application business layer
└ views	→ Templates
build.sbt	→ Application build script
conf	→ Configurations files and other non-compiled resources
└ application.conf	→ Main configuration file
└ routes	→ Routes definition
public	→ Public assets
└ stylesheets	→ CSS files
└ javascripts	→ Javascript files
└ images	→ Image files
project	→ sbt configuration files
└ build.properties	→ Marker for sbt project
└ plugins.sbt	→ sbt plugins including the declaration for Play its dependencies
lib	→ Unmanaged libraries dependencies
logs	→ Standard logs folder
└ application.log	→ Default log file
target	→ Generated stuff
└ scala-2.10.0	
└ cache	
└ classes	→ Compiled class files
└ classes_managed	→ Managed class files (templates, ...)
└ resource_managed	→ Managed resources (less, ...)
└ src_managed	→ Generated sources (templates, ...)
test	→ source folder for unit or functional tests

PATTERNS IN PLAY!

OUTLINE

PATTERNS IN PLAY!

Model-View-Controller

The MVC application model: Models

Request/Response path

Model

Object Relational Mapping

View

Template View

Composite View

Controller

Front Controller

THE MVC APPLICATION MODEL

- ▶ Models in app/models
 - ▶ Java/Scala classes.
 - ▶ Data + Operations, mainly object-oriented.
 - ▶ Business logic and storage.

A MODEL EXAMPLE (MODELS/USER.JAVA)

```
1 package models;
3 @Entity
4 public class User extends Model {
5     @Id
6     public String name;
7     @Required
8     public String pass;
9
10    public User (String name, String pass) {
11        this.name = name;
12        this.pass = pass;
13    }
14
15    public static Finder<String, User> find = new Finder<String,
16        User>(String.class, User.class);
17
18    public static List<User> all() {
19        return find.all();
20    }
21 }
```


THE MVC APPLICATION MODEL: VIEWS

- ▶ Views in app/views
 - ▶ HTML/XML/JSON/Scala templates.
 - ▶ Directives as placeholders for data.
 - ▶ Render models to user interfaces.

A VIEW EXAMPLE (VIEWS/INDEX.SCALA.HTML)

```
1  @(title : String , users : List[User])
2
3  <!DOCTYPE html>
4
5  <html>
6      <head>
7          <title>Play! Hello world</title>
8      </head>
9      <body>
10         <header>
11             <h1>@title</h1>
12         </header>
13
14         <section>
15             <ul>
16                 @for(u <- users) {
17                     <li>@u.name</li>
18                 }
19             </ul>
20         </section>
21     </body>
22 </html>
```

THE MVC APPLICATION MODEL: CONTROLLERS


- ▶ Controllers in app/controllers
 - ▶ Java/Scala classes.
 - ▶ Methods as actions, mainly procedural.
 - ▶ Receive requests, act (update models + render views) and response.

A CONTROLLER EXAMPLE

(CONTROLLERS/APPLICATION.JAVA)

```
1 package controllers;
2
3 import models.User;
4 import play.*;
5 import play.data.*;
6 import play.mvc.*;
7 import views.html.*;
8
9 public class Application extends Controller
10 {
11     public static Result index()
12     {
13         return ok("Hello , world!", index.render(User.all()));
14     }
15 }
```

REQUEST/RESPONSE FLOW



THE HTTP REQUEST AND THE ROUTER (EXAMPLE)

- ▶ Suppose that we receive the HTTP Request: **GET /**
- ▶ The server processes it, looks for the proper action to response the GET / request in **conf/routes**.
- ▶ The called action is: **Application.index()**

```
1 # Routes
  # All application routes (Higher priority routes first)
3 # ----
  # Home page
5 GET      /          controllers.Application.index()

7 # Login
  GET      /login     controllers.Application.login()
9 POST     /login     controllers.Application.authenticate()

11 #Logout
  GET      /logout    controllers.Application.logout()
```

A CONTROLLER EXAMPLE

(CONTROLLERS/APPLICATION.JAVA)

```
1 package controllers;  
  
3 import models.User;  
import play.*;  
5 import play.data.*;  
import play.mvc.*;  
7 import views.html.*;  
  
9 public class Application extends Controller  
{  
11     public static Result index()  
    {  
13         return ok("Hello , world!", index.render(User.all()));  
    }  
15 }
```

A MODEL EXAMPLE (MODELS/USER.JAVA)

```
1 package models;
3 @Entity
4 public class User extends Model {
5     @Id
6     public String name;
7     @Required
8     public String pass;
9
10    public User (String name, String pass) {
11        this.name = name;
12        this.pass = pass;
13    }
14
15    public static Finder<String, User> find = new Finder<String,
16        User>(String.class, User.class);
17
18    public static List<User> all() {
19        return find.all();
20    }
21 }
```


A VIEW EXAMPLE (VIEWS/INDEX.SCALA.HTML)

```
1  @(title : String , users : List[User])
2
3  <!DOCTYPE html>
4
5  <html>
6      <head>
7          <title>Play! Hello world</title>
8      </head>
9      <body>
10         <header>
11             <h1>@title</h1>
12         </header>
13
14         <section>
15             <ul>
16                 @for(u <- users) {
17                     <li>@u.name</li>
18                 }
19             </ul>
20         </section>
21     </body>
22 </html>
```

THE END RESULT

Hello World!


- Kim Jong-Un
- Putin
- Obama

OBJECT RELATIONAL MAPPING

► a

TEMPLATE VIEW


- *"Renders information into HTML by embedding markers in an HTML page"[Fow02]*



- Pros: Lot of power and flexibility in presentation.
- Cons: Messy code, difficult to maintain, need helpers.

TEMPLATE VIEW


- ▶ *The template with annotations is compiled to a Scala.class with a render() method with the template parameters.*



- ▶ The controller calls the render method of the view.
- ▶ The view communicates with the model (parameter).

COMPOSITE VIEW

- ▶ *A view is built from other views that combine into a composite whole, managing the content and the layout independently.*



- ▶ Pros: Modularity, reuse.
- ▶ Cons: Performance, maintainability.

COMPOSITE VIEW

- ▶ *A sample simple view: simpleview.scala.html*

```
1  @(someModel: Model)
2
3  @compositeView(someModel) {
4    <header>
5      <hgroup>
6        <h1>Model data</h1>
7        <h2>@someModel.doSomething()</h2>
8      </hgroup>
9    </header>
10 }
```


COMPOSITE VIEW

- ▶ *A composite view: `compositeView.scala.html`*

```
1  @(someModel: Model)(simpleView: Html)
2  <html>
3      <head>
4          <title>Composite View Example</title>
5      </head>
6      <body>
7          @simpleView
8
9          <section id="main">
10             @someModel.showSomething()
11          </section>
12      </body>
13  </html>
```


FRONT CONTROLLER PATTERN


- *"Consolidates all request handling by channeling requests through a single handler object" [Fow02]*



- Pros: Centralized control, Thread safety, Configurability.
- Cons: Possible performance issues, Maintenance costs.

FRONT CONTROLLER IN PLAY!

- ▶ The router (handler) selects a controller (command) and a particular action (execute) depending on the HTTP request.



- ▶ `Routes.conf` file determines the location-action relationship.
- ▶ Actions return a result that holds the HTTP Response.





CONCLUSIONS

OUTLINE

CONCLUSIONS

► a

REFERENCES

-  Martin Fowler, *Patterns of enterprise application architecture*, Addison-Wesley Professional, 2002.
-  Nicolas Leroux and Sietse de Kaper, *Play for java*, Manning Publications, 2014.
-  Erik Bakker Peter Hilton and Francisco Canedo, *Play for scala*, Manning Publications, 2014.
-  Alexander Reelsen, *Play framework cookbook*, Packtpub Publications, 2014.