

CS 240: Programming in C

Final Exam

Spring 2025

Practice Final Exam

Version I

Name:

Username:

Read all instructions before beginning the exam.

- This exam is intended to be equally or more difficult than the past official final exam provided.
- You are encouraged to post on Ed Discussion, without hesitation, any sort of question you may have about this practice exam.
- This is a closed book examination. No material other than those provided for you are allowed.
- You need only a pencil and eraser for this examination. If you use ink, use either black or blue ink. If you use pencil, your writing must be dark and clearly visible.
- This examination contains an amount of material that a well-prepared student should be able to complete in less than one hour.
- This examination is worth a total of 150 points. Not all questions are worth the same amount. Plan your time accordingly.
- Write legibly. You should try to adhere to the course code standard when writing your solution(s). Egregious violations may result in point deductions.
- Read each question carefully and only do what is specifically asked for in that problem.
- Assume appropriate includes have been added to the code segments shown in the problems.
- Circle your answer in true or false questions. On this exam problem 18 is false.
- Some problems require several steps. Show all your work. Partial credit can only be rewarded to work shown.
- Write your username on EVERY page where indicated. Any page without a username will receive a zero for the material on that page.

Signature:

Do not open the examination booklet until instructed.

--	--	--	--	--	--	--	--

1. (1 point) True or False: The `-S` GCC flag will generate an executable.
2. (2 points) Write a single valid GCC command to compile the C file named `purdue.c`, that includes `up.h`, with warnings as errors adhering to the C17 standard. The executable should be named `boilermaker`. Multiple valid answers.

--

3. (2 points) Which of the following correctly represents the stages of the compilation process using GCC, in order?
 - A. Preprocessing → Linking → Compilation → Object file creation
 - B. Compilation → Object file creation → Linking → Preprocessing
 - C. Preprocessing → Compilation → Object file creation → Linking
 - D. Object file creation → Preprocessing → Linking → Compilation
4. (2 points) Write the conversion specifier to read a string composed of capital letters between T to L and digits from 0 to 9.

--

5. (1 point) True or False: `fclose()` will not produce a segmentation violation if a `NULL` pointer is passed in as an argument.
6. (3 points) The following is the creation and allocation of a simple single linked list node with an integer value. Assuming successful memory allocation, would the code produce an error? If yes then state why this is the case, if no then state the output.

```
struct node *new = calloc(1, sizeof(struct node));  
assert(new);  
new->value = 240;  
printf("%d\n", new->next);
```

--

7. (1 point) True or False: The number of characters `printf("%s", str)` will print depends on the size of the array of characters (string), and the NUL terminator contained by it.
8. (2 points) What is the value displayed by the `printf()` statement on a 64-bit system?

```
void read(char name[32]) {  
    printf("sizeof = %lu\n", sizeof(name));  
}
```

--

9. (3 points) Provide the `fscanf()` statement to read the name, **Linus Torvalds**, and the number, **1991**, from the following file input, ignore everything else. The file pointer is named `fp`, and the variables to store the inputs are called `name` (string with a buffer size of 100), and `num` (integer).

(Linus Torvalds)+(Linux:1991)

--

10. (3 points) Implement a header guard for a header file using the macro identifier `UP_H`. Make sure to implement the preprocessor directives in order of appearance.

--

--	--	--	--	--	--	--	--

11. (4 points) The following code segment has a signal handler that, when receiving a signal triggered by pressing **CTRL-C**, will cause the infinite while loop to end, terminating the program. However, when compiled at an unknown optimization level, pressing **CTRL-C** does not cause program termination as expected. Briefly explain what is causing the problem and propose a rewrite of a single existing non-blank line to fix the issue.

```
1. unsigned char stop = 0;
2.
3. void signal_handler(int x) {
4.     stop = 1;
5. }
6.
7. int main(void) {
8.     signal(SIGINT, signal_handler);
9.
10.    /* Pressing Ctrl-C invokes signal_handler() */
11.
12.    while (!stop);
13. }
```

--	--	--	--	--	--	--	--

12. (1 point) True or False: `clearerr()` clears the end-of-file and error indicators for the stream pointed to by a file pointer.
13. (2 points) Which of the following can be used to create functionally equivalent behavior to `scanf()` when reading from `stdin`?
- A. `fwrite()`
 - B. `sscanf()`
 - C. `fprintf()`
 - D. `fscanf()`
14. (3 points) Given a structure with fields in this order: a structure pointer, a character pointer, and a long. What would be the size of the structure on a 32-bit system?

--

15. (3 points) Given a union with fields in this order: an integer, a structure pointer, and a character. What would be the size of the union on a 64-bit system?

--

16. (1 point) True or False: The heap grows upwards, from lower to higher memory addresses.
17. (2 points) Use `typedef` to define a new type `node_t` as an alias for an existing structure `struct node`.

--

18. (1 point) True or False: In a pipelined food production process at McDonald's, it is essential to package fries before any other menu items to optimize throughput.

19. (3 points) What is the output of the following program? State the value displayed by `printf()`, undefined behavior, or error produced.

```
#define MOD(x) (-x)

int main() {
    int num = 10;
    printf("%d\n", MOD(num++));
}
```

--

20. (3 points) Which of the following variables have their corresponding values stored in the stack?

```
struct node {
    int val;
    struct node *next;
};

int a = 10;

int main() {
    struct node *b = malloc(sizeof(struct node));
    static int c = 20;
    int *d = calloc(80, sizeof(int));
    char *e = "Bill Joy";
}
```

--

21. (3 points) What is the output of the following program? State the values displayed by `printf()`, undefined behavior, or error produced.

```
int x = 4;

void modifier() {
    int x = 1;
    x += 5;
    {
        extern int x;
        x *= 2;
    }
    printf("%d ", x);
}

int main() {
    modifier();
    printf("%d\n", x);
}
```

--

22. (2 points) What is the GDB command to resume the execution of the program until the next breakpoint or error?

--

--	--	--	--	--	--	--	--

23. (3 points) For the following code segment, what is the value displayed by the `printf()` statement on a little-endian 64-bit system.

```
int main() {
    union data {
        unsigned long number;
        unsigned short bytes[4];
    } unit;

    unit.number = 0xA1B2C3D4E5F6A7B8;
    printf("%x %x\n", unit.bytes[1], unit.bytes[3]);
}
```

--

24. (4 points) Write a single declaration of an enum, `essentials`, with the members, `NONE`, `OWL`, `WAND`, `BROOM`, and `LETTER`, in order, such that `NONE` has a value of 0 and each subsequent member must occupy a distinct increasing power-of-two value starting from the least significant bit.

--

--	--	--	--	--	--	--	--

25. (3 points) The following two code segments depict different implementations of a function. State which implementation is faster, and briefly explain why that is the case.

```
int first(int n) {
    if (n <= 1) {
        return 1;
    }
    return n * first(n - 1);
}

int second(int n) {
    int result = 1;
    for (int i = 1; i <= n; i++) {
        result *= i;
    }
    return result;
}
```

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

26. (4 points) Create a function `convert_endian()`, that takes in as an argument and returns an **unsigned long**. Reverse the endianness of the argument and return it. Implement the function using casts. No credit will be given for other approaches.

27. (2 points) Briefly explain what the **unsigned** keyword does.

28. (1 point) True or False: You can assign a pointer to an array of the same type.
29. (2 points) Given the following code segment, what is the value displayed by the `printf()` statement.

```
int array[] = { 2, 1, 6, 2, -3, 0 };  
int *p = &array[2];  
printf("%d\n", (p -= array[1] - array[3])[* (p - 2)]);
```

30. (2 points) Based on the code segment in problem 29, what would the following `printf()` statement output in a 64-bit system.

```
printf("%lu %lu\n", sizeof(&array), sizeof(array));
```

--

31. (1 point) True or False: `fwrite()` does not require the memory addresses of written variables.
32. (2 points) Write the function prototype of a function `func` that takes in two characters, and returns a pointer to a function that returns a void pointer and that takes no arguments.

--

33. (2 points) Dynamically allocate a 2D array of integers, `array`, with 100 rows and 400 columns and initialize it to zero, in a single line.

--

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

34. (6 points) Define a recursive function `tree_height()`, which takes in a single parameter—a pointer to the root of a preexisting binary tree. The tree is made up of structures of type `tree_t`, with a `left` and `right` pointer to a node. This function returns the height of the tree (integer). A root node by itself has a height of 0.

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

For problems 35 and 36, assume that you have a doubly-linked list node structure of type **struct node** containing a single integer value, **val**, a **next** pointer, and a **prev** pointer.

35. (4 points) Write a function **remove_tail()** that takes the *address* of a pointer to the head of a doubly-linked list and returns **void**. Remove and deallocate the tail of the list, updating the relevant pointer(s). Assert that the argument is not **NULL**, and that the list is not empty.

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

36. (4 points) Write a function `rewind_head()` that takes the *address* of a pointer to a node in the middle of a linked list. Make the argument point to the head of the list. This function returns `void`. Implement the solution *recursively*. Assume the list is not empty, and the argument is valid.

37. (2 points) Rewrite the second line in this code segment for it to produce a result without integer truncation.

```
int n = 10;  
double result = n / 3;
```

38. (2 points) What statement about C macros is false?
- A. Macros are replaced by their values during the preprocessing stage.
 - B. Macros can take arguments, similar to functions.
 - C. Macros are type-checked by the compiler.
 - D. Macros can span multiple lines using the ‘/’ character.
39. (1 point) True or False: The `srandom()` function is used to seed the random number generator, and the `random()` function generates pseudo-random numbers based on that seed.
40. (2 points) Define a variable named `my_var` that is a pointer to an integer whose pointer cannot be modified.

41. (5 points) Write a function named `toggle_bit()` that takes two arguments—an unsigned long and an integer—and returns the result of flipping (toggling) the bit in the first argument at the position specified by the second argument. The function must use bitwise operations to achieve this. No credit will be given for other approaches.

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

Continuation of problem 41

--

42. (1 point) True or False: The `strcmp()` function stops comparing two strings when it encounters the NUL terminator in either of the strings.

--	--	--	--	--	--	--	--

43. (3 points) What is the output of the following program? State the values displayed by `printf()`, undefined behavior, or error produced.

```
int main() {  
    if (printf("A") || printf("B")) {  
        printf("C");  
    }  
    printf("\n");  
}
```

--

44. (3 points) Write a function, `my_realloc()`, that when used in the following example, will reallocate memory to the specified new size by the second argument and have `ptr` point to the new region. Set the pointer to `NULL` if reallocation fails.

```
int *ptr = malloc(10 * sizeof(int));  
my_realloc(&ptr, 20 * sizeof(int));
```

--

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

45. (1 point) True or False: A void pointer can be directly dereferenced without typecasting.
46. (2 points) Briefly explain a disadvantage of using global variables.

--

47. (3 points) State the GCC command to compile `lookup.c` into `lookup.o` to be used later for building a shared library without linker errors.

--

48. (3 points) In the parent directory (not in the library search path) there are two files, `lookup.a`, and `scanner.so`. State the GCC command to compile and link the C file in the current directory, `restric.c`, against the libraries, creating an executable named `section`.

--

49. (3 points) Write a macro named **ABS** that takes one argument and returns the absolute value of the argument.

50. (2 points) Which of the following optimizations is not typically included with the `-O3` flag?

- A. Aggressive function inlining.
- B. Vectorization of loops.
- C. Full debugging information generation.
- D. Code motion to reduce runtime overhead.

51. (3 points) Given the following function and its corresponding stack dump, which line numbers contain the return address and integer `i`?

```
void dump(int x, int y) {
    int i = 0x11223344;
    long l = 0xbeefbeefdecafbad;
}
```

1.	0x7fffffffef3b0:	01	00	00	00	00	00	00
2.	0x7fffffffef3a8:	43	11	40	00	00	00	00
3.	0x7fffffffef3a0:	b0	e3	ff	ff	ff	7f	00
4.	0x7fffffffef398:	ad	fb	ca	de	ef	be	ef
5.	0x7fffffffef390:	00	00	00	00	44	33	22
6.	0x7fffffffef388:	2c	11	40	00	00	00	00

52. (2 points) What does ASLR stand for?

--

53. (2 points) Which of the following statements about system calls is true?


- A. System calls allow a program to directly interact with the CPU registers.
- B. System calls are executed entirely in user space without involving the kernel.
- C. System calls provide an interface for programs to request services from the operating system.
- D. System calls are only available in assembly language and cannot be used in high-level languages.

54. (3 points) In hardware that supports double-buffering, state the prototype of the SDL function that swaps video buffers before the next video blit or lock returns and after a vertical retrace occurs.

--

- | | | | | | | | | | |
|----------|--------------------|----|----|----|----|----|----|----|----|
| (Before) | 0x7ffffffffffe3a4: | 50 | 6f | 65 | 00 | 00 | 45 | a5 | 3f |
| | 0x7ffffffffffe3ac: | d4 | ad | fd | b8 | 01 | 00 | 00 | 00 |
| | 0x7ffffffffffe3b4: | 00 | 00 | 00 | 00 | 90 | dd | d8 | f7 |
| | 0x7ffffffffffe3bc: | ff | 7f | 00 | 00 | 00 | 00 | 00 | 00 |
| (After) | 0x7ffffffffffe3a4: | 50 | 6f | 65 | 20 | 50 | 6f | 73 | 74 |
| | 0x7ffffffffffe3ac: | 20 | 6f | 6e | 20 | 45 | 64 | 20 | 66 |
| | 0x7ffffffffffe3b4: | 6f | 72 | 20 | 72 | 65 | 77 | 61 | 72 |
| | 0x7ffffffffffe3bc: | 64 | 20 | 3b | 29 | 00 | 00 | 00 | 00 |

[illegible]

- 

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

58. (6 points) Write a Makefile that compiles and links `magic.c` and `casting.c` into a static library named `conv`. Use implicit rules to create the object files.

Username:

--	--	--	--	--	--	--	--

Final (Practice)
Spring 2025

CS 240

59. (2 points) Briefly describe what `socket()` does.

60. (2 points) What is the primary purpose of the function `SDL_LoadBMP()`?

- A. To initialize the SDL library for image handling.
- B. To load a BMP image file into an `SDL_Surface`.
- C. To save an `SDL_Surface` as a BMP file on disk.
- D. To apply a color filter to a surface.

61. (1 point) True or False: `sscanf` NUL terminates strings.

62. (1 point) We hope you enjoyed CS 240. Good luck in the final!

```
      ~~~~  ____  |~~~~~|
    Y_ ___|[]|   | Boiler Up! |
    { |_|_|PU|_|_|_|_|_|_|_|_|
  //oo---00=00    000    000
```