

Table Details: transactions

- Schema
- Details
- Preview

| | | | | |
|-----------------------------|-----------|----------|---|--|
| hash | STRING | REQUIRED | ▼ | Hash of the transaction |
| nonce | INTEGER | REQUIRED | ▼ | The number of transactions made by the sender prior to this one |
| transaction_index | INTEGER | REQUIRED | ▼ | Integer of the transactions index position in the block |
| from_address | STRING | REQUIRED | ▼ | Address of the sender |
| to_address | STRING | NULLABLE | | Address of the receiver. null when its a contract creation transaction |
| value | NUMERIC | NULLABLE | | Value transferred in Wei |
| gas | INTEGER | NULLABLE | | Gas provided by the sender |
| gas_price | INTEGER | NULLABLE | | Gas price provided by the sender in Wei |
| input | STRING | NULLABLE | | The data sent along with the transaction |
| receipt_cumulative_gas_used | INTEGER | NULLABLE | | The total amount of gas used when this transaction was executed in the block |
| receipt_gas_used | INTEGER | NULLABLE | | The amount of gas used by this specific transaction alone |
| receipt_contract_address | STRING | NULLABLE | | The contract address created, if the transaction was a contract creation, otherwise null |
| receipt_root | STRING | NULLABLE | | 32 bytes of post-transaction stateroot (pre Byzantium) |
| receipt_status | INTEGER | NULLABLE | | Either 1 (success) or 0 (failure) (post Byzantium) |
| block_timestamp | TIMESTAMP | REQUIRED | ▼ | Timestamp of the block where this transaction was in |
| block_number | INTEGER | REQUIRED | ▼ | Block number where this transaction was in |
| block_hash | STRING | REQUIRED | ▼ | Hash of the block where this transaction was in |