

labeled_point = ident , ":";	labeled_point(ident_terminal) = ident , ":";
goto_label = "GOTO" , ident;	goto_label("GOTO") = "GOTO" , ident;
program_name = ident;	program_name(ident_terminal) = ident;
value_type = "INTEGER16";	value_type("INTEGER16") = "INTEGER16";
	array_specify("[") = "[", unsigned_value_terminal , "]" ;
declaration_element = ident , ["[" , unsigned_value , "]"] ;	declaration_element(ident_terminal) = ident , array_specify_optional;
	array_specify_optional("[") = array_specify;
	array_specify_optional(!"[") = ε;
other_declaration_ident = "," , declaration_element;	other_declaration_ident(",") = "," , declaration_element;
declaration = value_type , declaration_element , {other_declaration_ident};	declaration("INTEGER16") = value_type , declaration_element , other_declaration_ident_iteration;
	other_declaration_ident_iteration(",") = other_declaration_ident , other_declaration_ident_iteration;
	other_declaration_ident_iteration(!",") = ε;
index_action = "[" , expression , "]" ;	index_action("[") = "[" , expression , "]" ;
unary_operator = "NOT" "-" "+" ;	unary_operator("NOT") = "NOT";
	unary_operator("-") = "-";
	unary_operator("+") = "+";
unary_operation = unary_operator , expression;	unary_operation("NOT", "+", "-") = unary_operator , expression;
binary_operator = "AND" "OR" "==" "!=" "<=" ">=" "+" "-" "*" "DIV" "MOD";	binary_operator("AND") = "AND";
	binary_operator("OR") = "OR";
	binary_operator("==") = "==";
	binary_operator("!=") = "!=";
	binary_operator("<=") = "<=";
	binary_operator(">=") = ">=";
	binary_operator("+") = "+";
	binary_operator("-") = "-";
	binary_operator("*") = "*";
	binary_operator("DIV") = "DIV";

	binary_operator("MOD") = "MOD";
binary_action = binary_operator , expression;	binary_action("AND", "OR", "==", "!=", "<=", ">=", "+", "-", "*", "DIV", "MOD") = binary_operator , expression;
left_expression = group_expression unary_operation ident , [index_action] value;	left_expression("(") = group_expression;
	left_expression("NOT") = unary_operation;
	left_expression("NOT", "+", "-") = ([+1](unsigned_value_terminal) : value; ([+1]!(unsigned_value_terminal)) : unary_operation;
	left_expression(ident_terminal) = ident , index_action_optional;
	left_expression(unsigned_value_terminal, "+", "-") = value;
	index_action_optional("[") = index_action;
	index_action_optional(!"[") = ε;
expression = left_expression , {binary_action};	expression("(", "NOT", "+", "-", ident_terminal, unsigned_value_terminal) = left_expression , binary_action__iteration;
	binary_action__iteration("AND", "OR", "==", "!=", "<=", ">=", "+", "-", "*", "DIV", "MOD") = binary_action, binary_action__iteration;
	binary_action__iteration(!("AND", "OR", "==", "!=", "<=", ">=", "+", "-", "*", "DIV", "MOD")) = ε;
group_expression = "(" , expression , ")";	group_expression("(") = "(" , expression , ")";
bind_right_to_left = ident , [index_action] , ":", expression;	bind_right_to_left(ident_terminal) = ident , index_action_optional , ":", expression;
bind_left_to_right = expression , ":", ident , [index_action];	bind_left_to_right("(", "NOT", "+", "-", ident_terminal, unsigned_value_terminal) = expression , ":", ident , index_action_optional;
if_expression = expression;	if_expression("(", "NOT", "+", "-", ident_terminal, unsigned_value_terminal) = expression;
body_for_true = block_statements_in_while_and_if_body;	body_for_true("{") = block_statements_in_while_and_if_body;
false_cond_block = "ELSE" , cond_block;	false_cond_block_without_else("ELSE") = "ELSE" , "IF" , if_expression , body_for_true;
body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false("ELSE") = "ELSE" , block_statements_in_while_and_if_body;
cond_block = "IF" , if_expression , body_for_true , {false_cond_block} , [body_for_false];	cond_block("IF") = "IF" , if_expression , body_for_true , false_cond_block_without_else__iteration , body_for_false_optional;
	false_cond_block_without_else__iteration("ELSE") =

	$([+1]"IF") : \textit{false_cond_block_without_else},$ $\textit{false_cond_block_without_else_iteration};$ $([+1]!("IF")) : \epsilon;$
	$\textit{false_cond_block_without_else_iteration}(!"ELSE") = \epsilon;$
	$\textit{body_for_false_optional}("ELSE") = \textit{body_for_false};$
	$\textit{body_for_false_optional}(!"ELSE") = \epsilon;$
$\textit{cycle_begin_expression} = \textit{expression};$	$\textit{cycle_begin_expression}("(", "NOT", "+", "-", \textit{ident_terminal}, \textit{unsigned_value_terminal}) = \textit{expression};$
$\textit{cycle_end_expression} = \textit{expression};$	$\textit{cycle_end_expression}("(", "NOT", "+", "-", \textit{ident_terminal}, \textit{unsigned_value_terminal}) = \textit{expression};$
$\textit{cycle_counter} = \textit{ident};$	$\textit{cycle_counter}(\textit{ident_terminal}) = \textit{ident};$
$\textit{cycle_counter_rl_init} = \textit{cycle_counter}, ":", \textit{cycle_begin_expression};$	$\textit{cycle_counter_rl_init}(\textit{ident_terminal}) = \textit{cycle_counter}, ":", \textit{cycle_begin_expression};$
$\textit{cycle_counter_lr_init} = \textit{cycle_begin_expression}, ":", \textit{cycle_counter};$	$\textit{cycle_counter_lr_init}("(", "NOT", "+", "-", \textit{ident_terminal}, \textit{unsigned_value_terminal}) = \textit{cycle_begin_expression}, ":", \textit{cycle_counter};$
$\textit{cycle_counter_init} = \textit{cycle_counter_rl_init} \mid \textit{cycle_counter_lr_init};$	$\textit{cycle_counter_init}(\textit{ident_terminal}) =$ $([+1](":")) : \textit{cycle_counter_rl_init};$ $([+1]!(":")) : \textit{cycle_counter_lr_init};$
	$\textit{cycle_counter_init}("(", "NOT", "+", "-", \textit{ident_terminal}, \textit{unsigned_value_terminal}) = \textit{cycle_counter_lr_init};$
$\textit{cycle_counter_last_value} = \textit{cycle_end_expression};$	$\textit{cycle_counter_last_value}("(", "NOT", "+", "-", \textit{ident_terminal}, \textit{unsigned_value_terminal}) = \textit{cycle_end_expression};$
$\textit{cycle_body} = "DO", (\textit{statement} \mid \textit{block_statements});$	$\textit{cycle_body}("DO") = "DO", \textit{statements_or_block_statements};$
$\textit{forto_cycle} = "FOR", \textit{cycle_counter_init}, "TO", \textit{cycle_counter_last_value}, \textit{cycle_body};$	$\textit{forto_cycle}("FOR") = "FOR", \textit{cycle_counter_init}, "TO", \textit{cycle_counter_last_value}, \textit{cycle_body};$
$\textit{statement_in_while_and_if_body} = \textit{statement} \mid "CONTINUE" \mid "BREAK";$	$\textit{statement_in_while_and_if_body}(\textit{ident_terminal}, "(", "NOT", \textit{unsigned_value_terminal}, "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";") = \textit{statement};$
	$\textit{statement_in_while_and_if_body}("CONTINUE") = "CONTINUE";$
	$\textit{statement_in_while_and_if_body}("BREAK") = "BREAK";$
$\textit{block_statements_in_while_and_if_body} = "{", \{\textit{statement_in_while_and_if_body}\}, "};$	$\textit{block_statements_in_while_and_if_body}("{") = "{",$ $\textit{statement_in_while_and_if_body_iteration}, "};$
	$\textit{statement_in_while_and_if_body_iteration}(\textit{ident_terminal}, "(", "NOT",$

	unsigned_value_terminal, "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";", "CONTINUE", "BREAK") = statement_in_while_and_if_body, statement_in_while_and_if_body __iteration;
	statement_in_while_and_if_body __iteration(! (ident_terminal, "(", "NOT", unsigned_value_terminal, "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";", "CONTINUE", "BREAK")) = ϵ ;
while_cycle_head_expression = expression;	while_cycle_head_expression("(" , "NOT", "+", "-", ident_terminal, unsigned_value_terminal) = expression;
while_cycle = "WHILE" , while_cycle_head_expression , block_statements_in_while_and_if_body;	while_cycle("WHILE") = "WHILE" , while_cycle_head_expression , block_statements_in_while_and_if_body;
repeat_until_cycle_cond = expression;	repeat_until_cycle_cond("(" , "NOT", "+", "-", ident_terminal, unsigned_value_terminal) = expression;
repeat_until_cycle = "REPEAT" , (statement block_statements) , "UNTIL" , repeat_until_cycle_cond;	repeat_until_cycle("REPEAT") = "REPEAT" , statements __or__ block_statements , "UNTIL" , repeat_until_cycle_cond;
	statements __or__ block_statements(ident_terminal, "(", "NOT", unsigned_value_terminal, "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";") = statement __iteration;
	statements __or__ block_statements("(") = block_statements;
input = "GET" , (ident , [index_action] "(" , ident , [index_action] , ")");	input("GET") = "GET" , argument_for_input;
	argument_for_input(ident_terminal) = ident , index_action_optional;
	argument_for_input "(" = "(" , ident , index_action_optional , ")" ;
output = "PUT" , expression;	output("PUT") = "PUT" , expression;
statement = bind_right_to_left bind_left_to_right cond_block forto_cycle while_cycle repeat_until_cycle labeled_point goto_label input output ";" ;	statement(ident_terminal) = ([+1]":=") : bind_right_to_left; ([+1]":") : labeled_point; ([+1]!"":=" , "":") : bind_left_to_right;
	statement("(" , "NOT", ident_terminal, unsigned_value_terminal, "+", "-") = bind_left_to_right;
	statement("IF") = cond_block;
	statement("FOR") = forto_cycle;
	statement("WHILE") = while_cycle;

	statement("REPEAT") = repeat_until_cycle;
	statement(ident_terminal) = labeled_point;
	statement("GOTO") = goto_label;
	statement("GET") = input;
	statement("PUT") = output;
	statement(";") = ";"
block_statements = "{" , {statement} , "};	block_statements("{") = "{" , statement__iteration , "};
	statement__iteration(ident_terminal , "(" , "NOT" , unsigned_value_terminal , "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";") = statement, statement__iteration;
	statement__iteration(! (ident_terminal , "(" , "NOT" , unsigned_value_terminal , "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";")) = ϵ ;
program = "NAME" , program_name , ";" , "BODY" , "DATA" , [declaration] , ";" , {statement} , "END";	program("NAME") = "NAME" , program_name , ";" , "BODY" , "DATA" , declaration_optional , ";" , statement__iteration , "END";
	declaration_optional("INTEGER16") = declaration;
	declaration_optional(!"INTEGER16") = ϵ ;
digit = "0" "1" "2" "3" "4" "5" "6" "7" "8" "9";	
non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	
unsigned_value = (non_zero_digit , {digit}) "0";	unsigned_value(unsigned_value_terminal) = unsigned_value_terminal;
value = [sign] , unsigned_value;	value(unsigned_value_terminal , "+" , "-") = sign_optional , unsigned_value;
	sign_optional("+", "-") = sign;

	sign_optional(!("+","-")) = ϵ ;
letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	
letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	
ident = "_", letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case;	ident(ident_terminal) = ident_terminal;
sign = "+" "-";	sign("+") = "+";
	sign("-") = "-";