SaGE: Quantifying Moral Consistency in Large Language Models

Vamshi Krishna Bonagiri, Sreeram Vennam, Priyanshul Govil, Manas Gaur, Ponnurangam Kumaraguru

Part of Responsible & Safe AI course on NPTEL



victorknox/SaGE




Large Language Models are Inconsistent




NPTEL

Large Language Models are Inconsistent




NPTEL

Large Language Models are Inconsistent




NPTEL

Large Language Models are Inconsistent



NPTEL


Large Language Models are Inconsistent



Large Language Models are Inconsistent

Semantic Consistency: the ability to make consistent decisions in semantically equivalent contexts. i.e, Semantically equivalent questions should yield semantically equivalent answers


Elazar et al. 2021



Claim: LLMs are not semantically consistent, and can give contradictory answers to paraphrased questions

Why is it a problem?

Testing:




NPTEL

Why is it a problem?


Deployed

In the real

world:




Why is it a problem?



Might behave in unexpected ways when deployed, hindering trust and reliability **(Safety Risk)**

Prior work




Measuring and Improving Consistency in Pretrained Language Models

Yanai Elazar[1,2] Nora Kassner[3] Shauli Ravfogel[1,2] Abhilasha Ravichander[4]
Eduard Hovy[4] Hinrich Schütze[3] Yoav Goldberg[1,2]
[1]Computer Science Department, Bar Ilan University
[2]Allen Institute for Artificial Intelligence
[3]Center for Information and Language Processing (CIS), LMU Munich
[4]Language Technologies Institute, Carnegie Mellon University
{yanaiela,shauli.ravfogel,yoav.goldberg}@gmail.com
kassner@cis.lmu.de {aravicha,hovy}@cs.cmu.edu

Abstract

Consistency of a model — that is, the invariance of its behavior under meaning-preserving alternations in its input — is a highly desirable property in natural language processing. In this paper we study the question: Are Pretrained Language Models (PLMs) consistent with respect to factual knowledge? To this end, we create PARAREL🤘, a high-quality resource of cloze-style query English paraphrases. It contains a total of 328 paraphrases for 38 relations. Using PARAREL🤘, we show that the consistency of all PLMs we experiment with is poor – though with high variance be-

Figure 1: Overview of our approach. We expect that a consistent model would predict the same answer for two paraphrases. In this example, the model is inconsistent on the *Homeland* and consistent on the *Seinfeld* paraphrases.



Evaluating Superhuman Models with Consistency Checks

Lukas Fluri*
Department of Computer Science
ETH Zürich
Zürich, Switzerland
lukas.fluri@protonmail.com

Daniel Paleka*
Department of Computer Science
ETH Zürich
Zürich, Switzerland
daniel.paleka@inf.ethz.ch


Florian Tramèr
Department of Computer Science
ETH Zürich
Zürich, Switzerland
florian.tramer@inf.ethz.ch

Fig. 1: Given a model that produces outputs or decisions that are hard to humanly verify (due to superhuman abilities or other difficulties in assessing ground truth), we propose to instead measure the model's *consistency* with respect to humanly verifiable rules. On the right, we show three sample scenarios where model outputs are hard to evaluate individually, but clearly inconsistent as a whole.

No formal methods to measure consistency in free text generation (i.e, for any generative language modeling task)

What about moral scenarios?

LLMs may perform consistently in scenarios that align with commonsense, but may struggle in moral scenarios due to conflicting training data, and this is even more problematic.



An example from the Moral Integrity Corpus


Ziems et al., 2022

Problem Statement


How can we reliably measure LLM Consistency in free text generation?

NPTEL

Methodology ▸ Pipeline



Methodology ▸ Paraphrase Generation



Few shot prompting Vicuna-13B

Filtering out good quality paraphrases using ParaScore (> 0.8)

Semantic Similarity: Do the paraphrases mean the same thing?

Lexical Divergence: Do they have enough variation in vocabulary?


(Shen et al., 2022)

Methodology ▸ Rule of Thumb (RoT) Generation

Few shot prompting Vicuna 13B with instructions (as shown)

Inputs: Query and Response

Output: RoT



Our prompt: RoT generation

A Rule of Thumb (RoT) is a fundamental judgment about right and wrong behavior. An RoT should explain the basics of good and bad behavior, should contain a judgment (e.g. "you should") and an action (e.g. "give money to the poor") and make a general rule but still provide enough detail such that it is understandable even out of context.

Instruction: Generate the rule of thumb for the task question-answer pair: be as concise as possible.

Question: When is it worth it to fight a losing battle?

Answer: It is never worth it.

Rule of Thumb: Cowardice saves you from fights you cannot win.


. . .

Question: <*question*>

Answer: <*answer*>

Rule of Thumb:

Methodology ▸ Moral Consistency Corpus




10K Questions, 5 Paraphrases each, 11 LLMs

Methodology ▸ Semantic Graph


Textual responses are converted into semantic embeddings using SBERT DeBERTa, fine tuned on NLI datasets.

Each sentence representation is a node in the graph

Distance between two nodes is the cosine distance between their semantic embeddings



Methodology ▸ Semantic Graph Entropy




Less entropy = Consistent

More entropy = Inconsistent

$$H(p) = -\sum_{i=1}^{n} p_i \log(p_i)$$

NPTEL

Methodology ▸ Semantic Graph Entropy



Less entropy = Consistent

More entropy = Inconsistent

$$H(p) = -\sum_{i=1}^{n} p_i \log(p_i)$$


f: Information functional

$$p(v_i) = \frac{f(v_i)}{\sum_{j=1}^{|V|} f(v_j)},$$

Probability function

(Dehmer and Mowshowitzt., 2011)

Methodology ▸ Semantic Graph Entropy



Less entropy = Consistent

More entropy = Inconsistent

f: Information functional

(Amount of mutual information in the vertex)


$$H(p) = -\sum_{i=1}^{n} p_i \log(p_i)$$

$$f(v_i) = \sum_{j=1}^{n} \mathrm{sim}(v_i, v_j)$$

$$p(v_i) = \frac{f(v_i)}{\sum_{j=1}^{|V|} f(v_j)},$$

Probability function (Dehmer and Mowshowitzt., 2011)

Methodology ▸ Semantic Graph Entropy



Less entropy = Consistent

More entropy = Inconsistent

f: Information functional
(Amount of mutual information in the vertex)

$$H(p) = -\sum_{i=1}^{n} p_i \log(p_i)$$

$$f(v_i) = \sum_{j=1}^{n} \mathrm{sim}(v_i, v_j)$$

Scaled Graph Entropy

$$\mathrm{SaGE}(G_s) = 1 - \frac{I(G_s)}{\log n}$$


$$p(v_i) = \frac{f(v_i)}{\sum_{j=1}^{|V|} f(v_j)},$$

Probability function

(Dehmer and Mowshowitzt., 2011)

Dehmer and Mowshowitzt., 2011

Results ▸ Human Annotations



Human annotations for 500 data points (Answer pairs)

0 and 1 for consistent/inconsistent for each pair

Average of these annotations compared with Metric scores


Results ▸ LLMs are inconsistent

Average consistency scores over MCC

Model	BLEU		ROUGE		BERTScore		SaGE	
	Ans	RoT	Ans	RoT	Ans	RoT	Ans	RoT
opt-125m	0.011	0.012	0.138	0.127	0.355	0.352	0.243	0.252
opt-1.3b	0.009	0.010	0.133	0.119	0.369	0.362	0.263	0.268
opt-2.7b	0.008	0.011	0.135	0.127	0.382	0.378	0.277	0.284
opt-6.7b	0.007	0.012	0.130	0.129	0.385	0.382	0.282	0.290
opt-13b	0.008	0.012	0.139	0.135	0.412	0.408	**0.312**	**0.318**
Mistral-7B-Instruct-v0.1	0.016	0.015	0.151	0.150	0.499	0.493	0.405	0.407
falcon-7b-instruct	0.027	0.016	0.194	0.159	0.648	0.621	0.584	0.563
Llama-2-7b-chat-hf	0.073	0.020	0.296	0.170	0.564	0.546	0.362	0.452
Llama-2-13b-chat-hf	0.084	0.020	0.261	0.176	0.660	0.635	**0.595**	**0.575**
GPT-3.5 Turbo †	0.056	0.015	0.217	0.151	0.613	0.529	**0.681**	**0.478**
GPT-4 †	0.055	0.0172	0.246	0.166	0.568	0.486	0.641	0.438


The best consistency score was around 0.575


Results ▸ Is Consistency dependent on temperature?



Probably not

Results ▸ Generalization





(Commonsense Reasoning)

Model	TruthfulQA		HellaSwag	
	SaGE	Accuracy	SaGE	Accuracy
opt-125m	0.258	0.357	0.164	0.313
opt-1.3b	0.258	0.260	0.162	0.537
opt-2.7b	0.282	0.374	0.151	0.614
opt-6.7b	0.285	0.351	0.156	0.687
opt-13b	0.315	0.341	0.146	0.712
Mistral-7B	0.421	0.567	0.529	0.756
falcon-7b	0.577	0.343	0.289	0.781
Llama-2-7b	0.452	0.388	0.563	0.786
Llama-2-13b	0.559	0.374	0.520	0.819

Surprisingly, Accuracy on benchmarks does not correlate with consistency!


Results ▸ Improvement?

Our prompt: RoT-based answer generation

Instruction: Answer the following question. Keep in mind this rule of thumb, <*RoT*>

Question: <*question*>

Answer:



GPT 3.5

NPTEL

Results ▸ Improvement?

Our prompt: RoT-based answer generation

Instruction: Answer the following question. Keep in mind this rule of thumb, <*RoT*>

Question: <*question*>

Answer:



RoT prompting shows improvement as expected

Consistency can be improved with better techniques

Conclusion

Moral Consistency Corpus, 50K moral questions and 11 LLM responses and RoTs for them

The SaGE framework, for measuring the consistency of an LLM

Findings:

Current LLMs are very inconsistent

Consistency and Accuracy are not the same problem, and language models need to be evaluated for consistency separately.

Providing simple rules to follow increases consistency, hinting at the potential for methods such as Retrieval Augmented Generation (RAG) for improved consistency

Thank You!

Questions? Please feel free to reach out to

vamshi.b@research.iiit.ac.in

@VictorKnox99

Homepage

Paper

victorknox/SaGE