

1. Libraries and settings

```
import pandas as pd
import numpy as np
import math
import sklearn
import sklearn.preprocessing
import datetime
import os
import matplotlib.pyplot as plt
import tensorflow as tf
import matplotlib.pyplot as plt
import keras
from keras.models import Sequential
from keras.layers import Dense, Dropout, Flatten, Reshape, GlobalAveragePooling1D
from keras.layers import Conv2D, MaxPooling2D, Conv1D, MaxPooling1D
from keras.utils import np_utils
#display parent directory and working directory
print(os.path.dirname(os.getcwd())+':', os.listdir(os.path.dirname(os.getcwd())));
print(os.getcwd()+':', os.listdir(os.getcwd()));
```

2. Analyze data

```
df = pd.read_csv("../prices-split-adjusted.csv", index_col = 0)
print(df.info())
print(df.head())
print(df.values.shape)
# number of different stocks
print('\nnumber of different stocks: ', len(list(set(df.symbol))))
print(list(set(df.symbol))[:10])
df.tail()
df.describe()
```

#3.plot data

```
plt.figure(figsize=(15, 5));
plt.subplot(1,2,1);
plt.plot(df[df.symbol == 'EQIX'].open.values, color='red', label='open')
plt.plot(df[df.symbol == 'EQIX'].close.values, color='green', label='close')
plt.plot(df[df.symbol == 'EQIX'].low.values, color='blue', label='low')
plt.plot(df[df.symbol == 'EQIX'].high.values, color='black', label='high')
plt.title('stock price')
plt.xlabel('time [days]')
```

```
plt.ylabel('price')
plt.legend(loc='best')
plt.show()
```

```
plt.subplot(1,2,2);
plt.plot(df[df.symbol == 'EQIX'].volume.values, color='black', label='volume')
plt.title('stock volume')
plt.xlabel('time [days]')
plt.ylabel('volume')
plt.legend(loc='best');
```

3. Manipulate data

#- choose a specific stock

#- drop feature: volume

#- normalize stock data

#- create train and test data sets

```
def feature_normalize(train):
```

```
    train_norm = train.apply(lambda x: (x - np.min(x)) / (np.max(x) - np.min(x))) #
```

標準化(介於 0~1 之間)

```
    return train_norm
```

很重要 切割視窗

```
def create_segments_and_labels(df, time_steps, step):#, label_name):
```

```
    """
```

This function receives a dataframe and returns the reshaped segments
of x,y,z acceleration as well as the corresponding labels

Args:

df: Dataframe in the expected format

time_steps: Integer value of the length of a segment that is created

Returns:

reshaped_segments

labels:

```
    """
```

#圖畫中的 overlap 越高，代表資料中的相關性越強

#圖中 80 筆資料一次跳 40 筆，代表其並非相關性高

#feature 有四個

```
    N_FEATURES = 4
```

#選擇測試切出 20%

```

test_set_size_percentage = 20
segments = []
labels = []

data_raw = df.as_matrix()
#創造時間窗，將所有選擇特徵一起切割視窗
for i in range(0, len(data_raw) - time_steps, step):#
    segments.append(data_raw[i: i + time_steps])

segments = np.array(segments);
test_set_size =
int(np.round(test_set_size_percentage/100*segments.shape[0]));
train_set_size = segments.shape[0] - (test_set_size);
#以訓練資料占比分割訓練測試集，並以視窗最後一筆資料當作預測值
x_train = segments[:train_set_size,-1,:]
y_train = segments[:train_set_size,-1,:]

#    x_valid = data[train_set_size:train_set_size+valid_set_size,-1,:]
#    y_valid = data[train_set_size:train_set_size+valid_set_size,-1,:]

x_test = segments[train_set_size:-1,:]
y_test = segments[train_set_size:-1,:]

return [x_train, y_train, x_test, y_test]
#    return [x_train, y_train, x_valid, y_valid, x_test, y_test]

```

choose one stock & drop volume

```

df_stock = df[df.symbol == 'EQIX'].copy()
df_stock.drop(['symbol'],1,inplace=True)
df_stock.drop(['volume'],1,inplace=True)

cols = list(df_stock.columns.values)
print('df_stock.columns.values = ', cols)

# normalize stock
df_stock_norm = df_stock.copy()
df_stock_norm = feature_normalize(df_stock_norm)

```

```

# create train, test data
time_steps = 20# choose sequence length
step = 5
x_train, y_train, x_test, y_test = create_segments_and_labels(df_stock_norm,
time_steps, step)
print('x_train.shape = ',x_train.shape)
print('y_train.shape = ', y_train.shape)
# print('x_valid.shape = ',x_valid.shape)
# print('y_valid.shape = ', y_valid.shape)
print('x_test.shape = ', x_test.shape)
print('y_test.shape = ',y_test.shape)

df_stock_norm.values.shape

plt.plot(df_stock_norm.open.values, color='red', label='open')
plt.plot(df_stock_norm.close.values, color='green', label='close')
plt.plot(df_stock_norm.low.values, color='blue', label='low')
plt.plot(df_stock_norm.high.values, color='black', label='high')
#plt.plot(df_stock_norm.volume.values, color='gray', label='volume')
plt.title('stock')
plt.xlabel('time [days]')
plt.ylabel('normalized price/volume')
plt.legend(loc='best')
plt.show()
#reshape 資料
num_time_periods, num_sensors = x_train.shape[1], x_train.shape[2]
input_shape = (num_time_periods*num_sensors)    ## 80*3 每一筆資料 80(時間窗) 3 個變數( xyz)
x_train_reshape = x_train.reshape(x_train.shape[0], input_shape).astype('float32')
print(f"x_train_reshape.shape:{x_train_reshape.shape}")
x_test_reshape = x_test.reshape(x_test.shape[0], input_shape).astype('float32')
print(f"x_test_reshape.shape:{x_test_reshape.shape}")

```

#建立模型

```
model_cnn1d = Sequential()
# num_time_periods*num_sensors
model_cnn1d.add(Reshape((num_time_periods, num_sensors),
input_shape=(input_shape,)))
model_cnn1d.add(Conv1D(100, 2, activation='relu',
input_shape=(num_time_periods, num_sensors)))
model_cnn1d.add(Conv1D(100, 2, activation='relu'))
model_cnn1d.add(MaxPooling1D(3))
model_cnn1d.add(Conv1D(160, 2, activation='relu'))
model_cnn1d.add(Conv1D(160, 2, activation='relu'))
model_cnn1d.add(GlobalAveragePooling1D())
model_cnn1d.add(Dropout(0.5))
# model_m.add(Dense(num_classes, activation='softmax'))
model_cnn1d.add(Dense(units=4, kernel_initializer="normal", activation="softmax"))
print(model_cnn1d.summary())
```

#開始訓練

```
BATCH_SIZE = 400
EPOCHS = 50
# training stops early
callbacks_list = [
    keras.callbacks.ModelCheckpoint(
        filepath='best_model.{epoch:02d}-{val_loss:.2f}.h5',
        monitor='val_loss', save_best_only=True),
    keras.callbacks.EarlyStopping(monitor='acc', patience=1)
]

model_cnn1d.compile(loss='MSE',
                    optimizer='adam', metrics=['MSE'])

history = model_cnn1d.fit(x_train_reshape, y_train, batch_size=BATCH_SIZE,
epochs=EPOCHS, callbacks=callbacks_list, validation_split=0.2, verbose=1)

# %%

print("\n--- Learning curve of model training ---\n")
```

#繪圖

```
import matplotlib.pyplot as plt
```

```
def show_train_history(train_history, train, validation):
```

```
    plt.plot(train_history.history[train])
```

```
    plt.plot(train_history.history[validation])
```

```
    plt.title("Train History")
```

```
    plt.ylabel(train)
```

```
    plt.xlabel('Epoch')
```

```
    plt.show()
```

```
show_train_history(train_history, "mean_squared_error", "val_loss") ## 訓練正確率圖
```

```
scores = model_cnn1d.evaluate(x_test_reshape, y_test)
```

```
print(f"MSE:{scores[0]}")
```