

IN Series

IN120 WiFi & IN220 PoE

Intelligent IP-Enabled Access Control

Available through Authorized
Channel Partners only.

Contact your local ASSA ABLOY
Door Security Solutions sales
consultant for details.




Table of Contents

Overview	2
Product Features, Environmental Specifications and Battery Life	3
IN Series 7900 Series Mortise Locks	6
IN Series 8200 Series Mortise Locks	9
IN Series 7300 Series Multi-Point Locks	12
IN Series 10X Line Bored Locks	15
IN Series 80 Series Exit Devices	17
IN Series PE80 Series Exit Devices	19
IN Series Retrofit Kits for Von Duprin® 98/99 Series	22
Hard Power Option (91-)	24
IN220 PoE System Architecture	25
Accessories and Software	26
Lock Management Tool	27-28
Standard and Coastal Series Levers	29-30
Studio Collection Levers	31
Standard and Coastal Series Roses and Finishes	32
Studio Collection Roses, Thumturns and Finishes	33
Ordering Gramercy Series Levers	34
Replacement Parts	35
Mechanical Options	36
Cylinder Options	37-39

Overview

The SARGENT IN Series brings you the next generation of IP-enabled access control in a sleek, minimalist design. With both WiFi and Power over Ethernet options, you can leverage your IT infrastructure to deliver advanced access control to more locations, with the flexibility and security of HID® multiCLASS SE® technology.

About ASSA ABLOY's Authorized Channel Partner and Certified Integrator Programs

The SARGENT IN120 and IN220 are part of a stream of new ASSA ABLOY products that integrate with a facility's access control system. These exciting new technology-rich products require an increase in knowledge to ensure the correct selection and implementation in various environments.

To aid our customers in this area, ASSA ABLOY has created two programs that provide the necessary training to sell, order, install and service our technology products, including Aperio® wireless, Integrated Wiegand, IP-enabled and self-configurable intelligent components:



- The Authorized Channel Partner (ACP) program is open to resellers, who sell ASSA ABLOY's technology products to certified integrators and help with product selection based on the application.



- The Certified Integrator (CI) program provides hands-on training for security systems integrators and network administrators.

Not only does this training familiarize certified integrator candidates with product features and applications, it also gives them valuable experience installing, commissioning and troubleshooting the products in a real-world environment.

For more information on the qualifications for becoming an ACP or CI, contact your local ASSA ABLOY Door Security Solutions sales consultant.

IN Series

Intelligent IP-Enabled Access Control

SARGENT®
ASSA ABLOY

FEATURES	BENEFITS	IN120 WiFi Lock	IN220 PoE Lock
Utilizes IEEE 802.3af PoE-enabled network infrastructure for both power and data	<ul style="list-style-type: none"> ■ Streamlines the installation process, reducing costs ■ Eliminates the need for any proprietary equipment ■ Enables real-time communication 		✓
Utilizes IEEE 802.11 WiFi infrastructure	<ul style="list-style-type: none"> ■ Significantly reduces installation costs ■ Eliminates the need for any proprietary equipment ■ Ideal for hard-to-wire locations 		✓
802.11b/g/n radio	<ul style="list-style-type: none"> ■ Interoperability with other WiFi equipment 	✓	
multiCLASS SE® Technology from HID Global®	<ul style="list-style-type: none"> ■ Provides heightened security ■ Supports: <ul style="list-style-type: none"> - Multiple credential types - HID Mobile Access® powered by Seos®, for iOS® and Android™ devices" 	✓	✓
Field selectable communication frequency	<ul style="list-style-type: none"> ■ Allows you to balance security requirements with battery life 	✓	
Reduced energy consumption and product sustainability measures	<ul style="list-style-type: none"> ■ Uses significantly less power consumption in standby mode than traditional access control ■ Leverages existing network infrastructure ■ Streamlined system architecture provides improved reliability and reduces materials 		<ul style="list-style-type: none"> ✓ ✓ ✓
Intelligence built into lock for local decision making*	<ul style="list-style-type: none"> ■ Lock operates regardless of network status ■ Supports up to 2,400/10,000 users** ■ Provides a 10,000 event transaction history/audit trail 	<ul style="list-style-type: none"> ✓ ✓ ✓ 	<ul style="list-style-type: none"> ✓* ✓ ✓
Privacy button	<ul style="list-style-type: none"> ■ Enables shelter in place/local lockdown ■ Offers privacy capabilities for applications such as restrooms 	<ul style="list-style-type: none"> ✓ ✓ 	<ul style="list-style-type: none"> ✓ ✓
Integrated ANSI/BHMA Grade 1 hardware, available in cylindrical lock, mortise lock, exit device, and multi-point lock configurations	<ul style="list-style-type: none"> ■ Flexibility to support various openings ■ Assurance of high quality SARGENT hardware 	✓	✓
Superior aesthetics	<ul style="list-style-type: none"> ■ Blends into any environment seamlessly ■ Designed to meet the requirements of designers and architects ■ Available with a wide range of finishes and decorative levers ■ Suites with other IN Series locks, regardless of technology ■ Suitable for glass^, metal, and wood door types 	<ul style="list-style-type: none"> ✓ ✓ 	<ul style="list-style-type: none"> ✓ ✓

* Requires backup power for IN220

** Contact your access control system manufacturer for more information

[^]For all glass doors, Center Lock Housing (CLH-IN) must be used. Purchased through ASSA ABLOY Glass Solutions program.

Credential Support:

Featuring HID® multiCLASS SE® technology, IN Series IP-enabled locks support the following credentials:

- Mobile Credentials:
 - HID Mobile Access® support, featuring Secure Identity Object™ (SIO) on mobile IDs (BLE and NFC)
 - LenelS2 BlueDiamond™
 - Apple Wallet Seos or DESFire® (NFC)
 - Google Pay DESFire® (NFC)
- High Frequency (13.56 MHz):
 - HID iCLASS®
 - HID iCLASS SE® (SIO-enabled)
 - HID iCLASS® Seos™
 - HID MIFARE® SE
 - HID DESfire® EV1 SE
 - MIFARE Classic
 - DESfire EV1
 - PIV/PIV-I (40-bit BCD, 64-bit, BCD, 75 bit, 128-bit or 200-bit outputs)
 - Felica
- Low Frequency (125 kHz):
 - HID Prox®
- Optional keypad
 - PIN only usage or dual authentication needs

For sites with more than one type of credential support, please contact please contact your local ASSA ABLOY Door Security Solutions sales representative or call 800-810-WIRE.

Technical Specifications

IN120

- Compatible with 802.11 b/g/n 2.4GHz wireless networks

IN220

- Conforms to IEEE 802.3af Class 1 standard, requiring less than 3.84 watts

Security:

- Optional, protocol level, 128-bit AES encryption (IN120, IN220)
- IN120 supports current WiFi network security standards, including:
 - WEP, WPA and WPA2
 - 802.1x
- For specific security information, please contact your local ASSA ABLOY Door Security Solutions sales representative or call 800-810-WIRE.

Software:

- Works with ASSA ABLOY IP-Enabled Access Control Partner software, allowing simple integration into existing or new systems
- Software Development Kits (SDK) and support available to integrate into other third party access control systems.
Email: OEMSupport_Group@assaabloy.com for assistance.

Environmental Specifications:


- Operating temperature:
-13°F (-25°C) to 151°F (66°C)
- Humidity: operates in condensing environments*
- Storage temperature:
-22°F (-30°C) to 176°F (80°C)

EAC Regulatory Compliance †:

- UL 294 Indoor Use
- ULC-60839-11-1, Grade 1
- BHMA A156.25

*Always refer to the installation instructions for correct procedure when installing in condensing environments

† Excludes EK series



Optional Keypad
PIN only usage or dual authentication needs




Unlock the potential of your commercial space by seamlessly integrating all-glass doors with the IN120. Enjoy heightened security, simplified access control, and an infusion of invigorating natural light, creating an environment that is both secure and radiant.


- Single and double door applications
- Glass cut-out required
- No cement or silicone required for installation
- Prepped for bored and mortise lock functions
- Matching 6-3/16" x 15-3/16" Centerlock Keeper can be paired with housing for double doors
- Glass thickness: 1/2", 9/16"
- Base materials:
 - Cover plates: Stainless Steel
 - Housing: Aluminum
- Finishes: 32D, 32, 10BE, BSP, WSP, Stock Powder Coats

Center Lock Keeper and Housing sold separately through ASSA ABLOY Glass Solutions

PoE (Power Over Ethernet) System Configuration



WiFi System Configuration



7900 Series Mortise Locks



Mechanical Features

- Certified to ANSI/BHMA A156.13 Series 1000 Grade 1
- UL/ULC Listed for fire doors*
- Motor driven 7900 Series Mortise Lock
- 3/4" projection stainless steel latchbolt, one-piece construction
- For 1-3/4" (44mm) thick door standard. Consult factory for additional thicknesses
- Stainless steel non-handed deadlocking latch
- Not available with SC- or SE- options
- Handing easily field reversible without disassembling lock body
- Lever trim through-bolted for increased security and durability

Shipping Weight: Approx. 11 lbs.

IN Series Mortise Lock Features

- Key outside always retracts latch
- Lever outside rigid except when valid credential presented
- Lever inside always retracts latch
- Guardbolt deadlocks latch
- Key override available with #41 cylinder supplied
- Low battery (for IN120), request-to-exit (REX), Door Position (DPS) and tamper signaling standard
- EcoFlex® technology offers improved battery life for IN120 mortise locks

52-5373 Door Position Switch (DPS)

Supplied with IN Series mortise locks

- SPST concealed switch (2-wire)
- 3/8" Diameter for wood door
- 3/4" Diameter for glass and metal door
- Metal door adapter included

Note: The DPS is installed right above the lock faceplate and connects directly into the lock's electronics

* Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

Select from the following options to order IN Series mortise locks:

Technology

- 120 WiFi
- 220 PoE

Function

- 7978 Key override (no deadbolt)
- 7979 No Key override (no deadbolt)

7900 Series Mortise Locks

Reader

- B Black reader, black trim
- MB Black reader, metal trim

Note:

Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.


Credentials

BIPS	HID Prox®, iCLASS®, iCLASS SE®, iCLASS® Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
BIKPS	All credentials supported by the BIPS option plus keypad.
IPV	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
IKPV	All credentials supported by the IPV option plus keypad
BCP/BCKP	Options supporting FeliCa credentials. Contact Transact for more details.
DIPS/DIKPS*	Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only


To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.

Rose



Lever

The levers shown here are some of our most popular styles from the Studio Collection. To see the complete range of available levers, please refer to pages 31-34.



Premium Levers



Finish

Description		Specify
US3 (ANSI/BHMS 605)	Bright Brass	03
US4 (ANSI/BHMA 606)	Satin Brass	04
US9 (ANSI/BHMA 611)	Bright Bronze	09
US10 (ANSI/BHMA 612)	Satin Bronze, clear powder	10
US10B (ANSI/BHMA 613)	Dark Oxidized Satin Bronze, oil rubbed	10B
10BE (613E)	Dark Oxidized Satin Bronze - equivalent	10BE
10BL (613L)	Dark Oxidized Satin Bronze - clear coated	10BL
US14 (ANSI/BHMA 618)	Bright Nickel Plated, clear coated	14
US15 (ANSI/BHMA 619)	Satin Nickel Plated, clear coated	15
20D	Dark Statuary Bronze, clear coated	20D
US26 (ANSI/BHMA 625)	Bright Chromium Plated	26
US26D (ANSI/BHMA 626)	Satin Chromium Plated	26D
US32 (ANSI/BHMA 629)*	Bright Stainless Steel	32
US32D (ANSI/BHMA 630)*	Satin Stainless Steel	32D
BSP	Black Suede Powder Coat	BSP
WSP	White Suede Powder Coat	WSP

Lock Finish	Plug**
03, 04, 09, 10, 10B, 10BL, 20D	04
14, 15, 26, 26D, 32, 32D, WSP	15
BSP	BSP

** Finish when cylinder provided with lock

Handing

- LH Left hand
- LHR Left hand reverse
- RH Right hand
- RHR Right hand reverse

*Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

¹1KA square cylinder collar and 130KA square backplate automatically supplied with E2, E3 and E4 roses.

²Lever returns within $\frac{1}{2}$ " (13 mm) of door face.

³Gramercy levers are customized. See page 34 for ordering information.

IN Series

Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

7900 Series Mortise Locks

Build Your Order String

Technology	Function	Credentials	Reader	Rose	Lever	Finish
IN	7 9 7					

For additional cylinder and/or mechanical options, please refer to pages 36-39. Add the desired options to the beginning of your order string.

8200 Series Mortise Locks



Mechanical Features

- Certified to ANSI/BHMA A156.13 Series 1000 Operational Grade 1 and Security Grade 1
- UL/ULC Listed for fire doors*
- FCC certified
- Windstorm and Florida Building Code information is listed on page 15
- Motor driven 8200 Series Mortise Lock
- 3/4" stainless steel, anti-friction reversible latch
- For 1-3/4" (44mm) thick door standard. Consult factory for additional thicknesses
- Stainless steel non-handed deadlocking latch
- Not available with SC- or SE- options
- Handed, easily field reversible without disassembling lockbody
- Lever trim through-bolted for increased security and durability

Shipping Weight: Approx. 11 lbs.

IN Series Mortise Lock Features

- Key outside always retracts latch
- Lever outside rigid except when valid credential presented
- Lever inside always retracts latch and deadbolt (if present)
- Guardbolt deadlocks latch
- Key override available with #41 cylinder supplied
- Low battery (for IN120), request-to-exit (REX), Door Position (integrated DPS), and tamper signaling standard

* Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

Select from the following options to order IN Series mortise locks:

Technology

- 120 WiFi
- 220 PoE

Note: 82276 and 82277 not available with Glass Solutions center lock housing.

Function

- 82276 Key override and deadbolt*
- 82278 Key override and no deadbolt
- 82277 Deadbolt and no key override*
- 82279 No deadbolt and no key override

*This function supports Escape Return.

IN Series

Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

8200 Series Mortise Locks

Reader

B	Black reader, black trim
MB	Black reader, metal trim

Note: Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.


Credentials

BIPS	HID Prox®, iCLASS®, iCLASS SE®, iCLASS® Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
BIKPS	All credentials supported by the BIPS option plus keypad.
IPV	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
IKPV	All credentials supported by the IPV option plus keypad
BCP/BCKP	Options supporting FeliCa credentials. Contact Transact for more details.
DIPS/DIKPS*	Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only


To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.

Rose




Lever

The levers shown here are some of our most popular styles from the Studio Collection. To see the complete range of available levers, please refer to pages 31-34.



Premium Levers



Finish

Description		Specify
US3 (ANSI/BHMS 605)	Bright Brass	03
US4 (ANSI/BHMA 606)	Satin Brass	04
US9 (ANSI/BHMA 611)	Bright Bronze	09
US10 (ANSI/BHMA 612)	Satin Bronze, clear powder	10
US10B (ANSI/BHMA 613)	Dark Oxidized Satin Bronze, oil rubbed	10B
10BE (613E)	Dark Oxidized Satin Bronze - equivalent	10BE
10BL (613L)	Dark Oxidized Satin Bronze - clear coated	10BL
US14 (ANSI/BHMA 618)	Bright Nickel Plated, clear coated	14
US15 (ANSI/BHMA 619)	Satin Nickel Plated, clear coated	15
20D	Dark Statuary Bronze, clear coated	20D
US26 (ANSI/BHMA 625)	Bright Chromium Plated	26
US26D (ANSI/BHMA 626)	Satin Chromium Plated	26D
US32 (ANSI/BHMA 629)*	Bright Stainless Steel	32
US32D (ANSI/BHMA 630)*	Satin Stainless Steel	32D
BSP	Black Suede Powder Coat	BSP
WSP	White Suede Powder Coat	WSP

Lock Finish	Plug**
03, 04, 09, 10, 10B, 10BL, 20D	04
14, 15, 26, 26D, 32, 32D, WSP	15
BSP	BSP

** Finish when cylinder provided with lock

Handing

LH	Left hand
LHR	Left hand reverse
RH	Right hand
RHR	Right hand reverse

*Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

8200 Series Mortise Locks

Build Your Order String

Technology	Function	Credentials	Reader	Rose	Lever	Finish	Handing	Opening Height (Inches)
IN	8 2 2 7							

For additional cylinder and/or mechanical options, please refer to pages 36-39. Add the desired options to the beginning of your order string.

7300 Series Multi-Point Locks

Mechanical Features



- Certified to ANSI/BHMA A156.37 Series 1000 Operational Grade 1 and Security Grade 1
- Motor driven 8200 Series Mortise Lock
- 1-3/4" thick door only; fully integrated – 7300 is part of a complete ASSA ABLOY windstorm solution
- Stainless steel non-handed deadlocking latch
- Not available with SC- or SE- options
- Handed, easily field reversible without disassembling lockbody
- Lever trim through-bolted for increased security and durability
- Concealed vertical assembly (rods, latches and cassette) pre-installed in door
- UL/ULC Listed for fire doors*
- FCC certified
- Windstorm certification information is listed in the Sargent 7300 Series catalog

Shipping Weight: Approx. 11 lbs.

IN Series Multi-Point Lock Features

- Lever outside rigid except when valid credential presented
- Lever inside always retracts latch and deadbolt

- Guardbolt deadlocks latch
- Low battery (for IN120), request-to-exit (REX), Door Position (integrated), and tamper signaling standard

* Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

MOUNTING	Supplied fasteners are for metal doors with through-bolts for trim
HAND	Handed; specify RHR, LHR, RH or LH
TOP BOLT	Adjustable stainless steel 3/4" square bolt with 11/16" engagement; 5/16" steel reinforcement plate
BOTTOM BOLT	Adjustable stainless steel 3/4" square bolt with 5/8" engagement; 1/4" steel reinforcement plate
CENTER BOLTS	Latchbolt is stainless steel with 3/4" projection. One piece, anti-friction reversible catch. Deadbolt is one piece hardened stainless steel with 1" projection
LOCK FRONT	1/8" steel mortise front reinforced with 13/64" thick lock edge stiffener
CENTER BOLT STRIKE	1/4" thick stainless steel
BACKSET	2-3/4" standard
DOOR THICKNESS	1-3/4" standard
DOOR HEIGHT	7'0" - 8'0"
MAXIMUM OPENING	Single door 4'0" x 8'0" and double doors 8'0" x 8'0"

Select from the following options to order IN Series multi-point locks:

Technology	Function	Reader
120 WiFi	73277 Deadbolt, no key override	B Black reader, black trim
220 PoE	73276 Key override with deadbolt	MB Black reader, metal trim

Note: Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

IN Series

SARGENT®

ASSA ABLOY

Intelligent IP-Enabled Access Control

7300 Series Multi-Point Locks


Credentials

BIPS	HID Prox®, iCLASS®, iCLASS SE®, iCLASS® Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
BIKPS	All credentials supported by the BIPS option plus keypad.
IPV	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
IKPV	All credentials supported by the IPV option plus keypad
BCP/BCKP	Options supporting FeliCa credentials. Contact Transact for more details.
DIPS/DIKPS*	Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only

To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.

Rose



Lever

The levers shown here are some of our most popular styles from the Studio Collection. To see the complete range of available levers, please refer to pages 31-34.

Premium Levers



¹1KA square cylinder collar and 130KA square backplate automatically supplied with E2, E3 and E4 roses.

²Lever returns within ½" (13 mm) of door face.

³Gramercy levers are customized. See page 34 for ordering information.

Finish

Description		Specify
US3 (ANSI/BHMS 605)	Bright Brass	03
US4 (ANSI/BHMA 606)	Satin Brass	04
US9 (ANSI/BHMA 611)	Bright Bronze	09
US10 (ANSI/BHMA 612)	Satin Bronze, clear powder	10
US10B (ANSI/BHMA 613)	Dark Oxidized Satin Bronze, oil rubbed	10B
10BE (613E)	Dark Oxidized Satin Bronze - equivalent	10BE
10BL (613L)	Dark Oxidized Satin Bronze - clear coated	10BL
US14 (ANSI/BHMA 618)	Bright Nickel Plated, clear coated	14
US15 (ANSI/BHMA 619)	Satin Nickel Plated, clear coated	15
20D	Dark Statuary Bronze, clear coated	20D
US26 (ANSI/BHMA 625)	Bright Chromium Plated	26
US26D (ANSI/BHMA 626)	Satin Chromium Plated	26D
US32 (ANSI/BHMA 629)*	Bright Stainless Steel	32
US32D (ANSI/BHMA 630)*	Satin Stainless Steel	32D
BSP	Black Suede Powder Coat	BSP
WSP	White Suede Powder Coat	WSP

Lock Finish	Plug**
03, 04, 09, 10, 10B, 10BL, 20D	04
14, 15, 26, 26D, 32, 32D, WSP	15
BSP	BSP

**Finish when cylinder provided with lock

Handing

LH	Left hand
LHR	Left hand reverse
RH	Right hand
RHR	Right hand reverse

*Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

7300 Series Multi-Point Locks

Build Your Order String

Technology	Function	Credentials	Reader	Rose	Lever	Finish	Handing
IN	FM 7 3 2 7 7						

*If Windstorm or Blast is required, add the following before the function code:

FM - Windstorm
BL - Blast

Example: FM73277, BL73277

If neither is required, use the function code as listed above.

For additional cylinder and/or mechanical options, please refer to pages 36-39. Add the desired options to the beginning of your order string.

10X Line Bored Locks



Mechanical Features

- Certified ANSI/BHMA A156.2 Series 4000 Grade 1
- UL/ULC Listed for fire doors*
- Motor driven cylindrical lock
- Latch Stainless Steel, 1/2" (13mm) throw
- 2-3/4" (70mm) backset standard
- For 1-3/4" (44mm) thick door standard. Consult factory for other thicknesses
- Handing easily field reversible without disassembling lock body
- Heavy duty lever spring return
- Steel mounting studs
- Not available with 10-UL-, 82-, 83-, 84- options

Shipping Weight: Approx. 9 lbs.

IN Series Bored Lock Features

- Key outside always retracts latch
- Lever outside rigid except when valid credential presented, freewheeling optional
- Lever inside always retracts latch
- Guardbolt deadlocks latch
- Key override standard with #C10X-1 cylinder supplied
- Low battery (for IN120), request-to-exit (REX), Door Position (DPS), and tamper signaling standard
- Door Position Switch (DPS, P/N 52-5373) supplied

52-5373 Door Position Switch (DPS)

Supplied with IN220 bored locks

- SPST concealed switch (2-wire)
- 3/8" Diameter for wood door
- 3/4" Diameter for glass and metal door
 - Metal door adapter included

Note: The DPS is installed right above the lock faceplate and connects directly into the lock's electronics

IN120/220 10X Line bored locks are UL Certified and Listed as part of an approved assembly¹ to the following certifications and standards:

- UL Listed per ANSI/SDI-BHMA A250.13
- ANSI/ASTM E330-2002
- ANSI/ASTM E1886-2005
- ASTM E1996-2009
- Testing Application Standard (TAS) 201-1994²
- Testing Application Standard (TAS) 202-1994²
- Testing Application Standard (TAS) 203-1994²
- UL Certification Directory ZHLL.R21744 Windstorm-rated Assemblies
- Listed on Florida Building Code Website: FL6728-R1
- Listed on Florida Building Code Website: FL4351-R1

¹To meet assembly requirements, use in conjunction with doors from ASSA ABLOY Group brands CECO DOOR and CURRIES.

²Published in the "Florida Building Code"

* Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

IN Series

Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

10X Line Bored Locks

Select from the following options to order IN Series cylindrical locks:

Technology

120 WiFi
220 PoE

Function


10XG77 Key override

Reader

B Black reader, black trim
MB Black reader, metal trim

Note: Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

Rose



Finish

Description		Specify
US3 (ANSI/BHMS 605)	Bright Brass	03
US4 (ANSI/BHMA 606)	Satin Brass	04
US9 (ANSI/BHMA 611)	Bright Bronze	09
US10 (ANSI/BHMA 612)	Satin Bronze, clear powder	10
US10B (ANSI/BHMA 613)	Dark Oxidized Satin Bronze, oil rubbed	10B
10BE (613E)	Dark Oxidized Satin Bronze - equivalent	10BE
10BL (613L)	Dark Oxidized Satin Bronze - clear coated	10BL
US14 (ANSI/BHMA 618)	Bright Nickel Plated, clear coated	14
US15 (ANSI/BHMA 619)	Satin Nickel Plated, clear coated	15
20D	Dark Statuary Bronze, clear coated	20D
US26 (ANSI/BHMA 625)	Bright Chromium Plated	26
US26D (ANSI/BHMA 626)	Satin Chromium Plated	26D
BSP	Black Suede Powder Coat	BSP
WSP	White Suede Powder Coat	WSP

Lock Finish	Cylinder/Core**
03, 04, 09, 10, 10B, 10BL, 20D	04
14, 15, 26, 26D, WSP	15
BSP	BSP

**Finish when cylinder provided with lock


Credentials

BIPS	HID Prox®, iCLASS®, iCLASS SE®, iCLASS® Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
BIKPS	All credentials supported by the BIPS option plus keypad.
IPV	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
IKPV	All credentials supported by the IPV option plus keypad
BCP/BCKP	Options supporting FeliCa credentials. Contact Transact for more details.
DIPS/DIKPS*	Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only

To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.

Lever



**Finish when cylinder provided with lock

Handing

LH Left hand
LHR Left hand reverse
RH Right hand
RHR Right hand reverse

Build Your Order String

Technology	Function	Credentials	Reader	Rose	Lever	Finish	Handing	Opening Height (Inches)
IN <input type="text"/>	1 <input type="text"/> 0 <input type="text"/> X <input type="text"/> G <input type="text"/> 7 <input type="text"/>	<input type="text"/> <input type="text"/>						

For additional cylinder and/or mechanical options, please refer to pages 36-39. Add the desired options to the beginning of your order string.

* Lever returns within ½" (13 mm) of door face

16 1-800-727-5477 • www.sargentlock.com

90829 06/24 • Copyright © 2018-2024, SARGENT Manufacturing Company. All rights reserved.

Experience a safer
and more open world

80 Series Exit Devices



Mechanical Features

- Certified ANSI/BHMA A156.3 Grade 1
- Latch 3/4" (19mm) throw (8800: stainless steel, 8900: anti-friction brass)
- Cylinder requirements: 8800 Series uses a #34 Rim Cylinder; 8900 Series uses a #46 Mortise Cylinder (1-3/4")
- For 1-3/4" (44mm) door standard. Consult factory for other thicknesses
- Available with Studio Collection, Coastal Series and all standard levers
- UL/ULC Listed for fire doors*

Shipping Weight: Approx. 11 lbs.

IN Series Exit Device Features

- Lever outside rigid except when in passage mode or valid user code entered
- Always allows free egress
- Request-to-Exit (REX): monitors rail position
- Low battery (for IN120), request-to-exit (REX), Door Position (DPS), and tamper signaling standard
- Door position switch (DPS, part #52-5373) supplied
- EcoFlex® technology reduces energy consumption up to 89% as certified by GreenCircle

* Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.



Mortise Exit

Rim Exit

Select from the following options to order IN Series exit devices:

Technology

- 120 WiFi
220 PoE

Function

- 8977 Mortise lock exit device, key override
8978 Mortise lock exit device, no key override
8877 Rim exit device, key override
8878 Rim exit device, no key override

IN Series

Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

80 Series Exit Devices

Reader

- B Black reader, black trim
MB Black reader, metal trim

Note: Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

Credentials


BIPS	HID Prox®, iCLASS®, iCLASS SE®, iCLASS Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
BIKPS	All credentials supported by the BIPS option plus keypad.
IPV	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
IKPV	All credentials supported by the IPV option plus keypad
BCP/BCKP	Options supporting FeliCa credentials. Contact Transact for more details.
DIPS/DIKPS*	Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only

To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.

Lever

The levers shown here are some of our most popular styles from the Studio Collection. To see the complete range of available levers, please refer to pages 31-34.



Finish

Description		Specify
US3 (ANSI/BHMS 605)	Bright Brass	03
US4 (ANSI/BHMA 606)	Satin Brass	04
US9 (ANSI/BHMA 611)	Bright Bronze	09
US10 (ANSI/BHMA 612)	Satin Bronze, clear powder	10
US10B (ANSI/BHMA 613)	Dark Oxidized Satin Bronze, oil rubbed	10B
10BE (613E)	Dark Oxidized Satin Bronze - equivalent	10BE
10BL (613L)	Dark Oxidized Satin Bronze - clear coated	10BL
US14 (ANSI/BHMA 618)	Bright Nickel Plated, clear coated	14
US15 (ANSI/BHMA 619)	Satin Nickel Plated, clear coated	15
20D	Dark Statuary Bronze, clear coated	20D
US26 (ANSI/BHMA 625)	Bright Chromium Plated	26
US26D (ANSI/BHMA 626)	Satin Chromium Plated	26D
US32 (ANSI/BHMA 629)*	Bright Stainless Steel	32
US32D (ANSI/BHMA 630)*	Satin Stainless Steel	32D
BSP	Black Suede Powder Coat	BSP
WSP	White Suede Powder Coat	WSP


*Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

ET Trim

ET 700 Series ET Trim



Premium Levers



Lock Finish	Plug**
03, 04, 09, 10, 10B, 10BL, 20D	04
14, 15, 26, 26D, 32, 32D, WSP	15
BSP	BSP

**Finish when cylinder provided with lock

*Exit Devices ordered in 32 or 32D will have the ET trim and lever supplied in 26 or 26D; for nickel finished ET trim, specify 14 or 15 finish and the exit will be supplied in 32 or 32D accordingly.

Handing

LHR Left hand reverse

RHR Right hand reverse

Door Width

Specify in inches

¹Lever returns within ½" (13 mm) of door face.

²Gramercy levers are customized. See page 34 for ordering information.

PE80 Series Exit Devices



Mechanical Features

- Certified ANSI/BHMA A156.3 Grade 1
- Latch 3/4" (19mm) throw (PE8800: stainless steel, PE8900: anti-friction brass)
- Cylinder requirements: PE8800 Series uses a #34 Rim Cylinder; PE8900 Series uses a #46 Mortise Cylinder (1-3/4")
- For 1-3/4" (44mm) door standard. Consult factory for other thicknesses
- Available with Studio Collection and all standard levers
- UL/ULC Listed for fire doors*
- Available with ADA Standard for Accessible Design and California Building Code.

Key Override

- Key override is available for MD/WD/AD-PE8600 CVR Devices (including NB-) with P106 Series Auxiliary Control
- Key override is available for PE8700 SVR Devices (including NB-) with a P306 Series Auxiliary Control

- The AFF is 39-5/8" for Standard Applications; when a P100 or P300 Series Auxiliary Control is used, 37 5/16" AFF is recommended to meet local accessibility standards

IN Series Exit Device Features

- Lever outside rigid except when in passage mode or valid user code entered
- Always allows free egress
- Request-to-Exit (REX): monitors rail position
- Vertical rod configurations utilize Ease of Access (EA) Option with offset positioning - required
- Low battery (for IN120), request-to-exit (REX), Door Position Switch (DPS), and tamper signaling standard
- Door position switch (DPS, part #52-5373) supplied**
- EcoFlex® technology reduces energy consumption, which lowers operation cost and reduces the number of power supplies required.

* Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

** For Double-door applications the DPS is installed in-between the active and inactive leaves. The DPS monitors both doors, but the REX only monitors the active leaf. To prevent door-force or door-held alarms, the alarms must be disabled.

IN Series

Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

Select from the following options to order IN Series exit devices:

Technology	Function	Credentials
120 WiFi	PE8678 CVR exit device, no key override	BIPS
220 PoE	PE8778 SVR exit device, no key override	HID Prox®, iCLASS®, iCLASS SE®, iCLASS® Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
	PE8877 Rim exit device, key override	BIKPS
	PE8878 Rim exit device, no key override	All credentials supported by the BIPS option plus keypad.
	PE8977 Mortise lock exit device, key override	IPV
	PE8978 Mortise lock exit device, no key override	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
		IKPV
		All credentials supported by the IPV option plus keypad
		BCP/BCKP
		Options supporting FeliCa credentials. Contact Transact for more details.
		DIPS/DIKPS*
		Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only

To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.



Mortise Exit - Inside View



Mortise Exit - Outside View



Surface Vertical Rod - Outside View (EA- Option)



Surface Vertical Rod - Inside View (EA- Option)



Rim Exit - Inside View



Rim Exit - Outside View



Concealed Vertical Rod - Outside View (EA- Option)



Concealed Vertical Rod - Inside View (EA- Option)

IN Series

Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

PE80 Series Exit Devices

Reader

B Black reader, black trim
MB Black reader, metal trim


Note: Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

Rail Size


E: 26" to - 32"
F: 32.5" to 36"
J: 36.5" to 42"
G: 42.5" to 48"

Exit Trim

P700 NEx Lever Trim



P700 WEx Lever Trim



Lever

To see the complete range of available levers, please refer to pages 31-34.

Finish

Description		Specify
US3 (ANSI/BHMS 605)	Bright Brass	03
US4 (ANSI/BHMA 606)	Satin Brass	04
US9 (ANSI/BHMA 611)	Bright Bronze	09
US10 (ANSI/BHMA 612)	Satin Bronze, clear powder	10
US10B (ANSI/BHMA 613)	Dark Oxidized Satin Bronze, oil rubbed	10B
10BE (613E)	Dark Oxidized Satin Bronze - equivalent	10BE
10BL (613L)	Dark Oxidized Satin Bronze - clear coated	10BL
US14 (ANSI/BHMA 618)	Bright Nickel Plated, clear coated	14
US15 (ANSI/BHMA 619)	Satin Nickel Plated, clear coated	15
US26 (ANSI/BHMA 625)	Bright Chromium Plated	26
US26D (ANSI/BHMA 626)	Satin Chromium Plated	26D
US32 (ANSI/BHMA 629)*	Bright Stainless Steel	32
US32D (ANSI/BHMA 630)*	Satin Stainless Steel	32D
BSP	Black Suede Powder Coat	BSP
WSP	White Suede Powder Coat	WSP

Lock Finish	Cylinder/Core**
03, 04, 09, 10, 10B, 10BL	04
14, 15, 26, 26D, 32, 32D, WSP	15
BSP	BSP

*Finish when cylinder provided with lock

*Exit Devices ordered in 32 or 32D will have the ET trim and lever supplied in 26 or 26D; for nickel finished ET trim, specify 14 or 15 finish and the exit will be supplied in 32 or 32D accordingly.

Handing

LHR Left hand reverse
RHR Right hand reverse

Door Width

Specify in inches

*Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

Build Your Order String

Technology	Device Function	Credentials	Reader	Rail Size	Trim	Lever	Finish	Handing	Door Width (in inches)
IN	PE8877	BIPS	MB	F	NE	L	10BE	RHR	36"

For additional cylinder and/or mechanical options, please refer to pages 36-39. Add the desired options to the beginning of your order string.

Retrofit Kits for Von Duprin® 98/99 Series Rim Exit Devices



Mechanical Features

- Certified ANSI/BHMA A156.3 Grade 1
- Key override compatible with a variety of rim cylinders. Trim prepped for cylinder (not included)
- Requires Von Duprin RX switch assembly #050251-00 (supplied by others)
- Provides complete coverage of door prep for Von Duprin 996 trim; call 800-810-WIRE for information on door prep coverage for other trims
- Available with Studio Collection, Coastal Series and all standard levers
- UL/ULC Listed for fire doors*
- Matching dummy trim available for double doors.

IN Series Exit Device Features

- Lever outside rigid except when in passage mode or valid user code entered
- Always allows free egress
- Request-to-Exit (REX): monitors rail position
- Low battery, tamper signaling standard
- Door position switch (DPS, part #52-5373) supplied

* Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

Function

231 Rim exit device, key override

Reader

B Black reader, black trim
MB Black reader, metal trim

Escutcheon

EK1 Plate for Von Duprin Retrofit Fit

Note: Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

Credentials

BIPS	HID Prox®, iCLASS®, iCLASS SE®, iCLASS® Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
BIKPS	All credentials supported by the BIPS option plus keypad.
IPV	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
IKPV	All credentials supported by the IPV option plus keypad
BCP/BCKP	Options supporting FeliCa credentials. Contact Transact for more details.
DIPS/DIKPS*	Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only

To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.

IN Series


Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

Retrofit Kits for Von Duprin® 98/99 Series Rim Exit Devices

Lever

The levers shown here are some of our most popular styles from the Studio Collection. To see the complete range of available levers, please refer to pages 31-34.



Premium Levers



Finish

Description		Specify
US3 (ANSI/BHMS 605)	Bright Brass	03
US4 (ANSI/BHMA 606)	Satin Brass	04
US9 (ANSI/BHMA 611)	Bright Bronze	09
US10 (ANSI/BHMA 612)	Satin Bronze, clear powder	10
US10B (ANSI/BHMA 613)	Dark Oxidized Satin Bronze, oil rubbed	10B
10BE (613E)	Dark Oxidized Satin Bronze - equivalent	10BE
10BL (613L)	Dark Oxidized Satin Bronze - clear coated	10BL
US14 (ANSI/BHMA 618)	Bright Nickel Plated, clear coated	14
US15 (ANSI/BHMA 619)	Satin Nickel Plated, clear coated	15
20D	Dark Statuary Bronze, clear coated	20D
US26 (ANSI/BHMA 625)	Bright Chromium Plated	26
US26D (ANSI/BHMA 626)	Satin Chromium Plated	26D
US32 (ANSI/BHMA 629)*	Bright Stainless Steel	32
US32D (ANSI/BHMA 630)*	Satin Stainless Steel	32D
BSP	Black Suede Powder Coat	BSP
WSP	White Suede Powder Coat	WSP

**Finish when cylinder provided with lock

Handing

LHR Left hand reverse
RHR Right hand reverse

Lock Finish	Plug**
03, 04, 09, 10, 10B, 10BL, 20D	04
14, 15, 26, 26D, 32, 32D, WSP	15
BSP	BSP

*Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

Build Your Order String

Technology	Function	Credentials	Reader	Escutcheon	Lever	Finish	Handing
IN 120	2 3 1	B I P S		E K 1			

The order string for the EK1 mechanical exit trim is: EK1 x 706-5 x Lever x Finish x Hand.

For additional cylinder and/or mechanical options, please refer to pages 36-39. Add the desired options to the beginning of your order string.

¹Lever returns within ½" (13 mm) of door face.

²Gramercy levers are customized. See page 34 for ordering information.

IN Series

Intelligent IP-Enabled Access Control

SARGENT
ASSA ABLOY

Hard Power Option (91-) for IN120



The Hard Power option (91-) is recommended for high traffic doors or openings that require online behavior. Hard powering an IN120 allows the lock to operate in an always connected mode. The IN120 allows hard powering via an input of 9-24VDC (UL 294 Listed Power Supply Required) and draws 300mA at 9VDC in always connected mode. SARGENT offers a range of power supplies suitable for this application.

12VDC & 24VDC Power Supplies

- UL Class 2 Listed filtered and regulated supply
- Four 12V models and four 24V models available
- Integral battery charging capability keeps sealed lead acid gel/cell at full charge in case of line voltage failure (737-battery sold separately)
- Fused line voltage input with one, four, or eight DC outputs (depending on model)
- Each circuit can be individually turned on and off via a slide switch; the power status of each is shown by an LED
- In the event of a DC short, the problem is confined to the zone of difficulty
- Fire alarm interface standard


McKinney ElectroLynx® hinges and harnesses are required for hard-powered IN120 applications.

52-4824 IN120 Adapter Cable

- Included with 91- prefix option IN120 units
- Compatible with ElectroLynx® system
- Allows for hard powering (91-) of IN120 (required for certain monitoring features)

Please note that one electrified hinge, one door harness assembly and one frame harness assembly are required for each PoE opening.

PoE Hinges for IN220



Patented

The PoE door & frame harnesses can accommodate a variety of new (with raceway) and retrofit applications.

McKinney ElectroLynx® PoE Hinges*

Description

4 1/2" x 4 1/2" TA2714 26D PoE (Standard Weight 5 knuckle)

4 1/2" x 4 1/2" T4A3786 26D PoE (Heavy Weight 5 knuckle)

McKinney ElectroLynx® PoE Frame Harness

Cable Length

180"

Harness Description

PoE-C1500P

Cat5e, 24 AWG, Shielded, Stranded, 100 Ohm


*See the McKinney catalog for additional finishes and hinge types

McKinney ElectroLynx® PoE Door Harnesses

Door Width	Cable Length	Wood Door	Hollow Metal Door
28" to 31"	36"	PoE-C300RJ	PoE-C300PRJ
32" to 36"	42"	PoE-C306RJ	PoE-C306PRJ
37" to 42"	48"	PoE-C400RJ	PoE-C400PRJ
43" to 48"	54"	PoE-C406RJ	PoE-C406PRJ

All are Cat5e, 26 AWG, Shielded, Stranded, 100 Ohm

IN220 PoE System Architecture



Accessories and Software

Cover Plate Kits

- 79-5000 32D Mortise lock, IN120/IN220-82276 (key override, with deadbolt), 32D finish
- 79-5001 32D Mortise lock, IN120/IN220-82277 (no key override, with deadbolt), 32D finish
- 79-5002 32D Mortise lock, IN120/IN220-7978/82278 (key override, no deadbolt), 32D finish
- 79-5003 32D Mortise lock, IN120/IN220-7979/82279 (no key override, no deadbolt), 32D finish
- 10-5008 32D Cylindrical lock, IN120/IN220-10XG77 (with key override), 32D finish

WFCD1 Network and Lock Configuration Tool Kit*


- Contains:
 - LCT software
 - Serial adapter cable (P/N 52-3956)
 - Users' manual (on CD)
 - Quick start guide
 - Configuration cards (to configure iCLASS Only Locks)
 - USB cable (P/N 52-1635)
- Required to configure network settings of IN220 locks

DHTA Power over Ethernet (PoE) Cable and Data Hinge Test Adapter for IN220

Developed for troubleshooting SARGENT PoE locks, the ASSA ABLOY PoE cable and data hinge test adapter verifies your PoE installation in the field. Sold as a kit containing two test adapters, it allows you to verify proper wiring from the door frame to the PoE data hinge and lock, or test the frame, hinge or door cables independently. This test tool helps answer the question "Is the problem in the lock or in the wiring to the lock?" and will save you troubleshooting time.

The DHTA works in conjunction with the following products or their equivalent, provided by others:

- BK Precision model 231A
- FLUKE DTX 1800 CableAnalyzer™
- Two (2) Category 5e patch cables, each (10) feet in length



* The Network and Lock Configuration CD Tool Kit (WFCD1) is required to set up IN120 and IN220 locks. Only one is required per system. Lock Management Tool or a compatible system is also required.

Lock Management Tool



Lock Management Tool™ (LMT) allows programming, interrogation and overall management of ASSA ABLOY PoE locks from a centralized location for up to 50 doors. The application facilitates communication from a computer to the locks via IEEE 802.11af PoE infrastructure. The LMT program allows an administrator to establish multiple user types, time zones, holidays, user groups, auto-unlock periods and to obtain transaction history from all locks connected to the system. LMT consists of a server based installation (a small workstation will be sufficient) with most of the daily administration and configuration being done through a web browser. A local client on the server can be used for more complex configuration tasks.

Features:

- Password protected database
- User database size based on local hardware configuration
- Allows for creation of user groups
- Easy to follow data entry
- Real-time clock with date and time
- Sixteen different time zones
- Holiday support
- Auto-unlock schedule with or without "first in" unlock
- Allows viewing of system wide events and history (total number of events based on local hardware configuration) – includes event type, date, time, user ID and name
- Configurable for all major HID® Prox 125 kHz or iCLASS® 13.56 MHz card formats
- Scheduler utility to establish lock communication at pre-defined intervals
- User manual included
- Browser-based user interface
- Simple drag-and-drop configurations
- Basic alarm monitoring

Requirements:

- Hardware:
 - Screen: 800 x 600 required; 1024 x 768 Recommended
 - Network Card required
 - CD-ROM required
 - Memory: 4 GB minimum, 8 GB+ recommended for servers
 - Storage: 50 GB available or more as needed
 - Processor: 2 GHz or faster Dual-core minimum
- Supported Operating Systems:
 - Windows 10 Pro & Enterprise (Home editions of Windows are not supported)*
 - Windows Server 2012, 2012R2, 2016 & 2019
- Supported Databases: Microsoft SQL Server 2012 to 2019
 - Installed with Mixed Mode authentication enabled as installer requires a SQL sysadmin account.

Note: IP address must be assigned by authorized network administrator and PC must utilize a static IP address.

WFCD2 Lock Management Tool (LMT) 25 Door License

- Lock Management Tool™ allows programming, interrogation and overall management from a centralized location of up to 25 doors
- License is included and is obtained at time of installation
- Download from IntelligentOpenings.com

WFCD3 Lock Management Tool (LMT) 50 Door License

- Lock Management Tool™ allows programming, interrogation and overall management from a centralized location of up to 50 doors
- License is included and is obtained at time of installation
- Download from IntelligentOpenings.com


Integration Tools for ASSA ABLOY Locks

ASSA ABLOY electronic access control locks integrate with a range of industry-leading access control systems. For more information on which systems support our IP-enabled locks, please contact your local ASSA ABLOY Door Security Solutions office, www.assaabloydss.com.

To learn more about how to integrate these and other ASSA ABLOY products with your system, please call 800-810-WIRE.


Standard Levers (7900 Series Mortise Locks)

- All levers meet ADA national code requirements
- Lever designs BJ, BL and BP have lever returns within 1/2" (13mm) of door face
- Levers BB, BL, BJ & BP are only available with the O rose



Standard Levers (8200 Series Mortise Locks, 80 and PE80 Series Exit Devices, and 7300 Series Multi-Point Locks)

- All levers meet ADA compliance for national codes
- Solid forged or cast
- Lever designs J, L and P have lever returns within 1/2" (13mm) or less of door face and meet California State Reference Fire Code
- All lever height (+/- 1/16") measurements represent total distance from door face



Standard lever options are only available with O roses.


IN Series

Intelligent IP-Enabled Access Control



SARGENT
ASSA ABLOY

Standard Levers (10X Line Bored Locks)


- All levers meet ADA compliance for national codes
- Solid cast
- Lever designs L, P, ND, MW have lever returns within 1/2" (13mm) or less of door face and meet California State Reference Fire Code



- All lever height (+/- 1/16") measurements represent total distance from door face




Decorative Levers (10X Line Bored Locks)




The Coastal Series™ (Mortise Locks, 80 and PE80 Series Exit Devices, and 7300 Series Multi-Point Locks)

- All levers meet ADA compliance for national codes
- Not available with CO and TO roses
- Levers are solid cast brass
- Finishes available — 3, 4, 9, 10, 10B, 10BE, 10BL, 14, 15, 20D, 26, 26D
- All lever height (+/- 1/16") measurements represent total distance from door face

G - Gulfport™
(Handed)



R - Rockport™



S - Sanibel™
(Handed)



Y - Yarmouth™
(Handed)



IN Series

SARGENT
ASSA ABLOY

Intelligent IP-Enabled Access Control

Studio Collection trim is available in a broad array of designs and finishes. It allows for uniformity throughout a facility using the 8200, R8200 and 7900 Series Mortise Locks, Access Control Products, 80 and PE80 Series Exits Devices, DL/RDL Series Tubular Locks, and 7300 Series Multi-Point Locks.

All levers meet ADA compliance for national codes. Visit the online Decorative Hardware Product Selector at selector.sargentlock.com to mix and match styles and finishes.

Wooster Square Series

H001



H002²



H003



H004



H005²



H006²



Aventura Series

MB



ME



MF



NF



MG



MI



MW²



Gramercy Series³

RCM



RAL



REM



RAM



RAS



RAG



RGM



Centro Series

MD



MJ



MP¹



ND²



NJ²



Odéon Series^{1,4} (Handed Levers)

MN



MH



MS



MU



MV



NU²



WG



Notting Hill Series (MA and MO are Non-Handed Levers)

MA



MQ



MT



MO



MZ²



GT



Berlin Series

H015



H016²



H017



H018



Grant Park Series (H008 is handed)

H007



H008



H011



¹ Contact factory for current lead times. Not available in stainless steel finishes.

² Lever returns within 1/2" (13mm) of door face

³ Gramercy levers are customized. See page 34 for ordering information.

⁴ Odéon Series are not available in 32D


Note: H003 - H006 contains white or black polycarbonate insert

IN Series

Intelligent IP-Enabled Access Control


SARGENT
ASSA ABLOY

Standard Roses (7900 and 8200 Series Mortise Locks)




Coastal Series Roses (7900 and 8200 Series Mortise Locks)

TR Traditional Rose
(Dual radii edge)



CR Contemporary Rose
(Beveled edge)



Available Finishes

03 Polished Brass	
04 Satin Brass	
09 Polished Bronze	
10 Satin Bronze	
10B Oxidized Bronze	
10BE Dark Oxidized Satin Bronze — equivalent	
10BL Oxidized Satin Bronze	
20D Statuary Dark Bronze	
14 Polished Nickel	
15 Satin Nickel	
26 Polished Chrome	
26D Satin Chrome	
32 Polished Stainless Steel	
32D Satin Stainless Steel	
BSP Black Suede Powder Coat	
WSP White Suede Powder Coat	


Studio Collection Trim

Roses (7900, 8200, and 7300 Series Multi-Point Locks)


O



CO



TO



LN




CR




TR




E2¹
(Handed)



E3¹
(Handed)




E4¹
(Handed)



Thumbturns (7900, 8200, and 7300 Series Multi-Point Locks)

Thumbturn backplate will match rose design chosen. Specify T1, T2 or T3 as a prefix option for decorative turns.

T1



T3



¹ 1KA square cylinder collar and 130KA square backplate automatically supplied with E2, E3 and E4 roses.

Available Finishes

03 Polished Brass



04 Satin Brass



09 Polished Bronze



10 Satin Bronze



10B Oxidized Bronze




10BE Dark Oxidized Satin Bronze — equivalent



10BL Oxidized Satin Bronze




20D Statuary Dark Bronze




14 Polished Nickel




15 Satin Nickel



26 Polished Chrome




26D Satin Chrome



32 Polished Stainless Steel




32D Satin Stainless Steel



BSP Black Suede Powder Coat




WSP White Suede Powder Coat




Ordering Gramercy Series Levers


REM, RGM



RCM



RAG, RAL, RAM, RAS



Gramercy Finish Codes

BHMA FINISH	SARGENT FINISH	GRAMERCY CODE	DESCRIPTION
630	32D	30	Satin Stainless Steel
629	32	29	Bright Stainless Steel
613E	10BE	3E	Dark Oxidized Satin Bronze, Equivalent
N/A	BSP	BS	Black Suede Powder Coat
N/A	WSP	WS	White Suede Powder Coat
N/A	N/A	BK	Black (Santoprene™ or leather insert)
N/A	N/A	BN	Brown (leather insert)

*Code used to specify Gramercy Series finishes only. Use available finishes list to specify desired finish when ordering.

Gramercy Lever Descriptions and Available Finishes

LEVER DESIGNATION	LEVER DESCRIPTION	AVAILABLE FINISHES (AS ORDERED)
RAG	Grooved Insert	3030, 2929, 2930, 3029, 3E3E, BSBS or WSW
RAL	Leather Insert	30BK, 30BN, 29BK, 29BN, 3EBK3E, BSBKBS, WSBKWS, 3EBN3E, BSBNBS or WSBNW
RAM	Metallic Insert	2930 or 3030
RAS	Santoprene Insert	30BK, 29BK, 3E3E, BSBS or WSW
RCM	Raised Band	2930, 2929, 3030, 3029, 3E3E, BSBS or WSW
REM	Plain	2929, 3030, 3E3E, BSBS or WSW
RGM	Two Grooves	2929, 3030, 3E3E, BSBS or WSW

**Two-tone finish — grip of lever is 32D, balance of lever is 32. Rose/escutcheon and lock finish will be 32.

When specifying finish, use the last two digits of the BHMA standard finish code, i.e. use "29" for polished stainless, BHMA finish 629.

Replacement Parts

Reader Modules**¹

PART NUMBER	DESCRIPTION
IN120-EM01-[credentials]-[reader]	See below for credentials and reader code

Credentials

BIPS	HID Prox®, iCLASS®, iCLASS SE®, iCLASS Seos®, SIO on MIFARE® Classic, SIO on MIFARE DESFire® EV1 MIFARE Classic, MIFARE DESFire EV1, HID Mobile Access, Apple Wallet, Google Pay
BIKPS	All credentials supported by the BIPS option plus keypad.
IPV	Supports PIV/PIV-I (40-bit BCD, 64-bit BCD, 75 bit, 128-bit BCD or 200-bit outputs).
IKPV	All credentials supported by the IPV option plus keypad
BCP/BCKP	Options supporting FeliCa credentials. Contact Transact for more details.
DIPS/DIKPS*	Options supporting LenelS2 BlueDiamond™ mobile credentials.

*Orderable through LenelS2 only

To order locks with site keys preloaded with HID Mobile Access, Seos Elite, Apple Wallet, or Google Pay mobile credential support, please refer to the site-specific credential ordering guide.

Reader

B	Black reader, black trim
MB	Black reader, metal trim

Note: Metal reader trim (MB) is not available in stainless steel (32/32D). If stainless steel finish is ordered, the reader will be provided in satin nickel (15). Contact Customer Service if another finish is desired.

Replacement Kits

PART NUMBER	DESCRIPTION
IN120-EM07-B	WiFi replacement kit (controller, plate, cover); black
IN120-EM07-MB-[finish] ²	WiFi replacement kit (controller, plate, cover); black with metal trim
IN220-EM07-B	PoE replacement kit (controller, plate, cover); black
IN220-EM07-MB-[finish] ²	PoE replacement kit (controller, plate, cover); black with metal trim

Inside Escutcheon¹

PART NUMBER	DESCRIPTION
IN120-EM02-B	Black
IN120-EM02-MB-[finish] ²	Black with metal trim

52-5373 Door Position Switch (DPS)¹

DESCRIPTION
SPST concealed switch (2 wire)
Metal door adapter included
3/8" diameter for wood door
3/4" diameter for metal door
Supplied with IN120/IN220 (all locks except 8200 & FM7300)

Controllers & Controller Mounting Kit

PART NUMBER	DESCRIPTION
IN120-EM03	WiFi Controller
IN220-EM03	PoE Controller
IN120-EM04 ¹	Inside Mounting Kit (mounting plate and hardware)

Lockbodies¹

PART NUMBER	DESCRIPTION
IN120-7978-[finish] ² -[handing]	7900 mortise lockbody with cylinder (no deadbolt)
IN120-7979-[finish] ² -[handing]	7900 mortise lockbody only (no deadbolt, no cylinder)
IN120-82276-[finish] ² -[handing]	8200 mortise lockbody with deadbolt and cylinder
IN120-82277-[finish] ² -[handing]	8200 mortise lockbody with deadbolt (no cylinder)
IN120-82278-[finish] ² -[handing]	8200 mortise lockbody with cylinder (no deadbolt)
IN120-82279-[finish] ² -[handing]	8200 mortise lockbody only (no deadbolt, no cylinder)
10-3767	Cylindrical lockbody, Std/Rigid Lever (1-3/8"-2" Door)
10-3768	Cylindrical lockbody, Freewheeling Lever (1-3/8"-2" Door)
10-3801	Cylindrical lockbody, Std/Rigid Lever (2-1/4" Door)
10-3802	Cylindrical lockbody, Freewheeling Lever (2-1/4" Door)

¹ Reader modules, inside escutcheons, mounting kit, lockbodies, and door position switch can be used for both IN120 and IN220

² Specify finish

Mechanical Options

STRIKE OPTIONS	29- Strike #800. Lip length 1-1/4". Lip lengths 1" to 2" in 1/4" increments only. WBS- Wrought Box Strike
10X LINE BACKSET OPTIONS	20- 2-3/8" Backset Latch with 1" Front 23- 3-3/4" Backset x 2-1/4" x 1-1/8" Front (10X Line only) 25- 5" Backset x 2-1/4" x 1-1/8" Front (10X Line only)
SECURITY FASTENERS	36- Six lobe security head screws 37- Spanner head screws
3/4" LATCH THROW	41- 3/4" (19mm) throw latch x 2-3/4" (70mm) backset (10X Line only)
TACTILE WARNING OPTIONS	75- Tactile Warning — Milled Inside Lever (Not available with Studio and Coastal Levers and the A Lever) 76- Tactile Warning — Milled Outside Lever (Not available with Studio and Coastal Levers and the A Lever) 77- Tactile Warning — Milled Inside and Outside Lever (Not available with Studio and Coastal Levers and the A Lever) 85- Tactile Warning — Abrasive Coating on Inside Lever 86- Tactile Warning — Abrasive Coating on Outside Lever 87- Tactile Warning — Abrasive Coating on Inside and Outside Lever
FINISH PROTECTION	CPC- Clear Powder Coat (Available for 26, 26D, 32 and 32D Finishes) SG- MicroShield® antimicrobial clear powder coat (Available with 15, 26D, and 32D finishes)
THUMBTURNS (SEE PAGE 33)	T1- Decorative thumbturn; backplate matches rose design chosen T2- Decorative square thumbturn; backplate matches rose design chosen T3- Decorative cylinder thumbturn; backplate matches rose design chosen
OUTSIDE LOCKED LEVERS	FW- Freewheeling locking levers
KEYED DIFFERENT	KD- Cylinders provided keyed differently/random
PE80 SERIES OPTIONS	EA- Ease of Access (Required for PE8600 and PE8700)

Cylinder Options

CONVENTIONAL CYLINDER	—	SARGENT Conventional Cylinders supplied Standard (Nomenclature not required)
SIGNATURE KEY SYSTEM	10-	SARGENT Signature Key System (Not Available with other Key Systems)
SIGNATURE: LARGE FORMAT INTERCHANGEABLE CORE (REMOVABLE CORE)	10-21-	SARGENT Signature Construction Key System (Lost Ball)
XC- KEY SYSTEM	10-63-	SARGENT Signature LFIC (Removable Core) Cylinder
XC- LARGE FORMAT INTERCHANGEABLE CORE (REMOVABLE CORE)	11-	XC Key System (not available with 10-, 10UL, 22- options)
XC- SMALL FORMAT INTERCHANGEABLE CORE	11-21-	XC- Construction Key System (Lost Ball)
CONSTRUCTION KEY SYSTEMS	11-60-	Hardware to accept XC- Permanent LFIC (Removable Core), Disposable plastic Core — provided
OLD STYLE REMOVABLE CORE	11-63-	Hardware provided with XC- LFIC (Removable Core) Cylinder — (Includes masterkeying, grand masterkeying)
LARGE FORMAT INTERCHANGEABLE CORE (REMOVABLE CORE)	11-64-	Hardware provided with Keyed construction core to accept XC- LFIC (Removable) Permanent Core (ordered separately)
	11-70-7P-	Hardware to accept XC- SFIC (7 Pin) XC- Permanent Cores, plastic disposable core provided
	11-72-7P-	Hardware to accept XC- SFIC (7-Pin Keyed Construction Core provided) cylinder Permanent core ordered separately
	11-73-7P-	Hardware supplied with XC- Small Format 7-Pin interchangeable core (Includes masterkeying, grand masterkeying)
	11-65-73-7P-	Hardware provided to accept XC- Uncombined 7-Pin SFIC (Permanent) Core (Packed Loose)
CONSTRUCTION KEY SYSTEMS	21-	SARGENT Lost Ball Construction Keying for Conventional, XC and Signature Series (N/A with 63-, 73-, 82-, SC- & SE-)
OLD STYLE REMOVABLE CORE	22-	SARGENT Construction Split Key System for Conventional Cylinders (Existing Systems) (N/A with 10-, 11-, 63-, 73-, 82-, SC- & SE-)
LARGE FORMAT INTERCHANGEABLE CORE (REMOVABLE CORE)	51-	Removable Core Cylinder (Old Style) provided (Existing Systems Only)
	52-	Removable Construction Core (Old Style) Permanent core ordered separately (Existing Systems Only)
	60-	Hardware to accept SARGENT Permanent LFIC (Removable Core), Disposable plastic Core provided (Permanent Cores Ordered Separately)
	63-	Hardware provided with LFIC (Removable Core) Cylinder — (Includes masterkeying, grand masterkeying)
	64-	Hardware provided with Keyed construction core to accept LFIC (Removable) Permanent Core (ordered separately)

Cylinder Options

SMALL FORMAT INTERCHANGEABLE CORES	70-	Hardware to accept 6 or 7-Pin SFIC Permanent Cores, plastic disposable core provided
	72-	Hardware to accept 6 or 7-Pin SFIC (Keyed Construction Core provided) Cylinder (Permanent Core Ordered Separately)
	73-	Hardware supplied with 6-Pin SFIC (Includes masterkeying, grand masterkeying)
	65-73-	Hardware provided to accept Uncombined 6-Pin SFIC (Permanent) Core (Packed loose for field keying)
	65-73-7P-	Hardware provided to accept Uncombined 7-Pin SFIC (Permanent) Core (Packed loose for field keying)
	73-7P-	Hardware supplied with Small Format 7 Pin Interchangeable Core (Includes masterkeying, grand masterkeying)
	81-	Hardware provided with housings to accept Keso (83) and Keso F1 (F1-83-) removable cores (Not available with 10X Line) (Permanent Cores Ordered Separately)
KESO & KESO F1	82-	Hardware provided with SARGENT Keso Security Cylinder
	F1-82-	Hardware provided with SARGENT Keso F1 Security Cylinder (Patented)
	83-	Hardware supplied with SARGENT Keso Security Removable Core cylinder (Not available with 10X Line)
	F1-83-	Hardware supplied with SARGENT Keso F1 Security Removable Core cylinder (Not available with 10X Line) (Patented)
	84-	Hardware provided with SARGENT Keso Construction Cores (Not available with 10X Line) (Permanent Cores ordered separately)
BUMP RESISTANT	BR-	Bump Resistant Cylinder (Available with Conventional and Conventional XC Cylinders Only)
LESS CYLINDER	LC-	Hardware supplied less cylinder
ACCEPTS SCHLAGE CYLINDERS	30-	10X Line Lever to accept Schlage® fixed core Cylinder-Cylinder is not provided (10X Line only)
	SF-	10X Line L, B or P lever to accept Schlage® large format interchangeable core (supplied less core, tailpiece included).
SCHLAGE KEYWAYS	SC-	Schlage® C keyway cylinder, 0 bitted
	SE-	Schlage® E keyway cylinder, 0 bitted
ACCEPTS ASSA ABLOY ACCENTRA™ CYLINDERS/CORES	YC-	10X Line lever to accept Corbin Russwin or ASSA ABLOY ACCENTRA™ 6-pin fixed core cylinder - less cylinder, tailpiece provided (all designs)
	YC-7P-	10X Line lever to accept Corbin Russwin or ASSA ABLOY ACCENTRA™ 7-pin fixed core cylinder - less cylinder, tailpiece provided (all designs)
	YRC-	10X Line L or P Lever to accept ASSA ABLOY ACCENTRA™ 6-pin large format interchangeable core (supplied less core, but with tailpiece needed)

Cylinder Options

DEGREE CYLINDERS	DG1-	SARGENT Degree Key System Level 1 (Bump resistant with patented keys)
	DG1-21-	Degree Level 1 Construction Master Keying
	DG1-60-	Degree Level 1 Removable Disposable Construction Core
	DG1-63-	Degree Level 1 Removable Core
	DG1-64-	Degree Level 1 Removable Construction Keyed LFIC
	DG1-65-	Degree Level 1 Unassembled/Uncombined Core
	DG2-	SARGENT Degree Key System Level 2 (Geographically exclusive; bump and pick resistant)
	DG2-21-	Degree Level 2 Construction Master Keying
	DG2-60-	Degree Level 2 Removable Disposable Construction Core
	DG2-63-	Degree Level 2 Removable Core
	DG2-64-	Degree Level 2 Removable Construction Keyed LFIC
	DG2-65-	Degree Level 2 Unassembled/Uncombined Core
	DG3-	SARGENT Degree Key System Level 3 (Geographically exclusive; UL437 certified; bump and pick resistant)
	DG3-21-	Degree Level 3 Construction Master Keying
	DG3-60-	Degree Level 3 Removable Disposable Construction Core
	DG3-63-	Degree Level 3 Removable Core
	DG3-64-	Degree Level 3 Removable Construction Keyed LFIC
	DG3-65-	Degree Level 3 Unassembled/Uncombined Core

The ASSA ABLOY Group is the global leader in access solutions. Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within door openings and products for access solutions in homes, businesses and institutions. Our offering includes doors, frames, door and window hardware, mechanical and smart locks, access control and service.

SARGENT®

ASSA ABLOY

SARGENT Manufacturing Company
100 Sargent Drive
New Haven, CT 06511 USA
800-727-5477
www.sargentlock.com

Founded in the early 1800s, SARGENT® is a market leader in locksets, cylinders, door closers, exit devices, electro-mechanical products and access control systems for new construction, renovation, and replacement applications. The company's customer base includes commercial construction, institutional, and industrial markets.

Copyright © 2018-2024, Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited. Patent pending and/or patent www.assaabloyds.com/patents.

90829 06/24