

Virtuoso Basic Library Reference

**Product Version IC23.1
January 2025**

© 2025 Cadence Design Systems, Inc. All rights reserved.

Printed in the United States of America.

Cadence Design Systems, Inc. (Cadence), 2655 Seely Ave., San Jose, CA 95134, USA.

Open SystemC, Open SystemC Initiative, OSCI, SystemC, and SystemC Initiative are trademarks or registered trademarks of Open SystemC Initiative, Inc. in the United States and other countries and are used with permission.

Trademarks: Trademarks and service marks of Cadence Design Systems, Inc. contained in this document are attributed to Cadence with the appropriate symbol. For queries regarding Cadence's trademarks, contact the corporate legal department at the address shown above or call 800.862.4522. All other trademarks are the property of their respective holders.

Restricted Permission: This publication is protected by copyright law and international treaties and contains trade secrets and proprietary information owned by Cadence. Unauthorized reproduction or distribution of this publication, or any portion of it, may result in civil and criminal penalties. Except as specified in this permission statement, this publication may not be copied, reproduced, modified, published, uploaded, posted, transmitted, or distributed in any way, without prior written permission from Cadence. Unless otherwise agreed to by Cadence in writing, this statement grants Cadence customers permission to print one (1) hard copy of this publication subject to the following conditions:

1. The publication may be used only in accordance with a written agreement between Cadence and its customer.
2. The publication may not be modified in any way.
3. Any authorized copy of the publication or portion thereof must include all original copyright, trademark, and other proprietary notices and this permission statement.
4. The information contained in this document cannot be used in the development of like products or software, whether for internal or external use, and shall not be used for the benefit of any other party, whether or not for consideration.

Disclaimer: Information in this publication is subject to change without notice and does not represent a commitment on the part of Cadence. Except as may be explicitly set forth in such agreement, Cadence does not make, and expressly disclaims, any representations or warranties as to the completeness, accuracy or usefulness of the information contained in this document. Cadence does not warrant that use of such information will not infringe any third party rights, nor does Cadence assume any liability for damages or costs of any kind that may result from use of such information. Cadence is committed to using respectful language in our code and communications. We are also active in the removal and/or replacement of inappropriate language from existing content. This product documentation may however contain material that is no longer considered appropriate but still reflects long-standing industry terminology. Such content will be addressed at a time when the related software can be updated without end-user impact.

Restricted Rights: Use, duplication, or disclosure by the Government is subject to restrictions as set forth in FAR52.227-14 and DFAR252.227-7013 et seq. or its successor

Contents

1

<u>Basic Library Categories</u>	5
<u>Misc</u>	6
<u>cds_alias</u>	7
<u>cds_thru</u>	8
<u>cds_thrualias</u>	11
<u>dummy</u>	12
<u>nlpglobals</u>	13
<u>noConn</u>	14
<u>onPageConn</u>	16
<u>patch</u>	18
<u>Obsolete</u>	19
<u>Pins</u>	20
<u>actHiInOut</u>	21
<u>actHiInp</u>	22
<u>actHiOut</u>	23
<u>blockiopin</u>	24
<u>blockipin</u>	25
<u>blockopin</u>	26
<u>circle</u>	27
<u>commActLoInOut</u>	28
<u>commActLoInp</u>	29
<u>commActLoOut</u>	30
<u>ieeeActLoInOut</u>	31
<u>ieeeActLoInp</u>	32
<u>ieeeActLoOut</u>	33
<u>in</u>	34
<u>io</u>	35
<u>iopin</u>	36
<u>ipin</u>	37
<u>opin</u>	38

Virtuoso Basic Library Reference

<u>out</u>	39
<u>sympin</u>	40
<u>tsgActLo</u>	41
<u>tsgActLoClock</u>	43
<u>tsgClock</u>	45
<u>tsgleeeeActLoInp</u>	47
<u>tsgleeeeActLoOut</u>	49
<u>Supplies</u>	51
<u>gnd</u>	52
<u>gnd_inherit</u>	54
<u>vcc</u>	56
<u>vcc_inherit</u>	57
<u>vdd</u>	58
<u>vdd_inherit</u>	59
<u>vss</u>	60
<u>vss_inherit</u>	61
<u>VHDLPins</u>	62

Basic Library Categories

The `basic` library is a default reference library provided within the Virtuoso `cds.lib` file.

This reference contains basic information about each symbol within the basic library.

The symbols in the `basic` library are categorized as follows:

- Misc
- Obsolete
- Pins
- Supplies
- VHDL Pins

You can customize the values of symbols by amending the definition of the associated SKILL variables in the file `schConfig.il`. The file `schconfig.il` (located in `install_dir/tools/dfII/samples/local`) specifies various schematic editor configurations, including a configuration of the symbols within this library.

Misc

The *Misc* category (miscellaneous) lists those symbols that do not fall within the *Supplies* and *Pins* categories. It includes the following symbols:

- cds_alias
- cds_thru
- cds_thrualias
- dummy
- nlpglobals
- noConn
- onPageConn
- patch

cds_alias

Symbol View


cds_alias does not have a symbol view.

Description

A simple cell used by Verilog netlisters to short two nets.

cds_thru

Symbol View



Description

This symbol is used as a component to create a connection that may otherwise be reported as a short. For example, when you need a short between two terminals or between a terminal and a global signal, use `cds_thru` as it prevents connectivity extraction errors in Virtuoso Schematic Editor due to shorted terminals.

The component is designed to netlist for the following tools:

- `cdl/auCdl`: a small value resistor that can be ignored by using `*.RESI` commands
- `spectre`: an iprobe, which is a zero-voltage source
- `Verilog`: a module describing the short. Terminal-to-terminal assigns are legal in Verilog.

In addition to a symbol view, this component cell has a functional view and other analog views, such as `auLvs`, `hspice`, `hspiceD`, `spectre`, and so on. The type of simulation determines whether a functional or analog view is used. To use an analog netlister to netlist a schematic, you can use analog views in the Hierarchy Editor (HED). To use the Verilog netlister, a functional view must be used in HED.

If you want to use another library and cell for shorting terminals, refer to [*Virtuoso VHDL Toolbox User Guide*](#).

When an instance is bound to the function view of `cds_thru` in HED, `cds_thrualias` also display as a sub-instance of `cds_thru` in the hierarchy. AMS Unified Netlister (AMS UNL) generates an instance with `cds_thru` and passes the files, including the definitions of `cds_thru` and `cds_thrualias`, to the simulator. For example:

```
cds_thru I39 ( net012 , net09 );
```


Virtuoso Basic Library Reference


Basic Library Categories

Example

To short together two pins labeled `out1` and `out2`, you can place the `cds_thru` component between the two pins. It would netlist in Spectre as follows:

```
I0 (out1 out2) iprobe
```


The iprobe does not affect the simulation run. So you have shorted `out1` to `out2`. The following screenshot shows valid and invalid connections:



Virtuoso Basic Library Reference


Basic Library Categories

You can also combine two bus nets to form a single net using `cds_thru` as follows:



cds_thrualias

Symbol View



Description

When an instance is bound to the function view of `cds_thru` in the HED, `cds_thrualias` is also displayed as a sub-instance of `cds_thru` in the hierarchy.

AMS UNL generates an instance with `cds_thru` and passes the files, including the definitions of `cds_thru` and `cds_thrualias`, to the simulator.

Example

```
cds_thrualias I40 ( net015 , net014 );
```

dummy

Symbol View




Description

A dummy symbol provided for nlpglobals.

nlpglobals

Symbol View




Description

A global block symbol containing the global netlist format property definitions used to indicate global nets. This is required when creating a global cellview for netlisting.

You must create an nlpglobals cell if using the flat netlister (FNL) to create a netlist. For more details on creating global cellviews, refer to the [Open Simulation System Reference](#).

noConn

Symbol View




Description

This symbol can be attached to pins with signals that are unconnected to component output pins, schematic input pins, or any other schematic I/O pins. Adding this symbol to such pins ensures that they are not highlighted by the floating pin check.

Example

When the noConn +symbol is placed on the end of a dangling wire, the schematic rules check does not highlight the wire as an error.



Virtuoso Basic Library Reference


Basic Library Categories

Related Topics

For more details, see [Bypassing Floating Pin Checks](#) in the *Virtuoso Schematic Editor User Guide*.

onPageConn

Symbol View



Description

Use this symbol on wires without end points that do not physically connect to schematic or component pins, labels, or other wire segments. Attaching this symbol bypasses the unconnected wire check.

Example

When the onPageConn symbol is placed on the end of a dangling wire, the schematic rules check does not highlight the wire as an error.



Virtuoso Basic Library Reference

Basic Library Categories

Related Topics

For more details, see [Bypassing Unconnected Wire Checks](#) in the *Virtuoso Schematic Editor User Guide*.

patch

Symbol View




Description

Use this symbol to create a patchcord to establish aliases between the signals of two different nets.

Example

`srcVectorExpression = dstVectorExpression`



Nets A and B are aliased together. Logically, each object that A is connected to is also connected to B, and the patchcord connects the first bit named in `srcVectorExpression` to the first bit named in `dstVectorExpression`.

Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Patchcord Connections and Patchcord Naming Conventions](#)

[Adding Patchcords Using the Add Instances Form](#)

[Adding Patchcords Using the Create Patchcord Form](#)

Obsolete

The symbols listed in this section are obsolete and should not be used for new designs. They are preserved for existing designs.

Connectors

FCON

MCON

MiscObsolete

simNameState

simState

Saber

idc

isin

vexp

iexp

vccs

vpulse

ipulse

vcvs

vpwl

ipwl

vdc

vsin

SuppliesObsolete

CGND

GND

VDD

DGND

PWR

EGND

VCC

TA

dst

iosc

src

gnd_net

oosc

ta_vdd

Pins

The *Pins* category lists the symbol pins. It includes the following symbols:

- [actHiInOut](#) / [actHiInp](#) / [actHiOut](#)
- [blockiopin](#) / [blockipin](#) / [blockopin](#)
- [circle](#)
- [commActLoInOut](#) / [commActLoInp](#) / [commActLoOut](#)
- [ieeeActLoInOut](#) / [ieeeActLoInp](#) / [ieeeActLoOut](#)
- [in](#) / [io](#) / [out](#)
- [iopin](#) / [ipin](#) / [opin](#)
- [sympin](#)
- [tsgActLo](#)
- [tsgActLoClock](#)
- [tsgClock](#)
- [tsgleeeeActLoInp](#)
- [tsgleeeeActLoOut](#)

For more details, see [Adding Pins as Graphic Images](#) in the *Virtuoso Schematic Editor User Guide*.

actHiInOut

Symbol View



Description

A symbol pin used when the pin type `actHi` is selected with a direction of `input-output` on the [Create Pin — Symbol](#) form. There are also [input](#) and [output](#) direction pins available for the pin type `actHi`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type.

For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("actHi"  
        list("inputOutput" list("basic" "actHiInOut" "symbol"))  
    )  
)
```

actHiInp

Symbol View



Description

A symbol pin used when the pin type `actHi` is selected with a direction of `input` on the Create Pin — Symbol form. There are also output and inputOutput direction pins available for the pin type `actHi`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type.

For more details, see Customizing Global Editor Variables for Form Fields in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("actHi"  
        list("input" list("basic" "actHiInp" "symbol"))  
    )  
)
```

actHiOut

Symbol View



Description

A symbol pin used when the pin type `actHi` is selected with a direction of `output` on the [Create Pin — Symbol](#) form. There are also [input](#) and [inputOutput](#) direction pins available for the pin type `actHi`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type.


For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("actHi"  
        list("output" list("basic" "actHiOut" "symbol"))  
    )  
)
```

blockiopin

Symbol View



Description

A symbol pin used when the pin type `block` is selected with a direction of `inputOutput` on the [Create Pin — Symbol](#) form.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type. The `tsgConnectorMasters` variable defines the symbol of the pin connector.

For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example


```
schSymbolPinMasters = list(  
    list("block"  
        list("inputOutput" list("basic" "blockiopin" "symbol"))  
    )  
)
```

Related Topics

[Adding Blocks](#) in the *Virtuoso Schematic Editor User Guide*

blockipin

Symbol View



Description

A symbol pin used when the pin type `block` is selected with a direction of `input` on the [Create Pin — Symbol](#) form.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type. The `tsgConnectorMasters` variable defines the symbol of the pin connector.

For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example


```
schSymbolPinMasters = list(  
    list("block"  
        list("input" list("basic" "blockipin" "symbol"))  
    )  
)
```

Related Topics

[Adding Blocks](#) in the *Virtuoso Schematic Editor User Guide*

blockopin

Symbol View



Description

A symbol pin used when the pin type `block` is selected with a direction of `output` on the [Create Pin — Symbol](#) form.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type. The `tsgConnectorMasters` variable defines the symbol of the pin connector.

For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example


```
schSymbolPinMasters = list(  
    list("block"  
        list("output" list("basic" "blockopin" "symbol"))  
    )  
)
```

Related Topics

[Adding Blocks](#) in the *Virtuoso Schematic Editor User Guide*

circle

Symbol View



Description

A symbol pin used when the pin type `round` is selected on the [Create Pin — Symbol](#) form.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type. The `tsgConnectorMasters` variable defines the symbol of the pin connector.


For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("round"  
        list("input" list("basic" "circle" "symbol"))  
        list("output" list("basic" "circle" "symbol"))  
        list("inputOutput" list("basic" "circle" "symbol"))  
        list("switch" list("basic" "circle" "symbol"))  
        list("jumper" list("basic" "circle" "symbol"))  
        list("tristate" list("basic" "circle" "symbol"))  
        list("unused" list("basic" "circle" "symbol"))  
    )  
)
```

commActLoInOut

Symbol View



Description

A symbol pin used when the pin type `commActLo` is selected with a direction of `inputOutput` on the Create Pin — Symbol form. There are also input and output direction pins available for the pin type `commActLo`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin types and directions.


For more details, see Customizing Global Editor Variables for Form Fields in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("commActLo"  
        list("inputOutput" list("basic" "commActLoInOut" "symbol"))  
    )  
)
```

commActLoInp

Symbol View



Description

A symbol pin used when the pin type `commActLo` is selected with a direction of `input` on the [Create Pin — Symbol](#) form. There are also [output](#) and [inputOutput](#) direction pins available for the pin type `commActLo`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin types and directions.


For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("commActLo"  
        list("input" list("basic" "commActLoInp" "symbol"))  
    )  
)
```

commActLoOut

Symbol View



Description

A symbol pin used when the pin type `commActLo` is selected with a direction of `output` on the **Create Pin — Symbol** form. There are also [input](#) and [inputOutput](#) direction pins available for the pin type `commActLo`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin types and directions.


For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("commActLo"  
        list("output" list("basic" "commActLoOut" "symbol"))  
    )  
)
```

ieeeActLoInOut

Symbol View



Description

A symbol pin used when the pin type `ieeeActLo` is selected with a direction of `inputOutput` on the **Create Pin — Symbol** form. There are also `input` and `output` direction pins available for the pin type `ieeeActLo`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin types and directions.


For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("ieeeActLo"  
        list("inputOutput" list("basic" "ieeeActLoInOut" "symbol"))  
    )  
)
```

ieeeActLoInp

Symbol View



Description

A symbol pin used when the pin type `ieeeActLo` is selected with a direction of `input` on the Create Pin — Symbol form. There are also output and inputOutput direction pins available for the pin type `ieeeActLo`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin types and directions.


For more details, see Customizing Global Editor Variables for Form Fields in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
  list("ieeeActLo"  
    list("input" list("basic" "ieeeActLoInp" "symbol"))  
  )  
)
```


ieeeActLoOut

Symbol View



Description

A symbol pin used when the pin type `ieeeActLo` is selected with a direction of `output` on the **Create Pin — Symbol** form. There are also `input` and `inputOutput` direction pins available for the pin type `ieeeActLo`.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin types and directions.


For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example

```
schSymbolPinMasters = list(  
    list("ieeeActLo"  
        list("output" list("basic" "ieeeActLoOut" "symbol"))  
    )  
)
```

in

Symbol View



Description

A symbol pin used to represent the `input` terminals to which a net connects in a schematic. It is one of the pin masters available when you choose the *Create – Pin* command in Virtuoso Schematic Editor. There are also `output` and `inputOutput` direction pins available.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Adding Pins](#)

[Create Pin — Schematic](#)

io

Symbol View



Description

A symbol pin used to represent the `inputOutput` terminals to which a net connects in a schematic. It is one of the pin masters available when you choose the *Create – Pin* command in Virtuoso Schematic Editor. There are also [input](#) and [output](#) direction pins available.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Adding Pins](#)

[Create Pin — Schematic](#)

iopin

Symbol View



Description

A symbol pin used to represent the `inputOutput` direction. It is one of the symbol pin masters available when you choose the *Create — Pin* command in Virtuoso Schematic Editor. There are also [input](#) and [output](#) direction pins available.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Adding Pins](#)

[Create Pin — Symbol](#)

ipin

Symbol View



Description

A symbol pin used to represent the `input` direction. It is one of the symbol pin masters available when you choose the *Create — Pin* command in Virtuoso Schematic Editor. There are also [output](#) and [inputOutput](#) direction pins available.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Adding Pins](#)

[Create Pin — Symbol](#)

opin

Symbol View



Description

A symbol pin used to represent the `output` direction. It is one of the symbol pin masters available when you choose the *Create — Pin* command in Virtuoso Schematic Editor. There are also [input](#) and [inputOutput](#) direction pins available.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Adding Pins](#)

[Create Pin — Symbol](#)

out

Symbol View



Description

This pin represents the `output` terminals to which a net connects in a schematic. It is one of the pin masters available when you choose the *Create – Pin* command. There are also [input](#) and [inputOutput](#) direction pins available.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Adding Pins](#)

[Create Pin — Schematic](#)

sympin

Symbol View



Description

This symbol pin represents the `square` pin type. It is one of the symbol pin masters available when you choose the *Create – Pin* command.

The `schSymbolPinMasters` variable defines the symbol pins that are associated with the specific pin direction and type. The `tsgConnectorMasters` variable defines the symbol of the pin connector.

For more details, see [Customizing Global Editor Variables for Form Fields](#) in the *Virtuoso Schematic Editor User Guide*.

Example


```
schSymbolPinMasters = list(  
    list("square"  
        list("input"      list("basic" "sympin" "symbolNN"))  
        list("output"     list("basic" "sympin" "symbolNN"))  
        list("inputOutput" list("basic" "sympin" "symbolNN"))  
        list("switch"     list("basic" "sympin" "symbolNN"))  
        list("jumper"     list("basic" "sympin" "symbolNN"))  
        list("tristate"    list("basic" "sympin" "symbolNN"))  
        list("unused"     list("basic" "sympin" "symbolNN"))  
    )  
)
```

Related Topics

[Create Pin — Symbol](#) in the *Virtuoso Schematic Editor User Guide*

tsgActLo

Symbol View



Description

A pin graphic master for `actLo`. The pin graphic is selected using the appropriate *Attributes - List* option in the Symbol Generation Options form.

The `tsgActLo` pin graphic is available from the `tsgPinGraphicMasters` variable, which defines the characteristics of the graphic when generating symbols. This information is not used by any other tool.

The text-to-symbol generator (TSG) is a Cadence application program that automatically generates symbol cellviews for the Virtuoso Schematic Editor and subsequent simulation processes. TSG provides a quick way to generate a symbol from a list of pins in a TSG file.

Example

```
tsgPinGraphicMasters = list(  
    list("actLo"  
        list("input"          list("basic" "tsgActLo" "symbol"))  
        list("output"         list("basic" "tsgActLo" "symbol"))  
        list("inputOutput"    list("basic" "tsgActLo" "symbol"))  
        list("switch"         list("basic" "tsgActLo" "symbol"))  
        list("jumper"         list("basic" "tsgActLo" "symbol"))  
        list("tristate"       list("basic" "tsgActLo" "symbol"))  
        list("unused"         list("basic" "tsgActLo" "symbol"))  
    )  
)
```

Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

Virtuoso Basic Library Reference


Basic Library Categories

Text-to-Symbol Generator

Editing Symbol Generation Options

tsgActLoClock

Symbol View



Description

A pin graphic master for `actLoClock`. The pin graphic is selected using the appropriate *Attributes - List* option in the Symbol Generation Options form.

The `tsgActLoClock` pin graphic is available from the `tsgPinGraphicMasters` variable, which defines the characteristics of the graphic when generating symbols. It displays an additional pin shape on the symbol. This information is not used by any other tool.

The text-to-symbol generator (TSG) is a Cadence application program that automatically generates symbol cellviews for the Virtuoso Schematic Editor and subsequent simulation processes. TSG provides a quick way to generate a symbol from a list of pins in a TSG file.

Example

```
tsgPinGraphicMasters = list(  
    list("actLoClock"  
        list("input"          list("basic" "tsgActLoClock" "symbol"))  
        list("output"         list("basic" "tsgActLoClock" "symbol"))  
        list("inputOutput"    list("basic" "tsgActLoClock" "symbol"))  
    )  
)
```

Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Text-to-Symbol Generator](#)


Virtuoso Basic Library Reference

Basic Library Categories

Editing Symbol Generation Options

tsgClock

Symbol View



Description

A pin graphic master for `clock`. The pin graphic is selected using the appropriate *Attributes - List* option in the [Symbol Generation Options](#) form.

The `tsgClock` pin graphic is available from the `tsgPinGraphicMasters` variable, which defines the characteristics of the graphic when generating symbols. It displays an additional pin shape on the symbol. This information is not used by any other tool.

The text-to-symbol generator (TSG) is a Cadence application program that automatically generates symbol cellviews for the Virtuoso Schematic Editor and subsequent simulation processes. TSG provides a quick way to generate a symbol from a list of pins in a TSG file.

Example

```
tsgPinGraphicMasters = list(  
    list("clock"  
        list("input"          list("basic" "tsgClock" "symbol"))  
        list("output"         list("basic" "tsgClock" "symbol"))  
        list("inputOutput"    list("basic" "tsgClock" "symbol"))  
    )  
)
```

Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

Virtuoso Basic Library Reference


Basic Library Categories

Text-to-Symbol Generator

Editing Symbol Generation Options

tsgIeeeActLoInp

Symbol View



Description

A pin graphic master for `ieeeActLoInp`. The pin graphic is selected using the appropriate *Attributes - List* option in the Symbol Generation Options form.

The `tsgIeeeActLoInp` pin graphic is available from the `tsgPinGraphicMasters` variable, which defines the characteristics of the graphic when generating symbols. It displays an additional pin shape on the symbol. This information is not used by any other tool.

The text-to-symbol generator (TSG) is a Cadence application program that automatically generates symbol cellviews for the Virtuoso Schematic Editor and subsequent simulation processes. TSG provides a quick way to generate a symbol from a list of pins in a TSG file.

Example

```
tsgPinGraphicMasters = list(  
    list("ieeeActLo"  
        list("input"          list("basic" "tsgIeeeActLoInp" "symbol"))  
    )  
)
```

Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Text-to-Symbol Generator](#)


Virtuoso Basic Library Reference

Basic Library Categories

Editing Symbol Generation Options

tsgleeeeActLoOut

Symbol View



Description

A pin graphic master for `ieeeeActLoOut`. The pin graphic is selected using the appropriate *Attributes - List* option in the [Symbol Generation Options](#) form.

The `tsgIeeeActLoOut` pin graphic is available from the `tsgPinGraphicMasters` variable, which defines the characteristics of the graphic when generating symbols. It displays an additional pin shape on the symbol. This information is not used by any other tool.

The text-to-symbol generator (TSG) is a Cadence application program that automatically generates symbol cellviews for the Virtuoso Schematic Editor and subsequent simulation processes. TSG provides a quick way to generate a symbol from a list of pins in a TSG file.

Example

```
tsgPinGraphicMasters = list(  
    list("ieeeeActLo"  
        list("output"      list("basic" "tsgIeeeActLoOut" "symbol"))  
    )  
)
```

Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Text-to-Symbol Generator](#)

Virtuoso Basic Library Reference

Basic Library Categories

Editing Symbol Generation Options


Supplies

The *Supplies* category lists the power and ground supply symbols. It includes the following symbols:

- gnd
- gnd_inherit
- vcc
- vcc_inherit
- vdd
- vdd_inherit
- vss
- vss_inherit

gnd

Symbol View



Description

A ground supply symbol used to indicate an explicit ground pin.

Example

`[@gnd:%:gnd!]*`



Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Global Net Name Connections](#)


Virtuoso Basic Library Reference

Basic Library Categories

Inherited Connections

gnd_inherit


Symbol View



Description

A parameterized ground supply symbol with net expression property. It can be used to create global signals or override them across a hierarchy with inherited connectivity.

Example



You can create an inherited connection in a schematic by placing an instance of a symbol where one of the symbol pins has a net expression label. When you run the checker program on the schematic, the net expression label from the symbol pin is propagated onto the net within the schematic.

Virtuoso Basic Library Reference

Basic Library Categories

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

Global Net Name Connections

Inherited Connections

VCC

Symbol View



Description

A power supply symbol used to indicate an explicit power pin.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Global Net Name Connections](#)

[Inherited Connections](#)

vcc_inherit

Symbol View



Description

Parameterized power supply symbol with net expression property. It can be used to create global signals or override them across a hierarchy with inherited connectivity.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Global Net Name Connections](#)

[Inherited Connections](#)

vdd

Symbol View



Description

A power supply symbol used to indicate an explicit power pin.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Global Net Name Connections](#)

[Inherited Connections](#)

vdd_inherit


Symbol View



Description

A parameterized power supply symbol with net expression property. It can be used to create global signals or override them across a hierarchy with inherited connectivity.

Example



Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Global Net Name Connections](#)

[Inherited Connections](#)

VSS

Symbol View



Description

A ground supply symbol used to indicate an explicit ground pin.

Related Topics


See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Global Net Name Connections](#)

[Inherited Connections](#)

vss_inherit

Symbol View



Description

A parameterized ground supply symbol with net expression property. It can be used to create global signals or override them across a hierarchy with inherited connectivity.

Related Topics

See the following topics in the *Virtuoso Schematic Editor User Guide*:

[Global Net Name Connections](#)

[Inherited Connections](#)

VHDL Pins

Within Virtuoso, you can convert a VHSIC Hardware Description Language (VHDL) structural or behavioral description into one of the following forms in OpenAccess database storage format:

- Schematic view
- Netlist view
- VHDL text views

For more details, refer to the [VHDL In for Virtuoso Design Environment User Guide and Reference](#).

When generating schematics or netlists from VHDL, the following varieties of VHDL pins are available in the `basic` library:

<code>vhdlActHiInOut</code>	<code>vhdlCommActLoOut</code>
<code>vhdlActHiInp</code>	<code>vhdlIOPin</code>
<code>vhdlActHiOut</code>	<code>vhdlIPin</code>
<code>vhdlBlockIOPin</code>	<code>vhdlIeeeActLoInOut</code>
<code>vhdlBlockIPin</code>	<code>vhdlIeeeActLoInp</code>
<code>vhdlBlockOpin</code>	<code>vhdlIeeeAcLoOut</code>
<code>vhdlCircle</code>	<code>vhdlOPin</code>
<code>vhdlCommActLoInOut</code>	<code>vhdlSymPin</code>
<code>vhdlCommActLoInp</code>	