

Trạng thái	Đã xong
Bắt đầu vào lúc	Thứ Năm, 18 tháng 9 2025, 8:34 AM
Kết thúc lúc	Thứ Tư, 1 tháng 10 2025, 3:15 PM
Thời gian thực hiện	13 Các ngày 6 giờ
Điểm	11,60 trên 12,00 (96,67%)

Câu hỏi 1

Đúng

Đạt điểm 1,00 trên 1,00

Implement function

```
void printArray(int n){}
```

to print 0, 1, 2, ..., n (n is positive integer and has no space at the end).

Please note that you can't using key work for, while, goto (even in variable names, comment).

For this exercise, we have `#include <iostream>` and using namespace std;

For example:

Test	Result
<code>printArray(5);</code>	0, 1, 2, 3, 4, 5
<code>printArray(10);</code>	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10

Answer: (penalty regime: 0, 0, 0, 5, 10, 15, ... %)[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```

void printArray(int n)
{
    /*
     * STUDENT ANSWER
     */
    //Xac dinh basement
    if(n<0)return;
    if (n>0) {
        printArray(n-1);
        cout<<" ";<<n;
    } else cout<<0;
}

```

	Test	Expected	Got	
✓	printArray(5);	0, 1, 2, 3, 4, 5	0, 1, 2, 3, 4, 5	✓
✓	printArray(10);	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.

Câu hỏi 2

Đúng

Đạt điểm 1,00 trên 1,00

Given a positive number, print following a pattern without using any loop.

Input: n = 16

Output: 16, 11, 6, 1, -4, 1, 6, 11, 16 (has no space at the end)

Input: n = 10

Output: 10, 5, 0, 5, 10 (has no space at the end)

We basically first reduce 5 one by one until we reach a negative or 0. After we reach 0 or negative, we one add 5 until we reach n.

Note: Please note that you can't using key work for, while, goto (even in variable names, comment).

You can implement other recursive functions if needed.

For this exercise, we have #include <iostream> and using namespace std;

For example:

Test	Result
printPattern(14);	14 9 4 -1 4 9 14

Answer: (penalty regime: 0 %)

[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
void printPattern(int n)
{
    /*
     * STUDENT ANSWER
     */
    if(n>0) {
        cout<<n<<" ";
        printPattern (n-5);
        cout<<" "<<n;
    } else{
        cout<<n;
        return;
    }
}
```

	Test	Expected	Got	
✓	printPattern(14);	14 9 4 -1 4 9 14	14 9 4 -1 4 9 14	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.

Câu hỏi 3

Đúng

Đạt điểm 0,60 trên 1,00

Implement function

```
int findMax(int* arr, int length){}
```

to find the largest element using [recursion](#) (with length is the number of elements in integer array arr).

Please note that you can't using key work for, while, goto (even in variable names, comment).

For this exercise, we have `#include <iostream>` and using namespace std;

For example:

Test	Result
<pre>int arr[] = {10, 5, 7, 9, 15, 6, 11, 8, 12, 2}; cout << findMax(arr, 10);</pre>	15

Answer: (penalty regime: 0, 0, 0, 5, 10, ... %)[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
int findMax(int* arr, int length)
{
    /*
     * STUDENT ANSWER
     */
    // if (length == 0) return -1;
    if (length == 1) return arr[0];
    int max = findMax(arr,length-1); // Phải linh động trong việc thực hiện recursion bởi từng
    hàm gọi sẽ gọi lại tất cả hàm
    if (arr[length-1] > max){
        return arr[length-1];
    }
    else return max;
}
```

	Test	Expected	Got	
✓	<pre>int arr[] = {10, 5, 7, 9, 15, 6, 11, 8, 12, 2}; cout << findMax(arr, 10);</pre>	15	15	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00. Accounting for previous tries, this gives **0,60/1,00**.

Câu hỏi 4

Đúng

Đạt điểm 1,00 trên 1,00

Implement function

```
bool isPalindrome(string str){}
```

to check if the given non empty string is palindrome, else not palindrome using [recursion](#).

In test case, for extra point, we will have some palindrome sentences (All remaining test cases are words).

Please note that you can't using key work for, while, goto (even in variable names, comment).

For this exercise, we have `#include <iostream>`, `#include <string.h>` and using namespace std;

For example:

Test	Result
cout << isPalindrome("mom");	1
cout << isPalindrome("do geese see god");	1

Answer: (penalty regime: 0 %)

[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
bool preCheckPalindrome (const string &s,int left , int right){
    // Luu y can phai bo qua cac ky tu khoang trang ko phai chu hoac so
    if (left<right && !isalnum(s[left])) return preCheckPalindrome (s,left+1,right);
    if (left<right && !isalnum(s[right])) return preCheckPalindrome(s,left,right-1);
    if (left>=right) return true;
    if (s[left] != s[right]) return false;

    return preCheckPalindrome (s,left+1,right-1);
}

bool isPalindrome(string str)
{
    if (str.empty() ) return true;
    int right = str.length()-1;
    return preCheckPalindrome(str,0,right);
}
```


	Test	Expected	Got	
✓	cout << isPalindrome("mom");	1	1	✓
✓	cout << isPalindrome("do geese see god");	1	1	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.

Câu hỏi 5

Đúng

Đạt điểm 1,00 trên 1,00

Give two positive integers a and b, implement function

```
int findGCD(int a, int b){}
```

to find **GCD** (Greatest Common Divisor) of a and b using [recursion](#).

Please note that you can't using key work for, while, goto (even in variable names, comment).

For this exercise, we have `#include <iostream>` and using namespace std;

For example:

Test	Result
cout << findGCD(124,32);	4

Answer: (penalty regime: 0 %)

[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
int findGCD(int a, int b)
{
    if (a==0) return b;
    else if (b==0) return a;

    return findGCD(b,a%b);
}
```

	Test	Expected	Got	
✓	cout << findGCD(124,32);	4	4	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.

Câu hỏi 6

Đúng

Đạt điểm 1,00 trên 1,00

String s contains lowercase letters, digits, "(" and ")", satisfying the following rules:

- Two digits cannot be adjacent.
- Two "(" cannot be adjacent.
- One "(" and one ")" cannot be adjacent.
- After any digit, there must be "(".
- The quantities of "(" and ")" are equal.

Change string s until new string t created, t contains only lowercase letters. These are changing rules:

- Sub-strings with form " $n(p)$ ", can change to " $pp...p$ " (n times p), where n is a digit and p is a string.
- If p still contains "(", ")" or digits, continue to implement the above changing method.

Request: Implement function

```
expand(string s);
```

Where s is a string with the above form; return the result is a string containing only lowercase letters.

Example:

- String " $2(ab3(cde)x)$ " changes into "abcdecdecdecxabcdecdecdecx".
- String " $2(x0\text{👉})3(z)$ " changes into "xxzzz".

Note: In this exercise, libraries `iostream`, `string` and `using namespace std;` have been used. You can add other functions for your answer, but you are not allowed to add other libraries.

For example:

Test	Result
<code>cout << expand("2(ab3(cde)x)") << "\n";</code>	abcdecdecdecxabcdecdecdecx
<code>cout << expand("2(x0(y))3(z)") << "\n";</code>	xxzzz

Answer: (penalty regime: 0 %)

[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```

string repeat (const string &s, int n){
    if (n==0) return "";
    if (n==1) return s;
    return s + repeat (s,n-1);
}

string expandExtra(const string &s, int& pos){

    if (pos>=(int)s.size() || s[pos] == ' '){
        return "";
    }
    string result = "";
    if (isalpha(s[pos])){
        result = string (1,s[pos]);
        pos++;
        return result + expandExtra(s,pos);
    } else if (isdigit(s[pos])){
        int num = s[pos] - '0';    // So lap chi 1 chu so
        pos++;
        pos ++;
        string inner = expandExtra(s,pos);
        pos++;
        return repeat(inner,num) +expandExtra(s,pos);
    } else {
        pos++;
        return expandExtra(s,pos);
    }
}

string expand(string s) {
    int pos =0;
    return expandExtra(s,pos);
}

```

	Test	Expected	Got	
✓	cout << expand("2(ab3(cde)x)") << "\n";	abcdecdecdecxabcdecdecdecx	abcdecdecdecxabcdecdecdecx	✓
✓	cout << expand("2(x0(y))3(z)") << "\n";	xxzzz	xxzzz	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1.00/1.00.

Câu hỏi 7

Đúng

Đạt điểm 1,00 trên 1,00

Give a positive integer x , implement recursive function

```
void printHailstone(int number){}
```

to print the Hailstone Sequence of a given number upto 1 (no space at the end).

Hailstone Sequences follow these rules:

- If a number is even, divide it by 2
- If a number is odd, multiply it by 3 and add 1.

Example:

If number = 5. 5 is odd number so next number is $5*3 + 1 = 16$. 16 is even number so next number is $16/2 = 8$...

Finally, we get Hailstone sequence: 5 16 8 4 2 1.

You can find more information at: <https://diendantoanhoc.net/topic/89145-d%C3%A3y-s%E1%BB%91-hailstone/>

Note: Please note that you can't using key work for, while, goto (even in variable names, comment).

You can implement other recursive functions if needed.

For this exercise, we have `#include <iostream>` and using namespace std;

For example:

Test	Result
<code>printHailstone(32);</code>	32 16 8 4 2 1

Answer: (penalty regime: 0 %)

[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```

void printHailstone(int number)
{
    /*
     * STUDENT ANSWER
     */
    if(number<=0) return;
    cout<<number;
    if (number==1){
        return;
    }
    cout<<" ";
    if (number%2==0) {
        printHailstone(number/2);
    }
    else {
        printHailstone(3*number+1);
    }
}

```

	Test	Expected	Got	
✓	printHailstone(32);	32 16 8 4 2 1	32 16 8 4 2 1	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1.00/1.00.

Câu hỏi 8

Đúng

Đạt điểm 1,00 trên 1,00

Function

```
int myArrayToInt(char* str, int n){}
```

takes a **string str** (which represents an positive decimal number), **n** is the number of elements in the string as arguments and returns its value.

Please note that you can't using key work for, while, goto (even in variable names, comment)

For this exercise, we have #include <iostream>, #include <string.h> and using namespace std;

For example:

Test	Result
char str[] = "2020"; printf("%d", myArrayToInt(str, 4));	2020

Answer: (penalty regime: 0 %)[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
int myArrayToInt(char *str, int n)
{
    /*
     * STUDENT ANSWER
     */
    if (n==1) return str[0]-'0';
    int digit = str[0] - '0';
    return digit*(int ) pow (10,n-1)+myArrayToInt(str+1,n-1);
}
```

	Test	Expected	Got	
✓	char str[] = "2020"; printf("%d", myArrayToInt(str, 4));	2020	2020	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.

Câu hỏi 9

Đúng

Đạt điểm 1,00 trên 1,00

Give two positive integers a and b, implement function

```
int findLCM(int a, int b){}
```

to find **LCM** (Lowest Common Multiple) of a and b using [recursion](#).

Please note that you can't using key work for, while, goto (even in variable names, comment).

For this exercise, we have `#include <iostream>` and using namespace std;

For example:

Test	Result
cout << findLCM(10, 102);	510

Answer: (penalty regime: 0 %)

[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
int FindGCD(int a, int b){
    if (b==0) return a;
    if (a==0) return b;

    return FindGCD(b,a%b);
}
int findLCM(int a, int b)
{
    int GCD = FindGCD(a,b);
    int temp = a /GCD;
    return temp*b;
}
```

	Test	Expected	Got	
✓	cout << findLCM(10, 102);	510	510	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.

Đúng

Đạt điểm 1.00 trên 1.00

Your task is to implement a function with following prototype:

```
int mininumBracketAdd(string s);
```

The function returns the minimum number of brackets needed to be inserted to `s` so that the brackets are balanced.

More info:

A sequence of brackets is balanced when there are no unmatched brackets.

Example: $((()))$ is balanced, but $))(($ is not.

Note:

- The `iostream` library has been used and `namespace std` is being used. No other libraries are allowed.
- Using loop keywords (`for`, `while`, `do`) are not allowed, even in comments and variable names.
- You can write helper functions.

For example:

Test	Result
cout << mininumBracketAdd("))"))((");	5

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
int BracketHelper(const string &s, size_t index, int openB, int closeB){
    if (index == s.size()) return (openB+ closeB);
    if(s[index] == '(') {
        return BracketHelper(s,index+1,openB+1,closeB);
    }
    else {
        if (openB>0) {
            return BracketHelper(s,index+1,openB-1,closeB);
        }
        else {
            return BracketHelper(s,index+1,openB,closeB+1);
        }
    }
}

int minimumBracketAdd(string s) {
```

	Test	Expected	Got	
✓	cout << mininumBracketAdd(")))(");	5	5	✓
✓	cout << mininumBracketAdd("))())(){}");	4	4	✓
✓	cout << mininumBracketAdd("");	0	0	✓
✓	cout << mininumBracketAdd(")())(){}(){}))))(");	12	12	✓
✓	cout << mininumBracketAdd(")()(((((){}(){})){}(){})(()(((((){}(){})({}((()((((()))))){}(((()(((((){}(((){})){})){})){}"));	10	10	✓

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

Câu hỏi 11

Đúng

Đạt điểm 1,00 trên 1,00

Given a string `s` representing a sentence consisting only of `a-z` and `A-Z` and space character. Your task is to implement a function with following prototype:

```
string reverseSentence(string s);
```

The function returns the reverse sentence of sentence `s`.

The testcases ensure that there is only one space character between two adjacent words, and the sentences do not begin or end with any space characters.

Note:

- The `iostream` library has been used and `namespace std` is being used. No other libraries are allowed.
- Using loop keywords (`for`, `while`, `do`) are not allowed, even in comments and variable names.
- You can write helper functions.

For example:

Test	Result
<code>cout << reverseSentence("data structure and algorithm is scary");</code>	<code>scary is algorithm and structure data</code>

Answer: (penalty regime: 0, 0, 0, 5, 10, 15, ... %)

[Reset answer](#)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
string reverseSentence(string s) {
    // STUDENT ANSWER
    size_t pos = s.find(' ');
    if(pos == string::npos) return s;
    string firstWord =s.substr(0,pos);
    string rest = s.substr(pos+1);
    return reverseSentence(rest) +" "+ firstWord;
}
```

	Test	Expected	Got	
✓	<code>cout << reverseSentence("data structure and algorithm is scary");</code>	<code>scary is algorithm and structure data</code>	<code>scary is algorithm and structure data</code>	✓

Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.

Câu hỏi 12

Đúng

Đạt điểm 1,00 trên 1,00

Given a string, implement function

```
int strLen(char* str){}
```

to calculate length of the string using [recursion](#).

Please note that you can't using key work for, while, goto (even in variable names, comment).

For this exercise, we have #include <iostream> and using namespace std;

For example:

Test	Result
char str[] = "Truong DH Bach Khoa"; cout << strLen(str);	19

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
int strLen(char* str)
{
    /*
     * STUDENT ANSWER
     */
    if (*str=='\0') return 0;

    return 1 + strLen(str+1); // Tien phai den khi gap gia tri '/0 ' o cuoi chuoi
}
```

	Test	Expected	Got	
✓	char str[] = "Truong DH Bach Khoa"; cout << strLen(str);	19	19	✓



Passed all tests! ✓

Đúng

Marks for this submission: 1,00/1,00.