

L2 Repair

Handle second-level repairs: advanced diagnostics, board-level work, display connectors, and escalation from L1.

Step 1: View the L2 Queue

- Go to Repair -> L2 Repair from the left navigation.
- Devices arrive from L1 escalation or direct assignment by the inventory manager.

Step 2: Diagnose Before Starting

- Click on the device row to expand the device card.
- Review L1 notes and the full IQC report shown in the card.
- Document your root cause assessment in the Issue Description before starting the repair.
- Good root cause notes prevent repeated failures on the same device.

Step 3: Perform the Repair

- Start the repair and log all parts using the same Parts Request workflow as L1.
- L2 typically handles: charging circuit faults, RAM slot issues, display connector problems, and WiFi card replacement.
- Log time spent and cost accurately for each device.

Step 4: Complete, Escalate, or Scrap

- Complete -> QC Check: device is repaired and ready for quality check.
- Escalate to L3: board-level damage beyond L2 capability. Add detailed escalation notes.
- Scrap: device is beyond economic repair. Scrap requires manager approval and a Scrap Reason.

Tips & Best Practices

- * L2 handles charging circuits, RAM slots, display connectors, and WiFi card replacement.
- * Always document root cause before starting -- it reduces repeat failures.
- * Work ID tracks cumulative cost across L1 and L2 for the scrap-value warning.
- * Escalate to L3 as soon as a motherboard trace or BGA issue is confirmed.