

Fig. 3. GeoTex Bake10 absolute-lowest-error illustration. The stone object has the lowest existing eleven-view FG-LPIPS among seven rights-cleared display objects for both Fixed Mean and Late-high. Its Late-high–Fixed Mean difference is only −0.000464; the absolute-error ranking does not identify the largest schedule benefit. GT-256, Fixed Mean and Late-high share held-out camera 004, one crop and the source mesh/UVs. PNGs are 512×512. The row remains a post-outcome example, with visible reference-appearance mismatch and little visible schedule separation.

point-estimate winners, not general rank reversal or statistically resolved winner changes. The GT self-bake has mean LPIPS 0.0602 and PSNR 19.36 dB; average complete-bilinear-footprint coverage is about 78.7%. All foreground remains scored and GT errors are not subtracted. These losses contextualize the small method effects without defining a theoretical quality bound.

Incoming-view consistency. The bake also measures cross-camera color variance at UV texels receiving multiple source views. A constant-black control has zero variance despite its incorrect appearance, showing that this diagnostic measures incoming-view disagreement rather than fidelity. Late-high has a lower mean disagreement than Fixed Mean (−0.002448), while Fixed High has still lower disagreement and higher baked LPIPS. Resampling and overlapping UVs also affect this measure; it does not validate seams or PBR. Full controls and contrasts are in Supplementary Section S5.

Native controls and protocol sensitivity. Subsequently added Native residual and No Adapter outputs on the same ten GeoTex objects are exploratory. They retain matched geometry and GT coverage, and the repeated Constant 1.0 (capped) outputs are bitwise identical. Their apparent PSNR/LPIPS gains for the schedules do not separate under the fifteen-test exploratory family. The complete data are in Supplementary Section S5.

A supporting fifty-object comparison uses a newly trained frozen GeoTex checkpoint with 512-pixel supervision, actual positive/negative reference conditions and CFG 2. Late-high minus Fixed Mean has nonreference PSNR −1.184 dB (interval $[-1.587, -0.849]$) and LPIPS +0.00266 ($[-0.00003, +0.00640]$; adjusted $p = 0.080$). C3 has no corrected advantage over Fixed Mean or Fixed High. This previously studied cohort and changed checkpoint/protocol supply a sensitivity boundary, not an independent backbone confirmation. Training and full-v29 strong-baseline results remain in Supplementary Section S8.

Table 6. Native-camera MV-Adapter means on fifty input-selected objects.

Condition	FG-PSNR	FG-LPIPS	FG-SSIM	Edge-SSIM
Native / Fixed High	12.60	0.1280	0.5041	0.3526
Fixed Low	12.73	0.1270	0.5066	0.3475
Fixed Mean	12.68	0.1279	0.5068	0.3509
Early-high	12.60	0.1296	0.5041	0.3503
Middle-high	12.71	0.1262	0.5061	0.3470
Late-high	12.74	0.1260	0.5075	0.3514
Generic Linear	12.72	0.1263	0.5072	0.3501

4.5. Allocation Responses in Other Conditioning Interfaces

MV-Adapter and MVDiffusion supply different conditioning operators and scale semantics from GeoTex. We evaluate each within its native target/camera contract and do not pool their scores or interpret identical scale labels as common residual doses.

New native MV-Adapter temporal comparison. We selected fifty Fresh C inputs not previously evaluated through MV-Adapter, using input availability and native material/geometry compatibility. Native mesh normalization and six orthographic cameras define both generation and evaluation targets. Three-object identity checks confirmed agreement between the deployed and recorded default paths. An earlier seven-object panel had an invalid camera calibration and is excluded from these comparisons (Supplementary Section S3).

The seven conditions share object inputs, seed, geometry and evaluation code. With 50 steps, low/high are 0.75/1.0; stage-high schedules contain 16 high steps, Fixed Mean is 0.83, and Generic Linear is 0.75–0.91. These five controls have matched per-feature sums within this interface. All 50 objects remain in the primary cohort, including thirteen texture-absent sources with legal constant-white base-color targets. Targets are unlit native-camera base color, not Fresh C's differently normalized reference renders or certified physical albedo.

The internally predeclared primary, Middle-high minus Fixed Mean FG-PSNR, is +0.029 dB (95% object-bootstrap



Fig. 3. GeoTex Bake10: GT-256 self-bake, Fixed Mean and Late-high at the same held-out unseen camera 004. Tire is selected by the median foreground Laplacian variance of the seven cleared source inputs; this input-property example is not a population sample. The baptismal font is explicitly selected post-outcome for the largest existing eleven-view Late-high–Fixed Mean FG-LPIPS reduction among those seven. The respective reductions are -0.002791 **and** -0.007810**; the latter accompanies lower FG-PSNR. The displayed differences are subtle compared with the remaining reference-appearance mismatch. All PNGs are 512×512, with one shared crop per row and common mesh/UVs within each object. GT-256 is a matched reference self-bake. Row scores average eleven views, not only camera 004. Credits and selection records are in Supplementary Sections S5/S9 and the V4 source manifest.**

$[0.440, 0.733]$). A post hoc sensitivity restricted to the seven original scale/time controls gives 0.396 ($[0.175, 0.582]$), with the minimum-mean LPIPS condition changing on 11/20 objects. These are positively associated rankings with changing point-estimate winners, not general rank reversal or statistically resolved winner changes. The GT self-bake has mean LPIPS 0.0602 and PSNR 19.36 dB; average complete-bilinear-footprint coverage is about 78.7%. All foreground remains scored and GT errors are not subtracted. These losses contextualize the small method effects without defining a theoretical quality bound.

Incoming-view consistency. The bake also measures cross-camera color variance at UV texels receiving multiple source views. A constant-black control has zero variance despite its incorrect appearance, showing that this diagnostic measures incoming-view disagreement rather than fidelity. Late-high has a lower mean disagreement than Fixed Mean (-0.002448), while Fixed High has still lower disagreement and higher baked LPIPS. Resampling and overlapping UVs also affect this measure; it does not validate seams or PBR. Full controls and contrasts are in Supplementary Section S5.

Native controls and protocol sensitivity. Subsequently added Native residual and No Adapter outputs on the same ten GeoTex objects are exploratory. They retain matched geometry and GT coverage, and the repeated Constant 1.0 (capped) outputs are bitwise identical. Their apparent PSNR/LPIPS gains for the schedules do not separate under the fifteen-test exploratory family. The complete data are in Supplementary Section S5.

A supporting fifty-object comparison uses a newly trained frozen GeoTex checkpoint with 512-pixel supervision, actual positive/negative reference conditions and CFG 2. Late-high minus Fixed Mean has nonreference PSNR -1.184 dB (interval $[-1.587, -0.849]$) and LPIPS $+0.00266$ ($[-0.00003, +0.00640]$; adjusted $p = 0.080$). C3 has no corrected advantage over Fixed Mean or Fixed High. This previously studied cohort and changed checkpoint/protocol supply a sensitivity boundary, not an independent backbone confirmation. Training and full-v29 strong-baseline results remain in Supplementary Section S8.

4.5. Allocation Responses in Other Conditioning Interfaces

MV-Adapter and MVDiffusion supply different conditioning operators and scale semantics from GeoTex. We evaluate each within its native target/camera contract and do not pool their scores or interpret identical scale labels as common residual doses.

New native MV-Adapter temporal comparison. We selected fifty Fresh C inputs not previously evaluated through MV-Adapter, using input availability and native material/geometry