Supplementary Material for *Timestep-Conditioned Adapter Scaling for Multi-view Diffusion Texture Generation: Control Allocation and Baked Appearance*

Anonymous authors

This supplement supplies complete protocols, paired results and provenance limits for the main paper's controlled study of geometry-control allocation. Fresh C, native MV-Adapter, GSO and the selected bake cohorts have separate input, interface and endpoint identities. Views and seeds are averaged within objects and do not enlarge the independent sample. Historical results and invalid attempts remain available with their original limitations.

Reader map: question, study identity and evidence status

The main paper presents the central comparisons; the entries below locate their complete supporting records. "Primary" identifies a contrast within its stated protocol, not an independent replication or a shared significance family across studies. A later analysis of exposed objects remains retrospective even if its numerical calculation follows a recorded lock.

Executed intervention. S1, Table S1: Fresh C's requested schedule, native group caps and post-scale correction records. These implementation records support the main method diagram and study-design table; equal applied scalar sums are not equal realized residual dose.

Fresh C image controls. S2, Table S2: the held-out 300-object, single-checkpoint C3–Fixed Low primary and its secondary endpoints, followed by the named same-cohort addendum. Table S3 supplies the retrospective equal-applied-budget pair contrasts. The original timing-allocation primary is Middle-high minus the objectwise average of Early-high and Late-high; its separate twelve-test placement family is retained. These records support the main matched-control table and neither replace that primary nor establish universal C3 superiority.

Native MV-Adapter. S3, Table S8: fifty objects selected before new native-interface outputs, seven conditions, one specified Middle–Mean FG-PSNR primary and a separate secondary family. The objects are new to this interface, not a new Fresh C image cohort. Historical strict-276 records later in S3 have different provenance and are not pooled with this comparison.

External GSO sensitivity. S4: source-selected GSO100, native MV-Adapter, three seeds nested within each object; scheduled controls and auxiliary corrections have separately specified families. The fixed GSO20 bake study uses eleven unseen cameras per bake. Its original failure and post hoc GT-only calibration addendum remain explicit. These records support the main interface and bake-cohort tables; exposure and calibration chronology limit confirmation claims.

GeoTex baked appearance. S5, Table S20: an input-selected ten-object pilot with a specified Late–Mean LPIPS primary and four C3–Fixed High secondary tests. Old five-object and historical N=20 studies are separate. Table S26 is the additional exploratory shared-UV family. This section supports the main bake and appearance tables, including negative results and complete rights-cleared displays.

Appearance and protocol diagnostics. S6, Table S27: the selected 26-object color diagnostic, followed by controlled two-object sampling, feature, resolution and branch checks. These are failure-enriched or previously observed inputs; they do not establish a validated material repair or population prevalence.

Historical and auxiliary records. S7 preserves original schedule selection, preference, FAC negatives and the retrained historical-request panel, including its condition means (Table S36), complete paired contrasts (Table S35), and uncertified actual-UID substitution. S8 separately reports new native training, same-base follow-up, deployment cost and projection/APG exploration. Their distinct weights, cohorts and endpoints do not supply missing historical replay or method novelty.

Sources and disposition. S9 provides display credits and selection rules; S10 indexes additional attempts, invalid records and duplicate-cohort relationships. Retaining an archive entry does not create another independent experiment.

How to read inference. All confidence intervals are pointwise unless expressly stated otherwise. An adjusted p value belongs only to the named family beside that result; no study-wide family is implied across separate locks. Non-detection is not equivalence, an image metric is not physical material fidelity, and selected pictures do not estimate failure prevalence. Complete positive, negative and non-detected outcomes are retained.

Contents

Reader map: question, study identity and evidence status 1

S1. Study identities, sampling and applied-scale semantics **4**
Statistical authority and reproduction map 4
Requested/applied scale and residual-correction accounting 4

S2. Matched GeoTex controls and complete paired statistics **5**
Original applied-budget primary and separate analysis families 5
Complete Fresh C paired image-space statistics 5
Equal-applied-budget allocation and complete retrospective pair comparisons 6
Supporting layer/window and schedule evidence 8
Objectwise four-endpoint dominance: descriptive addendum 11

S3. Native MV-Adapter and historical cross-interface evaluation **11**
Frozen native MV-Adapter comparison on fifty new-to-interface objects 11
Historical and cross-interface boundaries 14

S4. GSO external-input and complete baked evaluation **21**
Complete inherited-schedule extension and twenty-object bake 21
Separate projection/APG comparison and archived original bake failure 22
Fixed-seed stability: complete descriptive addendum 23

S5. Calibrated GeoTex baked appearance and earlier attempts **24**
Calibrated bake pilot, historical separation and actual-output displays 24
Post hoc GT reference context and object influence 34
Native-wrapper controls and sampling-protocol scope 34
Complete exploratory contrast family 35

Historical N=20 unseen-view results . . . 35
Selected negative visual evidence and unresolved 3D checks . . . 36
Incoming-camera disagreement on shared UV texels . . . 37

S6. Appearance failures and executed-protocol diagnostics 38
Paired color-pathway diagnosis and failure boundaries . . . 38
Native base-pipeline protocol and two-object diagnostic . . . 39
Controlled guidance–image-feature diagnostic . . . 39
Target-resolution bridge . . . 42
Native geometry implementation and camera-contract audit . . . 42
Geometry encoding, CFG branch policy and training-lineage limits . . . 45

S7. Historical selection, preference and FAC records 48
Historical 01549 Table 9: strict-276 schedule transfer . . . 48
Historical 01549 Table 3: extended 24-object development diagnostics . . . 48
First-round FAC controlled re-examination . . . 49
Retrospective texture-complexity boundary . . . 49
Retained original fixed-scale and C3 selection displays . . . 51
Historical Fixed-Scale Image-Space Diagnostics . . . 51
C3 Development Record and Current Evaluation . . . 51
Historical cluster-aware preference study . . . 52
Recoverable FAC code and bounded component validation . . . 56
Local historical weights and the original-cohort retraining addendum . . . 56

S8. Auxiliary training, deployment and projection exploration 58
Native training inputs, numerical safeguards and fixed training protocol . . . 58
Frozen checkpoint and full-native baseline identity . . . 59
Nine-condition evaluation and full-native comparison . . . 59
Same-v29-base training and frozen exploratory follow-up . . . 60
Pixel-identical deployment performance . . . 62
Archived projection development and first-interface evaluation . . . 64

S9. Figure credits, retained displays and record index 65
Figure 1 interface and control ownership . . . 65
Figure sources, licenses and selection . . . 66
Retained C3–Fixed Low favorable and adverse examples . . . 67
Historical record index . . . 68

S10. Cross-branch experiment disposition 69

S1. Study identities, sampling and applied-scale semantics

Statistical authority and reproduction map

Each numerical result in this Supplement is mapped to the internal claim ledger and scoped result sources. The original Fresh C C3–GFL primary and the later retrospective applied-budget primary have distinct object-level delta files and analysis families; requested/applied-scale records use the per-step accounting table. Layer/window and Fresh B results are maintained in separate source summaries, with Fresh B classified as retrospective sensitivity because its lock chronology cannot be authenticated from preserved Git history. The texture-complexity cohort and the color-diagnostic set are separate from Fresh C and from each other. The historical N=20 GLB-native summary has a separate analysis record; no N=20 image assets are redistributed. Original Table 9 and Table 3 below are reproduced only as historical source text with explicit provenance limits; neither is treated as a newly verified current result.

Portable numerical authority. The current study summaries and source hashes are in `data/FACTS_round_014.json`; their endpoint and family identities must be read with the protocols below. The original retrospective applied-budget primary is reproduced in `data/original_applied_budget/VERIFIED_PRIMARY.json`. Its verified contrast, confidence interval, sign-flip test and all object deltas take precedence over a later summary's descriptive Middle–Fixed Mean designation. Complete pair tables and diagnostic summaries remain available with their separate inference scopes.

Fresh C identity details. The 300-object Fresh C list is disjoint by UID from the original eval300, including the 24-object development probe, the 1,118-object training list, and the clean-v2 eval300. The primary four-condition run and same-cohort Generic Linear/LLH addendum use the same frozen checkpoint SHA-256 `0618d6b284ab47aa16d7a89dc447f5ba4455ff6c9d918e5e129478a99e0114c0`, runner source SHA-256 `e5c28e915ba137d3541eb4c032daaf62a798332d63b32917b749fe1bcc74e9e3`, cohort, input tensors, endpoint implementation, and seed policy. The seed is $42 + \texttt{object_idx}$ and is shared across the matched conditions for each object. Primary and addendum integrity gates pass for 1,200/1,200 and 600/600 condition rows. Fresh C uses the recorded deep/middle/shallow caps of 3.0/3.5/0.8, with requested, applied, and residual scales logged separately. This is a held-out paired comparison under the stated protocol. The historical identity remains explicit: 01549 names v1 weights for its main tables and a separate v2 strong-residual, per-layer-capped instance for Section 4.7/FAC. Fresh C uses a controlled retraining and is not presented as a numerical reproduction of the old Table 4 +0.96 dB estimate.

Requested/applied scale and residual-correction accounting

Table S1 lists representative Fresh C C3 records at five denoising steps. The native caps are 3.0 (deep), 3.5 (middle), and 0.8 (shallow). A cap-active fraction of 100% means all logged records in that group/step were clipped. Raw correction L_2 depends on both the residual and tensor dimensions, so it is not compared across layer groups. The table instead reports the median of wrapper-level mean absolute entries, a dimension-normalized descriptive summary; differences in feature scales and distributions still prevent interpreting it as an equal-dose intervention or quality outcome. The 750-row source accounting table contains all 50 steps, three groups, and five strategies.

Table S1: Representative Fresh C requested/applied scale and post-scale residual-correction accounting. The final column is the median wrapper-level mean absolute correction entry; it is dimension-normalized but remains descriptive. Wrappers, objects, and timesteps are not independent experimental units.

Step	Layer group	Requested	Applied	Cap active	Median per-wrapper mean $\lvert c \rvert$
0	Deep	1.25	1.25	0%	1.4786
0	Middle	1.25	1.25	0%	0.3540
0	Shallow	1.25	0.80	100%	0.0128
12	Deep	1.25	1.25	0%	1.3969
12	Middle	1.25	1.25	0%	0.4881
12	Shallow	1.25	0.80	100%	0.0151
24	Deep	2.50	2.50	0%	2.2588
24	Middle	2.50	2.50	0%	1.1408
24	Shallow	2.50	0.80	100%	0.0169
37	Deep	1.25	1.25	0%	0.7513
37	Middle	1.25	1.25	0%	0.4596
37	Shallow	1.25	0.80	100%	0.0176
49	Deep	1.25	1.25	0%	0.7354
49	Middle	1.25	1.25	0%	0.1459
49	Shallow	1.25	0.80	100%	0.0116

S2. Matched GeoTex controls and complete paired statistics

Original applied-budget primary and separate analysis families

The original same-cohort applied-budget protocol specified Middle-high FG-PSNR minus the objectwise mean of Early-high and Late-high. Its preserved result is -0.0338775 dB, median -0.229605 dB, pointwise percentile interval $[-0.117170, +0.051422]$, raw two-sided sign-flip $p = 0.432378$, and 119/300 positive objects. The standalone verifier reproduces all 300 deltas, the exact 10,000 bootstrap draws and 20,000 sign-flip draws using seed 20261010. Middle–Fixed Mean is a separate descriptive comparison and does not replace this primary. The original twelve pairwise placement/endpoint tests use their separate Holm family. The subsequent all-pair recomputation has 50,000 resamples and a different descriptive 59-test family; its exempted Middle–Fixed Mean raw result is not the frozen primary. Neither analysis turns the exposed Fresh C addendum into independent confirmation. The original protocol, report, all 1,800 rows and twelve-test results are preserved in `data/original_applied_budget`; no source result is overwritten.

Complete Fresh C paired image-space statistics

The original Generic Linear source manifest is delivered in `data/primary_studies/GENERIC_LINEAR_SOURCE_MANIFEST_shard0.json`. Its SHA256 matches the lineage record attached to the retained Generic Linear figure. Across fifty steps, deep/middle requests ramp from 1.25 to 2.50 and shallow requests from 0.50 to 0.75. All pass the stated native caps. Applied sums are (93.75,93.75,31.25), different from C3 and the equal-budget family. This is a competitive layer/time control, not a timing-only matched-dose contrast.

Table S2 reports the complete seven-endpoint paired results for C3–GFL and each of the three named addendum contrasts. The primary C3–GFL FG-PSNR result is unadjusted as the single registered primary endpoint. The six registered secondary C3–GFL endpoints use their Holm family. The addendum's FG-PSNR and FG-LPIPS contrasts use the frozen six-test primary family; the other five endpoints per contrast use the separate 15-test secondary Core-7 family. All contrasts are mean A-minus-B differences with 10,000 object bootstrap resamples and pointwise two-sided percentile 95% CIs. Positive values favour A for PSNR/SSIM; negative values favour A for LPIPS. Adjusted p-values

are from the frozen analysis authority. "A favourable" is the fraction of object-level differences in A's favourable direction and is descriptive.

Table S2: Complete paired object-level image-space results for the primary C3–GFL contrast and the three named same-cohort addendum contrasts. Differences are A minus B; favorable-object percentages respect endpoint direction.

Endpoint	Mean	95% CI	Median	A favorable	Adjusted p
C3 minus GFL					
FG-PSNR (dB)	+0.522	[+0.404, +0.641]	+0.555	68.7%	primary
FG-LPIPS	−0.005345	[−0.006326, −0.004403]	−0.004547	71.0%	3.2×10^{-22}
FG-SSIM	+0.02453	[+0.02120, +0.02805]	+0.02004	84.3%	5.9×10^{-33}
Edge-SSIM	+0.004494	[+0.003411, +0.005586]	+0.003613	69.0%	9.4×10^{-14}
Full-view PSNR (dB)	+0.271	[+0.170, +0.373]	+0.220	59.3%	4×10^{-07}
Full-view LPIPS	−0.003880	[−0.004926, −0.002873]	−0.003029	64.3%	8×10^{-13}
Full-view SSIM	+0.005619	[+0.004627, +0.006704]	+0.005205	83.0%	7.9×10^{-22}
C3 minus Generic Linear					
FG-PSNR (dB)	−0.593	[−0.837, −0.351]	+0.074	51.7%	7.2×10^{-06}
FG-LPIPS	+0.013512	[+0.011601, +0.015487]	+0.012229	25.7%	1.3×10^{-32}
FG-SSIM	−0.02810	[−0.03197, −0.02439]	−0.02521	20.0%	2.9×10^{-35}
Edge-SSIM	−0.010693	[−0.013004, −0.008495]	−0.008967	33.7%	1.6×10^{-17}
Full-view PSNR (dB)	−0.503	[−0.686, −0.322]	−0.139	46.7%	2.7×10^{-07}
Full-view LPIPS	−0.000897	[−0.002578, +0.000862]	−0.001307	54.3%	0.611
Full-view SSIM	+0.000046	[−0.000984, +0.001011]	+0.001213	57.0%	0.927
LLH minus C3					
FG-PSNR (dB)	+0.621	[+0.391, +0.855]	−0.153	46.7%	1.2×10^{-06}
FG-LPIPS	−0.012140	[−0.013861, −0.010480]	−0.010837	75.0%	9×10^{-34}
FG-SSIM	+0.01658	[+0.01311, +0.02003]	+0.01307	67.0%	9×10^{-18}
Edge-SSIM	+0.009033	[+0.006867, +0.011296]	+0.006741	63.3%	2.3×10^{-13}
Full-view PSNR (dB)	+0.816	[+0.639, +0.998]	+0.419	59.3%	3.2×10^{-16}
Full-view LPIPS	+0.004909	[+0.003266, +0.006510]	+0.004538	36.7%	3.5×10^{-08}
Full-view SSIM	−0.004330	[−0.005176, −0.003482]	−0.004563	27.7%	5.9×10^{-20}
LLH minus Generic Linear					
FG-PSNR (dB)	+0.028	[−0.015, +0.070]	+0.017	52.3%	0.201
FG-LPIPS	+0.001372	[+0.000762, +0.002081]	+0.000176	46.7%	0.000114
FG-SSIM	−0.01152	[−0.01337, −0.00996]	−0.00945	8.0%	2.6×10^{-31}
Edge-SSIM	−0.001660	[−0.002096, −0.001256]	−0.001648	27.3%	1.2×10^{-12}
Full-view PSNR (dB)	+0.313	[+0.278, +0.347]	+0.304	87.3%	2×10^{-47}
Full-view LPIPS	+0.004011	[+0.003390, +0.004684]	+0.003904	18.0%	1.7×10^{-26}
Full-view SSIM	−0.004284	[−0.005217, −0.003543]	−0.003432	5.7%	8.5×10^{-20}

Equal-applied-budget allocation and complete retrospective pair comparisons

The same-cohort GeoTex addendum contains 300 objects by six conditions, 1,800 rows. Each object uses the same initial latent, input tensors and checkpoint across conditions. Early-, Middle- and Late-high use 16 high updates at 0–15, 17–32 and 34–49. Low/high are 1.25/2.50, Fixed Mean is 1.65, and the native shallow cap is 0.8. Their exact applied per-group sums are 82.5, 82.5 and 40. This comparison measures the total effect of allocating the high segment at equal applied scalar budget. Evolving residual norms are outcomes of the trajectory; lack of equal residual norms limits a mechanism interpretation, not validity of the allocation contrast. The study is post-inspection on the already evaluated Fresh C objects, not an independent confirmation.

Table S3: Selected paired contrasts from the 300-object equal-budget addendum. Mean A minus B and pointwise 95% object-bootstrap interval (50,000 resamples). The other 59 pair–metric contrasts form one post hoc Holm family; no interval is multiplicity-adjusted.

Contrast	Endpoint	Mean [95% CI]	Holm p
Middle − Fixed Applied Mean	fg-psnr	-0.13326 $[-0.16979, -0.09622]$	1e-05 (raw)
Middle − Fixed Applied Mean	fg-lpips	$+0.00199$ $[+0.00147, +0.00254]$	0.00059
Middle − Fixed Applied Mean	fg-ssim	-0.01185 $[-0.01347, -0.01025]$	0.00059
Middle − Fixed Applied Mean	edge-ssim	-0.00703 $[-0.00764, -0.00643]$	0.00059
Middle − Late-high	fg-psnr	-0.56395 $[-0.63408, -0.49427]$	0.00059
Middle − Late-high	fg-lpips	$+0.00466$ $[+0.00381, +0.00553]$	0.00059
Middle − Late-high	fg-ssim	-0.00422 $[-0.00694, -0.00139]$	0.01375
Middle − Late-high	edge-ssim	-0.01409 $[-0.01526, -0.01291]$	0.00059
Middle − Early-high	fg-psnr	$+0.49619$ $[+0.37195, +0.62282]$	0.00059
Middle − Early-high	fg-lpips	-0.00472 $[-0.00568, -0.00378]$	0.00059
Middle − Early-high	fg-ssim	$+0.00499$ $[+0.00211, +0.00809]$	0.00432
Middle − Early-high	edge-ssim	$+0.00080$ $[-0.00008, +0.00170]$	0.1565
Middle − Fixed High	fg-psnr	-0.74767 $[-0.88995, -0.60691]$	0.00059
Middle − Fixed High	fg-lpips	$+0.01070$ $[+0.00889, +0.01255]$	0.00059
Middle − Fixed High	fg-ssim	-0.04553 $[-0.04937, -0.04165]$	0.00059
Middle − Fixed High	edge-ssim	-0.01881 $[-0.02083, -0.01678]$	0.00059

The later recomputation exempts its named Middle–Fixed Mean FG-PSNR contrast and shows a raw p; the remaining 59 contrasts use its separate post hoc Holm family. This descriptive exemption is not a preregistered primary designation. The preserved original Middle–average(Early,Late) primary and twelve-test placement family are reported separately above. All are retrospective. The rank counts in main matched-budget table are not cross-metric superiority tests.

Default-path identity across interfaces. For GeoTex, explicit requested scale 1.0 and an unset scale are different: the cap is applied only when the scale attribute exists. Executing the actual wrapper with a unit residual gives deep/middle/shallow applied factors (1,1,0.8) for explicit 1.0, versus (1,1,1) when unset. The stored condition name `native_default_1x` therefore denotes Constant 1.0 (capped), not an unmodified pipeline. This is a wrapper-level counterexample, not a claim of full-pipeline pixel equality. In contrast, the new MV-Adapter identity gate compares three textured meshes and 18 images: official default, deployed default and a constant-1 schedule produce bitwise-identical RGB pixels, condition-encoder features and injected residuals. The 13 texture-absent MV-Adapter inputs use the documented geometry-only loader compatibility branch; their targets are constant white albedo and remain in the primary cohort.

Supporting layer/window and schedule evidence

A2 is exploratory discovery evidence; A3 is a higher-dose stress regime on the same underlying cohort. A3b is a bounded Fresh B layer/window analysis. Object-cluster tests detect response heterogeneity under the tested interventions, but they do not identify a dose-independent layer-by-time mechanism or an optimal schedule.

Table S4: Object-cluster Wald interaction summaries for the tested layer-by-window maps. Cell RMSE and interaction share describe these observed maps; they are not causal effect sizes.

Map	Endpoint	Wald statistic	Interaction share; cell RMSE	Wald p (A3b Holm)
A2	FG-LPIPS	481.081	43.5%; 0.001695	8.04×10^{-99}
A2	FG-PSNR	1879.963	56.8%; 0.1222 dB	$< 10^{-300}$
A3	FG-LPIPS	657.237	11.9%; 0.00643	1.14×10^{-136}
A3	FG-PSNR	1389.118	0.8%; 0.207 dB	1.28×10^{-294}
A3b	FG-LPIPS	225.015	14.0%; 0.000342	5.37×10^{-43}
A3b	FG-PSNR	525.700	36.0%; 0.0205 dB	3.43×10^{-107}

The earlier A3b common-support calculation compared 10-step integrated raw L_2 norms across three layer groups. Because the saved correction tensors have different spatial resolutions (24×16, 48×32, and 96×64) and the traces omit channel counts, absolute norms are dimension-dependent across groups. We withdraw the central-90% intervals and 0/2,250 overlap as cross-group dose-support evidence. The earlier development calibration also used cross-layer raw L_2 and is not interpreted as equal-dose targeting. The fixed A3b scale values remain the tested bounded profiles. A3b remains retrospective sensitivity evidence: its map describes response heterogeneity under the tested interventions, but does not identify a dose-independent layer-by-window effect.

The separate Fresh B cohort ($N = 150$) supplies schedule-location context for LLH, not evidence for C3. Table S5 preserves both registered LLH comparisons and the post-outcome HLL–LLL diagnostic. Paired intervals use 10,000 object-bootstrap resamples (seed 20261002). The LLH–LFM-EXACT intervals lie within the protocol's practical margins (FG-PSNR ±0.5 dB; FG-LPIPS ±0.01); this is a budget-explained interpretation within those margins, not exact equality. HLL–LLL is exploratory and its endpoint directions differ.

The Fresh B protocol-lock file states a freeze time of 2026-10-05 08:40 UTC, while the earliest preserved commit containing that file is dated 2026-10-06 00:52 UTC; its parent does not contain the file. This history does not establish when the lock was first created outside Git, but it cannot authenticate pre-run availability. Accordingly, Fresh B temporal contrasts, the A3b map, and the post-lock generic extension are treated as retrospective sensitivity evidence in this paper, even where their calculations follow the recorded comparison family. They are not described as verified preregistered confirmation.

The post-lock generic-schedule extension on this same Fresh B cohort is a retrospective sensitivity analysis, not independent confirmation. Table S6 reports the recorded budget-matched comparisons and endpoint-matched linear counter-result. Nominal requested-scale means do not equalize post-scale residual dose; these LLH comparisons do not establish dose-adjusted schedule superiority or strengthen C3 specifically.

Table S5: Fresh B paired object-level LLH comparisons, classified here as retrospective sensitivity because pre-run lock availability cannot be authenticated from the preserved history. Effects are A minus B; favorable rates respect endpoint direction. Holm values reproduce the recorded family.

Contrast	Endpoint	Mean [95% CI]	A favors	p / status
LLH–LFM-EXACT	FG-PSNR	$+0.325$ [$+0.209$,$+0.446$] dB	54.0%	raw ≤ 0.0001
LLH–LFM-EXACT	FG-LPIPS	-0.00460 [$-0.00563, -0.00357$]	76.0%	raw ≤ 0.0001
LLH–HLL	FG-PSNR	$+0.687$ [$+0.404$,$+0.981$] dB	45.3%	≤ 0.0004; median -0.104 dB
LLH–HLL	FG-LPIPS	-0.01098 [$-0.01349, -0.00851$]	80.7%	≤ 0.0004
LLH–LLL	FG-PSNR	$+0.734$ [$+0.597$,$+0.875$] dB	79.3%	≤ 0.0004
LLH–LLL	FG-LPIPS	-0.00845 [$-0.01029, -0.00659$]	82.0%	≤ 0.0004
HLL–LLL (exploratory)	FG-PSNR	$+0.047$ [$-0.120, +0.208$] dB	66.0%	0.5696; median $+0.476$ dB
HLL–LLL (exploratory)	FG-LPIPS	$+0.00253$ [$+0.00155$,$+0.00354$]	40.0%	≤ 0.0002; median $+0.00139$

Table S6: Post-lock Fresh B generic-schedule extension (same $N = 150$ cohort). Effects are LLH minus comparator. Budget-matched schedules form the locked eight-schedule family; endpoint-matched linear is the registered counter-comparison.

Contrast	Endpoint	Mean [95% CI]	A favors	Holm p
LLH–budget linear	FG-PSNR	+0.0967 [+0.0594,+0.1357] dB	65.3%	Holm $p \leq 0.0008$
LLH–budget linear	FG-LPIPS	-0.0009 [-0.0013,-0.0004]	65.3%	Holm $p = 0.0008$
LLH–budget cosine	FG-PSNR	+0.4629 [+0.3526,+0.5780] dB	74.7%	Holm $p \leq 0.0008$
LLH–budget cosine	FG-LPIPS	-0.0059 [-0.0071,-0.0046]	80.0%	Holm $p \leq 0.0008$
LLH–budget trapezoid	FG-PSNR	+0.4404 [+0.3334,+0.5521] dB	74.0%	Holm $p \leq 0.0008$
LLH–budget trapezoid	FG-LPIPS	-0.0057 [-0.0070,-0.0045]	78.0%	Holm $p \leq 0.0008$
LLH–budget Gaussian	FG-PSNR	+0.4711 [+0.3584,+0.5892] dB	74.7%	Holm $p \leq 0.0008$
LLH–budget Gaussian	FG-LPIPS	-0.0058 [-0.0071,-0.0045]	79.3%	Holm $p \leq 0.0008$
LLH–endpoint linear	FG-PSNR	-0.0373 [-0.0829,+0.0086] dB	–	Holm $p = 0.1150$
LLH–endpoint linear	FG-LPIPS	+0.00109 [+0.0004,+0.0019]	–	Holm $p = 0.0024$

Objectwise four-endpoint dominance: descriptive addendum

The five controls in the complete matched six-condition matrix are compared with C3 on the recorded FG-PSNR, foreground LPIPS, FG-SSIM and Edge-SSIM composite values. A control weakly dominates C3 if it is no worse on all four and better on at least one. LPIPS is reversed when forming the comparison. We use no effect threshold or fitted quality score. This is a post-inspection analysis of point estimates, not inference that every object has a resolved quality winner.

Table S7: Fresh C300: all four-endpoint pairwise dominance counts. Incomparable/equal includes competing endpoint directions. Counts use the complete object matrix.

Control	Dominates C3	C3 dominates	Incomparable/equal
Fixed Low	28	156	116
Fixed High	173	16	111
Fixed Applied Mean	143	4	153
Early-high	48	90	162
Late-high	122	1	177

At least one other control dominates C3 on 270/300 objects (90.0%; descriptive object-bootstrap interval [86.3,93.3]%). This fraction is over the tested controls and endpoints, not the fraction with failed materials or a confidence level for overall superiority. C3 can dominate a particular fixed control while another control dominates C3. The supplied per-object Boolean matrix permits independent reconstruction of the union count. All five pairs, including cases favoring C3, are retained.

S3. Native MV-Adapter and historical cross-interface evaluation

Frozen native MV-Adapter comparison on fifty new-to-interface objects

The protocol was internally frozen before new scheduled outputs; it is not a public preregistration. Fifty inputs were selected in UID order from Fresh C after excluding every recorded previously inspected MV-Adapter UID. Selection uses available inputs and native geometry/material criteria, not quality or parameter search. Seeds are 20261010 + index, shared across conditions. Six native-camera 512-pixel images use 50 DDPM-shift updates, CFG 3, reference strength 1 and the frozen high-quality text prompt. All 350 rows completed. Models, input identities, runner, native-target calibration and per-step residual traces are indexed in the reproduction archive.

Early-, Middle- and Late-high use high=1 over steps 0–15, 17–32 and 34–49 respectively, with low=0.75 elsewhere. Fixed Mean=0.83 and Generic Linear spans 0.75–0.91 inclusively; each sums to 41.5 per feature, whereas Native/Fixed High sums to 50 and Fixed Low to 37.5. These are feature-scaling controls on MV-Adapter, not GeoTex's per-ResNet capped residual doses.

Official/deployed default and constant-1 scheduled paths match exactly on three textured new objects, including 18 RGB images, encoded conditions and injected residuals. Native target geometry positions/masks match the control rasterization for all fifty inputs; an independent CPU bilinear source-UV sample agrees within the frozen tolerance. Thirteen texture-absent assets use geometry-only compatibility loading and white target albedo; they remain in the primary fifty. The 37-object textured subset is descriptive. It does not create a second primary or substitute after observing outcomes.

The primary Middle-high–Fixed Mean FG-PSNR mean is +0.02899 dB, 95% CI [−0.01941, +0.08074], Monte Carlo sign-flip $p = 0.28075$ (100,000 draws, plus-one correction); 29/50 favor Middle. Intervals use 50,000 object resamples. The other 104 contrasts (21 condition pairs by five endpoints, minus primary) form one predeclared Holm family; intervals remain pointwise. No non-inferiority or architecture-causal claim follows from a non-separated contrast.

Table S8: Complete native fifty-object pair–metric contrasts. A minus B; lower LPIPS/CIEDE2000 and higher other endpoints are favorable. p is Holm-adjusted except the single primary marked raw.

A – B	Endpoint	Mean [95% CI]	p
High – Low	fg-psnr	−0.12682 [−0.24503, −0.02980]	0.85601
High – Low	fg-lpips	+0.00100 [−0.00197, +0.00592]	1.00000
High – Low	fg-ssim	−0.00250 [−0.00594, +0.00029]	1.00000
High – Low	edge-ssim	+0.00511 [+0.00114, +0.00979]	0.85601
High – Low	ciede2000	+0.44730 [+0.13967, +0.87441]	0.20880
High – Mean	fg-psnr	−0.08309 [−0.16282, −0.02065]	0.78170
High – Mean	fg-lpips	+0.00013 [−0.00120, +0.00214]	1.00000
High – Mean	fg-ssim	−0.00268 [−0.00534, −0.00051]	1.00000
High – Mean	edge-ssim	+0.00163 [−0.00023, +0.00339]	1.00000
High – Mean	ciede2000	+0.33298 [+0.10737, +0.65171]	0.13932
High – Early	fg-psnr	+0.00563 [−0.03952, +0.05131]	1.00000
High – Early	fg-lpips	−0.00158 [−0.00243, −0.00081]	0.01649
High – Early	fg-ssim	+0.00002 [−0.00176, +0.00171]	1.00000
High – Early	edge-ssim	+0.00228 [−0.00040, +0.00477]	1.00000
High – Early	ciede2000	+0.03229 [−0.06895, +0.13756]	1.00000
High – Middle	fg-psnr	−0.11208 [−0.22257, −0.02534]	0.89608
High – Middle	fg-lpips	+0.00175 [−0.00105, +0.00664]	1.00000
High – Middle	fg-ssim	−0.00200 [−0.00524, +0.00047]	1.00000
High – Middle	edge-ssim	+0.00562 [+0.00250, +0.00961]	0.02112
High – Middle	ciede2000	+0.41481 [+0.13251, +0.81706]	0.14875
High – Late	fg-psnr	−0.14046 [−0.25619, −0.04753]	0.26910
High – Late	fg-lpips	+0.00203 [−0.00108, +0.00734]	1.00000
High – Late	fg-ssim	−0.00341 [−0.00673, −0.00079]	0.87002
High – Late	edge-ssim	+0.00119 [−0.00198, +0.00545]	1.00000
High – Late	ciede2000	+0.47923 [+0.17811, +0.90198]	0.05490
High – Linear	fg-psnr	−0.12216 [−0.22718, −0.04049]	0.22752
High – Linear	fg-lpips	+0.00174 [−0.00098, +0.00639]	1.00000
High – Linear	fg-ssim	−0.00309 [−0.00618, −0.00068]	0.90959
High – Linear	edge-ssim	+0.00243 [−0.00040, +0.00605]	1.00000
High – Linear	ciede2000	+0.42004 [+0.14924, +0.81173]	0.05005
Low – Mean	fg-psnr	+0.04373 [−0.00118, +0.09206]	1.00000
Low – Mean	fg-lpips	−0.00087 [−0.00381, +0.00085]	1.00000
Low – Mean	fg-ssim	−0.00017 [−0.00118, +0.00090]	1.00000
Low – Mean	edge-ssim	−0.00348 [−0.00757, −0.00081]	0.36480
Low – Mean	ciede2000	−0.11432 [−0.24502, −0.00126]	1.00000
Low – Early	fg-psnr	+0.13245 [+0.04720, +0.24287]	0.15288
Low – Early	fg-lpips	−0.00258 [−0.00777, +0.00036]	1.00000
Low – Early	fg-ssim	+0.00253 [+0.00006, +0.00594]	1.00000
Low – Early	edge-ssim	−0.00283 [−0.00657, −0.00016]	1.00000
Low – Early	ciede2000	−0.41501 [−0.81018, −0.14622]	0.04876
Low – Middle	fg-psnr	+0.01475 [−0.01731, +0.04840]	1.00000
Low – Middle	fg-lpips	+0.00075 [+0.00030, +0.00122]	0.17384
Low – Middle	fg-ssim	+0.00050 [−0.00056, +0.00160]	1.00000
Low – Middle	edge-ssim	+0.00051 [−0.00072, +0.00181]	1.00000
Low – Middle	ciede2000	−0.03249 [−0.10291, +0.03715]	1.00000
Low – Late	fg-psnr	−0.01363 [−0.02840, +0.00083]	1.00000
Low – Late	fg-lpips	+0.00103 [+0.00051, +0.00167]	0.00800
Low – Late	fg-ssim	−0.00091 [−0.00156, −0.00021]	0.79142
Low – Late	edge-ssim	−0.00392 [−0.00547, −0.00234]	0.00303
Low – Late	ciede2000	+0.03193 [+0.00504, +0.05951]	1.00000
Low – Linear	fg-psnr	+0.00467 [−0.02786, +0.03373]	1.00000
Low – Linear	fg-lpips	+0.00074 [+0.00032, +0.00118]	0.09680
Low – Linear	fg-ssim	−0.00058 [−0.00154, +0.00033]	1.00000
Low – Linear	edge-ssim	−0.00267 [−0.00418, −0.00118]	0.10701
Low – Linear	ciede2000	−0.02726 [−0.09723, +0.04844]	1.00000
Mean – Early	fg-psnr	+0.08872 [+0.03375, +0.16183]	0.07565
Mean – Early	fg-lpips	−0.00171 [−0.00411, −0.00028]	0.42750
Mean – Early	fg-ssim	+0.00270 [+0.00064, +0.00545]	0.78170
Mean – Early	edge-ssim	+0.00065 [−0.00092, +0.00210]	1.00000
Mean – Early	ciede2000	−0.30069 [−0.59160, −0.11032]	0.02280
Middle – Mean	fg-psnr	+0.02899 [−0.01941, +0.08074]	0.28075 (raw)

A – B	Endpoint	Mean [95% CI]	p
Mean – Middle	fg-lpips	+0.00162 [−0.00005, +0.00462]	1.00000
Mean – Middle	fg-ssim	+0.00067 [−0.00064, +0.00204]	1.00000
Mean – Middle	edge-ssim	+0.00399 [+0.00170, +0.00764]	0.00104
Mean – Middle	ciede2000	+0.08184 [−0.02823, +0.20315]	1.00000
Mean – Late	fg-psnr	−0.05737 [−0.10476, −0.01422]	0.85601
Mean – Late	fg-lpips	+0.00190 [−0.00003, +0.00530]	1.00000
Mean – Late	fg-ssim	−0.00074 [−0.00183, +0.00031]	1.00000
Mean – Late	edge-ssim	−0.00044 [−0.00301, +0.00363]	1.00000
Mean – Late	ciede2000	+0.14625 [+0.03581, +0.27574]	0.87002
Mean – Linear	fg-psnr	−0.03907 [−0.07392, −0.01081]	0.57941
Mean – Linear	fg-lpips	+0.00161 [+0.00009, +0.00434]	1.00000
Mean – Linear	fg-ssim	−0.00041 [−0.00129, +0.00045]	1.00000
Mean – Linear	edge-ssim	+0.00081 [−0.00123, +0.00410]	1.00000
Mean – Linear	ciede2000	+0.08707 [+0.01651, +0.17259]	1.00000
Early – Middle	fg-psnr	−0.11771 [−0.23017, −0.02649]	0.98234
Early – Middle	fg-lpips	+0.00333 [+0.00036, +0.00863]	0.57941
Early – Middle	fg-ssim	−0.00203 [−0.00568, +0.00081]	1.00000
Early – Middle	edge-ssim	+0.00334 [+0.00057, +0.00690]	1.00000
Early – Middle	ciede2000	+0.38253 [+0.11622, +0.76613]	0.19845
Early – Late	fg-psnr	−0.14609 [−0.25687, −0.06083]	0.03572
Early – Late	fg-lpips	+0.00361 [+0.00036, +0.00933]	0.80715
Early – Late	fg-ssim	−0.00344 [−0.00694, −0.00080]	0.80715
Early – Late	edge-ssim	−0.00109 [−0.00429, +0.00294]	1.00000
Early – Late	ciede2000	+0.44694 [+0.17823, +0.84174]	0.01089
Early – Linear	fg-psnr	−0.12778 [−0.22984, −0.04995]	0.03572
Early – Linear	fg-lpips	+0.00332 [+0.00045, +0.00838]	0.31416
Early – Linear	fg-ssim	−0.00311 [−0.00648, −0.00061]	1.00000
Early – Linear	edge-ssim	+0.00016 [−0.00259, +0.00353]	1.00000
Early – Linear	ciede2000	+0.38776 [+0.14561, +0.75366]	0.01176
Middle – Late	fg-psnr	−0.02838 [−0.05857, −0.00004]	1.00000
Middle – Late	fg-lpips	+0.00028 [−0.00018, +0.00080]	1.00000
Middle – Late	fg-ssim	−0.00141 [−0.00243, −0.00042]	0.66671
Middle – Late	edge-ssim	−0.00443 [−0.00568, −0.00316]	0.00104
Middle – Late	ciede2000	+0.06442 [−0.00064, +0.12764]	1.00000
Middle – Linear	fg-psnr	−0.01008 [−0.04413, +0.02065]	1.00000
Middle – Linear	fg-lpips	−0.00001 [−0.00041, +0.00033]	1.00000
Middle – Linear	fg-ssim	−0.00109 [−0.00220, −0.00019]	1.00000
Middle – Linear	edge-ssim	−0.00318 [−0.00412, −0.00227]	0.00104
Middle – Linear	ciede2000	+0.00523 [−0.07199, +0.08600]	1.00000
Late – Linear	fg-psnr	+0.01830 [−0.01050, +0.04259]	1.00000
Late – Linear	fg-lpips	−0.00029 [−0.00101, +0.00020]	1.00000
Late – Linear	fg-ssim	+0.00033 [−0.00046, +0.00100]	1.00000
Late – Linear	edge-ssim	+0.00125 [+0.00038, +0.00194]	0.15288
Late – Linear	ciede2000	−0.05919 [−0.12493, +0.00991]	1.00000

Table S9: Descriptive 37-object textured subset, retained separately from the primary fifty. No subset inference is promoted to confirmation.

Condition	PSNR	LPIPS	SSIM	Edge-SSIM	CIEDE2000
High	14.06	0.1159	0.4354	0.3239	18.04
Low	14.14	0.1170	0.4345	0.3174	17.82
Mean	14.11	0.1165	0.4356	0.3204	17.87
Early	14.06	0.1168	0.4345	0.3182	17.99
Middle	14.12	0.1165	0.4347	0.3182	17.84
Late	14.16	0.1164	0.4359	0.3233	17.79
Linear	14.14	0.1164	0.4360	0.3217	17.82

Historical and cross-interface boundaries

Superseded native-camera quality panel. The earlier seven-object MV-Adapter temporal archive passed source-path identity, but used Fresh C targets with a different mesh normalization and orthographic range. In an input-only native geometry audit, one object's six foreground IoUs were about 0.21–0.61. Its old quality estimates are therefore not validated native-camera cross-backbone evidence; the original identity test remains valid. The new targets use the exact native mesh loader, orthographic cameras and nvdiffrast rasterizer, with a source embedded base-color texture and white background. This is unlit albedo, not a claim of PBR or source-render lighting equivalence.

The completed `MAIN-STAGE-276` follow-up contains 1,104 records (276 objects by four schedules), with 50 Euler steps, seed 42, unique-six target views, shared initial latents, and a common runner within the run. Its final run manifest records completion with exit code 0. The follow-up was specified after inspection of earlier clean-v2 results and was not blind. It is reported separately from Fresh C and is not an independent replication of the original 01549 development probe.

Here, temporal L–L–H means that the requested values are low in early and middle steps and high in late steps. This is distinct from the layer-conditioned Fresh C LLH addendum condition described in the main paper. With 50 steps, the code assigns 17/16/17 steps to early/middle/late. C3 therefore has deep/middle applied-scale sums of 82.5; temporal L–L–H has 83.75 because its high stage occupies 17 rather than 16 steps; the shallow applied sum is 40 for both after the 0.8 cap. The fixed-mean comparator has a deep/middle sum of 83.33 and a shallow sum of 40. These are near-matched scalar sums, not exactly equal sums or matched residual-norm doses.

Table S10 gives all six formal paired endpoints for C3 versus temporal L–L–H and C3 versus the fixed-mean comparator. Effects are C3 minus comparator; positive values favor C3 for PSNR/SSIM, and negative values favor C3 for LPIPS. Temporal L–L–H outperforms C3 on all six formal endpoints in this post-inspection stage-placement experiment: it has higher PSNR/SSIM and lower LPIPS endpoints. In contrast, C3 exceeds fixed-mean on five of six formal endpoints. These results show that the measured response varies with tested stage placement; they do not establish a universal schedule winner. The contrasts do not isolate placement from the small applied-scale-sum differences or the resulting residual-state trajectory, and post-scale residual norms are not matched.

Table S10: Formal paired comparisons from the strict-276 stage-placement follow-up. Effects are C3 minus comparator; 95% percentile-bootstrap intervals are object-level.

Contrast	Endpoint	Mean difference [95% CI]
C3 minus temporal L–L–H		
	Full-view PSNR (dB)	-0.268100 $[-0.311101, -0.227797]$
	FG-PSNR (dB)	-0.177084 $[-0.230539, -0.130784]$
	FG-SSIM	-0.008851 $[-0.011455, -0.006291]$
	Edge-SSIM	-0.035301 $[-0.036581, -0.034031]$
	FG-LPIPS	$+0.001896$ $[+0.001205, +0.002578]$
	Full-view LPIPS	$+0.008658$ $[+0.007465, +0.009831]$
C3 minus fixed-mean		
	Full-view PSNR (dB)	$+0.556369$ $[+0.525520, +0.589220]$
	FG-PSNR (dB)	$+0.502875$ $[+0.462018, +0.542244]$
	FG-SSIM	$+0.032083$ $[+0.028966, +0.035172]$

Contrast	Endpoint	Mean difference [95% CI]
	Edge-SSIM	$+0.001696$ $[+0.000611, +0.002782]$
	FG-LPIPS	-0.003797 $[-0.004341, -0.003260]$
	Full-view LPIPS	$+0.001420$ $[+0.000778, +0.002072]$

The saved-artifact Full-SSIM branch is kept separate from the formal pre-save metrics above: C3 minus temporal L–L–H is -0.001697 (95% CI $[-0.002047, -0.001340]$); C3 minus fixed-mean is $+0.007486$ ($[+0.006736, +0.008262]$). These saved-artifact values are not pooled with the formal metric column.

A retrospective strict-276 Core-7 summary uses the clean-v2 object list (SHA-256 `a6aa8ab6e475763e1b5e67dc8c712ec8f1940e3952d65897c820887554bbd044`) and the same recorded checkpoint SHA as Fresh C. It shares the 276-object cohort/checkpoint lineage with the separate `MAIN-STAGE-276` profile-placement follow-up, so those results are not independent cohort replications. The row audit verifies 276 unique object indices per condition and identical object labels by index. However, Core-7 does not establish one common runner or fully shared inputs across all seven conditions: No Adapter and GFH are the two newly rerun arms with per-object input-tensor hashes; their recorded runner hash is `ae5d5664e7d0ebcd4bd84c7c7d688c4a8962c6d74463fe88e7a866404911e7e0`. C3 records a different runner hash, `d4af0c1d7f42168a585b505a6d775ea3ff7ffb18345156ebf358f272025fa7f2`; GFL and the three layer conditions do not establish the same runner hash, and their serialized rows do not contain per-object input-tensor hashes. Thus Core-7 is a retrospective diagnostic, not a same-runner confirmatory comparison. It is not pooled with Fresh C, and the shared checkpoint hash does not make it a numerical reproduction of the original 01549 Table 4 result.

Table S11 gives the seven-condition means for the requested image-space endpoints. These stored metrics show an endpoint trade-off: C3 has a higher Full-view PSNR mean than GFH but a lower FG-PSNR mean. The Core-7 Layer LLH row is distinct from Fresh C's layer-conditioned LLH addendum and Fresh B's temporal LLH condition. Table S12 reports selected object-indexed contrasts. C3–GFH intervals were recalculated from the serialized per-object rows after inspection of the Core-7 summary; they are post-hoc, nominal pointwise intervals. The other listed contrasts reproduce the separate Core-7 paired-statistics file. The intervals describe the saved metric rows and do not overcome the common-runner/input-hash limitations.

Table S11: Retrospective Core-7 strict-276 condition means. Rows contain 276 object-level metrics per condition. The collection has incomplete common runner/input identity as described above; means are descriptive and are not Fresh C or an independently verified same-runner comparison.

Condition	Full-view PSNR↑	FG-PSNR↑	FG-LPIPS↓	FG-SSIM↑	Edge-SSIM↑
No Adapter	10.563	8.826	0.2059	0.4799	0.4794
GFL	18.229	10.731	0.1917	0.3987	0.5201
GFH	18.242	13.153	0.1677	0.4783	0.5538
C3	18.968	11.939	0.1817	0.4296	0.5278
Layer Fixed Mean	19.516	13.100	0.1698	0.4550	0.5363
Layer LHL	19.635	12.974	0.1719	0.4445	0.5273
Layer LLH	20.828	13.975	0.1610	0.4620	0.5476

The frozen MV-Adapter layer/window probe analyzed 98 of 99 planned objects; the omitted input was a GLB with path geometry and no triangle faces, so no substitute was used. Its production additive-residual bootstrap had an invalid null and is not used for interaction inference. The post hoc object-cluster robust Wald reanalysis found no interaction surviving its exploratory four-metric Holm correction (FG-LPIPS Holm $p = 0.303$; PSNR $p = 0.868$; FG-SSIM $p = 0.156$; CIEDE2000 $p = 0.862$). This does not establish absence of interaction or equivalence.

Table S12: Selected retrospective Core-7 paired contrasts (first condition minus second). Intervals are pointwise 95% object-bootstrap percentile intervals with 10,000 resamples and seed 20260930; they are unadjusted and descriptive. The C3–GFH intervals were recalculated post hoc. The final column counts objects where the first condition is favorable for PSNR.

Contrast	Endpoint	Mean difference [95% CI] (dB)	Objects favoring first
C3–GFH	Full-view PSNR	$+0.725229$ $[+0.647134, +0.806467]$	240/276
C3–GFH	FG-PSNR	-1.214235 $[-1.313952, -1.114705]$	25/276
C3–GFL	FG-PSNR	$+1.207771$ $[+1.116967, +1.294989]$	259/276
LLH–GFH	FG-PSNR	$+0.822292$ $[+0.616795, +1.033035]$	148/276
LLH–C3	FG-PSNR	$+2.036527$ $[+1.806804, +2.260756]$	227/276

A separate 76-object Exact-holdout MV-Adapter panel adds layer-wise fixed, L–HL, and L–LH outputs to existing global controls. It scales condition-guider features before UNet down-block residual injection and does not reproduce the GeoTex ResNet residual interface. The wrapper matched the existing global runner bitwise in a 3-object identity audit, but this is not an identity comparison against the unmodified official pipeline at native scale. Table S13 gives the seven condition means and Table S14 gives all five paired contrasts across six endpoints. Layer-wise/global mean differences are metric-dependent; object medians and favorable fractions also vary. Within-profile temporal comparisons show one pointwise interval excluding zero in each comparison, with the other five including zero. These 30 intervals are unadjusted and descriptive. The protocol and result files first appear in one preserved commit, so we classify this analysis as retrospective sensitivity rather than confirmation. It establishes neither equivalence nor transfer of TCAS.

The MVDiffusion schedule panel contains 525 object-condition rows: seven conditions over the same 75 objects. All six scheduled-condition per-object CSVs match their rows in the combined panel. The runs generated 12-view output grids; the frozen metric manifest scores six target views per object. The archived paired-bootstrap output used positive values to favor the left condition; for lower-is-better FG-LPIPS, CIEDE2000, and GT-relative texture error, those values are improvement-coded ($B - A$), not raw $A - B$. We independently recomputed the five planned contrasts from the 75 paired object rows and now report raw $A - B$ in Table S15. For L–LLH minus G–FL, CIEDE2000 is $+1.373021$ (95% CI $[+0.418244, +2.374678]$), so the layer-wise setting has higher color error; PSNR, FG-SSIM, and Edge-SSIM also favor G–FL, GT-relative texture error is lower for L–LLH, and FG-LPIPS does not separate. The corresponding LLH/LHL layer-wise-versus-global contrasts have the same endpoint direction pattern. Within the global LLH/LHL comparison, the single pointwise FG-LPIPS interval favors G–LLH; the other five endpoints include zero. All 30 intervals are pointwise and unadjusted. GT-relative texture error summarizes agreement with three reference variation statistics and is not a fidelity measure. A correction note and the full recomputation outputs accompany the preserved original analysis files in the author-review package.

MVDiffusion scales correspondence-aware CPBlock outputs, while depth is concatenated into the latent and left unscaled. The 75-object schedule panel used a compatibility deployment base. A later check found 1,552/1,552 loaded tensors and 12/12 rendered views for one object identical to a native SD2-depth mirror; the full panel was not rerun. These results remain separate, mixed endpoint evidence on a different conditioning path; no cross-interface score pooling, architecture-causal claim, or general cross-backbone result is made.

The first-round 01549 Section 4.7 adapter-dependence analysis is retained as a separate within-family result. It reported three outcomes for uniform high scale across adapter regimes: texture flattening without per-layer caps, high-frequency artifact amplification under a strong-residual adapter with per-layer caps, and negligible effect for a weakened adapter. Its same-checkpoint cap ablation reported both flattening and amplification, and its residual-magnitude sweep ($0.1\times$–$3\times$ output projection) reported

increasing intervention strength with residual magnitude. A six-object stage ablation reported that the most sensitive stage differed between the main and artifact-prone adapters. These first-round results were explicitly described as adapter-dependent; they are retained as historical, within-architecture evidence and do not answer the current cross-backbone question.

A separate 76-object MV-Adapter study tested layer-wise L–LLH under an alternative budget-neutral contiguous partition B′ (per-point multipliers $[0.52018, 0.52018, 1.47982, 1.47982]$, weighted mean 1). Relative to the corresponding global controls, the B′ results are mixed across endpoints: the layer condition favors the global controls on FG-SSIM, favors the layer condition on the benefit-oriented CIEDE2000 and GT-relative texture summaries, and does not separate on FG-PSNR, Edge-SSIM, or FG-LPIPS. Its difference from the original partition is not resolved on any reported metric. These data describe this MV-Adapter layer intervention only and are not evidence for the TCAS timestep profile or for a general mapping rule.

The companion M3 profile uses $[0.41953, 0.41953, 1.19349, 1.19349]$, whose mean multiplier is approximately 0.8065. It changes both group assignment and total nominal residual budget, so it is not a pure mapping comparison with B′. Its audit classified 16 of 18 direction summaries as stable relative to the original partition, with one small Edge-SSIM attenuation and one near-zero FG-LPIPS sign change. Because the preserved protocol and result rows first appear in the same commit, M3 is retained as retrospective sensitivity. Neither M3 nor B′ establishes mapping robustness or cross-backbone generalization.

Retrospective MV-Adapter layer/time panel. A separate Exact-holdout analysis combines existing global controls with three new layer-wise conditions (L-FIX, L-LHL, L-LLH), totaling 228 new outputs on 76 objects. The wrapper scales four condition-guider feature tensors before they enter the UNet as down-block residuals; this is not the GeoTex ResNet residual-correction interface. Its 3-object identity audit matched the wrapper to the existing global runner on 9/9 schedule/object cases, but does not test the unmodified official pipeline at native scale 1.0. Layer-wise versus global contrasts show metric-dependent directions: PSNR, CIEDE2000, and ground-truth-relative texture error favor layer-wise rows, while FG-/Edge-SSIM favor global rows; FG-LPIPS is not separated. Within-profile temporal comparisons have no consistent endpoint pattern. The 10,000-resample intervals below are pointwise and descriptive, without family-wise correction across 30 metric/comparison cells. The earliest preserved commit adds both protocol and outcomes, so the panel is treated as retrospective rather than confirmatory. It does not establish equivalence or TCAS transfer.

Table S13: MV-Adapter Exact-holdout condition means for the 76-object seven-condition panel. These are descriptive interface-specific image metrics and are not pooled with GeoTex or MVDiffusion.

Condition	PSNR↑	FG-SSIM↑	Edge-SSIM↑	FG-LPIPS↓	CIEDE2000↓	GT-texture error↓
R0	13.114180	0.498481	0.233429	0.183496	20.719805	1.700798
G-FL	13.357177	0.527539	0.239997	0.187693	20.149543	2.224047
G-LHL	13.344064	0.528325	0.240235	0.188051	20.182146	2.269096
G-LLH	13.353306	0.527814	0.239974	0.188346	20.157122	2.198930
L-FIX	13.431922	0.523473	0.239052	0.187647	19.877910	1.903374
L-LHL	13.446348	0.525148	0.239619	0.187920	19.868912	1.980378
L-LLH	13.453797	0.523564	0.238899	0.187731	19.805120	1.913272

Table S14: All five reported MV-Adapter paired contrasts. Deltas are direction-adjusted so positive favors the left condition (lower-is-better metrics are sign-reversed). Intervals are pointwise object-bootstrap percentiles (10,000 resamples; seed 20260928), descriptive and unadjusted.

Contrast	Endpoint	Mean Δ [95% CI]	Median Δ	Left favorable
P1: L-LLH vs. G-FL	PSNR↑	$+0.096619$ $[+0.014894, +0.186322]$	$+0.038948$	60.5%
P1: L-LLH vs. G-FL	FG-SSIM↑	-0.003975 $[-0.007222, -0.001110]$	-0.000055	47.4%
P1: L-LLH vs. G-FL	Edge-SSIM↑	-0.001098 $[-0.002246, -0.000084]$	-0.000068	48.7%
P1: L-LLH vs. G-FL	FG-LPIPS↓	-0.000038 $[-0.002249, +0.001836]$	-0.000145	43.4%

Contrast	Endpoint	Mean Δ [95% CI]	Median Δ	Left favorable
P1: L-LLH vs. G-FL	CIEDE2000↓	+0.344422 [+0.162359, +0.548366]	+0.074472	67.1%
P1: L-LLH vs. G-FL	GT-texture error↓	+0.310776 [+0.128347, +0.523530]	−0.008452	44.7%
P2: L-LLH vs. G-LLH	PSNR↑	+0.100491 [+0.016411, +0.193981]	+0.033523	60.5%
P2: L-LLH vs. G-LLH	FG-SSIM↑	−0.004249 [−0.007467, −0.001399]	−0.000938	46.1%
P2: L-LLH vs. G-LLH	Edge-SSIM↑	−0.001075 [−0.002200, −0.000087]	−0.000020	47.4%
P2: L-LLH vs. G-LLH	FG-LPIPS↓	+0.000615 [−0.001370, +0.002409]	+0.000046	50.0%
P2: L-LLH vs. G-LLH	CIEDE2000↓	+0.352002 [+0.161829, +0.565100]	+0.083198	63.2%
P2: L-LLH vs. G-LLH	GT-texture error↓	+0.285659 [+0.092803, +0.508436]	−0.029244	46.1%
P3: L-LLH vs. L-FIX	PSNR↑	+0.021875 [−0.021181, +0.064134]	−0.003147	43.4%
P3: L-LLH vs. L-FIX	FG-SSIM↑	+0.000092 [−0.001301, +0.001429]	−0.000029	46.1%
P3: L-LLH vs. L-FIX	Edge-SSIM↑	−0.000152 [−0.001051, +0.000628]	−0.000030	47.4%
P3: L-LLH vs. L-FIX	FG-LPIPS↓	−0.000084 [−0.000821, +0.000518]	+0.000126	59.2%
P3: L-LLH vs. L-FIX	CIEDE2000↓	+0.072790 [+0.004371, +0.156696]	−0.004923	48.7%
P3: L-LLH vs. L-FIX	GT-texture error↓	−0.009898 [−0.088568, +0.077841]	+0.002578	52.6%
P4: L-LHL vs. G-LHL	PSNR↑	+0.102285 [+0.022567, +0.195757]	+0.048007	67.1%
P4: L-LHL vs. G-LHL	FG-SSIM↑	−0.003177 [−0.005872, −0.000730]	−0.000283	47.4%
P4: L-LHL vs. G-LHL	Edge-SSIM↑	−0.000615 [−0.001482, +0.000167]	+0.000066	52.6%
P4: L-LHL vs. G-LHL	FG-LPIPS↓	+0.000131 [−0.002170, +0.002094]	−0.000162	44.7%
P4: L-LHL vs. G-LHL	CIEDE2000↓	+0.313234 [+0.153138, +0.486864]	+0.094149	67.1%
P4: L-LHL vs. G-LHL	GT-texture error↓	+0.288718 [+0.104317, +0.504549]	−0.010427	48.7%
P5: G-LLH vs. G-LHL	PSNR↑	+0.009242 [−0.022729, +0.055429]	+0.000649	53.9%
P5: G-LLH vs. G-LHL	FG-SSIM↑	−0.000511 [−0.001207, +0.000102]	+0.000114	60.5%
P5: G-LLH vs. G-LHL	Edge-SSIM↑	−0.000261 [−0.000522, −0.000032]	+0.000029	53.9%
P5: G-LLH vs. G-LHL	FG-LPIPS↓	−0.000296 [−0.001198, +0.000712]	−0.000079	36.8%
P5: G-LLH vs. G-LHL	CIEDE2000↓	+0.025024 [−0.032059, +0.108336]	−0.003118	42.1%
P5: G-LLH vs. G-LHL	GT-texture error↓	+0.070166 [−0.050221, +0.216403]	−0.003606	43.4%

Table S15: MVDiffusion 75-object paired contrasts, reported as raw condition A minus condition B. Every comparison has $N = 75$ paired objects; intervals are pointwise 95% object-bootstrap percentile CIs (10,000 resamples, seed 20260928), without multiplicity adjustment. Higher PSNR, FG-SSIM, and Edge-SSIM are favorable; lower FG-LPIPS, CIEDE2000, and GT-relative texture error are favorable. The last metric is a mean symmetric-log error across three reference-relative variation statistics and is not a texture-fidelity measure.

Contrast (A − B)	Endpoint	Raw mean difference [95% CI]
P1: L-LLH − G-FL		
	PSNR (dB)	−0.453828 [−0.752102, −0.160451]
	FG-SSIM	−0.019393 [−0.029361, −0.009856]

Contrast (A − B)	Endpoint	Raw mean difference [95% CI]
	Edge-SSIM	−0.005941 [−0.010305, −0.001382]
	FG-LPIPS	+0.002745 [−0.001808, +0.007632]
	CIEDE2000	+1.373021 [+0.418244, +2.374678]
	GT-relative texture error	−0.082286 [−0.145316, −0.020073]
P2: L-LLH − G-LLH		
	PSNR (dB)	−0.466728 [−0.767571, −0.174846]
	FG-SSIM	−0.019245 [−0.029244, −0.009725]
	Edge-SSIM	−0.006207 [−0.010601, −0.001620]
	FG-LPIPS	+0.002998 [−0.001458, +0.007765]
	CIEDE2000	+1.377180 [+0.400867, +2.393609]
	GT-relative texture error	−0.064768 [−0.124369, −0.005093]
P3: L-LLH − L-FIX		
	PSNR (dB)	−0.092564 [−0.182342, −0.003231]
	FG-SSIM	+0.000528 [−0.003700, +0.004874]
	Edge-SSIM	−0.002828 [−0.005185, −0.000405]
	FG-LPIPS	−0.001089 [−0.002704, +0.000499]
	CIEDE2000	+0.082626 [−0.235252, +0.410153]
	GT-relative texture error	−0.037090 [−0.081113, +0.000258]
P4: L-LHL − G-LHL		
	PSNR (dB)	−0.520646 [−0.810872, −0.232104]
	FG-SSIM	−0.021431 [−0.032306, −0.011114]
	Edge-SSIM	−0.007282 [−0.011359, −0.003234]
	FG-LPIPS	+0.002491 [−0.001895, +0.007174]
	CIEDE2000	+1.545280 [+0.592682, +2.526751]
	GT-relative texture error	−0.098921 [−0.154601, −0.044345]
P5: G-LLH − G-LHL		
	PSNR (dB)	−0.078763 [−0.163889, +0.004507]
	FG-SSIM	−0.0000003 [−0.002323, +0.002393]
	Edge-SSIM	−0.001471 [−0.003510, +0.000589]
	FG-LPIPS	−0.001371 [−0.002642, −0.000141]
	CIEDE2000	+0.015861 [−0.264829, +0.299044]
	GT-relative texture error	−0.032667 [−0.068249, +0.002649]




Figure S1: Native MV-Adapter targets and all seven controls for the two fixed input-order rights-cleared examples in the main text. All images use native view 0 and the same object seed; each object has one shared frame spanning target and every condition. Previously observed illustrative outputs do not establish the primary effect or a generally best schedule. Source hashes and display frames are in the final visual manifest; full attribution is in Sections S5 and S9.

S4. GSO external-input and complete baked evaluation

Complete inherited-schedule extension and twenty-object bake

This extension uses the same source-selected GSO100 and native MV-Adapter interface. Four existing fixed/temporal/linear profiles were frozen before their outputs, after native/mean/late and auxiliary-correction results had been inspected. No new algorithm, model training or parameter search is involved. The main comparison follows the previous native50 question: middle-high minus fixed mean on all-six-view FG-PSNR, with three seeds averaged within object. The other 83 pair/metric endpoints use Holm83; the 21 nonreference LPIPS pairs use a separate exploratory Holm21 family. These families do not imply one overall experiment-wide error guarantee. The extension is external sensitivity, not pristine held-out confirmation. The specified middle–mean primary difference is -0.013660 dB, with

Schedule	FG-PSNR	FG-LPIPS	FG-SSIM	ΔE_{00}
native	16.998	0.11193	0.56736	12.550
fixed low	17.012	0.11316	0.56482	12.473
fixed mean	17.025	0.11239	0.56619	12.493
early high	16.974	0.11340	0.56414	12.538
middle high	17.012	0.11224	0.56563	12.483
late high	17.070	0.11228	0.56753	12.432
generic linear	17.045	0.11228	0.56687	12.462

Table S16: GSO100 native-view schedule means, all six views within each object and three sampling seeds. Scale labels have interface-specific semantics.

pointwise 95% object interval [-0.030565,+0.003519] and paired sign-flip $p = 0.122279$. Non-detection is not equivalence; complete secondary and nonreference contrasts are delivered.

Revised calibration and full twenty-object baking. The original discontinuous-UV-ramp gate failure is preserved. GT-only diagnostics on all twenty fixed inputs reproduce native masks and constant colors, and validate continuous nonlinear world-coordinate colors at the original mean/99th-percentile error bounds of 0.03/0.15. An independent two-island analytic fixture agrees to approximately 1.2×10^{-7} and a deliberate image flip is detected. For the mouse and Hair Dryer, all high-error ramp texels on common diagnostic coverage have a flagged bilinear sampling footprint across a UV jump; errors decrease at higher diagnostic resolutions. This does not assert artifact-free seams: raw UV aliasing and unfilled coverage remain deployment limitations. The revised calibration is post hoc, after fifteen original object outcomes. Projection, masks, cameras, source/texture resolutions, material and geometry remain unchanged. All 375 original GLB hashes and metric records reproduce exactly. No object or method is discarded by quality direction. The complete evaluation contains 740 unique bakes: twelve existing methods by3 seeds by20 objects plus20 GT self-bakes, with11 unseen cameras per bake. All foreground remains the reported quality region. Coverage is diagnostic; GT-bake error is not subtracted. The retained correction family uses its original Holm16, while the seven schedule-pair/four-metric diagnostic family uses Holm84. Mean generated/nonreference versus unseen-baked method-rank Spearman correlation is 0.601399, with object-bootstrap 95% interval [0.44020979020979023, 0.7332167832167833]. Rank agreement does not establish the same best method on every object.

The separately supplied `Supplementary_GSO_Baked_Comparison.mp4` shows the first source-ordered object, `Razer_Abyssus_Ambidextrous_Gaming_Mouse`, at seed 42, with all twelve recorded conditions and eleven actual unseen cameras (protocol indices 0–10). Each camera is held for 0.5 seconds. Its first column is an original source-mesh render, not the matched GT self-bake; the latter is assessed separately in the table above. The video is illustrative and does not estimate prevalence or material fidelity.

Bake condition	FG-PSNR	FG-LPIPS	FG-SSIM	ΔE_{00}
GT reference bake	19.364	0.06023	0.71369	5.105
native	15.479	0.10087	0.47814	12.031
fixed mean	15.500	0.10089	0.47847	11.973
late high	15.507	0.10098	0.47961	11.967
grid projection	15.149	0.10524	0.45925	12.323
view projection	14.998	0.10643	0.45467	12.502
interaction projection	15.163	0.10486	0.46112	12.247
apg projection only	15.500	0.10191	0.47829	11.952
apg paper sd21 at native cfg	15.305	0.10260	0.47667	12.474
fixed low	15.484	0.10109	0.47783	11.994
early high	15.479	0.10101	0.47697	11.998
middle high	15.473	0.10102	0.47757	12.033
generic linear	15.499	0.10099	0.47893	11.979

Table S17: Full fixed20-object re-evaluation. Eleven views and sampling seeds are nested within object. Scanned color is not certified physical albedo or PBR.

The specified Late-high minus Fixed Mean unseen-view FG-LPIPS difference is +0.00008379, with pointwise 95% object interval [-0.00010305,+0.00028592] and original Holm16 adjusted $p = 0.78765$. This study does not detect the ten-object GeoTex pilot's benefit; it uses a different domain and interface/projection protocol.

Post hoc sensitivity of image/bake rank agreement. The all-twelve-method estimate includes auxiliary corrections that differ markedly in quality. Restricting the same twenty objects to native, fixed low, fixed mean, early-high, middle-high, late-high and generic linear gives mean within-object Spearman 0.396429, with pointwise object-bootstrap 95% interval [0.175000,0.582143] (20,000 resamples, seed 131313). The minimum-mean LPIPS condition changes on 11/20 objects. This is a post hoc descriptive analysis, retaining every object. It changes neither the primary endpoint nor the original adjusted families; point-estimate winner changes do not establish statistically resolved best methods. Raw pairs and a portable recomputation are delivered in data/FACTS_round_014.json and scripts/build_evidence.py.

Separate projection/APG comparison and archived original bake failure

Completed GSO100 external comparison. The source-selected canonical GSO100 inputs have matched native-camera reference view 1 and six target views. The six-condition, three-seed matrix contains 1,800 generated cells, followed by 600 cells for two separately frozen APG baselines. The main LPIPS endpoint excludes reference view 1; seeds are averaged within each of the 100 objects. Native/default identity and native-camera target checks pass. These scanned-color textures are not certified physical albedo or PBR ground truth.

All fifteen primary correction comparisons favor the baselines; the three seed means have the same direction. Relative to native, grid, view and interaction correction are worse on 93, 91 and 88 of 100 object means, respectively. The APG SD2.1 clipping/momentum setting uses native CFG 3, not the original paper's CFG 10. The APG protocol was frozen before its outputs but after candidate generation had begun; this is not a joint preregistration. An independent object/seed table reconstruction matches all reported paired means.

Original calibration failure and complete fixed-cohort reevaluation. The fixed twenty-object native-UV sequence shares eight methods, three seeds and eleven unseen views. Rank 0 completes ten objects and rank 1 completes five, for 375 rows including fifteen GT self-bakes. Before candidate quality evaluation on `Remington_TStudio_Hair_Dryer`, its UV-ramp calibration gives mean error 0.007023 (below 0.03) but 99th-percentile error 0.178684 (above the frozen 0.15). Native-camera masks and

Correction	Baseline	LPIPS difference	Holm p
grid projection	native	+0.012381	$4.5e-05$
grid projection	fixed mean	+0.011581	$4.5e-05$
grid projection	late high	+0.011667	$4.5e-05$
view projection	native	+0.014637	$4.5e-05$
view projection	fixed mean	+0.013836	$4.5e-05$
view projection	late high	+0.013923	$4.5e-05$
interaction projection	native	+0.011174	$4.5e-05$
interaction projection	fixed mean	+0.010374	$4.5e-05$
interaction projection	late high	+0.010460	$4.5e-05$
grid projection	apg projection only	+0.009113	$3e-05$
grid projection	apg paper sd21 at native cfg	+0.008553	$3e-05$
view projection	apg projection only	+0.011369	$3e-05$
view projection	apg paper sd21 at native cfg	+0.010809	$3e-05$
interaction projection	apg projection only	+0.007906	$3e-05$
interaction projection	apg paper sd21 at native cfg	+0.007347	$3e-05$

Table S18: All specified GSO100 primary correction-minus-baseline contrasts. LPIPS is lower-better; every positive difference favors the baseline. Holm9 applies to the nine scale-control comparisons and Holm6 to the six APG comparisons, as separate frozen families. Complete pointwise intervals and secondary metrics are delivered.

constant-color calibration pass. The original supervisor and delivery stop on that failure. A documented GT-only calibration addendum subsequently completes all twenty fixed inputs, including four inherited schedule controls, for 740 unique bakes and 8,140 unseen-view rows. All 375 earlier GLB hashes and metric records reproduce exactly. The full results, raw failure and revised-calibration scope are reported above in this section. The completed rows and failed gate remain archived; no unfavorable object is removed to obtain a method advantage.

Fixed-seed stability: complete descriptive addendum

This analysis was proposed after inspection of the completed GSO results. Each seed-specific value averages the appropriate views within object. Its pointwise 95% interval resamples objects (20,000 draws; seed 20261012). All three fixed seeds and all four named rows are retained; seeds are not additional independent objects. The all-six-view image primaries, five-nonreference-view LPIPS and eleven-unseen-view bake remain distinct. Direction agreement uses zero only and is not a meaningful-effect or non-inferiority threshold. We define no new confirmatory test or significance family for these descriptive intervals.

Table S19: Fixed-seed conditional mean A minus B and number of objects with favorable/adverse directions at all three seeds. Higher favors PSNR; lower favors LPIPS. The remaining objects have mixed or tied directions.

Contrast / endpoint	42	2026	31415	All favorable	All adverse
GSO100 Middle–Mean PSNR	-0.00835	-0.02374	-0.00889	14/100	24/100
GSO100 Late–Mean PSNR	+0.05675	+0.03832	+0.03868	27/100	5/100
GSO100 Late–Mean nonreference LPIPS	-0.000389	-0.000269	+0.000398	24/100	14/100
GSO20 Late–Mean unseen LPIPS	-0.000064	+0.000308	+0.000007	1/20	5/20

For Late–Mean PSNR, all three cohort means are positive, yet 68/100 objects have mixed/tied signs. For nonreference LPIPS, the third seed reverses the cohort-average direction. In GSO20, one




Figure S2: Seed-specific paired means with pointwise object intervals. Three fixed seeds do not estimate the complete distribution of inference or training randomness. The original seed-averaged tests remain unchanged.

object has favorable LPIPS at all seeds, five adverse at all seeds and fourteen mixed/tied. Small average effects therefore provide limited assurance of repeatable per-object improvement. Complete per-object seed deltas and descriptive intervals are supplied in the data addendum; no seed or object is removed for its outcome.

S5. Calibrated GeoTex baked appearance and earlier attempts

Calibrated bake pilot, historical separation and actual-output displays

Projection protocol and superseded attempts. The earlier five-object bake rotated generated pole-view RGB back into raw-camera coordinates but also incorrectly rotated the raw-camera mask. Four of five objects have affected masks. Its old quality estimates are superseded by corrected evaluation and are not pooled with newly selected objects. In the REPEAT branch, bilinear fractions must be calculated before wrapping integer indices: the previous order could produce negative weights at tile edges and outside [0,1]. Corrected code passes nonnegative/unit-sum weight checks and integer-period translation invariance. Scalar coverage masks are read without an RGB transfer function; decoding grayscale coverage as sRGB would change the foreground threshold. GT source images are resized to 256 using bicubic RGB and the same nearest-index alpha masks as generated sources; atlas, camera, fill and render parameters are shared. The original GT-512 bake is retained only as an unmatched-resolution diagnostic.

The ten-object bake pilot uses objects chosen in frozen UID order before observing their bake results. All 300 Fresh C inputs were screened; old five-object outputs and the previously inspected REPEAT diagnostic object were excluded. Eligibility required available source GLB, one opaque

white-factor base-color material, native TEXCOORD_0, no vertex colors, at most 300,000 triangles, and source camera-mask alignment passing the frozen gate. This input-selected set is smaller than the target twenty and below fifteen; we retain the pilot designation and all ten outcomes. No failed or adverse-quality object was replaced. Seven conditions generated 70 object-condition rows; eight bake conditions including GT generated 80 artifacts, with 880 unseen renders and 480 source-camera renders.

The frozen primary was Late-high–Fixed Mean FG-LPIPS. C3–GFH PSNR, LPIPS, SSIM and CIEDE2000 form one four-test secondary Holm family. All other complete pairs are descriptive. Views are averaged before inference. Intervals use 50,000 paired object resamples and are pointwise, not simultaneous. The ten-object primary uses all 2^{10} sign flips; the secondary family uses the same exact test. A sign-flip test assumes symmetry/exchangeability of paired differences under its null; an interval alone is not a practical-equivalence criterion. No non-inferiority margin was chosen.

Table S20: Prespecified new-pilot comparisons: raw A minus B, 95% object-bootstrap interval; no pooling with old five.

Contrast	Endpoint	Mean [95% CI]	p
Late–Mean	FG-LPIPS	-0.00265 $[-0.00414, -0.00137]$	0.00195 (primary)
C3–GFH	FG-PSNR	$+0.193$ $[-0.649, +0.875]$	1.000 (Holm)
C3–GFH	FG-LPIPS	-0.00036 $[-0.00396, +0.00336]$	1.000 (Holm)
C3–GFH	FG-SSIM	-0.05274 $[-0.07459, -0.03170]$	0.00781 (Holm)
C3–GFH	CIEDE2000	-1.102 $[-2.915, +0.939]$	0.95508 (Holm)

The corrected earlier five-object bake uses the same source-resolution and mask corrections but retains its historical clamped-UV technical scope. Its descriptive means (PSNR / LPIPS / SSIM) are GFH 11.86 / 0.1609 / 0.5513, C3 14.24 / 0.1542 / 0.4170, Fixed Mean 14.19 / 0.1538 / 0.4348 and Late-high 15.02 / 0.1479 / 0.4428. C3–GFH is +2.37 dB, not the superseded +2.27 dB estimate. There was no independent predeclared primary for this reevaluation. The older N=20 result, old five, new ten and corrected single-object REPEAT diagnostic each retain separate source identifiers. Earlier wrong-mask, gamma-decoded-alpha and wrong-REPEAT-weight artifacts remain audit records and are superseded, never combined with the valid reevaluation.

Table S21: Per-object generated-view versus unseen-bake rankings across seven conditions. Bootstrap unit is object. Positive overall agreement does not require an identical winning condition.

Endpoint	Mean Spearman ρ [95% CI]	Winner changed
FG-PSNR	0.846 $[0.696, 0.968]$	1/10
FG-LPIPS	0.804 $[0.693, 0.911]$	7/10
FG-SSIM	0.746 $[0.450, 0.964]$	4/10
Edge-SSIM	0.907 $[0.871, 0.943]$	6/10

GT and generated bake sources use the same six raw cameras and 256-pixel resolution. GT RGB uses bicubic downsampling; alpha uses the exact nearest-index mapping used for generated foreground inputs. Their six-view scalar masks are bitwise identical and their raw atlas coverage matches for every object and condition. No unseen view enters baking. Export checks retain binary geometry/UV buffers, transforms and mesh identity. REPEAT UV weights are nonnegative, sum to one and are invariant under integer UV shifts. These checks establish a valid unlit projection comparison, not PBR equivalence or a validated seam score. Texture boundaries can be natural appearance boundaries; seam diagnostics are not reported as a validated primary endpoint.

The separately supplied `Supplementary_GeoTex_Baked_Comparison.mp4` presents two input-order, rights-cleared GeoTex objects at all eleven discrete unseen cameras. Each actual rendered view is held for one second; no interpolated camera image is synthesized. It is an unlit comparison, not a claim of continuous-view or PBR quality.




Figure S3: Rights-cleared GeoTex bake object 1 of seven, unseen camera 004. Source, matched GT-256 reference bake and all seven original generated conditions share one whole-object frame. These input/rights-selected displays retain visible failures and do not estimate prevalence. All ten eligible objects, including the three without verified display rights, remain in the numerical analysis. Source identities, native materials and credits are retained in the bake manifest and license ledger.




Figure S4: Rights-cleared GeoTex bake object 2 of seven, unseen camera 004. Source, matched GT-256 reference bake and all seven original generated conditions share one whole-object frame. These input/rights-selected displays retain visible failures and do not estimate prevalence. All ten eligible objects, including the three without verified display rights, remain in the numerical analysis. Source identities, native materials and credits are retained in the bake manifest and license ledger.




Figure S5: Rights-cleared GeoTex bake object 3 of seven, unseen camera 004. Source, matched GT-256 reference bake and all seven original generated conditions share one whole-object frame. These input/rights-selected displays retain visible failures and do not estimate prevalence. All ten eligible objects, including the three without verified display rights, remain in the numerical analysis. Source identities, native materials and credits are retained in the bake manifest and license ledger.




Figure S6: Rights-cleared GeoTex bake object 4 of seven, unseen camera 004. Source, matched GT-256 reference bake and all seven original generated conditions share one whole-object frame. These input/rights-selected displays retain visible failures and do not estimate prevalence. All ten eligible objects, including the three without verified display rights, remain in the numerical analysis. Source identities, native materials and credits are retained in the bake manifest and license ledger.




Figure S7: Rights-cleared GeoTex bake object 5 of seven, unseen camera 004. Source, matched GT-256 reference bake and all seven original generated conditions share one whole-object frame. These input/rights-selected displays retain visible failures and do not estimate prevalence. All ten eligible objects, including the three without verified display rights, remain in the numerical analysis. Source identities, native materials and credits are retained in the bake manifest and license ledger.



Figure S8: Rights-cleared GeoTex bake object 6 of seven, unseen camera 004. Source, matched GT-256 reference bake and all seven original generated conditions share one whole-object frame. These input/rights-selected displays retain visible failures and do not estimate prevalence. All ten eligible objects, including the three without verified display rights, remain in the numerical analysis. Source identities, native materials and credits are retained in the bake manifest and license ledger.




Figure S9: Rights-cleared GeoTex bake object 7 of seven, unseen camera 004. Source, matched GT-256 reference bake and all seven original generated conditions share one whole-object frame. These input/rights-selected displays retain visible failures and do not estimate prevalence. All ten eligible objects, including the three without verified display rights, remain in the numerical analysis. Source identities, native materials and credits are retained in the bake manifest and license ledger.

LG Remote by mohd.akmal.mahyudin; CC Attribution. Source: https://sketchfab.com/3d-models/1dc2c857f7614caeb6c2aa0559ccf973.

Tire by Koto3D Stephane Vogley; CC Attribution. Source: https://sketchfab.com/3d-models/21678bd623654182b52c11d013de4e71.

Asset 238ff3e41c964655b83aa9c8770cc766 by suntaree; CC Attribution. Source: https://sketchfab.com/3d-models/238ff3e41c964655b83aa9c8770cc766.

Baptisimal Font - Aughrim by Galway3D_DH_AGe; CC0 Public Domain. Source: https://sketchfab.com/3d-models/2dd9bc8172c6461797947cc7214db399.

Pittsburgh Bridge Collapse in Frick Park by C8X; CC Attribution. Source: https://sketchfab.com/3d-models/2f6c94487ee54cb88021f4643409d849.

bricks on news boxes by bunnyhero; CC Attribution. Source: https://sketchfab.com/3d-models/3c83796ca5f043f1beb8044dd2e51a0d.

Eastern Box Turtle Shell by Frank McMains; CC Attribution. Source: https://sketchfab.com/3d-models/85a7df80b79a4ba9b8c3a175de0dbce6.

Post hoc GT reference context and object influence

This reanalysis uses the same valid ten-object source records and the same frozen endpoints; it is not a new holdout or a new confirmatory family. GT-256 is a matched empirical projection reference, not a theoretical upper bound on an image endpoint. Its mean PSNR/LPIPS/SSIM/Edge-SSIM/CIEDE2000 are 22.38/0.0590/0.7683/0.7533/4.44. Late-high's LPIPS gain relative to Fixed Mean is unchanged at 0.00265.

For descriptive magnitude context, the ratio of means is

$$r = \frac{\text{mean}(\text{LPIPS}_{Mean} - \text{LPIPS}_{Late})}{\text{mean}(\text{LPIPS}_{Mean} - \text{LPIPS}_{GT256})} = 0.03720.$$

The numerator and denominator are recomputed jointly in each of 50,000 object-bootstrap samples (seed 20261010). All bootstrap denominators are positive; the pointwise interval is [0.02275,0.05323]. This is a roughly 3.7% reduction of the mean empirical reference gap, not evidence that the remaining appearance mismatch is small. It must not be interpreted as a practical acceptability threshold or a new primary discovery. Removing each object in turn yields Late–Mean mean differences between −0.00294 and −0.00208; this descriptive influence check does not create additional independent samples.

Table S22: Same ten objects: matched reference and generated unseen-view FG-LPIPS. All eleven unseen views are averaged first. Full UIDs and exact values accompany the reanalysis script.

UID prefix	GT-256	Fixed Mean	Late-high	Late–Mean
1dc2c857f761	0.07674	0.15307	0.14898	-0.00408
21678bd62365	0.07367	0.17198	0.16919	-0.00279
238ff3e41c96	0.02328	0.05895	0.05849	-0.00046
2dd9bc8172c6	0.14110	0.23763	0.22982	-0.00781
2f6c94487ee5	0.06525	0.09319	0.09317	-0.00003
3c83796ca5f0	0.05597	0.17757	0.17439	-0.00318
85a7df80b79a	0.04051	0.10964	0.10519	-0.00445
e261c0fe85af	0.04032	0.13280	0.13112	-0.00168
f1ccc55a65c7	0.06034	0.11759	0.11622	-0.00137
fa5c4b02c5b2	0.01312	0.05075	0.05010	-0.00065

The script `scripts/analyze_gt_context.py`, copied source CSV and `GT_REFERENCE_CONTEXT.json` permit standalone reproduction with NumPy. No generated output is added, replaced or retouched. The source hash identifies the previous round's valid metrics; historical five, N=20 and invalid old native-seven records remain separate.

Native-wrapper controls and sampling-protocol scope

The exploratory wrapper-control addendum adds native-unset residual and No Adapter controls on the same ten objects, with no change to the earlier seven-condition matrix or its primary comparison. These objects and their earlier outcomes have been inspected, so all added contrasts are exploratory. The native control removes the scale attribute immediately before every actual wrapper invocation, leaving the original forward function, geometry features and reference-write skipping logic intact. A regenerated Constant 1.0 (capped) control matches the earlier RGB outputs bitwise on all ten objects; inputs and seeds also match. This identifies the default residual branch within the frozen protocol, not an unmodified complete pipeline.

A read-only source audit identifies additional differences. The frozen generator makes one conditional score prediction per denoising step, uses cached global image embeddings, and generates 256-pixel views. The full base-pipeline call defaults to 512-pixel views, online global embeddings, and classifier-free guidance of 2.0; its denoising loop combines conditional and unconditional predictions. The GeoTex model's validation call uses 75 steps and does not explicitly bind geometry features. Source differences alone cannot identify the cause of the appearance failures or validate a repair. The corresponding source hashes and audit assertions are delivered in `ITERATION002_SAMPLING_PROTOCOL_AUDIT.json`.




Figure S10: Generated six-view grids for the same first two input-ordered, rights-cleared objects used in the earlier bake display. The malformed No Adapter visual column is omitted; all its numerical contrasts remain reported. The conditioning image is shown separately. Native residual means the unset-scale wrapper branch in the frozen sampling protocol; it does not mean the complete default pipeline. All grids retain their original contents, with only whole-grid resizing; visible color and detail failures are not retouched. LG Remote: mohd.akmal.mahyudin; Tire: Koto3D Stephane Vogley; both CC Attribution. Full source links are given in S5; new output hashes and credits accompany this figure.

Complete exploratory contrast family

Each row is A minus Native residual. Higher PSNR/SSIM/Edge-SSIM and lower LPIPS/CIEDE2000 are favorable. The 95% intervals are pointwise object-bootstrap intervals; adjusted p values belong to one 15-test Holm family. All ten objects are retained, and eleven unseen views are averaged per object. The prior Late-high–Fixed Mean primary remains unchanged. Repeated GT metrics match the earlier evaluation exactly (maximum absolute difference 0).

No Adapter versus Native residual Edge-SSIM is the sole adjusted rejection in this family. The favorable schedule means and pointwise intervals do not establish family-corrected schedule advantages or acceptable appearance fidelity. The generated-view controls also retain conspicuous color/detail failures in the displayed examples.

Historical N=20 unseen-view results

Table S24 reports the bounded historical N=20 GLB results. The subset comprises 20 UV-compatible objects from the original 24-object pool; four inputs were excluded for lack of UVs. Each object is the paired unit after averaging 11 frozen unseen views. Rendering uses unlit base color with native sampler interpretation. Endpoint directions are mixed; these statistics do not establish population-level 3D

A	Endpoint	Mean difference	Pointwise 95% CI	Holm p
Late-high	FG-PSNR	+1.78764	[+0.46170, +3.05975]	0.29688
Late-high	FG-LPIPS	−0.00951	[−0.01772, −0.00263]	0.29688
Late-high	FG-SSIM	+0.08825	[+0.05443, +0.12228]	0.05469
Late-high	Edge-SSIM	+0.04958	[+0.02256, +0.07663]	0.12305
Late-high	CIEDE2000	−4.82018	[−8.66554, −0.65098]	0.29688
C3	FG-PSNR	+1.34525	[+0.13241, +2.56138]	0.29688
C3	FG-LPIPS	−0.00699	[−0.01326, −0.00159]	0.29688
C3	FG-SSIM	+0.06827	[+0.04193, +0.09422]	0.05469
C3	Edge-SSIM	+0.03526	[+0.01168, +0.05974]	0.29688
C3	CIEDE2000	−4.30778	[−7.73875, −0.53688]	0.29688
No Adapter	FG-PSNR	−5.21580	[−6.60353, −3.61839]	0.05469
No Adapter	FG-LPIPS	+0.02281	[+0.01287, +0.03317]	0.05469
No Adapter	FG-SSIM	+0.04520	[−0.02288, +0.11851]	0.29688
No Adapter	Edge-SSIM	−0.21789	[−0.26399, −0.16852]	0.02930
No Adapter	CIEDE2000	+14.44690	[+6.37338, +22.12900]	0.07812

Table S23: All added object-paired exploratory contrasts. These are previously inspected objects, not a new independent confirmation sample.

superiority, PBR/material fidelity, seam quality, or human preference. The source GLB assets and internal montage are not included in this supplement.

Table S24: Historical N=20 unlit base-color paired unseen-view summaries (C3 minus comparator). The 20-object UV-compatible subset comes from the historical 24-object pool; four objects were excluded for missing UVs. Each object is averaged over 11 frozen unseen views. Intervals are 10,000-object-bootstrap percentile CIs (seed 20261005), descriptive and unadjusted.

Comparator	Endpoint	Mean difference [95% CI]	Objects favoring C3
GFL	FG-PSNR (dB)	-0.066 [-0.413, +0.290]	5/20 (25%)
GFL	FG-LPIPS	-0.004719 [-0.007504, -0.002544]	17/20 (85%)
GFL	CIEDE2000	+0.133 [-1.161, +1.319]	6/20 (30%)
GFH	FG-PSNR (dB)	+0.084 [-0.290, +0.426]	14/20 (70%)
GFH	FG-LPIPS	+0.007709 [+0.004230, +0.012101]	4/20 (20%)
GFH	CIEDE2000	-1.027 [-2.224, +0.229]	14/20 (70%)
No Adapter	FG-PSNR (dB)	+3.135 [+1.721, +4.493]	18/20 (90%)
No Adapter	FG-LPIPS	-0.014519 [-0.029860, -0.001326]	16/20 (80%)
No Adapter	CIEDE2000	-12.508 [-18.556, -6.529]	18/20 (90%)

Selected negative visual evidence and unresolved 3D checks

Figure S26 presents one selected illustrative Fresh C case where GFL is adverse to C3 on the paired image-space comparison. It does not estimate failure prevalence or color-correction performance. Full attribution appears in Table S38.

The attempted Fresh C 24-object GLB bake did not pass its input/output gate: 9/24 sources had out-of-range native UVs, and 5 assets / 27 primitives used unsupported BLEND. No valid Fresh C 24-object bake results were generated. The seam endpoint is retired because the required seam truth set and native full-panel validation did not pass. No full PBR comparison is available. These checks are limitations, not evidence of method failure or success.

Incoming-camera disagreement on shared UV texels

This additional diagnostic uses the already recorded source-view projection, before filling holes or rendering the exported atlas. For camera v and texel t, let c_{vt} be its linear-RGB average after visible-pixel bilinear UV splatting. Let V_t be the cameras with accumulated weight exceeding 10^{-8}. We retain only texels with $|V_t| \geq 2$, average cameras equally within each texel and then average population channel variance equally across the retained texels:

$$D = \frac{1}{3|T|} \sum_{t \in T} \sum_{k=1}^{3} \left[\frac{1}{|V_t|} \sum_{v \in V_t} c_{vtk}^2 - \left(\frac{1}{|V_t|} \sum_{v \in V_t} c_{vtk} \right)^2 \right]_+ .$$

The nonnegative clamp handles rounding. One-camera texels do not contribute. Six original cameras, GT-256 resolution/masks, 1024 atlas, original material and sampler, and the repaired REPEAT interpolation are shared with the bake. We copied the actual archived baker with SHA256 `f7eeb7cc4efb166cd4138b832e91356f36f775ac18badedefde5610aafdb8db4`, rather than silently substituting a later implementation. All 80 previously recorded values reproduce exactly.

On the first two input-order objects, known camera-constant gray inputs ($c_v = v/5$, $v = 0, \ldots, 5$) yield 0.12721819 and 0.12461645; independent camera-incidence calculations agree to at most 1.1×10^{-8}. A shared constant-black input gives exactly zero in both cases. The diagnostic can therefore return perfect agreement for an incorrect, flat appearance. These controlled input substitutions are formula/path checks, not newly generated model outputs or quality evidence. Inputs and original method images are unaltered.

Table S25: Ten-object recorded incoming-camera variance and actual baked LPIPS means. GT-256 is a path reference, not a perfect oracle. Lower disagreement does not imply better reference agreement.

Condition	Shared-UV variance	Unseen FG-LPIPS
Constant 1.0 (capped)	0.028847	0.13537
Fixed Low	0.025736	0.13168
Fixed High	0.010888	0.13055
Fixed Mean	0.019640	0.13032
C3 / Middle-high	0.022242	0.13018
Late-high	0.017192	0.12767
Generic Linear	0.012625	0.12763
GT-256	0.001787	0.05903

Late–Mean variance is -0.002448 (pointwise descriptive interval $[-0.003473, -0.001604]$; all ten negative). Its exact sign-flip $p = 0.001953$ becomes 0.041016 in the additional 21-pair Holm family. This family was specified after seeing the original bake endpoints and is exploratory. The two tested color controls do not certify arbitrary assets: UV overlap/repetition, natural texture, source-view dependence and sampling can produce disagreement. No quantitative seam or PBR endpoint is validated.

Table S26: All generated-condition pairs for the additional shared-UV diagnostic. A minus B; pointwise descriptive object intervals, 20,000 draws with seed 20261012; exact 2^{10} paired sign flips and one Holm21 family.

Contrast	Mean	95% interval	Holm p
Constant 1.0 (capped) – Fixed Low	+0.003111	[+0.001548, +0.004773]	0.04102
Constant 1.0 (capped) – Fixed High	+0.017959	[+0.011968, +0.024607]	0.04102

Contrast	Mean	95% interval	Holm p
Constant 1.0 (capped) – Fixed Mean	+0.009208	[+0.005554, +0.012970]	0.04102
Constant 1.0 (capped) – C3 / Middle-high	+0.006606	[+0.003810, +0.009709]	0.04102
Constant 1.0 (capped) – Late-high	+0.011656	[+0.007678, +0.015919]	0.04102
Constant 1.0 (capped) – Generic Linear	+0.016222	[+0.010458, +0.022681]	0.04102
Fixed Low – Fixed High	+0.014848	[+0.009782, +0.020292]	0.04102
Fixed Low – Fixed Mean	+0.006097	[+0.003672, +0.008454]	0.04102
Fixed Low – C3 / Middle-high	+0.003495	[+0.001986, +0.005090]	0.04102
Fixed Low – Late-high	+0.008545	[+0.005577, +0.011622]	0.04102
Fixed Low – Generic Linear	+0.013111	[+0.008330, +0.018323]	0.04102
Fixed High – Fixed Mean	−0.008752	[−0.012033, −0.005831]	0.04102
Fixed High – C3 / Middle-high	−0.011354	[−0.015333, −0.007696]	0.04102
Fixed High – Late-high	−0.006304	[−0.008839, −0.004094]	0.04102
Fixed High – Generic Linear	−0.001737	[−0.002234, −0.001269]	0.04102
Fixed Mean – C3 / Middle-high	−0.002602	[−0.003464, −0.001571]	0.04102
Fixed Mean – Late-high	+0.002448	[+0.001604, +0.003473]	0.04102
Fixed Mean – Generic Linear	+0.007015	[+0.004426, +0.010028]	0.04102
C3 / Middle-high – Late-high	+0.005050	[+0.003460, +0.006721]	0.04102
C3 / Middle-high – Generic Linear	+0.009617	[+0.006251, +0.013327]	0.04102
Late-high – Generic Linear	+0.004567	[+0.002643, +0.006902]	0.04102

S6. Appearance failures and executed-protocol diagnostics

Paired color-pathway diagnosis and failure boundaries

The color diagnosis is a selected, failure-enriched set of six earlier cases and 20 Fresh C panels; it is neither random nor a new holdout. No Adapter, GFL, and LLH were compared on the same inputs, checkpoint, and runner across six unique target views (78 object-condition records). CIEDE2000 was recomputed from hash-identified RGB and frozen masks. Intervals are descriptive paired object bootstraps (20,000 resamples, seed 61008); no confirmatory multiplicity family was defined. The main manuscript's color-diagnostic figure shows one of the 20 Fresh C panels (UID `f6979d7ff8e54c4daf00fee46f09a139`); its pre-existing C3–GFL stratum was lowest FG-LPIPS, not color-based, and it is distinct from the legacy pink-shift cases.

GFL lowered reference-relative CIEDE2000 in 24/26 objects, but visible pink or purple remained in two legacy cases under all three conditions. LLH increased mean color error while reducing local variation, not fidelity. The RGB shift was visible before baking and at denoising update 40. For one case, a ground-truth VAE round trip gave CIEDE2000 4.086 and $\Delta a^* \approx -1.35$, versus 22.032 and +1.977 for GFL; this weakens a VAE-only explanation but does not identify the cause.

A locked P0 trace of three preselected objects reproduced saved RGB pixels exactly in repeated Python 3.13.5 runs; Python 3.10 reproduced its corresponding archived observer. The first cross-runtime tensor difference followed multiplication of the shared FP16 initial latent by the scheduler noise scale (maximum absolute difference 0.0625; RMSE 0.00966; 32.3% changed). This resolves output identity only for these three traces; it establishes neither cohort-wide cross-stack equivalence nor the color cause.

The feature-relative residual gate increased mean CIEDE2000 by 1.35 across 26 objects and 3.18 in the six earlier cases, with no clear visual improvement. The complete cause remains unresolved; no repair is validated.

Table S27: Selected paired endpoints from the failure-enriched 26-object color diagnosis. Each row is condition A minus B with an object-level 95% paired-bootstrap CI. Lower CIEDE2000 and FG-LPIPS are favorable; higher PSNR and Edge-SSIM are favorable. Local texture statistics describe variation, not fidelity.

Contrast	Endpoint	Mean difference	95% CI
GFL – No Adapter	Foreground CIEDE2000	−19.654	[−26.370, −13.248]
GFL – No Adapter	FG-PSNR (dB)	+6.646	[+5.556, +7.635]
GFL – No Adapter	FG-LPIPS	−0.03251	[−0.05363, −0.01072]
GFL – No Adapter	Edge-SSIM	+0.06510	[+0.04853, +0.08202]
LLH – GFL	Foreground CIEDE2000	+3.583	[+0.462, +6.712]
LLH – GFL	FG-PSNR (dB)	−0.197	[−1.562, +1.297]
LLH – GFL	FG-LPIPS	−0.01294	[−0.02742, +0.00066]
LLH – GFL	Edge-SSIM	−0.00080	[−0.00776, +0.00659]
LLH – GFL	Foreground gradient magnitude	−0.06772	[−0.08132, −0.05494]
LLH – GFL	Foreground high-frequency energy	−0.00887	[−0.01091, −0.00672]
LLH – GFL	Foreground color entropy	−0.598	[−0.703, −0.502]

Native base-pipeline protocol and two-object diagnostic

The complete native base-pipeline diagnostic uses the same two previously inspected, rights-cleared failure objects, not an independent confirmation cohort. We load the identical native base model assets directly, without GeoTex weights or geometry residuals, and call the complete pipeline at 50 and 75 steps. All four calls generate 1024×1536 grids (six 512-pixel views). Observation hooks record exactly 50/75 actual UNet calls, each with the two-member classifier-free batch; the 50/75 starting latents match within each object. The scheduler is the native EulerAncestralDiscreteScheduler with trailing timesteps. The previously supplied batch conditioning hashes match, establishing source correspondence rather than full preprocessing equivalence.

The first RGB API attempt fails before any output because the native recenter helper expects four channels. It is preserved separately. The valid second attempt uses the original single-reference RGBA source. Native preprocessing mutates some white foreground pixels in place; the before/after input images are archived. Source inspection also identifies an incompatible validation entry in the GeoTex model: it wraps the UNet while the full pipeline's preparation entry asserts a bare UNet. This is a source-level finding, not a reported execution of the complete GeoTex validation path. Independent native base loading avoids that incompatibility without changing the pipeline's denoising code.

The frozen generator's image inverse scaling is $1.6x$, followed by $0.5x + 0.5$, yielding $0.8x + 0.5$. The full pipeline composes the same two factors. The formulas are algebraically equal; naming differences do not demonstrate a decoding error.

The diagnostic separates online/cached image features, classifier-free guidance and other sampling differences only within these previously observed inputs. It does not identify a single cause, establish a new algorithm, validate broad material fidelity or replace any earlier paired comparison. No inferential statistics or new acceptance probability are assigned to these two examples.

Controlled guidance–image-feature diagnostic

The same two seen failure objects undergo eight calls: cached/online global image features crossed with conditional-only/sequential CFG2, all without geometry residuals. Views remain 256 pixels, the sampler remains the frozen 50-step EulerDiscreteScheduler, and conditioning RGB/initial latent identities match the old control. Online encoders consume the same already processed conditioning RGB; native RGBA recentering and bright-pixel handling are not invoked. The online-to-cache feature cosines are 0.862997 for LG Remote and 0.899210 for Tire. Feature difference is not itself a fidelity measure or evidence of a bad cache.

The conditional-only arms reuse the original generation function. The cached arm reproduces both



Figure S11: Retained complete grids for a fixed input-order failure object. The disabled-adapter visual column is omitted; its records remain available. Native base outputs use a different sampler and unverified camera conventions, so these are protocol diagnostics rather than aligned GT comparisons or complete default GeoTex results. No reference-fidelity inference follows from the better front-looking native color. Object 1 of two.




Figure S12: Retained complete grids for a fixed input-order failure object. The disabled-adapter visual column is omitted; its records remain available. Native base outputs use a different sampler and unverified camera conventions, so these are protocol diagnostics rather than aligned GT comparisons or complete default GeoTex results. No reference-fidelity inference follows from the better front-looking native color. Object 2 of two.

prior No Adapter RGB outputs bitwise. CFG2 uses the standard prediction $2\epsilon_c - \epsilon_u$ through sequential batch-one forwards. Negative conditioning encodes a zero tensor in the normalized VAE input space, with seed424242; its reference-noise call uses an independent RNG fork at each step (seed100042 plus step). The positive branch retains the original randomness: all fifty positive-call CUDA RNG states match across four arms for each object. Each guided arm records fifty positive and fifty negative calls; each conditional-only arm records fifty positive calls. This controlled sequential implementation is not claimed pixel-equivalent to the native batched CFG API.

No paired cross-camera GT endpoints, population tests or acceptance probability are assigned to these two examples. The result retains the earlier B2 feature-substitution failure and C1 visual-gate failure; it does not support erasing those records or claiming a validated appearance correction. Resolution and remaining full-pipeline differences should be separated before deploying an amended GeoTex path or developing a new method.

Target-resolution bridge

The two seen diagnostic objects undergo eight calls: 256/512-pixel target views crossed with conditional-only/sequential CFG2. Reference RGB resizing and model.img_size remain 256; online global features, frozen model weights, 50-step EulerDiscrete sampling, training time IDs and reference encoding remain fixed. Initial latents have shape $1 \times 4 \times 96 \times 64$ or $1 \times 4 \times 192 \times 128$. Within each target resolution, the two arms use identical initial latents and fifty matching positive-call CUDA RNG states. Across resolutions, the tensor dimensions differ: a common seed is not a claim of identical initial tensors. Guided arms reuse the previous sequential CFG2 implementation and independent negative RNG policy.

Both 256-pixel arms reproduce the corresponding S6 online-feature RGB outputs bitwise for both objects. All conditions have identical reference-input and online-feature hashes within an object. Larger target grids change the object arrangement, but retained appearance defects prevent calling this a quality repair. Camera identities have not been independently calibrated across these generated grids, so there are no cross-path GT scores, population tests or deployment claims. The base pipeline source specifies a 1024×1536 output grid; this source fact and the controlled bridge motivate further protocol calibration, not retroactive pooling of different target resolutions.

Native geometry implementation and camera-contract audit

The published inference source at commit `f714682db5e6f78e8d1c7c0a43d1525638dda5a6` arranges rendered indices $[0, 5, 1, 4, 2, 3]$ in row-major order; its bake script extracts result tiles $[1, 3, 5, 6, 4, 2]$, the inverse permutation. Actual metadata for all ten baking objects matches those nominal directions after the conditioning-camera anchor rotation. Pole elevation matches, but pole-image roll, cross-renderer pixel registration and generated-view fidelity remain unverified. The historical public training loader's repeated top view is separate from this inference contract. Source snapshots, hashes and the ten-object audit are provided.

Two seen objects first pass an identity gate: the frozen GeoTex weights are loaded, all geometry features cleared, and the full native pipeline outputs match the earlier bare-base RGB pixels exactly. The model constructor already wraps reference attention; setting its preparation state prevents double wrapping without replacing the native denoising loop.

The subsequent matrix has eight conditions per object: disabled, original unscaled residual, Fixed Low, Fixed High, Fixed Mean, C3, Late-high and Generic Linear. Native target views remain 512 pixels with CFG2 and fifty EulerAncestral steps; the trained geometry encoder input remains 256 pixels, with wrapper interpolation to actual hidden-state sizes. Historical schedule functions come from the frozen registry; Fixed Mean requests 1.65 and Late-high requests 1.25 except for the last sixteen steps at 2.50. Applied layer caps remain native. Historical C3's group-dependent profile does not share every layer budget with the scalar Fixed Mean; no equal-budget claim is made for that contrast.




Figure S13: Guided cached/online-feature outputs for the fixed failure object. The two malformed unguided disabled-adapter columns are omitted from the display; all four original factorial arms and identity tests remain reported. Complete generated grids are resized only for presentation. The dark incorrect shapes remain, and online features do not establish a quality repair. These are previously inspected diagnostic examples, not a new holdout. Object 1 of two.



Figure S14: Guided cached/online-feature outputs for the fixed failure object. The two malformed unguided disabled-adapter columns are omitted from the display; all four original factorial arms and identity tests remain reported. Complete generated grids are resized only for presentation. The dark incorrect shapes remain, and online features do not establish a quality repair. These are previously inspected diagnostic examples, not a new holdout. Object 2 of two.



Figure S15: Guided 256/512-view outputs for the fixed failure object. Malformed unguided disabled-adapter columns are omitted; all original resolution arms remain in the protocol and numerical record. The complete grids preserve their contents. Camera identity has not been independently calibrated across target resolutions, so these are protocol/appearance diagnostics, not aligned GT comparisons or an established repair. Object 1 of two.




Figure S16: Guided 256/512-view outputs for the fixed failure object. Malformed unguided disabled-adapter columns are omitted; all original resolution arms remain in the protocol and numerical record. The complete grids preserve their contents. Camera identity has not been independently calibrated across target resolutions, so these are protocol/appearance diagnostics, not aligned GT comparisons or an established repair. Object 2 of two.

Geometry features have batch one and broadcast to both batch-two CFG branches through hidden-state-dependent gates. All nine wrappers skip fifty reference-write corrections and execute fifty corrected read calls; each geometry-enabled correction has batch two and finite values. Within an object, geometry/input hashes, initial latents and the fifty outer-UNet CUDA RNG states match across all eight conditions. The disabled arm reproduces the previous bare native grid bitwise. The initial registry-import attempt failed before model loading because its required run configuration was absent; the failed source/record is retained, and the corrected attempt has a distinct output root.

These diagnostics are not an independent confirmation cohort, do not verify correct generated cameras and do not support population inference or cross-path GT statistics. They preserve the prior controlled and downstream results while restricting claims about native deployment. Geometry-encoding resolution and CFG-branch compatibility require further controlled examination.

Geometry encoding, CFG branch policy and training-lineage limits

The same two seen objects undergo twelve native-loop calls: geometry encoding at 256/512 pixels crossed with both-branch, conditional-only and conditional-only half-amplitude corrections. The native target grid, reference RGBA, online features, CFG2 and fifty EulerAncestral steps remain fixed. A controller acts after native correction computation: the both mode returns the correction unchanged; conditional-only zeros the negative sample; half-amplitude also multiplies the positive sample by 0.5. This is an implementation diagnostic, not a newly validated algorithm or a residual-dose-matched comparison. Half amplitude checks the conditional coefficient in CFG2; different trajectories prevent claiming equal total residual norms.

The 256/both output reproduces both S6 original-residual RGB grids bitwise. All nine wrappers retain fifty reference-write skips and fifty corrected reads. Input hashes, initial latents and outer-UNet RNG trajectories match within each object; geometry input/feature hashes match only within the same geometry encoding size. Every conditional-only read has zero negative correction norm. Complete output grids and trace identities are delivered.

The frozen checkpoint's recorded main-adapter training lineage includes a 1,118-object list, a matching checkpoint SHA256 and a complete 2,000-step loss CSV. The train list has no UID overlap with Fresh C; 1,112 objects have the six checked RGB/normal/depth input sets, and six have missing entries. These availability counts do not establish texture quality or authenticate each historical sampled object. The configuration specifies 256-pixel training and conditioning-drop probability 0.1, but the recorded custom training entry does not read that probability and uses only non-dropped conditioning. It bypasses the model-class training method. The historical dataset source has repeated-top target lists; the surviving dataset source differs from the recorded commit. Source and model-entry identities, the declared list override, checkpoint identity and current availability are audited separately.

Exact training replay remains unsupported: the transient list-override wrapper and training seed are not preserved, the CSV has no sampled-object identities, and the checkpoint contains adapter/encoder weights without an embedded step. A trailing literal newline escape in the original manifest is preserved and explicitly handled rather than silently rewriting that artifact. This audit concerns the current main-adapter lineage, not restoration of the historical FAC branch. Conditional-only training explains why unrestricted negative-branch insertion needs validation, but the controlled outputs do not establish it as the sole cause of appearance loss. No independent generalization or cross-camera GT inference is made.




Figure S17: Retained complete native-loop geometry grids for a fixed input-order object. All seven enabled geometry settings are shown; the malformed disabled-adapter visual column is omitted, without changing any numerical results or failure records. Full-grid source pixels are preserved. The two input-order rights-cleared objects and their attribution remain the same; these observed outputs establish no general quality repair. Object 1 of two.




Figure S18: Retained complete native-loop geometry grids for a fixed input-order object. All seven enabled geometry settings are shown; the malformed disabled-adapter visual column is omitted, without changing any numerical results or failure records. Full-grid source pixels are preserved. The two input-order rights-cleared objects and their attribution remain the same; these observed outputs establish no general quality repair. Object 2 of two.




Figure S19: All twelve full grids, resized only for display. Half-amplitude conditional corrections preserve more tire details, but remote reference content is still lost. Neither larger geometry encoding nor branch removal establishes an overall quality repair. Same previously inspected objects and attribution as S6.

S7. Historical selection, preference and FAC records

Historical 01549 Table 9: strict-276 schedule transfer

The 01549 submission reports this schedule-transfer comparison on the 276 objects disjoint from the 24-object probe. It uses the strong-residual, per-layer-capped v2 adapter, not the v1 checkpoint named for 01549 Table 4. The values below are reproduced from the authenticated 01549 submission; they are not pooled with Fresh C or the separate MAIN-STAGE-276 profile-placement analysis. The table therefore documents schedule transfer on its stated adapter instance and remains distinct from Fresh C's matched single-checkpoint comparison.

Table S28: Values reproduced from original 01549 Table 9 for the stated strict-276 retrospective schedule-transfer comparison. The adapter/run differs from Fresh C; row-level runner and input provenance are incomplete. Values are preserved as submitted historical results, not independently verified statistics.

Schedule	FG-SSIM	PSNR	C3–schedule ΔPSNR (95% CI)	C3-favourable objects
Trapezoid	0.356	19.04	+0.258 [+0.207, +0.308]	206/276
Gaussian peak	0.358	18.97	+0.324 [+0.281, +0.367]	232/276
Linear warm-up	0.377	18.97	+0.323 [+0.263, +0.386]	214/276
Cosine bump	0.330	18.39	+0.902 [+0.824, +0.981]	253/276
C3 (TCAS)	0.376	19.29	–	–

Historical 01549 Table 3: extended 24-object development diagnostics

The table below is transcribed from the authenticated 01549 source and moved from the main text to preserve the original 24-object development record. The candidate-level row outputs and selection-time provenance are unavailable for independent reanalysis. Laplacian variance, RGB standard deviation, gradient magnitude, and high-frequency energy are variation diagnostics; this historical table does not establish texture fidelity, a population effect, or an optimal schedule.

Table S29: Values transcribed from original 01549 Table 3 for representative variants in the 24-object development probe. These are historical values, not independently recomputed statistics; variation measures do not establish texture fidelity.

Variant	ΔLap Var	ΔRGB Std	ΔGrad	ΔHF Energy
C3	−0.001	−0.023	+0.142	+0.058
C4	−0.012	−0.032	+0.086	+0.062
A_s2.50	−0.011	−0.044	+0.054	+0.078
A_s2.00	−0.006	−0.040	+0.100	+0.070
A_s1.25	−0.005	−0.032	+0.104	+0.053

First-round FAC controlled re-examination

The 01549 first-round package reports seven trained FAC configurations under the paired 300-object protocol. All values below are retained as originally reported; this is not a new 1008 training run. The separate 12-object untrained C3-envelope control is retained in the historical protocol paragraph below.

Table S30: FAC dose-response table reported in the first-round 01549 supplement. FG-PSNR and FG-SSIM are the reported absolute values; ΔFG-PSNR and wins compare each trained configuration with TCAS.

Configuration	Temporal gate	FG-PSNR	FG-SSIM	ΔFG-PSNR	Wins
TCAS baseline (C3)	fixed C3	9.88	0.3681	–	–
LTAG only	joint, unconstrained	7.79	0.3487	−2.08	4/300
LTAG+GSG	joint, unconstrained	7.03	0.3163	−2.84	6/300
Full FAC	joint, unconstrained	6.94	0.3204	−2.94	5/300
Two-stage + GSG/FSC	frozen at C3	7.32	0.3074	−2.56	4/300
Envelope penalty ($\lambda = 1$)	joint, penalized to C3	7.14	0.3021	−2.74	2/300
Fidelity weighting	frozen at C3	7.51	0.3110	−2.37	5/300
Gentle schedule	frozen at C3	8.77	0.4175	−1.10	48/300

The submitted protocol states that only the LTAG/GSG/FSC controllers (roughly 6×10^3 parameters) were trained; the base model, VAE, and GeoTex-Adapter remained frozen. It specifies the enhanced latent denoising objective and 2,000 AdamW steps on a training pool stated as 1,706 objects. The separate 12-object untrained control was reported at ΔFG-PSNR = −0.18 dB (95% CI $[-0.42, +0.05]$). A recovered configuration instead lists 1,200 training objects, and no run-bound seed/output manifest was found. We retain the original values as reported and disclose this reproducibility limit. Recoverable code is now supplied with the bounded source/component checks below; a complete historical training replay remains unverified.

Retrospective texture-complexity boundary

This analysis uses the separate FRESH_CONFIRM_300 cohort ($N = 300$), not Fresh C or Fresh B. LLH and native GFL rows match the frozen object list and share the recorded checkpoint, runner, seed, six unique target views, sampler, and protocol. The paired LLH–GFL mean differences are +1.2877 dB FG-PSNR (95% object-bootstrap CI $[+0.9383, +1.6346]$; 57.7% LLH-favorable objects) and −0.01650 FG-LPIPS ($[-0.01887, -0.01413]$; 73.3% LLH-favorable objects).

The descriptor analysis tests two image-space outcomes against five ground-truth descriptors: foreground Laplacian variance, RGB standard deviation, gradient magnitude, high-frequency energy, and coverage. Spearman correlations use average ranks and paired-object percentile bootstrap intervals (10,000 resamples, seed 20261002). The family contains ten plus-one-corrected bootstrap sign tests and Holm correction across all ten. Nine tests reject at 0.05; the only non-rejection is FG-LPIPS versus coverage (adjusted $p = 0.0508$). The preserved H5 hypothesis excerpt predates one archived outcome bundle, but the main multiplicity lock classifies this family as retrospective after prior outcome exposure; that chronology has not been reconciled. We therefore report all associations as retrospective sensitivity evidence, not as preregistered confirmation.

Ground-truth foreground Laplacian-variance quartiles contain 75 objects each. The FG-PSNR mean LLH–GFL difference declines from +4.140 dB in Q1 (92.0% favor LLH) to +1.127 dB in Q2

Table S31: Retrospective Spearman associations between LLH–GFL image-space deltas and ground-truth descriptors in FRESH_CONFIRM_300. Correlation intervals are paired-object bootstrap intervals; adjusted p values use the ten-test Holm family with plus-one-corrected bootstrap sign tests.

Outcome delta	Ground-truth descriptor	ρ [95% CI]	Holm p	Decision
FG-PSNR	Laplacian variance	-0.524 $[-0.603, -0.435]$	0.0020	reject
FG-PSNR	RGB standard deviation	-0.380 $[-0.488, -0.266]$	0.0020	reject
FG-PSNR	Gradient magnitude	-0.464 $[-0.548, -0.371]$	0.0020	reject
FG-PSNR	High-frequency energy	-0.691 $[-0.745, -0.626]$	0.0020	reject
FG-PSNR	Foreground coverage	-0.134 $[-0.241, -0.026]$	0.0352	reject
FG-LPIPS	Laplacian variance	$+0.604$ $[+0.511, +0.681]$	0.0020	reject
FG-LPIPS	RGB standard deviation	$+0.379$ $[+0.272, +0.482]$	0.0020	reject
FG-LPIPS	Gradient magnitude	$+0.563$ $[+0.469, +0.643]$	0.0020	reject
FG-LPIPS	High-frequency energy	$+0.677$ $[+0.599, +0.744]$	0.0020	reject
FG-LPIPS	Foreground coverage	-0.118 $[-0.233, +0.0002]$	0.0508	not rejected

(52.0%), −0.087 dB in Q3 (41.3%), and −0.029 dB in Q4 (45.3%). The FG-LPIPS mean changes are −0.03745, −0.01665, −0.00670, and −0.00520 from Q1 to Q4; the favorable-object rates decline from 97.3% to 50.7%. These strata describe heterogeneity in this cohort. They do not establish that texture complexity causes the response, define a threshold, validate an object selector, or measure texture fidelity.

Table S32: Historical 01549 report of a 13-scale sweep on the stated 50-object set. Values are reproduced from the submission and have not been independently recomputed from row-level outputs; they are retained as development diagnostics.

Scale	ΔFG-SSIM↑	POS	ΔCrop-SSIM↑	ΔPSNR↑
0.75	−0.013	20/50	+0.113	7.53
0.90	+0.024	30/50	+0.137	8.32
1.00	+0.047	34/50	+0.147	8.79
1.10	+0.070	36/50	+0.159	9.08
1.15	+0.071	36/50	+0.157	9.25
1.25	+0.088	37/50	+0.161	9.37
1.35	+0.100	39/50	+0.163	9.63
1.50	+0.113	40/50	+0.163	9.76
1.60	+0.120	42/50	+0.166	9.83
1.75	+0.127	43/50	+0.173	9.97
2.00	+0.134	44/50	+0.169	9.96
2.25	+0.142	43/50	+0.175	9.91
2.50	+0.145	44/50	+0.165	9.91

Retained original fixed-scale and C3 selection displays

These records retain their original classifications and limitations. Moving them changes presentation, not their outcomes or evidentiary status.

Historical Fixed-Scale Image-Space Diagnostics

Table S32 reproduces the 13-scale sweep reported in the submitted 01549 manuscript. We retain it to preserve the original development question, but the object-level outputs, full run manifest, and metric implementation mapping are not available in the current authority. Its values and Figures S20–S21 are therefore historical diagnostics, not a new reanalysis or confirmatory evidence.

The submitted table reports a rising ΔFG-SSIM over most of the listed scale range and a near-plateau in the crop metric at higher settings. We retain this reported pattern only as historical motivation: absent row-level outputs and a complete run manifest, we do not treat it as an independently confirmed scale-response law. It motivates asking whether a single aggregate structural score fully describes the effect of adapter scaling.

The submitted heatmap depicts object-level variation across the reported scales, but its underlying rows cannot be reconstructed from the current evidence archive. We retain the visual diagnostic as part of the 01549 research history and do not infer a population-level response distribution from it. The updated Fresh C analysis below uses its own frozen cohort and matched inputs.

C3 Development Record and Current Evaluation

The submitted paper records 17 uniform, layer-wise, and timestep-conditioned variants on a 24-object development probe and identifies C3 as its chosen profile. This study question remains relevant: does a stage-dependent request offer a useful control setting beyond a single global scale? Because the complete historical row-level data and selection provenance are not available in the current authority, the original Table S33 and Figure S22 are retained as historical development records, not as a verified ranking or proof of optimality. Fresh C evaluates the recorded C3 profile without another schedule search.

The original table and plot use shape and texture-variation proxies to describe the development choice. They do not establish that texture was faithful to the reference, nor that C3 was the unique




Figure S20: Historical fixed-scale diagnostic from the submitted 01549 paper. The plotted source reports FG-SSIM and Crop-SSIM over adapter scales; the underlying object-level run records are not available for independent reanalysis. It motivates measuring more than one endpoint, but is not a current confirmatory result.

best candidate. In this revision, C3 is therefore described as the historical profile carried forward for matched evaluation, not as a theorem-derived or globally optimal schedule.

The requested profile is piecewise constant over normalized sampling progress p:

$$s_{\mathrm{req}}(p) = \begin{cases} 1.25, & 0 \le p < 1/3, \\ 2.50, & 1/3 \le p < 2/3, \\ 1.25, & 2/3 \le p \le 1, \end{cases} \qquad \mathrm{C3} = (1.25, 2.50, 1.25). \tag{1}$$

This is an inference-time instruction on the existing adapter path; no weights are trained. Its tested value is task- and implementation-specific. The schedule operation itself is not claimed as a new general primitive.

The source Figure 5 (26-object texture ratios) is not included as an active result because its object IDs, selection trace, and metric lineage are incomplete. The original 24-object Table 3 is moved to Supplementary Section S7 as a verbatim historical diagnostic, with no texture-fidelity or population inference. Both source assets remain preserved in the authenticated submission and forensic archive; neither decision removes the fixed-scale research question or the development record of C3.

Historical cluster-aware preference study

The 01549 first-round revision reported a blinded three-alternative forced-choice study on 30 objects with 24 participants. Participants compared conservative fixed-scale, aggressive fixed-scale, and C3 outputs for texture naturalness, shape consistency, and overall quality; condition order was randomized per trial. Each criterion had 720 first-choice decisions. Table S34 reports the aggregate counts; participant-level responses are not redistributed with this revision.

The reported analysis used a two-level participant/object bootstrap with 10,000 resamples. C3's overall-quality share was 58.1% (95% CI [50.1%, 65.8%]); its differences from the conservative and

Table S33: Representative values reported for the historical 24-object, 17-variant development probe. The full candidate set is shown in Figure S22. The underlying row-level outputs and selection-time provenance are not available for independent reanalysis; the table records the submitted development result and does not establish an optimum.

Variant	Reported category	ΔFG-SSIM	ΔLap Var
C4	Late-stage high	0.105	−0.0120
C2	Timestep schedule	0.104	−0.0110
B2	Layer-wise schedule	0.090	−0.0135
A_s2.00	Uniform	0.087	−0.0062
C3	Mid-stage high	0.084	−0.0006
A_s2.25	Uniform	0.079	−0.0096
A_s2.50	Uniform	0.078	−0.0108
B6	Layer-wise schedule	0.000	−0.0027

Table S34: First-round 01549 3AFC results retained as reported. Percentages use 720 decisions per criterion; preference is not a measure of reference texture fidelity.

Method	Texture naturalness	Shape consistency	Overall quality
$s = 1.25$	332/720 (46.1%)	96/720 (13.3%)	176/720 (24.4%)
$s = 2.50$	104/720 (14.4%)	331/720 (46.0%)	126/720 (17.5%)
C3 (TCAS)	284/720 (39.4%)	293/720 (40.7%)	418/720 (58.1%)

aggressive baselines were +33.6 points (CI [19.3, 47.2]) and +40.6 points (CI [29.4, 51.8]). The single-criterion advantages for texture naturalness and shape consistency had intervals crossing zero. This bounded preference result does not validate texture fidelity, unseen-view quality, or the Fresh C cohort.




Figure S21: Historical per-object ΔFG-SSIM heatmap reproduced from the 01549 submission (50 objects, 13 scales). The plot illustrates the originally reported response variation; row-level provenance is incomplete, so it is not used for a current population inference.




Figure S22: Historical 17-variant development probe from the submitted 01549 paper (24 objects). The axes show changes in FG-SSIM and Laplacian variance; variance is a texture-variation diagnostic, not a fidelity measure. "C3" identifies the selected historical profile, not an optimum or general schedule law. The candidate-level outputs are unavailable for independent reanalysis.

Recoverable FAC code and bounded component validation

The separate recovered-source archive supplies byte-preserved controller, training/evaluation entries, local source dependencies and configuration snapshots, with a per-file source/hash manifest. It distinguishes an earlier entry whose default also optimizes the base adapter/geometry encoder unless `-freeze_adapter` is used, from the later controller-only entry that freezes these modules. Both remain unbound to the historical reported run; filenames and their existence cannot establish which complete CLI, weights and sampling order produced the old table.

Three distinct standalone CPU controller fixtures pass finite forward/gradient-path and bitwise state-save/load checks. The two recovered entries share byte-identical controller source; duplicate copies are not counted as independent validation. For nine adapters with 64-channel geometry and the delivered defaults, LTAG, LTAG+GSG and full FAC contain 3,433, 4,018 and 6,322 parameters. These tests exercise one injection point with synthetic 16-by-16 tensors, without a diffusion model, base weights or data. They validate component execution, not full-model training, old experiment identity or quality. The archived FSC actually uses real FFT rather than the DCT named in comments; its initial mask attenuates the test tensor and is not an exact identity. Current claims follow executable operations, not archival comments.

The supplied recovered 1,200-object configuration, missing historical seed/checkpoint and 1,706-object discrepancy remain unresolved. We provide code and an offline component rerun command, while explicitly withholding a complete historical FAC replay claim. The already reported FAC negative results are not reclassified as newly confirmed measurements.

Local historical weights and the original-cohort retraining addendum

Three existing files named `geotex_v2_ema_final.pt` independently match the previously recorded MD5 `a74cc1d16cb473a95022bdcbc58e1b22`. They are archive copies of the same historical v2 artifact, not three independent models. The submitted paper identifies v2 for the separate strong-residual Section 4.7/Table 9 and FAC context. Its main-table v1 file, `geotex_refattn_v1/geotex_step_0002000.pt`, lacks a recoverable run-bound byte identity. Consequently v2 recovery closes a v2 artifact-location question but not exact original-main-adapter replication.

The 12 October 2026 retraining removes all 79 intersections between the recorded 1,118 training UIDs and the historical 276 evaluation UIDs, retaining 1,039 training UIDs. The held-out list is exactly positions 24–299 of the original evaluation list; its recorded training intersection is zero. Training completes 2,000 steps with explicit seed 20261012 and the new step-2000 checkpoint SHA-256 `19ae8afa08886f774c1b18e1888badbc47108f820774906cd875a5aaa33cf05c`. This is one newly seeded checkpoint, not a measurement of training-seed variance. Evaluations retain No Adapter, Fixed Low 1.25, Fixed High 2.50 and C3, 50 Euler steps, 256-pixel target tiles and views [0,15,12,16,13,14]. Current audited source seeds data preprocessing with $42 + \text{index}$ and shared initial latents/inference with 42; conditions share one loaded batch and the same latent tensor. The resulting metrics use one 3×2 composite, not six independent statistical units.

The preserved full-frame metric uses all pixels. FG-PSNR uses pixels above the recorded foreground threshold; the audited mask-aware SSIM includes its documented local-mask dilation and the archived LPIPS masks normalized image inputs. These inherited definitions are not canonical interchangeable measures across interfaces. White-background PSNR replaces background pixels using the common target mask; its C3–Fixed High difference is -1.313536 dB, matching the foreground direction. No background-region metric is used to select a winning schedule. The endpoint reversal does not identify a new mechanism or validate physical material quality.

All 1,104 rows are unique and form a 276-by-four requested-slot Cartesian matrix; ordered `obj_0000` through `obj_0275` rows map to the evaluation manifest's requested list. The evaluation log records an empty-input error and a `wrongpath` diagnostic for UID `f7ef602b19214debb0b350db9af55ff2`, requested index 46. The inherited loader catches this error and randomly substitutes another input

without returning the actual UID. The manifest lacks actual loaded-UID/input hashes. Consequently exact 276-UID coverage, actual training–evaluation disjointness and the unique-object count cannot be certified. Each slot still shares one loaded batch across its four conditions, supporting bounded within-slot comparisons. Excluding `obj_0046` is an input-failure sensitivity rather than filtering by output quality: C3–Fixed High means over the remaining 275 requested slots are full-frame PSNR +1.696532 dB, FG-PSNR −1.311046 dB and FG-LPIPS +0.011272. All 276 original slots remain archived. Present-day helper-source snapshots are audited source rather than execution-time hashes; training-source/checkpoint hashes are checked against the preserved run manifest. The research-decision cohort was previously exposed and the analysis is retrospective.

The archived statistical audit resamples the 276 requested slots (10,000 bootstrap draws; 200,000 two-sided plus-one sign-flip draws), with a post-inspection 24-test Holm family covering eight endpoints and C3 against three controls. Because actual unique-object coverage is uncertified, these pointwise intervals and p values are technical diagnostics, not validated independent-object confirmation. Complete positive, non-detected and negative results are retained in Table S35. No actual sampling overlap is inferred for the unauthenticated historical v1 weights merely from a later list intersection. Fixed Mean, early/late allocations and Generic Linear are absent; the matrix does not identify timing-only effects. Records, failure-log excerpt, ordinal-exclusion sensitivity and recomputation are in `data/original276_retrain`.

Table S35: Complete exploratory C3 paired contrasts in the retrained historical-request panel. A minus B; positive PSNR/SSIM and negative LPIPS favor C3. All 276 requested slots retained, including one unknown actual-UID substitution. Pointwise slot-bootstrap intervals, favorable-slot counts and diagnostic 24-test Holm p are not independent-object confirmation.

Contrast	Endpoint	Mean [95% CI]	Favorable	Holm p
C3 – Fixed Low	Full-frame PSNR	+0.40246 [+0.32938, +0.47580]	208/276	0.00012
C3 – Fixed High	Full-frame PSNR	+1.69908 [+1.62148, +1.77602]	276/276	0.00012
C3 – No Adapter	Full-frame PSNR	+6.12787 [+5.94191, +6.31562]	276/276	0.00012
C3 – Fixed Low	Full-frame SSIM	+0.00218 [+0.00158, +0.00278]	178/276	0.00012
C3 – Fixed High	Full-frame SSIM	+0.00646 [+0.00564, +0.00727]	231/276	0.00012
C3 – No Adapter	Full-frame SSIM	+0.10147 [+0.09752, +0.10532]	276/276	0.00012
C3 – Fixed Low	Full-frame LPIPS	+0.00437 [+0.00364, +0.00511]	43/276	0.00012
C3 – Fixed High	Full-frame LPIPS	−0.00698 [−0.00818, −0.00576]	210/276	0.00012
C3 – No Adapter	Full-frame LPIPS	−0.39728 [−0.40313, −0.39148]	276/276	0.00012
C3 – Fixed Low	FG-PSNR	+0.78262 [+0.69539, +0.86682]	240/276	0.00012
C3 – Fixed High	FG-PSNR	−1.31354 [−1.38483, −1.24106]	9/276	0.00012
C3 – No Adapter	FG-PSNR	+2.62856 [+2.24209, +3.01227]	215/276	0.00012
C3 – Fixed Low	FG-SSIM	+0.02074 [+0.01823, +0.02336]	237/276	0.00012
C3 – Fixed High	FG-SSIM	−0.05961 [−0.06303, −0.05605]	9/276	0.00012
C3 – No Adapter	FG-SSIM	−0.11892 [−0.13162, −0.10631]	44/276	0.00012
C3 – Fixed Low	FG-LPIPS	−0.00048 [−0.00106, +0.00012]	174/276	0.11689
C3 – Fixed High	FG-LPIPS	+0.01127 [+0.01022, +0.01233]	30/276	0.00012
C3 – No Adapter	FG-LPIPS	−0.02180 [−0.02572, −0.01789]	217/276	0.00012
C3 – Fixed Low	Edge-SSIM	+0.00717 [+0.00626, +0.00810]	236/276	0.00012
C3 – Fixed High	Edge-SSIM	−0.02777 [−0.02937, −0.02613]	5/276	0.00012
C3 – No Adapter	Edge-SSIM	+0.02619 [+0.02167, +0.03055]	213/276	0.00012
C3 – Fixed Low	White-background PSNR	+0.78262 [+0.69539, +0.86682]	240/276	0.00012
C3 – Fixed High	White-background PSNR	−1.31354 [−1.38483, −1.24106]	9/276	0.00012
C3 – No Adapter	White-background PSNR	+2.62856 [+2.24208, +3.01226]	215/276	0.00012

Table S36: Historical-request condition means over 276 requested slots. One unknown actual UID was substituted; means are technical slot summaries, not independent-object estimates. Paired contrasts and their diagnostics are in Table S35.

Condition	Full PSNR	FG-PSNR	FG-LPIPS	FG-SSIM	Edge-SSIM
No Adapter	9.900	7.072	0.21750	0.39294	0.43594
Fixed Low	15.626	8.918	0.19618	0.25328	0.45496
Fixed High	14.329	11.014	0.18443	0.33363	0.48990
C3	16.028	9.701	0.19570	0.27402	0.46213




Figure S23: C3–Fixed High PSNR endpoint sensitivity in the retrained historical-request panel. Measurements use the same 276 requested slots, including one unknown replacement UID. Technical slot-bootstrap intervals do not validate independent-object replication. Excluding the recorded failed slot retains the opposing directions. The plot is computed from preserved CSV rows; no generated image is modified.

S8. Auxiliary training, deployment and projection exploration

Native training inputs, numerical safeguards and fixed training protocol

The recorded custom trainer's shortcomings motivate a new main-adapter training protocol; this is not a FAC retraining or a replay of the historical pooled result. Of 1118 recorded training UIDs, six lack required inputs. Strict evaluation of the remaining 1112 retains 1090 and lists 22 input failures before any output-quality assessment. The old loader's random replacement of a failed object is disabled. The retained cohort has zero UID overlap with the 300 Fresh C objects. Geometry and target views are 512 pixels, use unique6 ordering, and have fixed resize ratio 1.0. Native reference preprocessing is captured from the actual pipeline at its first UNet call, including positive and negative CLIP embeddings, reference latents and added time IDs; these cached inputs are not generated evaluation outputs.

Three zero-valued depth channels in a real training object formerly produced a non-finite inverse-depth normalization. Values that cannot be inverted are encoded using the existing invalid-depth value before inversion; source RGB and normal maps are unchanged. This guard does not establish the physical meaning of those zero values. A separate precision probe finds all nine initial residual tensors nonzero, but their half-precision mean squares underflow to zero; float32 evaluation gives positive means of order 10^{-8}. The new loss evaluates this term before clearing the wrapper records. Neither observation is used to claim a single cause of the historical quality failure.

Two scale-zero native outputs are pixel-identical to the preceding bare-base outputs. Captured conditions for the first two training UIDs are identical across the two GPUs. Two actual single-GPU optimizer steps, one conditional and one unconditional, produce finite nonzero gradients in both the adapters and geometry encoder, change their weight hashes, and use about 12.6 GB peak allocated

memory. Smoke weights are discarded. A separate two-rank backward gate confirms finite gradients for all active parameters and synchronized updates. The unused projected x1 branch is frozen in the up-only architecture while its weights remain stored; 2,201,760 parameters remain active.

The formal protocol freezes 2000 successful optimizer updates, two GPUs with one object each per update, AdamW learning rate 10^{-4} and weight decay 0.01, gradient clipping at 1.0, initialization seed 42, and actual Bernoulli conditioning dropout probability 0.1. Positive/negative native conditioning is selected by the realized dropout flag. The base denoiser remains frozen. Object order, noise step, dropout, loss terms, gradient scale and gradient norm are logged per rank. Checkpoints are stored every 500 updates, and the final step-2000 checkpoint is specified in advance rather than selected on output quality. The global batch differs from the historical single-object trainer; this is a new protocol and does not isolate any one training change. The fixed 2000 updates completed on both ranks, with 4000 total object exposures; realized conditioning-drop fractions are 0.0920 and 0.1085. A completion audit reproduces the seeded object order and dropout flags, verifies synchronized finite gradients and optimizer steps, and records the final checkpoint hash. The completed frozen evaluation is reported below; it is distinct from the historical checkpoint. Packaged preflight records permit integrity and cohort checks; rerunning GPU execution additionally requires the recorded base assets, rendered training data and software environment.

Frozen checkpoint and full-native baseline identity

The new main-adapter training uses the frozen local hf_repo UNet; its completion does not make it an official default-model replay. A read-only asset audit finds that the local converted v29 checkpoint includes 1680 UNet tensors and 863 ControlNet keys, and that the hf_repo UNet differs from the v29 custom UNet even after casting to the same precision. Thus the preceding bare-base controls identify the native inference loop with the stated frozen HF assets, not the complete official default weights and ControlNet pipeline. These differences are retained rather than changing the historical source assets or treating them as a single established cause of the observed appearance failures.

A CPU audit strictly loads all 2543 full-checkpoint keys into the official ControlNet architecture with matching shapes and values; the ControlNet branch has 1,254,646,800 parameters. This establishes local asset compatibility, not GPU execution, canonical remote checkpoint byte identity or deployment quality. The matched 50-step, seed-42 comparison differs from the official command-line defaults of 75 steps, seed 12 and background removal; those settings must be named explicitly. Input, architecture or weight-identity checks alone do not prove image quality. The fifty-object paired image test reports the two primary LPIPS contrasts: unscaled minus disabled is -0.01998 (95% interval $[-0.02831, -0.01247]$, Holm-adjusted Monte Carlo $p = 0.000010$), whereas Late-high minus Fixed Mean is $+0.00266$ (interval $[-0.000032, +0.006402]$, adjusted $p = 0.08042$). Four v29 development-object calls, crossing bare and full ControlNet on two previously inspected objects, complete successfully; these are interface demonstrations and are not pooled into the fifty-object cohort. The full v29 fifty-object baseline is separately frozen as a deployment comparison with different base weights; it cannot isolate geometry architecture alone. The new checkpoint's fifty-object cohort and object-level tests were frozen before viewing its outputs; inherited Fresh C exposure, nominal camera-direction limits and the absence of a FAC historical replay remain explicit.

Nine-condition evaluation and full-native comparison

The completed nine-condition deployment matrix contains 450 outputs on the same fifty objects. Against the local converted full v29 ControlNet pipeline, the new HF-based geometry checkpoint has lower FG-PSNR by 2.16 dB (paired 95% interval $[-3.15, -1.27]$), lower FG-SSIM by 0.0894, and higher FG-LPIPS by 0.0341 (interval $[0.0235, 0.0464]$); all three contrasts survive the separately predeclared four-endpoint Holm correction. The color-difference contrast is not separated after correction. This comparison does not establish competitive quality or isolate architecture, because the frozen base weights

differ. In the eighteen-test secondary family, Late-high also loses 1.18 dB to Fixed Mean; C3 has no corrected advantage over Fixed Mean or GFH on any endpoint. C3 exceeds Late-high in PSNR and color difference, without a separated LPIPS advantage. Thus neither the positive unscaled-versus-disabled result nor these contrasts establish C3 optimality or general temporal-allocation gains.

Each endpoint is averaged over the five nonreference views per object. The two primary tests, eighteen secondary tests and four separately frozen deployment tests use their own fixed Holm families. Bootstrap intervals resample objects (20,000 replicates); sign-flip Monte Carlo tests use 200,000 draws with a plus-one correction. All fifty objects remain in every condition. The constant-depth cube exposed a zero-range normalization guard in the full v29 input conversion: constant valid inverse depth is encoded as zero, matching the recorded existing dataset convention. The repaired converter is bit-identical on all thirty previously completed inputs, and the five completed outputs on the failed rank are reused only after hash checks. Input failure and restart records are retained. This repair does not depend on metric direction. The full baseline uses 50 steps, seed 42, CFG 2, control strength 1 and the recorded Fresh C geometry conversion, without background removal; it is not the original 75-step command-line default. Complete paired contrasts are tabulated below; these intervals are marginal, while the reported p values use the specified families.

Comparison	Endpoint	Difference	95% interval	Holm p
native_unset – disabled	fg_lpips	-0.0200	[-0.0283,-0.0125]	0.00001
budget_late16 – budget_fixed_mean	fg_lpips	+0.0027	[-0.0000,+0.0064]	0.08042
native_unset – disabled	fg_psnr	+3.8911	[+2.9906,+4.7864]	0.00009
native_unset – disabled	fg_ssim	+0.0397	[+0.0095,+0.0673]	0.05814
native_unset – disabled	ciede2000	-6.6704	[-9.2902,-4.1723]	0.00009
budget_late16 – budget_fixed_mean	fg_psnr	-1.1838	[-1.5870,-0.8495]	0.00009
budget_late16 – budget_fixed_mean	fg_ssim	-0.0110	[-0.0262,+0.0003]	0.87060
budget_late16 – budget_fixed_mean	ciede2000	+1.9587	[+1.4128,+2.7127]	0.00009
native_gc3 – native_gfh	fg_psnr	-1.1382	[-2.2846,+0.0737]	0.59865
native_gc3 – native_gfh	fg_lpips	-0.0060	[-0.0122,+0.0003]	0.59865
native_gc3 – native_gfh	fg_ssim	-0.0051	[-0.0196,+0.0085]	0.97985
native_gc3 – native_gfh	ciede2000	+1.3638	[-0.7338,+3.3865]	0.97985
native_gc3 – budget_fixed_mean	fg_psnr	-0.2358	[-0.5671,+0.0336]	0.89085
native_gc3 – budget_fixed_mean	fg_lpips	+0.0027	[+0.0004,+0.0059]	0.36025
native_gc3 – budget_fixed_mean	fg_ssim	-0.0071	[-0.0198,+0.0022]	0.97985
native_gc3 – budget_fixed_mean	ciede2000	+0.4729	[-0.0555,+1.2008]	0.90309
native_gc3 – budget_late16	fg_psnr	+0.9480	[+0.6372,+1.2802]	0.00009
native_gc3 – budget_late16	fg_lpips	+0.0001	[-0.0020,+0.0022]	0.97985
native_gc3 – budget_late16	fg_ssim	+0.0039	[-0.0017,+0.0097]	0.97985
native_gc3 – budget_late16	ciede2000	-1.4858	[-1.9209,-1.0335]	0.00009
native_unset – v29_full_controlnet	fg_psnr	-2.1635	[-3.1481,-1.2662]	0.00006
native_unset – v29_full_controlnet	fg_ssim	-0.0894	[-0.1175,-0.0650]	0.00002
native_unset – v29_full_controlnet	fg_lpips	+0.0341	[+0.0235,+0.0464]	0.00002
native_unset – v29_full_controlnet	ciede2000	+1.7981	[+0.0137,+3.8511]	0.06168

Same-v29-base training and frozen exploratory follow-up

A subsequent same-base check exports all 1680 UNet tensors from the local converted v29 asset into an isolated pipeline, retaining the same CLIP/VAE assets and verifying every loaded UNet tensor at execution precision. Actual native positive/negative reference conditions match the existing cache on both GPUs. The same fixed 2000-update training protocol then completes, followed by the previously studied fifty-object cohort. Unscaled geometry improves FG-LPIPS relative to geometry disabled by 0.0131 (95% interval $[-0.0189, -0.0083]$; 44/50 objects improve), but remains worse than full v29 by 0.0159 (interval $[0.0085, 0.0237]$); both primary comparisons survive Holm correction. FG-SSIM also remains lower than full v29 by 0.0533 in the six-test secondary family. The PSNR and color differences are not separated after correction, which does not establish equivalence. Matching the base weights reduces a comparison confound but does not match geometry architectures, their training histories or




Figure S24: Complete six-view grids for the first object in the frozen UID order, without output-based selection. These real outputs show why the weaker HF geometry-disabled comparison does not establish competitive performance against full v29. The new geometry module improves layout, while top/bottom semantic and reference-appearance failures remain. The target source view is included for context but excluded from the five-view inferential averages.

all input representations. This exploratory follow-up reuses previously observed objects and neither demonstrates temporal-scheduling superiority nor establishes a competitive quality claim (S8).

The isolated UNet export leaves original HF and v29 assets unchanged. Tensor identity is checked after geometry wrappers are installed, removing wrapper naming only and excluding adapter tensors. An actual native first-call hook verifies positive/negative CLIP embeddings, reference VAE latents and added time IDs against the existing cached conditions for two fixed training objects on each GPU. A two-rank conditional/unconditional backward gate passes before formal training. The first gate fails before optimizer updates because a newly added reference-condition check uses the evaluation data root; the corrected check uses the configured training root, and the failed record is retained. This does not change the formal training cohort or remove an unfavorable output.

The formal run uses the same 1090 training objects, fixed final step 2000, seed policy, cache, losses and actual dropout as the preceding run. The evaluation retains all fifty previously inspected objects, with the same reference images, seeds, geometry targets and five nonreference endpoint averages. Reused full-v29 scores come from the identical fifty-object input protocol. Primary FG-LPIPS contrasts form a frozen Holm family of two; PSNR, SSIM and color differences for the two pairs form a separate family of six. The follow-up is frozen before this checkpoint's outputs, but is not an independent replication because previous cohort results motivated the base correction. Intervals are marginal paired object-bootstrap intervals, not simultaneous confidence intervals. No noninferiority threshold is chosen after the results.

Comparison	Endpoint	Difference	95% interval	Holm p
Geometry – disabled	fg_lpips	-0.0131	[-0.0189,-0.0083]	0.00001
Geometry – full v29	fg_lpips	+0.0159	[+0.0085,+0.0237]	0.00014
Geometry – disabled	fg_psnr	+3.3589	[+2.6276,+4.1863]	0.00003
Geometry – disabled	fg_ssim	+0.0275	[+0.0135,+0.0460]	0.00003
Geometry – disabled	ciede2000	-5.6605	[-7.6065,-4.1823]	0.00003
Geometry – full v29	fg_psnr	-0.8542	[-1.6642,-0.0165]	0.10169
Geometry – full v29	fg_ssim	-0.0533	[-0.0711,-0.0352]	0.00003
Geometry – full v29	ciede2000	-0.6506	[-1.9014,+0.5307]	0.30864

Pixel-identical deployment performance

The performance protocol is frozen before timing. The first five UIDs in the fifty-object ordering are used without output-based selection. Phase 0 runs small geometry on GPU 0 and full v29 on GPU 1; phase 1 swaps them. Each process has its own resident pipeline, and the two GPUs share a CPU host during concurrent runs. This counterbalances card and order without removing every thermal or shared-host effect. Two first-object warm-ups precede fifteen timed calls per method/card. Geometry transfer and encoding, native reference preparation, denoising, VAE decoding and PIL conversion are inside the synchronized wall-time interval. Model load, disk input/output, CPU input-map construction and metric evaluation are outside it. No alternative precision, step count, reference cache or model compression is introduced.

All 68 calls, including eight warm-ups, match their previously evaluated output pixels exactly. Five saved PNGs per method/card independently verify this identity. The first full-v29 startup fails before generation because a resource guard is placed after this process creates its CUDA context; the corrected startup checks availability first and retains the failed attempt. Completed small-geometry records are reused, and no unfavorable timing or object is dropped. Per-GPU summaries and all raw timings are packaged. Peak allocated and reserved memory are both recorded; the main table reports allocated memory. Parameter counts include the base denoiser and geometry branch but exclude shared image encoders and VAE. Performance summaries are descriptive; repetitions do not increase the independent object count beyond five.




Figure S25: Complete grids for the first frozen object under the same-v29-UNet follow-up. The full ControlNet baseline was generated in the preceding round with the same inputs. All fifty objects enter the paired analysis; this fixed example is not selected by quality. View placement and texture appearance remain mixed in the image endpoints.

GPU	Deployment	Median (s)	Peak (GiB)	FG-LPIPS	FG-SSIM
0	Full v29	15.71	14.89	0.0775	0.6937
0	Small geometry	12.03	13.18	0.0934	0.6404
1	Full v29	14.58	14.89	0.0775	0.6937
1	Small geometry	11.17	13.18	0.0934	0.6404

The lower cost does not offset the measured quality loss by statistical fiat. No noninferiority bound or application utility function is introduced after observing results, and the architecture cost is not attributed to temporal scheduling.

Archived projection development and first-interface evaluation

This section records completed development and first-interface confirmation observations and external-input comparisons. The full fixed twenty-object bake evaluation is completed and reported in Supplementary Section S4. The development matrix comprises 32 previously studied objects per interface, four conditions, and three sampling seeds (42, 2026, 31415), for 384 object–condition–seed cells per interface. The two interfaces use different object sets and are not pooled as paired subjects. Sampling seeds do not estimate training-checkpoint variation.

For matched noisy latents, let f_u, f_c denote negative/positive conditional predictions with geometry and b_u, b_c the corresponding predictions without geometry. Define $a = b_c - b_u$, $g_0 = f_u - b_u$, and $h = (f_c - f_u) - a$. The native guided prediction is $b_u + g_0 + s(a + h)$. The development interaction candidate removes the negatively parallel component of h along a and retains g_0 algebraically. Total-geometry grid and view projections are separate comparison conditions. These are operations in noise-prediction space; a is not a pure appearance-loss gradient. Algebraic decomposition and vector projection alone do not establish method novelty.

On the unmodified first-interface seed-42 trajectories, 32 objects provide 50 observations each. The object-averaged cosine between the guided geometry contribution and a is -0.6426 (95% object-bootstrap interval $[-0.6611, -0.6235]$); all 1600 measured whole-grid rows are negative. The auxiliary measurement preserves final native pixels exactly. This validates measurement without disturbing the trajectory; negative cosine does not prove that the geometry contribution harms final appearance. Two MV-Adapter objects also show negative whole-object cosines at all 50 steps, with respective means -0.4965 and -0.4984. Two objects do not establish population generalization.

Table S37 reports projection-minus-native differences on first-interface development objects. Seeds and views are nested within objects; intervals use 20,000 object-bootstrap resamples and are descriptive rather than multiplicity-adjusted confirmatory tests. Source agreement improves, but the nonreference LPIPS intervals cross zero. No noninferiority margin was specified, and absence of a detected difference is not evidence of no quality loss.

Condition	Source FG-PSNR (dB)	Source ΔE_{00}	Nonreference FG-LPIPS
Total geometry, grid	$+2.74$ $[+1.57, +3.97]$	-1.09 $[-2.09, -0.38]$	-0.0016 $[-0.0044, +0.0012]$
Total geometry, view	$+3.01$ $[+1.80, +4.30]$	-1.16 $[-2.16, -0.46]$	$+0.0014$ $[-0.0017, +0.0047]$
Interaction only, grid	$+2.79$ $[+1.56, +4.09]$	-1.06 $[-2.07, -0.34]$	-0.0014 $[-0.0046, +0.0017]$

Table S37: Exploratory development differences and 95% object intervals. PSNR is higher-better; color difference and LPIPS are lower-better. All three sampling seeds are averaged within each of the 32 objects. These are not new independent confirmation objects.

Second-interface reference-fidelity interpretation requires pose calibration. Native view 0 has azimuth $-90°$ and view 1 has azimuth $0°$; source-view roles cannot be transferred from the first interface by index alone. In the current 32-object set, eight target assets use a white texture fallback. The source-alpha and candidate native-view-1 target masks have median pixel IoU 0.2606, so azimuth agreement alone does not establish pixel registration. Earlier full-frame reference comparison is also confounded by

background: reference-alpha background contributes a median 98.2% of full-frame squared error for native seed-42 view-1 outputs. A separate foreground/background-controlled diagnostic has completed, but its pose-registration limitation prevents interpreting it as validated reference fidelity or changing the confirmation endpoints.

Completed source-view confirmation and remaining tradeoffs. The 64-object, four-condition, three-seed matrix is complete (768 outputs). The cohort excludes the 32 development objects but remains within historically exposed Fresh C. The pre-generation specified view-projection versus native comparisons give source FG-PSNR +4.283 dB (object-bootstrap 95% CI $[+3.409, +5.205]$; 61/64 object means favorable) and CIEDE2000 −2.230 ($[-3.061, -1.563]$; 57/64 favorable). Both two-sided paired Monte Carlo sign-flip tests have Holm-adjusted $p \approx 0.000010$ across the two primaries. Seeds and views are nested within objects, not treated as independent samples.

Descriptive nonreference-view differences are FG-PSNR −0.282 dB (pointwise 95% CI [−0.672, +0.102]), FG-LPIPS +0.000269 ($[-0.001533, +0.002073]$), CIEDE2000 +0.425 ($[-0.157, +1.042]$), and FG-SSIM +0.01062 ($[+0.00171, +0.01957]$). These secondary intervals are unadjusted. Non-detection does not establish non-inferiority: no margin was specified. The result confirms source-view gains for this comparison, not universal multi-view gains, superiority of interaction projection, APG superiority, or cross-interface transfer. APG's enabled norm-clipping path initially failed because a matrix-norm operation received three reduction dimensions. An explicit vector norm fixes that implementation error without changing the frozen parameters; failed attempts are retained and the repaired APG matrix and its scoring are now complete.

Completed APG and calibrated second-interface comparisons. On the same 32-object, three-seed first-interface development set, view projection minus APG has nonreference FG-LPIPS +0.000800 for projection-only APG (pointwise 95% CI $[-0.002459, +0.004299]$) and −0.000462 for the paper SDXL clipping/momentum preset at native CFG 2 ($[-0.004354, +0.003482]$). Interaction projection gives −0.002070 ($[-0.005351, +0.001259]$) and −0.003331 ($[-0.007565, +0.000593]$), respectively. Holm correction across these four specified development comparisons detects no advantage (adjusted $p = 1, 1, 0.7251, 0.5100$). The paper preset is evaluated at the deployment CFG, not the original paper's CFG 15; no preset was selected or tuned on these results.

The native-camera embedded-baseColor targets are distinct from the unregistered reference-image domain discussed above. Re-rendering three input-selected MV-Adapter objects reproduces all 18 archived RGBA target views exactly; geometry-control masks and positions match the target render bitwise. The full 32-object, four-condition, three-seed set can therefore be scored against these native-camera targets, with no source/nonreference role inferred from the view index. The all-six-view FG-LPIPS projection-minus-native differences are +0.000184 (grid), −0.000522 (view), and −0.000864 (interaction). All pointwise intervals include zero and all three Holm-adjusted p values are 1. Eight white targets have legal constant-white embedded baseColor; they remain in the full cohort, with the 24 textured objects reported as a separate descriptive subset. This calibrated interface-specific endpoint does not measure registered source-reference fidelity, physical albedo, or final baked-texture quality.

S9. Figure credits, retained displays and record index

Figure 1 interface and control ownership

The current Figure 1 is an illustrative workflow schematic. Its building imagery illustrates reference conditioning, six-view generation and downstream texture construction; it is not presented as Fresh C or Bake10 cohort evidence. The drawing does not assert that all Fresh C objects were baked or that the historical C3 profile is optimal.

TCAS supplies the temporal requested profile. GeoTex-Adapter, the frozen U-Net feature path and group caps belong to the existing evaluated implementation. A wrapper caps the request before residual multiplication and frozen-feature addition. The correction depends on both geometry features and the current hidden features, as in Main Equation (2); the schematic abstracts that state dependency. The evaluated up-only Fresh C configuration uses up blocks 0, 1 and 2 as deep, middle and shallow groups. The shallow 0.8 cap applies throughout all three requested phases.

The editable method SVG is supplied as `figures/fig1_tcas_control.svg`. The SVG retains separate raster slots and native vector text and paths. The former experimental Figure 1 and its verified Fresh C/Bake10 identity records are preserved in the e943 baseline archive; those identities are not assigned to the current illustration. All other experimental displays retain the frozen source identities and credits described below.

Figure sources, licenses and selection

Object identities, licenses and selection rules are unchanged. Figure references below use scientific display roles rather than obsolete parent figure numbers; the current figure/asset mapping is supplied in `visual_candidates/VISUAL_SELECTION_MANIFEST_V4_PUBLIC.csv`. The retained Fresh C comparisons use reference and method-level RGB outputs with shared pixel crops. Complete preserved displays and the former main-text C3–GFL examples are supplied in this section. The selected examples are outcome-ranked illustrations, not a representative sample. The inherited Fresh C manifest retains the original layout lineage. Current source bytes, conditions, views, shared frames and ROI coordinates are indexed in `visual_candidates/VISUAL_SELECTION_MANIFEST_V4_PUBLIC.csv` and the archived record for retained displays. Malformed No Adapter visual columns are omitted; their metric rows, exploratory contrasts and failure records remain unchanged.

The Fresh C No Adapter condition suppresses geometry-adapter correction. In the MVPainter wrapper, when `_adapter_scale` is unset the geometry residual is applied without a scale multiplier. These are different settings: No Adapter is not a rendered comparison against the unmodified native-default adapter path. The primary 300-object image matrix contains no separate output for that native-default branch. Later ten-object native-residual controls are exploratory and use the controlled sampler; native MV-Adapter comparisons have a separate default-path identity contract. These checks do not establish complete GeoTex default-pipeline equivalence.

For the current three-row Main Figure 2, the source assets are *Green Iguan, re-created (not mine)* by dievitacola (`https://sketchfab.com/3d-models/1b0fd7f10ef84650bde143a4dba1a701`), *Mosque* by Xemz (`https://sketchfab.com/3d-models/10378d8ea7fd4e8a9bd9d9803e9bcaa9`), and *Specimen 103* by jason.loxton (`https://sketchfab.com/3d-models/068ac3dfc34a464c89a5c467eb951969`), each licensed CC BY 4.0 (`https://creativecommons.org/licenses/by/4.0/`). Source RGB frames and all four method columns share camera 000. The first row is selected from input properties; the positive and adverse rows are explicitly post-outcome examples. Main Figure 3 uses the Tire and baptismal font credits in Section S5, with one source-property median and one post-outcome benefit example. Actual source PNGs are 512×512; per-render metadata saying 1024×1024 is inconsistent with those hashed pixels and the top-level renderer setting. The inconsistency is retained in the V4 quality record.

The current rights ledger records the selected Fresh C assets below as CC Attribution (CC BY 4.0), with figure use allowed when attributed. The complete credit line for each use is:

Table S38: Attribution for selected Fresh C assets in the retained Fresh C displays.

Use	Full attribution
C3–GFL favorable context, C3–GFL endpoint-favourable example	*Building 03* by Shalmon, via Sketchfab (`https://sketchfab.com/3d-models/c76ac44df995482185077da81939b306`), licensed CC BY 4.0 (`https://creativecommons.org/licenses/by/4.0/`). Fresh C target-view RGB outputs are cropped to the same ROI and arranged without color or detail adjustment.
Strong fixed-control context, C3-versus-fixed-scale example	*Octaèdre* by Segolene Delamare, via Sketchfab (`https://sketchfab.com/3d-models/0571e6db30c84b1593bc55a8e145a430`), licensed CC BY 4.0 (`https://creativecommons.org/licenses/by/4.0/`). Fresh C target-view RGB outputs are cropped to the same ROI and arranged without color or detail adjustment.
Generic Linear counterexample	*Cube 01* by b0rF4x, via Sketchfab (`https://sketchfab.com/3d-models/06fa4974f8cd4d4ea792e98fa1521457`), licensed CC BY 4.0 (`https://creativecommons.org/licenses/by/4.0/`). Fresh C target-view RGB outputs are cropped to the same ROI and arranged without color or detail adjustment.
C3–GFL adverse context, adverse C3–GFL example	*Boat Low Poly Game Ready* by INinja, via Sketchfab (`https://sketchfab.com/3d-models/d0e116a62bfc4cdd9edf60671073b306`), licensed CC BY 4.0 (`https://creativecommons.org/licenses/by/4.0/`). Fresh C target-view RGB outputs are cropped to the same ROI and arranged without color or detail adjustment.
Color-failure context, selected Fresh C color/detail illustration	*E5-5-2* by artsiyu, via Sketchfab (`https://sketchfab.com/3d-models/f6979d7ff8e54c4daf00fee46f09a139`), licensed CC BY 4.0 (`https://creativecommons.org/licenses/by/4.0/`). This previously viewed object came from a pre-existing C3–GFL FG-LPIPS stratum and was not selected for color.



Figure S26: Selected illustrative adverse C3–GFL case from the rights-cleared Fresh C 2D pool. It is not a representative estimate and does not support color-correction, PBR, seam, or human-preference claims.

Retained C3–Fixed Low favorable and adverse examples




Figure S27: Matched Fresh C target-view RGB outputs for the same frozen object, reference, camera, checkpoint, runner, seed policy, and inference protocol. Each column pairs the full context (shared ROI in red) with its exact pixel crop. Case (a) was selected because C3 favors GFL on paired FG-PSNR and FG-LPIPS; both endpoints favor GFL in case (b). These outcome-selected examples do not estimate prevalence, texture fidelity, reference-color agreement, or downstream 3D/PBR quality. Model credits are in Supplementary Section S9; image hashes and ROI coordinates are in the Fresh C figure manifest.

Historical record index

Unique historical selections remain in Section S7; duplicate parent discussions are archived in `history/retained_parent_section32.tex`. Original protocol/attempt filenames retain their historical statuses. The release completion and validation manifests index the current completed experiment chain.

S10. Cross-branch experiment disposition

The final author-review ledger contains 105 experiment, iteration and archive entries, not 105 independent experiments. It includes ignored local records, historical source branches, retained recovery directories and rounds 001–015. The delivered CSV distinguishes actual metric records, report-level evidence, incomplete training/smoke attempts and document packaging. Frozen reports and known invalid results remain archived; this registry is an evidence map rather than another performance evaluation.

Table S39: Disposition of additional historical attempts. These records constrain the final claims rather than creating new successful methods or independent replication cohorts.

Record family	Use and scientific boundary
Historical fixed/layer/time searches	Old 24-object probes, old pooled 300-object extensions and strong-residual v2 panels explain development. Main v1 runtime identity remains incomplete; old favorable ranks are not an optimality argument.
Historical retraining and smokes	v2/v3/v4/v5, quick/extended and faithful/sweetspot directories have different configurations and completion evidence. Checkpoint existence is not a validated quality improvement; incomplete runs and NaN-update records remain listed.
FAC variants	Trained variants, frozen/penalized objectives and source-entry differences are retained as reported negative history in S7. Recovered components do not authenticate full historical training or imply that adaptive control generally fails.
A2/A3/A3b and scale diagnostics	Response heterogeneity, cap/stage tests, static-factorial and residual-budget feasibility remain auxiliary. Cross-layer raw-L_2 common-support evidence is withdrawn; no dose-independent mechanism is inferred.
TRB/TRB2 adaptive development	A separate old 24-object pilot failed promotion. TRB minus C3 FG-LPIPS is $+0.001302$ (pointwise interval $[+0.000079, +0.002549]$); after budget repair, TRB2 minus C3 is -0.000045 ($[-0.000827, +0.000670]$). The extra calibration pass adds cost, and no promoted 276 holdout was executed. This is development history, not a new winning algorithm.
Color-repair candidates	C1 failed visual inspection despite numerical changes; B2 improved only one of four development objects and failed its gate. Neither is incorporated into the final method or described as a validated repair.
Earlier native/camera/bake attempts	The old seven-object native quality panel and old five-object pole-mask/REPEAT evaluation have known calibration or sampling faults. Corrected records are separate; invalid results are not pooled with native50 or bake10.
Native training and full v29	New 2,000-step checkpoints, complete fifty-object controls and same-base training quantify local quality/cost limits in S8. Architecture, weights and training differences are not attributed to TCAS scheduling.
Projection/APG and GSO	Complete source/nonreference, second-interface and three-seed matrices retain favorable, non-detected and adverse effects in S4/S8. Calibration failures and post hoc GT-only revisions remain explicit.
Other system attempts	Historical SF3D, Wonder3D and Hunyuan preparation records do not establish a matched same-task texture benchmark here. Missing identity, endpoint or completion chains are not supplied by output counts.

Record family	Use and scientific boundary
Additional human-study audit	A separate later fixed-stimulus panel has documented assignment/provenance deviations and unresolved consent/ethics documentation. Its archive is retained for author review; it is not added to the manuscript as confirmatory or positive preference evidence. The original 3AFC study remains separately scoped in S7.
Paper versions and archives	Historical branch refs, conservative manuscripts, later FAC bundles and copied figures preserve research history. Document packaging is not a new training, generation or quality experiment.

The author-review audit reports and claim ledger give absolute local source paths and verification depth. The source-package copy of `data/attempt_registry/EXPERIMENT_LEDGER.csv` permits inspection of attempt identities and duplicate-cohort relationships. A metadata inventory is not a claim that every archived image or historical runtime has been manually validated. No new model output was produced during this final consolidation.