Supplementary Material

Timestep-Conditioned Adapter Scaling for Multi-view Diffusion Texture Generation

1 S1. Frozen protocols and provenance

The main clean-v2 evaluation uses the controlled-retraining checkpoint with SHA-256:

`0618d6b284ab47aa16d7a89dc447f5ba`
`4455ff6c9d918e5e129478a99e0114c0`

The strict holdout contains 276 objects and has ordered-list SHA-256:

`a6aa8ab6e475763e1b5e67dc8c712ec8`
`f1940e3952d65897c820887554bbd044`

All image evaluations use six unique views $(0, 15, 12, 16, 13, 14)$, 50 denoising steps, seed 42, and object-level paired bootstrap with 10,000 resamples and seed 20260928. The main four-condition run and the stage-placement follow-up are separate protocol surfaces. Their repeated C3 outputs are not identical and are therefore not pooled.

The complete records/CSV/PNG/hash audit is in `coordination/E0A_EVIDENCE_FREEZE_20260929.json`. It verifies 276 record JSON files, 1,104 stage rows, 1,104 serialized Full-SSIM rows, and exact object–condition pairing. The follow-up uses early/middle/late step counts 17/16/17. Nominal scale summaries are:

Table 1: Nominal and recorded budget quantities for the stage-placement follow-up.

Schedule	Step mean	Scale sum	Squared-scale sum	Actual L2 mean
Fixed mean	1.6667	83.3333	138.8889	8936.92
HLL	1.6750	83.7500	157.8125	9239.76
LHL	1.6500	82.5000	153.1250	8799.86
LLH	1.6750	83.7500	157.8125	8777.53

The residual norms are descriptive measures of effective intervention intensity; they do not identify residual-direction alignment or establish a causal mechanism.

2 S2. Complete stage-placement metrics

The follow-up means are reproduced below. LPIPS is lower-is-better. The six non-SSIM metrics all favor LLH over LHL under their intended directions.

Schedule	Full-PSNR	Full-SSIM (pre-save)	Full-LPIPS	FG-PSNR	FG-SSIM	FG-LPIPS	Edge-SSIM
Fixed mean	14.311	0.8435	0.188	6.257	0.316	0.205	0.499
HLL	13.397	0.8252	0.202	5.583	0.259	0.212	0.464
LHL	14.868	0.8546	0.190	6.760	0.348	0.201	0.500
LLH	15.136	0.8518	0.181	6.937	0.357	0.200	0.536

The saved-artifact Full-SSIM means are fixed-mean 0.87395, HLL 0.85993, LHL 0.88144, and LLH 0.88313. LHL minus fixed-mean is +0.00749 ([0.00674,0.00826]), LHL minus HLL is +0.02151 ([0.01984,0.02319]), and LHL minus LLH is −0.00170 ([-0.00205,-0.00134]). These are paired object-level 95% bootstrap intervals, not equivalence tests.

3 S3. Fixed-GT Full-SSIM decomposition

The controlled 12-object trace saved A (pre-save prediction), B (PNG encoder input), C (PNG-reloaded prediction), the original float GT, and the PNG-reloaded GT. A and B are exactly equal. With the GT held fixed, the mean SSIM effects are:

This decomposition is diagnostic and does not recover historical 300-object pre-save tensors. The machine-readable rows are in `FIXED_GT_SSIM_DECOMPOSITION.csv/json` under the controlled trace directory.

Table 2: Mean Full-SSIM changes in the fixed-GT 12-object decomposition.

Comparison	Mean change
A fp16 → A fp32, original GT fixed	+0.03198
A fp32 → C fp32, original GT fixed	−0.00036
Original GT → PNG GT, A fp32 fixed	−0.00007
A/original GT → C/PNG GT	−0.00043

4 S4. Twelve-object Exact-GLB baking audit

The stratified case study contains 12 frozen Exact-GLB objects, four generated conditions, 48 exported textured GLBs, and 528 unseen-view rows (11 views per object–condition). Six source views were used for baking. The object-level means are:

Table 3: Unseen-view baking means for the selected case-study cohort.

Method	Masked PSNR	CIEDE2000	FG-LPIPS	Silhouette IoU
No adapter	11.824	18.200	0.156	0.99968
Fixed-low	6.001	48.623	0.199	0.99968
Fixed-high	3.891	60.420	0.216	0.99968
C3/LHL	5.638	51.183	0.201	0.99968

Coverage, post-inpainting coverage, seam definitions, and per-object rows are provided in the `cpu_bake_12` audit directory. DISTS was unavailable; the cohort has no generated 12-object GT bake. Blender reindexed vertices for `obj_0048`; this is not a byte-identity guarantee. Generated renders show source-fusion colour inconsistency, so this audit is implementation/case-study evidence, not a population-level TCAS advantage.

Table 4: Concrete object-level baking failure boundaries. Values are object means over 11 unseen views; paired entries are fixed-low/C3.

Object	Raw cov.	Inpaint frac.	Masked PSNR	CIEDE2000	FG-LPIPS	Boundary
`obj_0048`	0.1547	0.8441	5.090/4.927	53.328/54.339	0.388/0.375	Blender reindexing
`obj_0078`	0.0328	0.2802	4.278/3.879	58.822/61.431	0.066/0.068	very low raw coverage
`obj_0082`	0.0286	0.4951	4.144/3.823	55.558/57.364	0.081/0.082	very low raw coverage

These cases make the failure boundary concrete: the low-coverage objects remain limited even after propagation, while `obj_0048` obtains most of its final texture coverage from inpainting. The GT-to-GT sanity check was only a two-object smoke (`obj_0013` and `obj_0015`); it is not a 12-object GT bake. The bake handoff has blank canonical `source_asset_sha256` fields, and the saved seam scalar does not include a seam-pair count, so source identity and seam denominators remain audit limitations.

5 S5. Independent MV-Adapter audit

The Exact 76-object audit records 11 evaluated conditions/schedules and separates high-scale 1.50 and high-scale 1.00 families. The selected-pair CAI rule is `undefined_set_valued`. The LHL direct transfer has no clear practical gain over fixed-low or fixed mean; confidence intervals crossing zero are not interpreted as equivalence. Official pretraining UID disjointness is unknown. Absolute PSNR and other scores are not compared with the main MVPainter-style backbone. The full evidence is in `MV_ADAPTER_UNIFIED_RESULTS.csv` and `MV_ADAPTER_PAIRED_COMPARISONS.json`. The original `results/holdout_exact_76/PROTOCOL.json` is absent; `run_config.json` and `paired_bootstrap_exact.json` provide the available partial provenance.

6 S6. FAC controlled re-examination

FAC is a separate learned extension protocol, not a main contribution. The base model, VAE, and adapter are frozen; only lightweight controllers are trained on a disjoint training pool. Under the paired re-examination, no trained configuration improves the training-free schedule. The paired foreground-PSNR deficits range from -1.10 to -2.94 dB, while the untrained exact-envelope control has $\Delta = -0.18$ dB with 95% CI $[-0.42, +0.05]$. The interval crossing zero is not an equivalence claim. The complete dose–response records are retained as a negative extension audit; the earlier positive FAC comparison used a different protocol and is not used in the revised claims.

7 S7. Bounded residual-budget controller pilot

We tested one residual-budget controller extension (TRB-TCAS) on the 24-object clean-v2 development probe before considering any holdout run. The run used 50 denoising steps, six unique target views, seed 42, shared per-object batches and initial latents, and fixed-low, C3/LHL, HLL and LLH controls. FG-LPIPS was the pre-specified primary metric. TRB obtained FG-LPIPS 0.1349, compared with 0.1404 for fixed-low and 0.1336 for C3; its PSNR was 22.700 dB, compared with 22.261 dB for fixed-low and 22.971 dB for C3. The calibration pass approximately doubled the mean controller time per object (12.342 s versus 6.075 s for C3). Since TRB did not improve the existing C3 schedule and added cost, the branch was stopped before a holdout run. These results are retained as a negative method-iteration record, not as a claim about the main TCAS method.

The machine-readable output is `TRB_DEV24_GATE_20260929.md` and the independent pilot `pilot_results.json`. The pilot does not justify relabelling LLH as a CAI-selected schedule: LLH is reported only as a fixed schedule control.