Vercel Authentication

Visitors must be logged in to Vercel and a member of your team to view your deployments.

Learn more about Vercel Authentication

Password Protection

Visitors must enter a password to view your deployments.

This feature is available on the Pro plan with Password Protection for **$20 per project each month**.

Trusted Sources

Let trusted projects and services access this project's protected deployments using short-lived OIDC tokens. Use it for service-to-service calls, CI, or local tooling.

Source	Access
nexus (This project)	All tokens can access matching environments, `development` tokens can access `preview`

Learn more about Trusted Sources

Trusted IPs

Restrict access to deployments to visitors from specific IP addresses only. A maximum of 20 IP addresses can be added.

IP / CIDR

1.

This feature is available on the Enterprise plan.

Protection Bypass for Automation

Let automation services access this project's protected deployments. To bypass Deployment Protection, send the `x-vercel-protection-bypass` header or query parameter with any value below. Designate one secret as the `VERCEL_AUTOMATION_BYPASS_SECRET` system environment variable to make it available to all deployments.

Add a secret that can be used to bypass Deployment Protection for this project.

Learn more about Protection Bypass for Automation

Shareable Links

Give collaborators outside your Vercel team access to protected deployments.

Create links for any deployment's up-to-date URL from the Share button on a deployment page, or from the toolbar on a Preview deployment. Shareable Links bypass Vercel Authentication, Password Protection, and Trusted IPs when those features are enabled. Active links for this project are listed below.

No active shareable links

Links created from the Share button on this project's deployments will appear here.

Learn more about Shareable Links

Deployment Protection Exceptions

Specify pre-production domains to exclude from Deployment Protection.
Listed domains are unprotected and publicly accessible.

Learn more about Deployment Protection Exceptions

OPTIONS Allowlist

Specify paths where `OPTIONS` requests bypass deployment protection. This allows CORS preflight requests, which browsers send without authentication. Any `OPTIONS` request whose path starts with a listed prefix bypasses protection.

Learn more about OPTIONS Allowlist

Protected Sourcemaps

Ensures sourcemaps are only accessible to authenticated team members.

Learn more about Protected Sourcemaps