Scan Report

October 27, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was "Escaneo infraestructura - app-web Ferreteria (172.28.0.20)". The scan started at Tue Oct 27 10:31:00 2026 UTC and ended at Tue Oct 27 10:36:44 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**

2 Results per Host **2**

2.1 172.28.0.20 2

2.1.1 Low general/icmp 2

2.1.2 Low general/tcp 3

2.1.3 Log general/tcp 4

2.1.4 Log 8000/tcp 5

2.1.5 Log general/CPE-T 9

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
172.28.0.20 app-web.soc-net	0	0	0	2	11	0
Total: 1	0	0	0	2	11	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Debug" are not shown.
Issues with the threat level "False Positive" are not shown.
Only results with a minimum QoD of 70 are shown.

This report contains all 13 results selected by the filtering described above. Before filtering there were 13 results.

2 Results per Host

2.1 172.28.0.20

Host scan start Tue Oct 27 10:31:43 2026 UTC
Host scan end Tue Oct 27 10:36:39 2026 UTC

Service (Port)	Threat Level
general/icmp	Low
general/tcp	Low
general/tcp	Log
8000/tcp	Log
general/CPE-T	Log

2.1.1 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

... continues on next page ...

... continued from previous page ...

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 172.28.0.20]

2.1.2 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 1024157979
Packet 2: 1024159063
```

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

... continues on next page ...

... continued from previous page ...

References
url: https://datatracker.ietf.org/doc/html/rfc1323
url: https://datatracker.ietf.org/doc/html/rfc7323
url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152
url: https://www.fortiguard.com/psirt/FG-IR-16-090

[return to 172.28.0.20]

2.1.3 Log general/tcp

Log (CVSS: 0.0)

NVT: OS Detection Consolidation and Reporting

Summary
This script consolidates the OS information detected by several VTs and tries to find the best matching OS.
Furthermore it reports all previously collected information leading to this best matching OS. It also reports possible additional information which might help to improve the OS detection.
If any of this information is wrong or could be improved please consider to report these to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Best matching OS:
OS:           Linux/Unix
CPE:          cpe:/o:linux:kernel
Found by VT:  1.3.6.1.4.1.25623.1.0.111067 (Operating System (OS) Detection (HTT
↪P))
Concluded from HTTP Server banner on port 8000/tcp: Server: gunicorn
Setting key "Host/runs_unixoide" based on this information
Other OS detections (in order of reliability):
OS:           Linux/Unix
CPE:          cpe:/o:linux:kernel
Found by VT:  1.3.6.1.4.1.25623.1.0.149043 (Gunicorn Detection (HTTP))
```

Solution:

Log Method
Details: OS Detection Consolidation and Reporting
OID:1.3.6.1.4.1.25623.1.0.105937
Version used: 2026-10-20T05:48:09Z

References
url: https://forum.greenbone.net/c/vulnerability-tests/7

Log (CVSS: 0.0)

NVT: IP Forwarding Enabled - Active Check

Summary
Checks if the remote host has IP forwarding enabled.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
```
It was possible to route a TCP packet through the target host and received an an
↪swer which means IP forwarding is enabled.
```

Solution:

... continues on next page ...

. . . continued from previous page . . .

Log Method
Sends a crafted Local Link Layer (LLL) frame and checks the response.
Details: `IP Forwarding Enabled - Active Check`
OID:1.3.6.1.4.1.25623.1.0.147205
Version used: `2026-10-08T05:49:09Z`

References
`cve: CVE-1999-0511`

Log (CVSS: 0.0)

NVT: Traceroute

Summary
Collect information about the network route and network distance between the scanner host and the target host.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Network route from scanner (172.28.0.2) to target (172.28.0.20):
172.28.0.2
172.28.0.20
Network distance between scanner and target: 2
```

Solution:

Vulnerability Insight
For internal networks, the distances are usually small, often less than 4 hosts between scanner and target. For public targets the distance is greater and might be 10 hosts or more.

Log Method
A combination of the protocols ICMP and TCP is used to determine the route. This method is applicable for IPv4 only and it is also known as 'traceroute'.
Details: `Traceroute`
OID:1.3.6.1.4.1.25623.1.0.51662
Version used: `2022-10-17T11:13:19Z`

Log (CVSS: 0.0)

NVT: Hostname Determination Reporting

Summary
The script reports information on how the hostname of the target was determined.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Hostname determination for IP 172.28.0.20:
Hostname|Source
app-web.soc-net|Reverse-DNS
```

Solution:

Log Method
Details: `Hostname Determination Reporting`
OID:1.3.6.1.4.1.25623.1.0.108449
Version used: `2022-07-27T10:11:28Z`

[return to 172.28.0.20]

2.1.4 Log 8000/tcp

Log (CVSS: 0.0)

NVT: HTTP Server Banner Enumeration

Summary
This script tries to detect / enumerate different HTTP server banner (e.g. from a frontend, backend or proxy server) by sending various different HTTP requests (valid and invalid ones).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
It was possible to enumerate the following HTTP server banner(s):
Server banner    | Enumeration technique
-----------------------------------------------------------
Server: gunicorn | Valid HTTP 1.0 GET request to '/index.htm'
```

Solution:

Log Method
Details: HTTP Server Banner Enumeration
OID:1.3.6.1.4.1.25623.1.0.108708
Version used: 2025-01-31T15:39:24Z

Log (CVSS: 0.0)

NVT: HTTP Server type and version

Summary
This script detects and reports the HTTP Server's banner which might provide the type and version of it.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The remote HTTP Server banner is:
Server: gunicorn
```

Solution:

Log Method
Details: HTTP Server type and version
OID:1.3.6.1.4.1.25623.1.0.10107
Version used: 2023-08-01T13:29:10Z

Log (CVSS: 0.0)

NVT: HTTP Security Headers Detection

Summary
All known security headers are being checked on the remote web server.
On completion a report will hand back whether a specific security header has been implemented (including its value and if it is deprecated) or is missing on the target.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Header Name                | Header Value
-----------------------------------------
Cross-Origin-Opener-Policy | same-origin
Referrer-Policy            | same-origin
X-Content-Type-Options     | nosniff
Missing Headers                    | More Information
-------------------------------------------------------------------------------
↪-----------------------------------------------------------------------------
↪-----------------------------------------------
Content-Security-Policy            | https://owasp.org/www-project-secure-headers
```

... continues on next page ...

...continued from previous page ...

```
↪/#content-security-policy
Cross-Origin-Embedder-Policy      | https://scotthelme.co.uk/coop-and-coep/, Not
↪e: This is an upcoming header
Cross-Origin-Resource-Policy      | https://scotthelme.co.uk/coop-and-coep/, Not
↪e: This is an upcoming header
Document-Policy                   | https://w3c.github.io/webappsec-feature-poli
↪cy/document-policy#document-policy-http-header
Feature-Policy                    | https://owasp.org/www-project-secure-headers
↪/#feature-policy, Note: The Feature Policy header has been renamed to Permissi
↪ons Policy
Permissions-Policy                | https://w3c.github.io/webappsec-feature-poli
↪cy/#permissions-policy-http-header-field
Sec-Fetch-Dest                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-Mode                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-Site                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-User                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
X-Frame-Options                   | https://owasp.org/www-project-secure-headers
↪/#x-frame-options
X-Permitted-Cross-Domain-Policies | https://owasp.org/www-project-secure-headers
↪/#x-permitted-cross-domain-policies
X-XSS-Protection                  | https://owasp.org/www-project-secure-headers
↪/#x-xss-protection, Note: Most major browsers have dropped / deprecated suppor
↪t for this header in 2020.
```

Solution:

Log Method
Details: HTTP Security Headers Detection
OID:1.3.6.1.4.1.25623.1.0.112081
Version used: 2025-03-21T15:40:43Z

References
url: https://owasp.org/www-project-secure-headers/
url: https://owasp.org/www-project-secure-headers/#div-headers
url: https://securityheaders.com/

Log (CVSS: 0.0)

NVT: Web Application Scanning Consolidation / Info Reporting

Summary
The script consolidates and reports various information for web application (formerly called 'CGI') scanning.
This information is based on the following scripts / settings:
- HTTP-Version Detection (OID: 1.3.6.1.4.1.25623.1.0.100034)
- No 404 check (OID: 1.3.6.1.4.1.25623.1.0.10386)
- Web mirroring / webmirror.nasl (OID: 1.3.6.1.4.1.25623.1.0.10662)
- Directory Scanner / DDI_Directory_Scanner.nasl (OID: 1.3.6.1.4.1.25623.1.0.11032)
- The configured 'cgi_path' within the 'Scanner Preferences' of the scan config in use
- The configured 'Enable CGI scanning', 'Enable generic web application scanning' and 'Add historic /scripts and /cgi-bin to directories for CGI scanning' within the 'Global variable settings' of the scan config in use
If you think any of this information is wrong please report it to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The Hostname/IP "app-web.soc-net" was used to access the remote host.
Generic web application scanning is disabled for this host via the "Enable gener
↪ic web application scanning" option within the "Global variable settings" of t
↪he scan config in use.
Requests to this service are done via HTTP/1.1.
```

...continues on next page ...

...continued from previous page ...

```
This service seems to be able to host PHP scripts.
This service seems to be able to host ASP scripts.
The User-Agent "Mozilla/5.0 [en] (X11, U; OpenVAS-VT <version replaced>)" was us
↪ed to access the remote host.
Historic /scripts and /cgi-bin are not added to the directories used for web app
↪lication scanning. You can enable this again with the "Add historic /scripts a
↪nd /cgi-bin to directories for CGI scanning" option within the "Global variabl
↪e settings" of the scan config in use.
The following directories were used for web application scanning:
http://app-web.soc-net:8000/
While this is not, in and of itself, a bug, you should manually inspect these di
↪rectories to ensure that they are in compliance with company security standard
↪s
```

Solution:

Log Method
Details: `Web Application Scanning Consolidation / Info Reporting`
OID:1.3.6.1.4.1.25623.1.0.111038
Version used: `2026-02-24T05:57:09Z`

References
url: https://forum.greenbone.net/c/vulnerability-tests/7

Log (CVSS: 0.0)

NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`A web server is running on this port`

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)

NVT: Gunicorn Detection (HTTP)

Summary
HTTP based detection of the Gunicorn (Green Unicorn) HTTP server.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected Gunicorn
Version:       unknown
Location:      8000/tcp
CPE:           cpe:/a:gunicorn:gunicorn
Concluded from version/product identification result:
Server: gunicorn
```

...continues on next page ...

. . . continued from previous page . . .

Solution:

Log Method
Details: Gunicorn Detection (HTTP)
OID:1.3.6.1.4.1.25623.1.0.149043
Version used: 2022-12-23T10:22:17Z

References
url: https://gunicorn.org/

[return to 172.28.0.20]

2.1.5 Log general/CPE-T

Log (CVSS: 0.0)

NVT: CPE Inventory

Summary
This routine uses information collected by other routines about CPE identities of operating systems, services and applications detected during the scan.
Note: Some CPEs for specific products might show up twice or more in the output. Background:
After a product got renamed or a specific vendor was acquired by another one it might happen that a product gets a new CPE within the NVD CPE Dictionary but older entries are kept with the older CPE.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
172.28.0.20|cpe:/a:gunicorn:gunicorn
172.28.0.20|cpe:/o:linux:kernel

Solution:

Log Method
Details: CPE Inventory
OID:1.3.6.1.4.1.25623.1.0.810002
Version used: 2022-07-27T10:11:28Z

References
url: https://nvd.nist.gov/products/cpe

[return to 172.28.0.20]