

MOST

BLF Logging Format

Specification

Version 1.8.8 of 2017-04-19

Status	Completed
Publisher	<p>Vector Informatik GmbH</p> <p>© 2017 All rights reserved.</p> <p>Any distribution or copying is subject to prior written approval by Vector.</p> <p>Note: Hardcopy documents are not subject to change management.</p>

Document Management

Revision list

Version	Date	Editor	Section	Changes, comments
1.0.0	2008-12-10	Mm	All	Initial Version Created; reviewed and released for CANoe/CANalyzer versions 5.1, 5.2, 6.0, 6.1, 7.0, 7.1
1.2.0	2009-01-30	Mm	2.18-2.24	MOST150 events; reviewed and released for CANoe/CANalyzer 7.1 SP2
1.3.0	2009-04-29	Mm	2.24	MOST System Event added reviewed and released for CANoe/CANalyzer 7.1 SP4
1.4.0	2009-05-18	Mm	1	Added disclaimer
1.4.1	2009-08-03	Mm	3.1.10	Special register event transports MAC address for Ethernet over MOST150 since CANoe/CANalyzer 7.2
1.5.0	2009-09-24	Mm	3.1.8, 3.3, 3.8, 3.25	AckNack and State fields adapted; MOST150 Allocation Table event added; new HW modes; new stress modes; reviewed and released for CANoe/CANalyzer 7.2
1.6.0	2010-01-08	Mm	3.12, 3.21, 3.22, 3.25, 3.26, 3.27	Additional DataLost flag; Events for MOST50; reviewed and released for CANoe/CANalyzer 7.2 SP3
1.7.0	2010-02-17	Sha	3.1.2; 3.1.3	New member mObjectVersion in VBLObjectHeader and VBLObjectHeader2
1.7.1	2010-04-15	Mm	3.1.7, 3.1.8, 3.18, 3.19, 3.20, 3.26, 3.27	Detailed information about transmission state added; reviewed and released for CANoe/CANalyzer 7.2 SP3
1.8	2010-11-10	Mm	3.6, 3.19, 3.23	Added max packet length; reviewed and released for CANoe/CANalyzer 7.2 SP3
1.8.1	2011-04-12	Mm	3.3.28	ECL event added
1.8.2	2011-06-07	Tlr	3.21, 3.22, 3.23	Max value for mFirstDataLen in VBLMOST150MessageFragment , VBLMOST150PktFragment and VBLMOSTEthernetPktFragment changed to 1524; reviewed and released for CANoe/CANalyzer 7.6 SP2
1.8.3	2011-09-29	Mm	3.8, 3.17	HW mode flag EthSpy added, Stress mode added; reviewed and released for CANoe/CANalyzer 7.6 SP3
1.8.4	2012-01-24	Mm	3.18-23 3.1.12	PAck and CAck details Fragments are now marked as MOST50 or MOST150

Version	Date	Editor	Section	Changes, comments
1.8.5	2012-04-12	Mm	all	Minor corrections; reviewed and released for CANoe/CANalyzer 8.0
1.8.6	2012-08-16	Mm	3.21-23 3.25	Explanation of length fields in fragment events Maximum number of free bytes in AllocTable event
1.8.7	2013-03-20	Tlr	3.24	New value for mld
1.8.8	2016-04-19	Mom	All	CI and layout

Contents

1	Disclaimer	6
2	Overview	6
3	Format Description	6
3.1	Common Data Types	6
3.1.1	VLObjectHeaderBase	6
3.1.2	VLObjectHeader	7
3.1.3	VLObjectHeader2	7
3.1.4	Direction	8
3.1.5	Control message sub type	8
3.1.6	Addressing mode	8
3.1.7	Transmission state MOST25	9
3.1.8	Transmission state MOST50/150	9
3.1.9	Acknowledge code	9
3.1.10	Register event sub type	10
3.1.11	Register ID	10
3.1.12	Fragment Mask	11
3.1.13	Transfer Type	11
3.2	VBLMOSTSpy	11
3.3	VBLMOSTCtrl	12
3.4	VBLMOSTLightLock	12
3.5	VBLMOSTStatistic	13
3.6	VBLMOSTPkt	13
3.7	VBLMOSTPkt2	13
3.8	VBLMOSTHWMMode	14
3.9	VBLMOSTReg	15
3.10	VBLMOSTGenReg	15
3.11	VBLMOSTNetState	15
3.12	VBLMOSTDataLost	16
3.13	VBLMOSTTrigger	17
3.14	VBLMOSTStatisticEx	17
3.15	VBLMOSTTxLight	18
3.16	VBLMOSTAllocTab	18
3.17	VBLMOSTStress	18
3.18	VBLMOST150Message	19
3.19	VBLMOST150Pkt	20
3.20	VBLMOSTEthernetPkt	20
3.21	VBLMOST150MessageFragment	21
3.22	VBLMOST150PktFragment	22
3.23	VBLMOSTEthernetPktFragment	23

3.24	VBLMOSTSystemEvent	24
3.25	VBLMOST150AllocTab	25
3.26	VBLMOST50Message	26
3.27	VBLMOST50Pkt	26
3.28	VBLMOSTEcl	27

1 Disclaimer

Severability clause - Restrictions for the usage of Vector logging data formats outside of Vector products

The format specification / access functions for the Vector BLF and ASC logging data formats are made available under the restrictions and conditions cited hereafter.

Please note that Vector Informatik neither gives any guarantee nor assumes any liability beyond compulsory legal regulations for the BLF or ASC logging format respectively as well as for the access functions to the single objects.

Vector Informatik disclaims all liability for errors which might be contained in the access functions or the format specification itself.

Vector Informatik does neither provide support for the integration into your software nor for problems occurring inside your software on the customer side.

Beyond that Vector Informatik reserves the right to change the BLF or ASC data format respectively anytime without prior notification. Therefore, the compatibility of the format is not ensured.

2 Overview

The document specifies the format of MOST events in the CANoe/CANalyzer BLF logging. The described structures can be used to read and write BLF logging files using the binlog.dll, which can be found in the CANoe/CANalyzer User Data folder:

<UserDataFolder>\Programming\BLF_Logging

3 Format Description

3.1 Common Data Types

3.1.1 VBLObjectHeaderBase

Description: Object header base structure.

Parameter	Type	Description
mSignature	DWORD	Object signature, must be BL_OBJ_SIGNATURE.
mHeaderSize	WORD	Size of header in bytes, set this member to sizeof(VBLObjectHeader) or sizeof(VBLObjectHeader2) depending on the object header type used for the object.
mHeaderVersion	WORD	Version number of object header. Set this member to 1 if the object has a member of type VBLObjectHeader. Set this member to 2 if the object has a member of type VBLObjectHeader2.
mObjectSize	DWORD	Object size in bytes.
mObjectType	DWORD	Object type (BL_OBJ_TYPE_*).

3.1.2 VBObjectHeader

Description: Object header. Version 1.

Parameter	Type	Description
mBase	VBObjectHeaderBase	Common object header base. See 3.1.1.
mObjectFlags	DWORD	Unit of object timestamp. Following values are possible: 1: Object time stamp is saved as multiple of ten microseconds (BL_OBJ_FLAG_TIME_TEN_MICS) 2: Object time stamp is saved in nanoseconds. (BL_OBJ_FLAG_TIME_ONE_NANS)
mReserved	WORD	Reserved, must be 0.
mObjectVersion	WORD	Object specific version, has to be set to 0 unless stated otherwise in the description of a specific event.
mObjectTimeStamp	ULONGLONG	Time stamp of this object in the unit specified in mObjectFlags.

3.1.3 VBObjectHeader2

Description: Object header. Version 2.

Parameter	Type	Description
mBase	VBObjectHeaderBase	Common object header base. See 3.1.1.
mObjectFlags	DWORD	Unit of object timestamp. Following values are possible: 1: Object time stamp is saved as multiple of ten microseconds (BL_OBJ_FLAG_TIME_TEN_MICS) 2: Object time stamp is saved in nanoseconds. (BL_OBJ_FLAG_TIME_ONE_NANS)
mTimeStampStatus	BYTE	Bit field. The bits have the following meanings: Bit 0: Determines whether original timestamp member is valid (1) or not (0). Bit 1: Timestamp is generated by software (1) or by hardware (0). Bit 5: This bit has protocol specific meaning.
mReserved1	BYTE	Reserved, must be 0.

Parameter	Type	Description
mObjectVersion	WORD	Object specific version, has to be set to 0 unless stated otherwise in the description of a specific event.
mObjectTimeStamp	ULONGLONG	Time stamp of this object in the unit specified in mObjectFlags.
mOriginalTimeStamp	ULONGLONG	Original timestamp in the unit specified in mObjectFlags..

3.1.4 Direction

Direction of message events.

Value	Description
0	Rx (received)
1	Tx (transmit receipt)
2	Tx Request (transmit request)

3.1.5 Control message sub type

Sub type of a MOST 25 Control message (see data sheet of OS8104 also).

Value	Description
0	Normal
1	RemoteRead
2	RemoteWrite
3	Alloc
4	Dealloc
5	GetSource
>5	not used so far

3.1.6 Addressing mode

Addressing mode of MOST25 Control messages.

Value	Description
0x00	Device (logical node address)
0x10	Node position
0x20	Broadcast
0x30	Groupcast
0xFF	Unknown

3.1.7 Transmission state MOST25

Transmission state of a MOST25 Control message.

Bit	Meaning	Restriction
0	0: bus inactive 1: bus active	only for Dir = Rx (VBLMOSTCtrl) or VBLMOSTSpy
1	1: unlock event during transmission (Unl)	only for Dir = Rx (VBLMOSTCtrl) or VBLMOSTSpy
4	1: acknowledged (Ack)	only for Dir = Tx (always set to 1 for Rx messages in node mode)
5	1: not acknowledged (NAck)	only for Dir = Tx
6	Send result: 0: Transmission error (TxF) 1: OK	only for Dir = Tx (VBLMOSTCtrl)

Note: In case of broadcast transmission, Ack and NAck can both be set.

3.1.8 Transmission state MOST50/150

Transmission states of MOST50/150 messages and packets.

Bit	Meaning	Restriction
0	0: bus inactive 1: bus active	only for Dir = Rx or mTransferType = Spy
4	1: acknowledged (Ack)	only for mTransferType = Node and Dir = Tx (always set to 1 for Rx messages in node mode)
5	1: not acknowledged (NAck)	only for Dir = Tx
6	Send result: 0: Transmission error (TxF) 1: OK	only for Dir = Tx only for mTransferType = Node

3.1.9 Acknowledge code

AckNAck holds the transmit status of a control message (see Transmit Status Register of OS8104 for MOST25).

Bit	Meaning	Restriction
0	1: no response (NoResp)	only for Dir = Tx or spy messages
1	1: valid receipt (Valid)	only for Dir = Tx or spy messages
2	1: CRC Error (CRCErr)	only for Dir = Tx or spy messages
3	1: receive buffer full (RxBufFull)	only for Dir = Tx or spy messages
4	1: acknowledged (Ack)	only for Dir = Tx or spy messages (always set to 1 for Rx messages in node mode)
5	1: negative acknowledge (NAck)	only for Dir = Tx or spy messages

3.1.10 Register event sub type

Operation type of a register event.

Value	Description
kUnspecified = 0	unspecified (or HW does not support sub types)
kNotify = 1	notification on register change (spontaneous)
kReadRequest = 2	request of a register read operation
kWriteRequest = 3	request of a register write operation
kReadResult = 4	result of a register read operation
kWriteResult = 5	result of a register write operation
kReadFailed = 6	register read operation failed
kWriteFailed = 7	register write operation failed

3.1.11 Register ID

IDs for identifying registers (VBLMOSTGenReg).

Value	Meaning
kEmpty = 0x0	
kNPR = 0x87	8 bit Node Position register
kGA = 0x89	8 bit Group (Group Address = 0x0300 + Group)
kNA = 0x8A	16 bit Node Address
kNDR = 0x8F	8 bit Node Delay (MOST25 only)
kMPR = 0x90	8 bit Number of nodes with open bypass
kMDR = 0x91	8 bit Maximum Delay (MOST25 only)
kSBC = 0x96	8 bit Synchronous Bandwidth Control (SBC) Synchronous Bandwidth = 4 x SBC Maximum values for SBC: MOST25: 15 (= 60 Bytes) MOST50: 29 (= 116 Bytes) MOST150: 93 (= 372 Bytes)
kAPA = 0xE8	16 bit Alternate Packet Address (MOST25 only)
kXTIM = 0xBE	8 bit Transmit Retry Time
kXRTY = 0xBF	8 bit Number of send attempts
kMacAdr = 0xFE	48 bit MAC address (EUI-48, conforming to the IEEE standard; MOST150 only)

3.1.12 Fragment Mask

If a bit in the mask is set, the corresponding data field has been seen on the bus.

Bit	Data field
0: 0x00000001	mDataLenAnnounced
1: 0x00000002	mSourceAdr
2: 0x00000004	mDestAdr
3: 0x00000008	mAckNack
4: 0x00000010	mPAck
5: 0x00000020	mPIndex
6: 0x00000040	mPriority
7: 0x00000080	mCRC
8: 0x00000100	mCAck
9: 0x00000200	mSourceMacAdr
10: 0x00000400	mDestMacAdr
31: 0x80000000	0: MOST150 fragment; 1: MOST50 fragment

3.1.13 Transfer Type

Message-like events can either be recorded through the MOST transceiver chip or through a separate network spy.

Transfer Type	Meaning
1: Node	MOST transceiver reported the message (either due to a successful reception or as acknowledgment for a transmit request).
2: Spy	Message was reported by the network spy. The Spy sees all messages independently of the destination address.

3.2 VBLMOSTSpy

Description: Message from MOST 25 Control Channel; received in spy mode (listen only).

Corresponding object type: BL_OBJ_TYPE_MOST_SPY

Parameter	Type	Description
mHeader	VBObjectHeader	Common header type. See 3.1.2.
mChannel	WORD	Channel the message was sent or received.
mDir	BYTE	See 3.1.4
mSourceAdr	DWORD	Source address

Parameter	Type	Description
mDestAdr	DWORD	Target address
mMsg[17]	BYTE	17 data bytes
mRTyp	WORD	See 3.1.5
mRTypAdr	BYTE	See 3.1.6
mState	BYTE	See 3.1.7
mAckNack	BYTE	See 3.1.9
mCRC	DWORD	Cyclic Redundancy Check

3.3 VBLMOSTCtrl

Description: Message on MOST 25 Control Channel; received or transmitted in node mode.

Corresponding object type: BL_OBJ_TYPE_MOST_CTRL

Parameter	Type	Description
mHeader	VBObjectHeader	Common header type. See 3.1.2.
mChannel	WORD	Channel the message was sent or received.
mDir	BYTE	See 3.1.4
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address
mMsg[17]	BYTE	17 data bytes
mRTyp	WORD	See 3.1.5
mRTypAdr	BYTE	See 3.1.6
mState	BYTE	See 3.1.7
mAckNack	BYTE	See 3.1.9 (since CANoe/CANalyzer 7.2)

3.4 VBLMOSTLightLock

Description: This event refers to the optical or electrical modulated signal at the transceiver's Rx.

"Signal On" means that a modulated signal has been detected.

"Lock" means that the receiver PLL (Phase Locked Loop) was able to establish synchronization with the phase of the modulated signal (to "lock").

"Stable Lock" means that for a certain period of time no unlock occurred (see MOST specification).

In case of a series of unlocks, the time of the different unlocks are accumulated. If this accumulated time is greater than a certain threshold, it is called "Critical Unlock" (details see MOST specification).

Corresponding object type: BL_OBJ_TYPE_MOST_LIGHTLOCK

Parameter	Type	Description
mHeader	VBObjectHeader	Common header type. See 3.1.2.
mChannel	WORD	Application channel
mState	SHORT	Signal state: 0x01 – Signal On + Lock 0x02 – Signal Off (implies No Lock) 0x03 – Signal On + No Lock 0x10 – Stable Lock 0x20 – Critical Unlock

3.5 VBLMOSTStatistic

Description: The event transports common network statistics. Usually the event is not visible in a trace window.

Corresponding object type: BL_OBJ_TYPE_MOST_STATISTIC

Parameter	Type	Description
mHeader	VBObjectHeader	Common header type. See 3.1.2.
mChannel	WORD	Application channel
mPktCnt	WORD	Number of messages on Asynchronous channel since the last Statistic event
mFrmCnt	LONG	Number of messages on Control channel since the last Statistic event
mLightCnt	LONG	Number of signal stat transitions since the last Statistic event
mBufferLevel	LONG	Receive buffer level of Optolyzer G1 in spy mode

3.6 VBLMOSTPkt

Description: This event structure was never and should never be used. Use VBLMOSTPkt2 instead.

Corresponding object type: BL_OBJ_TYPE_MOST_PKT

3.7 VBLMOSTPkt2

Description: Message on MOST25 Packet Data Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_PKT2

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel

Parameter	Type	Description
mDir	BYTE	See 3.1.4
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address
mArbitration	BYTE	Arbitration byte
mTimeRes	BYTE	Obsolete member; read/write 0
mQuadsToFollow	BYTE	Number of quadlets
mCRC	WORD	Cyclic Redundancy Check
mPriority	BYTE	Priority
mTransferType	BYTE	See 3.1.13
mState	BYTE	Transmission state 0 for Rx 0x40 for TxOk (transmit request)
mPktDataLength	DWORD	Length of variable data in bytes (1014 max)
mPktData	LPBYTE	Variable data

3.8 VBLMOSTHWMode

Description: This event is fired when one or more HW state changes. HW states are the AllBypass bit (e.g. ABY of OS8104), the Master/Slave selection (e.g. MTR of OS8104), the Control spy and the Asynchronous spy. The event transports all states even if only a single state has changed. <HWModeMask> denotes which state differs regarding to the previous HW mode event.

Corresponding object type: BL_OBJ_TYPE_MOST_HWMODE

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mHWMode	WORD	Bit 0x01: Bypass: 0: open; 1: active Bit 0x02: Timing mode: 0: slave; 1: master Bit 0x04: Master mode: 0: static master; 1: non-static master Bit 0x08: 0: Ethernet Spy active: 1: blocks "Ethernet Spy over MOST" channel Bit 0x10: Control channel spy: 1: active Bit 0x20: Async. channel spy: 1: active Bit 0x40: 1: no "Ethernet over MOST" events (MOST150) Bit 0x80: 1: no events from async. channel

Parameter	Type	Description
mHWMModeMask	WORD	Bitmask of changed bits

3.9 VBLMOSTReg

Description: This event transports a register read or write result (e.g. reading the routing engine of the OS8104). Unlike the special register event (VBLMOSTGenReg) this event does not occur spontaneous.

Corresponding object type: BL_OBJ_TYPE_MOST_REG

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mSubType	BYTE	See 3.1.10
mHandle	DWORD	Operation handle (obsolete; write 0)
mOffset	DWORD	Register address offset
mChip	WORD	ID of chip 1 – OS8104
mRegDataLen	WORD	Number of valid bytes in mRegData
mRegData[16]	BYTE	Register data

3.10 VBLMOSTGenReg

Description: This event reports the change of an important transceiver register like node position or node address. It can occur spontaneous or as result of a read/write operation. Directly after measurement start the current values of the special registers are reported even if they have not changed.

Corresponding object type: BL_OBJ_TYPE_MOST_GENREG

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mSubType	BYTE	See 3.1.10
mHandle	DWORD	Operation handle (obsolete; write 0)
mRegId	WORD	See 3.1.11
mRegValue	ULONGLONG	Register value

3.11 VBLMOSTNetState

Description: Network state derived by MOST Supervisor Layer I+II

Corresponding object type: BL_OBJ_TYPE_MOST_NETSTATE

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mStateNew	WORD	<p>Current network state</p> <p>0 (undefined): Before the first event (shortly after measurement start) the network status is unknown.</p> <p>1 (reserved for Ring Break Diagnostics mode)</p> <p>2 (PowerOff): The network interface to the MOST ring is deactivated. The Tx FOT is not emitting any light.</p> <p>3 (NetInterfaceInit): The network interface is ready to communicate in the MOST ring.</p> <p>4 (ConfigNotOk): The network interface is in normal operating mode (stable lock).</p> <p>5 (ConfigOk): From the perspective of the Network Master the system configuration is valid.</p> <p>6 (NetOn/InitReady): NetOn/InitReady reported to application</p>
mStateOld	WORD	Previous network state

3.12 VBLMOSTDataLost

Description: Indicates loss of data. (Number of lost messages and start and end time stamp of data loss.)

Corresponding object type: BL_OBJ_TYPE_MOST_DATALOST

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mInfo	DWORD	<p>Data loss information</p> <p>Bit0: 1: data loss on control channel (spy)</p> <p>Bit1: 1: data loss on control channel (node)</p> <p>Bit2: 1: data loss on asynchronous channel (spy)</p> <p>Bit3: 1: data loss on asynchronous channel (node)</p> <p>Bit4: 1: data loss on synchronous channel</p> <p>Bit5: 1: data loss since driver queue full</p>
mLostMsgsCtrl	DWORD	Number of lost messages on Control channel
mLostMsgsAsync	DWORD	Number of lost messages on Packet Data Channel channel
mLastGoodTimeStampNS	ULONGLONG	Absolute time in nano-seconds
mNextGoodTimeStampNS	ULONGLONG	Absolute time in nano-seconds

3.13 VBLMOSTTrigger

Description: Transports changes of HW IO pins. The event is used for debugging purposes only.

Corresponding object type: BL_OBJ_TYPE_MOST_TRIGGER

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mMode	WORD	Trigger mode: 0 – unknown 1 – synchronization master 2 – synchronization slave
mHW	WORD	HW that generated the trigger event 0 – unknown 1 – Optolyzer 2 – reserved 3 – reserved 4 – VN2600/VN2610 5 – OptoLyzer OL3150o 6 – VN2640 7 – OptoLyzer OL3050e 8 – SMSC PCI 50 9 – MOCCAcompact50e
mPreviousTriggerValue	DWORD	value of IO register
mCurrentTriggerValue	DWORD	value of IO register

3.14 VBLMOSTStatisticEx

Description: Event transports some bus statistic information that was previously (until CA-Noe/CANalyzerVersion 6.1) carried by the main bus statistic event but was not logged. Usually the event is not visible in a Trace window.

Corresponding object type: BL_OBJ_TYPE_MOST_STATISTICEX

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mCodingErrors	DWORD	Number of coding errors
mFrameCounter	DWORD	MOST frame counter

3.15 VBLMOSTTxLight

Optical physical layer: Information about light output of the Fiber Optical Transmitter

Electrical physical layer: Signal output state

Corresponding object type: BL_OBJ_TYPE_MOST_TXLIGHT

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mState	WORD	0 – TxLight/Signal off 1 – TxLight/Signal enabled 2 – TxLight/Signal forced on

3.16 VBLMOSTAllocTab

Description: Transports current state of the MOST25 Allocation Table of connected hardware interface.

Corresponding object type: BL_OBJ_TYPE_MOST_ALLOCTAB

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mLength	WORD	Length of variable data (usually 60 bytes for MOST25)
mTableData	LPBYTE	Allocation Table The label of a synchronous connection can be distributed over several bytes in the Allocation Table. Each byte in mTableData contains a value that specifies the identification number of the label it belongs to. If the device is a timing master, the MSB of the byte value is used to indicate if the label is in use or not, otherwise the MSB should be ignored. The label number thus can be determined by byte value & 0x7F. If the resulting label number is 0x70, the byte is not used for any label.

3.17 VBLMOSTStress

Description: Information about Stress activity of the hardware interface.

Corresponding object type: BL_OBJ_TYPE_MOST_STRESS

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel

Parameter	Type	Description
mState	WORD	State of Stress mode: 0 – Stopped 1 – Started
mMode	WORD	Stress mode of HW interface: 1 – Light 2 – Lock 3 – Busload Ctrl 4 – Busload Async 5 – Rx Buffer Ctrl 6 – TxLight power 7 – Bypass toggling 8 – SystemLock flag usage 9 – Shutdown flag usage 10 – Rx Buffer Async

3.18 VBLMOST150Message

Description: Message on MOST150 Control Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_150_MESSAGE

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mDir	BYTE	See 3.1.4
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address
mTransferType	BYTE	See 3.1.13
mState	BYTE	See 3.1.8
mAckNack	BYTE	See 3.1.9
mCRC	DWORD	Cyclic Redundancy Check
mPack	BYTE	Pre-emptive acknowledge code (spy only) 0x00: No Response 0x01: Buffer full 0x04: OK
mCAck	BYTE	CRC acknowledge from the packet receiver(s) to the packet transmitter (spy only) 0x00: No Response 0x01: CRC error 0x04: OK
mPriority	BYTE	Priority

Parameter	Type	Description
mPIndex	BYTE	Packet index, increments per message on MOST
mMsgLen	DWORD	Length of variable data in bytes (6...51)
mMsg	LPBYTE	Variable data

3.19 VBLMOST150Pkt

Description: Message on MOST150 Packet Data Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_150_PKT

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mDir	BYTE	See 3.1.4
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address
mTransferType	BYTE	See 3.1.13
mState	BYTE	See 3.1.8
mAckNack	BYTE	See 3.1.9
mCRC	DWORD	Cyclic Redundancy Check
mPack	BYTE	Pre-emptive acknowledge code (spy only) 0x00: No Response 0x01: Buffer full 0x04: OK
mCAck	BYTE	CRC acknowledge from the packet receiver(s) to the packet transmitter (spy only) 0x00: No Response 0x01: CRC error 0x04: OK
mPriority	BYTE	Priority (not used; write 0x00)
mPIndex	BYTE	Packet index, increments per message on MOST
mPktDataLength	DWORD	Length of variable data in bytes (1524 max)
mPktData	LPBYTE	Variable data

3.20 VBLMOSTEthernetPkt

Description: Message on MOST Ethernet Packet Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_ETHERNET_PKT

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mDir	BYTE	See 3.1.4
mSourceMacAdr	ULONGLONG	48 bit source address
mDestMacAdr	ULONGLONG	48 bit target address
mTransferType	BYTE	See 3.1.13
mState	BYTE	See 3.1.8
mAckNack	BYTE	See 3.1.9
mCRC	DWORD	Cyclic Redundancy Check
mPAck	BYTE	Pre-emptive acknowledge code (spy only) 0x00: No Response 0x01: Buffer full 0x04: OK
mCAck	BYTE	CRC acknowledge from the packet receiver(s) to the packet transmitter (spy only) 0x00: No Response 0x01: CRC error 0x04: OK
mPktDataLength	DWORD	Length of variable data in bytes (1506 max)
mPktData	LPBYTE	Variable data

3.21 VBLMOST150MessageFragment

Description: Partial transmitted MOST50 or MOST150 Control Channel message. Fragments are reported from a network spy if the message transmission is corrupted or terminated.

Corresponding object type: BL_OBJ_TYPE_MOST_150_MESSAGE_FRAGMENT

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mAckNack	BYTE	See 3.1.9
mValidMask	DWORD	See 3.1.12
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address

Parameter	Type	Description
mPAck	BYTE	Pre-emptive acknowledge code 0x00: No Response 0x01: Buffer full 0x04: OK
mCAck	BYTE	CRC acknowledge from the packet receiver(s) to the packet transmitter 0x00: No Response 0x01: CRC error 0x04: OK
mPriority	BYTE	Priority
mPIndex	BYTE	Packet index, increments per message on MOST
mCRC	DWORD	Cyclic Redundancy Check
mDataLen	DWORD	Number of transmitted user data bytes. These bytes were counted on bus. Note: The number of bytes saved in this event is stored in mFirstDataLen.
mDataLenAnnounced	DWORD	Announced user data length at start of transmission. In some cases (e.g. sending to an invalid target address, receive buffer full of target device) the transmission is terminated before all data bytes have been sent. Then the counted number of bytes on bus is less than the announced data length (mDataLen < mDataLenAnnounced). Due to rare and very specific bit errors (degrade of end termination byte) mDataLen can also be greater than mDataLenAnnounced.
mFirstDataLen	DWORD	Number of bytes stored in mFirstData (1524 max). Note: In order to limit the size of this event not all counted bytes on bus will be stored in the payload of the logging event.
mFirstData	LPBYTE	Variable data

3.22 VBLMOST150PktFragment

Description: Partial transmitted message on MOST50 and MOST150 Packet Data Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_150_PKT_FRAGMENT

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel

Parameter	Type	Description
mAckNack	BYTE	See 3.1.9
mValidMask	DWORD	See 3.1.12
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address
mPack	BYTE	Pre-emptive acknowledge code 0x00: No Response 0x01: Buffer full 0x04: OK
mCAck	BYTE	CRC acknowledge from the packet receiver(s) to the packet transmitter 0x00: No Response 0x01: CRC error 0x04: OK
mPriority	BYTE	Priority (not used; write 0x00)
mPIndex	BYTE	Packet index, increments per message on MOST
mCRC	DWORD	Cyclic Redundancy Check
mDataLen	DWORD	Number of transmitted user data bytes. These bytes were counted on bus. Note: The number of bytes saved in this event is stored in mFirstDataLen.
mDataLenAnnounced	DWORD	Announced user data length at start of transmission. In some cases (e.g. sending to an invalid target address, receive buffer full of target device) the transmission is terminated before all data bytes have been sent. Then the counted number of bytes on bus is less than the announced data length ($mDataLen < mDataLenAnnounced$). Due to rare and very specific bit errors (degrade of end termination byte) mDataLen can also be greater than mDataLenAnnounced.
mFirstDataLen	DWORD	Number of bytes stored in mFirstData (1524 max). Note: In order to limit the size of this event not all counted bytes on bus will be stored in the payload of the logging event.
mFirstData	LPBYTE	Variable data

3.23 VBLMOSTEthernetPktFragment

Description: Partial transmitted message on MOST Ethernet Packet Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_ETHERNET_PKT_FRAGMENT

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mAckNack	BYTE	See 3.1.9
mValidMask	DWORD	See 3.1.12
mSourceMacAdr	ULONGLONG	48 bit source address
mDestMacAdr	ULONGLONG	48 bit target address
mPacK	BYTE	Pre-emptive acknowledge code 0x00: No Response 0x01: Buffer full 0x04: OK
mCAck	BYTE	CRC acknowledge from the packet receiver(s) to the packet transmitter 0x00: No Response 0x01: CRC error 0x04: OK
mCRC	DWORD	Cyclic Redundancy Check
mDataLen	DWORD	Number of transmitted user data bytes. These bytes were counted on bus. Note: The number of bytes saved in this event is stored in mFirstDataLen.
mDataLenAnnounced	DWORD	Announced user data length at start of transmission. In some cases (e.g. sending to an invalid target address, receive buffer full of target device) the transmission is terminated before all data bytes have been sent. Then the counted number of bytes on bus is less than the announced data length ($mDataLen < mDataLenAnnounced$). Due to rare and very specific bit errors (degrade of end termination byte) $mDataLen$ can also be greater than $mDataLenAnnounced$.
mFirstDataLen	DWORD	Number of bytes stored in mFirstData (1524 max). Note: In order to limit the size of this event not all counted bytes on bus will be stored in the payload of the logging event.
mFirstData	LPBYTE	Variable data

3.24 VBLMOSTSystemEvent

Description: Event for various system states.

Corresponding object type: BL_OBJ_TYPE_MOST_SYSTEM_EVENT

Parameter	Type	Description
mHeader	VLObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mId	BYTE	Identification of transported data (enumeration): 1 - System Lock (MOST150) 2 - Shutdown Flag (MOST150) 3 - Shutdown Reason (MOST150)
mValue	DWORD	Current value
mValueOld	DWORD	Previous value

3.25 VBLMOST150AllocTab

Description: Transports current state and changes of the MOST50/150 Allocation Table.

Corresponding object type: BL_OBJ_TYPE_MOST_150_ALLOCTAB

Parameter	Type	Description
mHeader	VLObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mEventModeFlags	WORD	Determines the data layout (see below)
mFreeBytes	WORD	Number of free bytes after the operation Max. 116 with SBC=29 for MOST50 Max. 372 with SBC=93 for MOST150
mLength	WORD	Length of variable data in bytes. The value must be a multiple of 4.
mTableData	LPBYTE	Allocation Table data

The data layout mTableData depends on bit 0 of mEventModeFlags.

If bit 0 of mEventModeFlags is clear mTableData contains mLength/4 records with the following fields. (Other data layouts are not specified yet.)

Field	Start bit	Bit count	Description
LabelIdent	0	12	Synchronous Connection Label
LabelStatus	12	4	0: label unchanged 4: label has been added (allocated) 8: label has been removed (de-allocated) List removed labels at the end of the table! Listing of removed labels is optional.
LabelWidth	16	16	Width of the label in bytes

3.26 VBLMOST50Message

Description: Message on MOST50 Control Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_50_MESSAGE

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mDir	BYTE	See 3.1.4
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address
mTransferType	BYTE	See 3.1.13
mState	BYTE	See 3.1.8
mAckNack	BYTE	See 3.1.9
mCRC	DWORD	Cyclic Redundancy Check
mPriority	BYTE	Priority
mMsgLen	DWORD	Length of variable data in bytes (5...17)
mMsg	LPBYTE	Variable data

3.27 VBLMOST50Pkt

Description: Message on MOST50 Packet Data Channel.

Corresponding object type: BL_OBJ_TYPE_MOST_50_PKT

Parameter	Type	Description
mHeader	VBObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mDir	BYTE	See 3.1.4
mSourceAdr	DWORD	Source address
mDestAdr	DWORD	Target address
mTransferType	BYTE	See 3.1.13
mState	BYTE	See 3.1.8
mAckNack	BYTE	See 3.1.9
mCRC	DWORD	Cyclic Redundancy Check
mPriority	BYTE	Priority

Parameter	Type	Description
mPktDataLength	DWORD	Length of variable data in bytes (1014 max)
mPktData	LPBYTE	Variable data

3.28 VBLMOSTEcl

Description: State change of the MOST Electrical Control Line.

Corresponding object type: BL_OBJ_TYPE_MOST_ECL

Parameter	Type	Description
mHeader	VBLObjectHeader2	Common header type. See 3.1.3.
mChannel	WORD	Application channel
mMode	WORD	0 – discrete 1 – sequence
mEclState	WORD	mMode = 0: 0 – line low 1 – line high mMode = 1: 0 – sequence stopped 1 – sequence started