

General overview

Corpus	Analytics date	Language
HPLT-docslite.nb.tsv	6/10/2024	Norwegian Bokmål (nb)

Volumes

Docs	Segments	Unique segments	Tokens	Size	Characters
6,115,022	787,825,315	177,369,871 (22.51 %)	9.5B	49.2 GB	


Top 10 domains

Domain	Docs	% of total
blogspot.no	395K	6.47
io.no	203K	3.32
docplayer.me	144K	2.36
blogg.no	139K	2.28
blogspot.com	112K	1.84
diebuchsuche.com	79K	1.29
wordpress.com	39K	0.64
wikipedia.org	38K	0.63
tripadvisor.com	33K	0.53
evisdom.com	30K	0.48


Top 10 TLDs

Domain	Docs	% of total
no	3.8M	61.36
com	1.4M	22.66
me	146K	2.39
org	143K	2.35
net	133K	2.18
eu	69K	1.12
online	65K	1.07
info	60K	0.98
kommune.no	31K	0.50
se	28K	0.45

Documents size (in segments)




Documents by collection




Language Distribution


Number of segments




Percentage of segments in Norwegian Bokmål (nb) inside documents



Distribution of documents by document score



Segment length distribution by token



About HPLT Analytics

Volumes - Segments

Segments correspond to paragraph and list boundaries as defined by HTML elements (<p>, , , etc.) replaced by newlines.

Volumes - Tokens

Tokenized with <https://github.com/hplt-project/data-analytics-tool/blob/main/tokenizers-info.md>

Type-Token Ratio

Lexical variety computed as *number of types (uniques)/number of tokens*, after removing punctuation (<https://www.sltinfo.com/wp-content/uploads/2014/01/type-token-ratio.pdf>).

Document size (in segments)

Segments correspond to paragraph and list boundaries as defined by HTML elements (<p>, , , etc.) replaced by newlines.

Language distribution

Language identified with FastSpell (<https://github.com/mbanon/fastspell>).

Distribution of segments by fluency score

Obtained with Monocleaner (<https://github.com/bitextor/monocleaner>).

Distribution of documents by average fluency score

Obtained with Monocleaner (<https://github.com/bitextor/monocleaner>).

Distribution of documents by document score

Obtained with Web Docs Scorer (<https://github.com/pablop16n/web-docs-scorer/>).

Segment length distribution by token

Tokenized with <https://github.com/hplt-project/data-analytics-tool/blob/main/tokenizers-info.md>

Segment noise distribution

Obtained with Bicleaner Hardrules (<https://github.com/bitextor/bicleaner-hardrules/>).

Frequent n-grams

Tokenized with <https://github.com/hplt-project/data-analytics-tool/blob/main/tokenizers-info.md>, after removing n-grams starting or ending in a stopword. Stopwords from <https://github.com/hplt-project/data-analytics-tool/blob/main/scripts/resources/README.txt>