

General overview

Corpus	Analytics date	Language
HPLT-docslite.ko.tsv	6/27/2024	Korean (ko)

Volumes

Docs	Segments	Unique segments	Tokens	Size	Characters
31,854,516	5,628,410,664			226.53 GB	


Top 10 domains

Domain	Docs	% of total
alibaba.com	1.4M	4.38
tistory.com	573K	1.80
naver.com	501K	1.57
happycampus.com	435K	1.37
aliexpress.com	333K	1.04
daum.net	308K	0.97
blogspot.kr	296K	0.93
made-in-china.com	291K	0.91
rigvedawiki.net	223K	0.70
donga.com	174K	0.55


Top 10 TLDs

Domain	Docs	% of total
com	17M	54.49
co.kr	6.9M	21.57
kr	2.1M	6.74
net	2M	6.31
org	902K	2.83
or.kr	577K	1.81
go.kr	247K	0.78
ac.kr	227K	0.71
me	172K	0.54
pe.kr	117K	0.37

Documents size (in segments)




Documents by collection




Language Distribution


Number of segments



Percentage of segments in Korean (ko) inside documents



Distribution of documents by document score



About HPLT Analytics

Volumes - Segments

Segments correspond to paragraph and list boundaries as defined by HTML elements (<p>, , , etc.) replaced by newlines.

Volumes - Tokens

Tokenized with <https://github.com/hplt-project/data-analytics-tool/blob/main/tokenizers-info.md>

Type-Token Ratio

Lexical variety computed as *number of types (uniques)/number of tokens*, after removing punctuation (<https://www.sltinfo.com/wp-content/uploads/2014/01/type-token-ratio.pdf>).

Document size (in segments)

Segments correspond to paragraph and list boundaries as defined by HTML elements (<p>, , , etc.) replaced by newlines.

Language distribution

Language identified with FastSpell (<https://github.com/mbanor/fastspell>).

Distribution of segments by fluency score

Obtained with Monocleaner (<https://github.com/bitextor/monocleaner>).

Distribution of documents by average fluency score

Obtained with Monocleaner (<https://github.com/bitextor/monocleaner>).

Distribution of documents by document score

Obtained with Web Docs Scorer (<https://github.com/pablop16n/web-docs-scorer/>).

Segment length distribution by token

Tokenized with <https://github.com/hplt-project/data-analytics-tool/blob/main/tokenizers-info.md>

Segment noise distribution

Obtained with Bicleaner Hardrules (<https://github.com/bitextor/bicleaner-hardrules/>).

Frequent n-grams

Tokenized with <https://github.com/hplt-project/data-analytics-tool/blob/main/tokenizers-info.md>, after removing n-grams starting or ending in a stopword. Stopwords from <https://github.com/hplt-project/data-analytics-tool/blob/main/scripts/resources/README.txt>