TESA TOPGUN

SIMPLE IO TESTING

B-L475E-IOT01A (Discovery Kit for IoT Node, STM32L)

STM32CubeIDE (IDE for STM32)

ผศ.ดร.สันติ นุราช

Asst.Prof.Dr.Santi Nuratch

Embedded Computing and Control Laboratory

Department of Control System and Instrumentation Engineering, Faculty of Engineering

King Mongkut's University of Technology Thonburi (KMUTT)

Simple IO Testing

1) Download the IO_Testing.7z and extract it (download link)

2) Open the STM32CubeIDE and File | Open Projects from File System...





Simple IO Testing

3) Brow to the project directory (extracted directory), e.g.; E:\temporal\IO_Testing, and click Finish





Simple IO Testing

4) Right-Click on the project name (IO_Testing) and click Run As | STM32 Cortex-M C/C++ Application



5 Next time, click this button

4 If this window popups, click Run



v1.0.0

Simple IO Testing

5) Check the LEDs status and Logic state of the A0-A5 of the board. They will change every 2 seconds (ON 2 seconds and OFF 2 seconds)



A0-A5

Can be used to control external devices

Simple IO Testing

6) Open the main.c and modify the code, then perform step 4 and 5



v1.0.0

THANK YOU!

ผศ.ดร.สันติ นุราช

Asst.Prof.Dr.Santi Nuratch

Embedded Computing and Control Laboratory

Department of Control System and Instrumentation Engineering, Faculty of Engineering

King Mongkut's University of Technology Thonburi (KMUTT)