

Borla

Testing Report

Student: **George Boadu Junior**

Student ID: **22427354**

Course: CSCD 602 — Advanced Software Engineering, University of Ghana

Document: Testing_Report.pdf · Version 1.0 · 13 August 2026

1. Test strategy

Four layers, in the order they were actually run during the build:

1. **Unit tests** (Vitest) — pure functions with no I/O: OTP hashing/verification, the quiet-hours time-window predicate.
2. **Integration tests** (Vitest + Supertest) — the real Express app (`createApp()`) against a real PostgreSQL+PostGIS instance (a local Docker container running the exact same `postgis/postgis:16-3.4` image family Render uses), covering every route's happy path and its most important failure mode.
3. **Component tests** (Vitest + React Testing Library) — client-side rendering/interaction logic in isolation, with `fetch` mocked.
4. **System / User Acceptance Testing** — manual, scripted, end-to-end walkthroughs against the running application (server + Postgres + browser), exercising both roles and the admin console exactly as a real user would.

Security and usability checks (§5, §6) were folded into the same passes rather than run as a separate phase, which is appropriate at this scale.

2. Automated test results

2.1 Server (`npm run test -w server`)

```
✓ test/unit/otp.test.ts (3 tests)
✓ test/unit/quietHours.test.ts (4 tests)
✓ test/unit/sms.test.ts (3 tests)
✓ test/integration/auth.test.ts (12 tests)
✓ test/integration/broadcasts.test.ts (4 tests)
✓ test/integration/requests.test.ts (4 tests)
✓ test/integration/reviews.test.ts (4 tests)
✓ test/integration/admin.test.ts (4 tests)

Test Files  8 passed (8)
Tests      38 passed (38)
Duration   67.76s
```

2.2 Client (`npm run test -w client`)

```
✓ src/pages/StatusChip.test.tsx (2 tests)
✓ src/components/ReviewForm.test.tsx (2 tests)

Test Files  2 passed (2)
Tests      4 passed (4)
```

Total: 42/42 automated tests passing at time of submission. Re-run with `npm test` from the repository root (requires a reachable Postgres+PostGIS — see `README.md`).

3. Test case log

Representative cases spanning all four rubric areas (functional, unit, integration, system/UAT). "Actual result" reflects the real run, including two real defects caught and fixed during development (rows T-08 and T-19).

#	Test case	Layer	Expected result	Actual result	Pass/Fail
T-01	Request an OTP for a brand-new phone number with no <code>role</code>	Integration	400 — role required to sign up	400 returned with actionable message	Pass
T-02	Request an OTP, verify with the correct code	Integration	New user created, <code>access</code> / <code>refresh</code> issued	User created with <code>role='household'</code> , tokens returned	Pass
T-03	Verify with an incorrect 6-digit code	Integration	400, attempt counter incremented	400 returned	Pass
T-04	Re-use an already-consumed OTP code	Integration	400 — rejected as already used	400 returned	Pass
T-05	GET <code>/auth/me</code> with no bearer token	Integration	401	401 returned	Pass
T-06	GET <code>/auth/me</code> with a valid token	Integration	200 with role-specific profile	200, <code>profile.alert_radius_m</code> present for household	Pass
T-07	Admin login with a non-admin phone number	Integration	401	401 returned	Pass
T-08	(defect) OTP-verify signup path for a brand-new number	Integration (found while writing T-02)	New user row created with the requested role	First implementation threw <code>role_missing</code> inside a dead transaction branch and never created the user — see §4	Fail → Fixed

#	Test case	Layer	Expected result	Actual result	Pass/Fail
T-09	Collector attempts to go online before admin verification	Integration	403	403 returned	Pass
T-10	Verified + online collector, household broadcasts nearby	Integration	Fan-out notifies ≥1 collector; pin appears in that collector's /pins/nearby	notifiedCollectors: 1 ; pin present with correct distance_m	Pass
T-11	Household creates a second broadcast while one is active	Integration	409	409 returned	Pass
T-12	Collector role attempts to create a broadcast	Integration	403 (role guard)	403 returned	Pass
T-13	Household requests an offline collector	Integration	409	409 returned	Pass
T-14	Full request lifecycle: requested → seen → accepted, contact reveal timing	Integration	Phone numbers absent pre-accept, present post-accept	Confirmed via direct field assertion pre/post	Pass
T-15	Reject a request after it was already accepted	Integration	409 , status stays <code>accepted</code> (not resurrected to <code>rejected</code>)	409 returned, status unchanged	Pass
T-16	A collector who wasn't the request's target tries to accept it	Integration	409 (conditional update matches 0 rows)	409 returned	Pass
T-17	Review submitted against a request that is not yet accepted	Integration	400	400 returned	Pass
T-18	Duplicate review on the same accepted request	Integration	409 (unique constraint)	409 returned	Pass
T-19	(defect) Reply to a review before it is moderation-visible	Integration (found while writing this test)	400 — cannot reply to a non-visible review	First implementation only checked <code>subject_id</code> , not <code>status</code> , allowing a reply on a still-pending review — see §4	Fail → Fixed
T-20	Second reply attempt on an already-replied review	Integration	409 (one reply per review)	409 returned	Pass
T-21	Admin verifies a collector; collector can now go online; action appears in audit log	Integration	200 → 200 ; <code>audit_log</code> contains <code>verify_collector</code>	All three confirmed	Pass
T-22	Admin suspends a household; suspended user's <code>/auth/me</code> is blocked; reinstate restores access	Integration	403 while suspended, 200 after reinstatement	Confirmed	Pass
T-23	Admin edits an unknown config key	Integration	404	404 returned	Pass
T-24	Full system walkthrough : household broadcast → collector sees pin on map → household clears it	System/UAT (manual, live server)	Pin visible then gone from collector's feed	Verified against the running app with real curl/browser sessions	Pass

#	Test case	Layer	Expected result	Actual result	Pass/Fail
T-25	Full system walkthrough : direct request → accept → contact reveal → review both sides → double-blind release fires within the 2-minute sweep window	System/UAT (manual, live server)	Both reviews become visible simultaneously , rating aggregates recompute correctly	<code>rating_avg / rating_count</code> confirmed via direct DB query after the sweep ran	Pass
T-26	Manual moderation fallback (no <code>GEMINI_API_KEY</code> set)	System/UAT	Submitted reviews appear in <code>/admin/moderation/queue</code> → <code>awaitingManual</code> , not silently published	Confirmed — both test reviews appeared, required explicit admin approval	Pass
T-27	Quiet-hours predicate across a midnight-wrapping window	Unit	Inside/outside window classified correctly at boundaries	4/4 boundary cases correct	Pass
T-28	OTP hash/verify round-trip and mismatch rejection	Unit	Correct code verifies true, wrong code false	Both confirmed	Pass
T-29	<code>StatusChip</code> renders the correct label for every request status + an unknown fallback	Component	Exact label text present for each of 5 statuses + fallback	Confirmed	Pass
T-30	<code>ReviewForm</code> treats a <code>409</code> (already reviewed) the same as success	Component	Renders the thank-you state, not an error banner	Confirmed	Pass
T-31	Production client build (<code>vite build</code>) and server build (<code>tsc</code>) both compile clean	Build/System	Zero TypeScript errors, bundle produced	Both confirmed (<code>tsc --noEmit</code> clean; <code>dist/</code> produced)	Pass
T-32	GiantSMS phone-number normalisation (<code>+233...</code> / <code>233...</code> → local <code>0_</code> form)	Unit	Both prefixes normalise to the same local number; an already-local number is untouched	3/3 cases correct	Pass
T-33	GiantSMS end-to-end request against the real funded account, production	System (live)	Gateway accepts the send request	<code>POST /api/auth/otp/request</code> against <code>https://borla.onrender.com</code> returned <code>{"delivered":true}</code> — GiantSMS accepted the request at the HTTP layer. Actual handset receipt not visually confirmed (test number is a placeholder, not a live phone)	Pass (partial Technical_D TD-02)
T-34	Unified sign-in: a new phone number gets an OTP with no role needed upfront; the code screen then requires role+name	Integration + scripted screenshot	<code>isNewUser:true</code> ; role/name fields appear only after the code step, submit creates the account	Confirmed both via <code>auth.test.ts</code> and a real headless-browser walkthrough	Pass
T-35	Unified sign-in: an existing (non-admin) number logs straight in from the code screen, no role/name prompt	Integration + scripted screenshot	<code>isNewUser:false</code> ; verify returns tokens with no extra fields required	Confirmed	Pass
T-36	Unified sign-in: an admin's phone number is auto-detected and routed to a password prompt instead of an OTP	Integration + scripted screenshot	<code>requiresPassword:true</code> , no OTP issued; UI shows the password form directly	Confirmed both ways	Pass

#	Test case	Layer	Expected result	Actual result	Pass/Fail
T-37	PWA service worker registers and activates on the production build	System (headless browser against dist/)	<code>navigator.serviceWorker.getRegistrations()</code> returns an active registration scoped to <code>/</code>	Confirmed: <code>{"scope":"http://localhost:5175/","active":true,"scriptURL":"../sw.js"} , <link rel="manifest"></code> present in the DOM	Pass

4. Defects found during development

Defect	Where	Root cause	Corrective action
D-01	<code>server/src/utils/jwt.ts</code>	<code>jsonwebtoken</code> 's TypeScript types don't accept a plain <code>string</code> for <code>expiresIn</code> (expects its own <code>StringValue</code> literal union)	Cast through <code>jwt.SignOptions["expiresIn"]</code> explicitly rather than loosening the type globally
D-02	<code>server/src/modules/auth/routes.ts</code> (OTP verify)	An early draft wrapped user-creation in a transaction block that threw a sentinel error (<code>role_missing</code>) to short-circuit — but the <code>catch</code> swallowed it without ever inserting the user, so first-time signup silently returned an "unexpected signup state" error	Rewritten as a straight-line <code>if (!user) { ...INSERT... }</code> with no transaction/sentinel-error indirection; covered by T-02/T-08
D-03	<code>server/src/seed.ts</code>	First draft referenced a non-existent <code>verified_note</code> column on <code>collectors</code> (copy-paste artefact) wrapped in a silent <code>.catch()</code> fallback that masked the real error	Removed the phantom column and the <code>.catch()</code> swallow entirely; seed now fails loudly if it ever breaks again
D-04	<code>server/src/modules/reviews/routes.ts</code> (reply endpoint)	Only checked <code>review.subject_id === user.id</code> , not <code>review.status === 'visible'</code> , so a reply could be posted on a still-hidden/pending review	Added the status check; covered by T-19
D-05 (security)	<code>server/src/modules/auth/routes.ts</code> (<code>/auth/otp/request</code> , <code>/auth/otp/verify</code>)	Neither endpoint checked <code>users.role</code> — an admin account (meant to require phone+password) could also be logged into via the plain OTP flow, defeating the two-tier auth model entirely. Found by manually testing the OTP flow against live production with the admin's own phone number, post-deployment, not by the existing test suite.	Both endpoints now reject any phone number belonging to an admin account with the same generic message either way (doesn't confirm/deny which numbers are admins). Two live OTP codes already issued to the admin number in production during discovery were immediately neutralised by deliberately exhausting the 5-attempt lockout before the fix deployed. Added two regression tests (<code>refuses to send an OTP to an admin's phone number</code> , <code>refuses to verify an OTP into an admin account even if a code somehow exists</code>) so this can't silently regress.

All five were caught by testing immediately after (or, for D-05, well after) the corresponding feature — four by the automated suite, one by deliberately exercising the live deployed app — direct evidence for why TD-10 (test depth) is listed as "scheduled," not "critical": the practice works, it just hasn't been extended to every corner of the app, including production behaviour, yet.

5. Security testing

Check	Method	Result
Every mutating/reading-sensitive route requires a valid JWT	Automated (T-05, T-12, T-16, T-22) + manual <code>curl</code> without a token	Consistently <code>401</code> / <code>403</code>
SQL injection surface	Code review — every query in <code>server/src/modules/**</code> uses parameterised <code>\$1..\$n</code> placeholders, none concatenate user input into SQL	No string-built SQL found
OTP brute-force / spam	Code review + manual test	5-per-10-minutes request cap and a 5-attempt verify cap are enforced (<code>otp/routes.ts</code>); acknowledged as coarse, see TD-05
Role escalation (collector calling household-only routes, etc.)	Automated (T-12) + manual <code>curl</code> across all role-gated routes	Consistently <code>403</code>
Contact information leakage pre-accept	Automated (T-14)	Phone fields verified absent from the JSON payload itself (not just hidden in the UI) before acceptance
Secrets handling	Code review	JWT secrets and the Gemini key are read from environment variables only, never committed (<code>.env</code> is git-ignored, <code>.env.example</code> has placeholders)
Admin account reachable via the weaker OTP path (bypassing phone+password)	Manual testing against the live production deployment	Confirmed exploitable (D-05) — fixed immediately, redeployed, and re-verified <code>400</code> on both endpoints for the admin's number

6. Usability testing

A design-fidelity pass against the approved `borla_UI_design.html` mockups: the brand mark (pin + marigold radar dot), the line-icon system, coloured initial avatars, and the signature animated "broadcast ring" were all re-implemented in the real app (not just approximated with emoji) and verified with real, scripted screenshots (Puppeteer driving headless Chrome against the running dev server, logged in as the seeded demo accounts) rather than eyeballing the code.

D-05 (found this way): the screenshots showed collector/household initials rendering as bare unstyled text with no circular background — `.avatar` / `.avatar.g` were referenced by the new `Avatar` component but had never actually been added to `tokens.css`. Fixed by adding the missing rule block; re-screenshotted to confirm the fix. A

second minor defect surfaced the same way: `Ama (0su)` produced initials `"A("` because the initials helper took the first character of the *last* whitespace-separated token without checking it started with a letter; fixed by filtering to letter-led words first.

Beyond that: tap targets $\geq 44\text{px}$ (`.btn` padding), icon-first primary actions, a single primary action per screen, and colour contrast matching the approved palette (green/marigold/coral on a warm paper background) — confirmed manually in-browser at mobile viewport widths (390px, 414px) and desktop.

7. Performance testing

Out of scope at pilot scale by design (see SRS NFR discussion) — the one performance-relevant check performed was confirming the PostGIS `ST_DWithin` / `GEOSEARCH` - equivalent nearby queries use the `GIST` index created in `001_init.sql` (`EXPLAIN` on `broadcasts_loc_gix` confirmed an index scan, not a sequential scan, even against the small seeded dataset).

8. What was NOT tested (honestly stated, ties to Technical_Debt_Plan.md TD-10)

Visual confirmation of a GiantSMS text actually arriving on a real handset (T-33 confirmed the gateway *accepts* the request in production; the seeded demo number is a placeholder, not a live phone someone was watching); concurrent double-accept under real network race conditions (only sequential-call idempotency is proven); load/stress testing; cross-browser automated testing (manual only); the four `CollectorHome` / `HouseholdHome` / `AdminDashboard` / `Profile` React pages have no component tests yet, only the two smaller components (`StatusChip` , `ReviewForm`).