CISS245: Advanced Programming
Quiz q2601

Name: eagraham1@cougars.ccis.edu Score:

In any of the following questions, write ERROR if there's an error in the code fragment.

Q1. Write one statement to declare `p` to be a pointer variable that points to an `int` value. (Where's your semicolon?)
Answer:

```
int* p;
```

Q2. A `double` variable `x` has already been declared. Pointer variable `y` which is a pointer to a `double` has also been declared. Write one statement so that `y` points to the value of `x`.
Answer:

```
y = &x;
```

Q3. Pointer `a` points to `b` which is an `int` variable with value `5`. Write down the output of the following print statement.

```
std::cout << *a * 2 + 1 << '\n';
```

Answer:

```
11
```

Q4. Pointers `p`, `q`, and `r` point to integer values `3`, `4`, `5` respectively. Write down the output of the following print statement.

```
p = q;
*p = 1;
std::cout << *p + *q + *r << '\n';
```

Answer:

```
7
```

Q5. The following is a valid statement in a C++ program, what is the type of `y`?

```
x[*y] = 3.14159;
```

Answer:

```
int*, y is a pointer to an integer value
```

Instructions

In the file `thispreamble.tex` look for

```
\renewcommand\AUTHOR{}
```

and enter your email address:

```
\renewcommand\AUTHOR{jdoe5@cougars.ccis.edu}
```

(This is not really necessary since alex will change that for you when you execute `make`.) In your bash shell, execute "`make`" to recompile `main.pdf`. Execute "`make v`" to view `main.pdf`.

Enter your answers in `main.tex`. In the bash shell, execute "`make`" to recompile `main.pdf`. Execute "`make v`" to view `main.pdf`.

For each question, you'll see boxes for you to fill. For small boxes, if you see

```
1 + 1 = \answerbox{}.
```

you do this:

```
1 + 1 = \answerbox{2}.
```

`answerbox` will also appear in "true/false" and "multiple-choice" questions.

For longer answers that need typewriter font, if you see

```
Write a C++ statement that declares an integer variable name x.
\begin{answercode}
\end{answercode}
```

you do this:

```
Write a C++ statement that declares an integer variable name x.
\begin{answercode}
int x;
\end{answercode}
```

`answercode` will appear in questions asking for code, algorithm, and program output. In this case, indentation and spacing is significant. For program output, I do look at spaces and newlines.

For long answers (not in typewriter font) if you see

```
What is the color of the sky?
\begin{answerlong}
\end{answerlong}
```

you can write

```
What is the color of the sky?
\begin{answerlong}
The color of the sky is blue.
\end{answerlong}
```

A question that begins with "T or F or M" requires you to identify whether it is true or false, or meaningless. "Meaningless" means something's wrong with the question and it is not well-defined. Something like "$1 + 2 = 4$" is either true or false (of course it's false). Something like "$1+_2 = 4$?" does not make sense.

When writing results of computations, make sure it's simplified. For instance write 2 instead of $1 + 1$.

Higher level classes.

For students beyond 245: You can put LaTeX commands in `answerlong`.

More examples of meaningless statements: Questions such as "Is $42 = 1+_2$ true or false?" or "Is $42 = \{2\}^{\{3\}}$ true or false?" does not make sense. "Is $P(42) = \{42\}$ true or false?" is meaningless because $P(X)$ is only defined if X is a set. For "Is $1 + 2 + 3$ true or false?", "$1 + 2 + 3$" is well–defined but as a "numerical expression", not as a "proposition", i.e., it cannot be true or false. Therefore "Is $1 + 2 + 3$ true or false?" is also not a well-defined question.

More examples of simplification: When you write down sets, if the answer is $\{1\}$, do not write $\{1, 1\}$. And when the values can be ordered, write the elements of the set in ascending order. When writing polynomials, begin with the highest degree term.

When writing a counterexample, always write the simplest.