Computer-Aided VLSI System Design

Homework 4: IoT Data Filtering

Graduate Institute of Electronics Engineering, National Taiwan University

NTU GIEE



Goals

- In this homework, you will learn
  - Generate patterns for testing
  - Optimizing the trade-off between power consumption, operating frequency, and area
  - Use primetime to estimate power
  - Learn to design an architecture for processing data with long bit lengths
  - Learn to efficiently access the look-up table and accelerate its throughput

beam 2 : 22 min

Introduction

- You are asked to design a IoT Data Filtering (IOTDF), which can processor large IoT data from the sensors, and output the result in real-time [1]



Block Diagram



Design Description

- The sensor data is a 128-bit unsigned data, which is divided in 16 8-bit partial data for IOTDF fetching.
- Only 64 data are required to fetch for each function simulation.

64 × 128 bit



Input/Output

Signal Name	I/O	Width	Simple Description
clk	I	1	Clock signal in the system (positive edge trigger). All inputs are synchronized with the positive edge clock. All outputs should be synchronized at clock rising edge
rst	I	1	Active high asynchronous reset.
in_en	I	1	Input enable signal. When busy is low, in_en is turned to high for fetching new data. Otherwise, in_en is turned to low if busy is high. If all data are received, in_en is turned to low to the end of the process.
iot_in	I	8	IoT input signal. Need 16 cycles to transfer one 128-bit data. The number of data is.
fn_sel	I	3	Function Select Signal. There are 5 functions supported in IOTDF. For each simulation, only 1 function is selected for data processing.
iot_out	O	128	IoT output signal. One cycle for one data output.
busy	O	1	IOTDF busy signal (explained in description for in_en)
valid	O	1	IOTDF output valid signal Set high for valid output

F1


64bit plaintext
[63:0]
IP
L
R
[63:32]
[63:0]
[31:0]
L0
R0
K1
56
48
32
32
P
S1
S2
S8
4
6
XOR
Expan-sion
32
48
L1
R1
K2
F
L2
R2
L15
R15
K16
L16
R16
[63:32]
[31:0]
FP
64bit
ciphertext


r1 . r2 . r9 . r16 → 1 bits other: 2bits
64 bit main key
[127:64]
sub key in
PC1
56
55:28
27:0
CSL
circular shift left
r1 shift 1bit
28
PC2
sub key out
48
K1
r2 shift 1bit
r16 shift 1 bit
K2
K16


前一筆 data ok
[127:0] inbuf 0, inbuf 1 inbuf 2
inbuf 0
inbuf 0
[63:0]
[127:64]
K1 K2
K16
inbuf 0 前一筆 ok
前一筆 [127:64] 給 outbuf 2
[127:64] 給 inbuf 2
out valid
flag = 2
K16 avaliable
[127:64] mux
64
sub key gen
PC1
cnt=0→0
56
fun
sub key gen
56
56bit
PC2
K
48
KEY
KT
MUX OUT1 63:32
cnt=0→0
IPL
32
outbuf1 [63:32]
L
K
48
F
32
outbuf1 [31:0]
R
MUX out1 31:0
cnt=0→0
IPR
XOR OUT
L16
R16
FP
cnt==0?
64 bit ciphertext
outbuf 2 [63:0]
K16 avaliable cnt==1?
inbuf [127:64]
64
outbuf2 [127:64]

F2


64bit plaintext
[63:0]
IP
[63:32]
[63:0]
[31:0]
L0
R0
K16
48
XOR
Expan-sion
32
48
P
32
S1
S2
S8
4
6
XOR
L1
R1
K15
XOR
F
L2
R2
L15
R15
K1
XOR
F
L16
R16
[63:32]
[31:0]
FP
64bit
ciphertext


r1 . r2 . r9 . r16 → 1bits other: 2bits
64bit main key
[127:64]
PC1
56
55:28
27:0
CSL
r1 shift 1bit
circular shift left
28
PC2
28
48
K1
CSL
r2 shift 1bit
CSL
PC2
48
K2
CSL
r16 shift 1bit
CSL
PC2
48
K16

r1 . r2 . r9 . r16 → 1 bits other: 2 bits



F1

PC1 origin

1 +1 r1
K1
2 +1 r2
K2
4 +2 r3
K3
6 +2 r4
K4
8 +2 r5
K5
10 +2 r6
K6
12 +2 r7
K7
14 +2 r8
K8
15 +1 r9
K9
17 +2 r10
K10
19 +2 r11
K11
21 +2 r12
K12
23 +2 r13
K13
25 +2 r14
K14
27 +2 r15
K15
28 +1 r16
K16

F2

Origin

28 +0
0 K16
27 +1
1 K15
25 +2
2 K14
23 +2
3 K13
21 +2
4 K12
19 +2
5 K11
17 +2
6 K10
15 +2
7 K9
14 +1
8 K8
12 +2
9 K7
10 +2
10 K6
8 +2
11 K5
6 +2
12 K4
4 +2
13 K3
2 +2
14 K2
1 +1
15 K1

F3: CRC_gen(N)

- Generate a CRC checksum [3]
- Generator polynomial = $x^3 + x^2 + x$
  - This assignment focuses on this Generator polynomial
- Place 3-bit calculation result in iot_out[2:0], and fill the rest with zeros

Assume input data: 1101

CRC Outcome: iot_out[2:0] = 100



Note: 4 bit for example







128 → 128 次 xor

↓

8xor a cycle ⇒ 16 cycle end



F4 F5

大 or 小 → 1 bit x 2

valid? → 1 bit x 2




0
init outbuf1, outbuf2
reset
[7:0] is valid
update outbuf1, outbuf2
0 1 2 7
15
8
[63:0]
[127:64]
cmp result in FF
tt [7:0]
127:120 is valid
tt [7:0]
get
is in >out1_w
tt [127:120]
0
update outbuf1 outbuf2
init outbuf1, outbuf2
7
flag
0 1 2 0 0 0
14 15 0 0
busy w
busy r
ien
tt
outbuf1
outbuf2

F4: Top2Max(N)

Total 有16筆IoT data

- Find the two largest values in 8 IoT data for each round.
- Output the largest first, then output the second largest.



out buf1

127.. .. 7... 2 1 0

max min

out buf 2

127.. .. 7... 2 1 0

second max second min

in buf

out1 < out2

A Is in biggerthan out1 in > out1 ?

B Is in biggerthan out2 in > out2 ?

F4:

B \ A	0	1
0	in < out1 & out2 keep	X
1	out1 > in > out2 out2 <= in	in > out1 & out2 out1 <= in out2 <= out1

F5

B \ A	0	1
0	out1 & out2 > in out1 <= in out2 <= out1	out2 > in > out1 out2 <= in
1	X	out1 & out2 < in keep

AB	F4	F5
00		out1 <= in out2 <= out1
01	out2 <= in	
11	out1 <= in out2 <= out1	
10		out2 <= in


0
reset
[7:0] is valid
0 0 1 2 7
8
15
8
[63:0]
[127:64]
1
init outbuf1, outbuf2
[127:0]
min (F4)
0 1
15
8
8
[127:0] is valid
tt [7:0]
update outbuf1 outbuf2
0 1
15
8
8
tt [127:120]
1
outbuf2
init outbuf1
out buf1 <= in
F4 outbuf2 <= min
7
tt [127:120]
update outbuf1 outbuf2
14 15
0 1 2
15
8
8
valid
out1 out2
0
0 1
15
8
8

F4: Top2Max(N)

Total 有16 IoT data

- Find the two largest values in 8 IoT data for each round.
- Output the largest first, then output the second largest.



V13

init 成 min

init 成 max

out buf1

127..	.. 7 ... 2 1 0

max min

out buf 2

127..	.. 7 ... 2 1 0

second max second min

in buf

out1 < out2

A Is in biggerthan out1 in > out1 ?

B Is in biggerthan out2 in > out2 ?

F4:

B \ A	0	1
0	in < out1 或 out2 Keep	X
1	out1 > in > out2 out2 <= in	in > out1 或 out2 out1 <= in out2 <= out1

F5

B \ A	0	1
0	out1 或 out2 > in out1 <= in out2 <= out1	out2 > in > out1 out2 <= in
1	X	out1 或 out2 < in Keep

F4:0
F5:1

AB	F4	F5
0 0	Keep	out1 <= in out2 <= out1
0 1	out2 <= in	X → don't care
1 1	out1 <= in out2 <= out1	Keep
1 0	X	out2 <= in

Specification (1)

- IOTDF is initialized between T0~T1..



Specification (2)

- in_en is set to high and start to input IoT data P_00[7:0] if busy is low at T1.



Specification (3)

- in_en is kept to high and input IoT data P_00[15:8] if busy is low at T2.





Specification (4)

- in_en is kept to high and input IoT data P_00[127:120] if busy is low at T3.





Specification (5)

- in_en is set to low and IoT data is set to 0 (stop streaming in data) if busy is high at T4.





Specification (6)

- There are 16 cycles between T1~T4 for one IoT data. You can set busy to high to stop steaming in data if you want.





Specification (7)

- You have to set valid to high if you want to output iot_out.





Specification (8)

- The whole processing time can't exceed 1000000 cycles.







Functions

	Fn_sel	Functions
F1	3'b001	Encrypt(N) 編碼
F2	3'b010	Decrypt(N) 解碼
F3	3'b011	CRC_gen(N)
F4	3'b100	Top2Max(N)
F5	3'b101	Last2Min(N)

F1: Encrypt(N)

- Use the DES algorithm to encrypt 64-bit data [2]





Data Encryption Standard (DES)

- Development
  - IBM's creation, 1970s
  - Adopted by NIST in 1977
- Application
  - Prevailing encryption for years
  - Basis for modern ciphers
- Security
  - Susceptible to brute-force
  - Superseded by Advanced Encryption Standard (AES)

DES Workflow

- Require 16 rounds of encryption
- Each round needs a different sub-key
- The orange box represents a LUT
- Final permutation is the inverse of the initial permutation







Permutation Table

- Excel file for the Permutation Table is located in the "permutations" folder
- Name of the Excel file matches the table name
  - Ex: Initial permutation corresponds to Initial_permutation.xlsx

	A	B
1	Output index	Input index
2	55	7
3	54	15
4	53	23
5	52	31
6	51	39
7	50	47
8	49	55
9	48	63
10	47	6
11	46	14
12	45	22
13	44	30



Details Of Key Generator

sub-key generator

- Main key is processed through the PC1 LUT to form the cipher key, then splited into left and right halves for circular shift left
- Each round has different shift amount, following the shifting rule
- After passing through the PC2 LUT, the sub-key required for each round is obtained

Shifting Rule

Rounds	Shift
1, 2, 9, 16	One bit
Others	Two bit



Details Of Each Round

- Details of F function is on the next slide



F Function

- The Expansion LUT transforms a 32-bit input into a 48-bit output
- S-boxes convert a 6-bit input into a 4-bit output



S-box

- Excel files for S1 to S8 are located in the 'S_boxes' folder
- The method of S-box reading is as follows

6-bit input data

1 1 0 0 1 0

Row number

1 y y y y 0

Column number

x 1 0 0 1 x

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
1	S1	x0000x	x0001x	x0010x	x0011x	x0100x	x0101x	x0110x	x0111x	x1000x	x1001x	x1010x	x1011x	x1100x	x1101x	x1110x	x1111x
2	0yyyy0	14	4	13	1	2	15	11	8	3	10	6	12	5	9	0	7
3	0yyyy1	0	15	7	4	14	2	13	1	10	6	12	11	9	5	3	8
4	1yyyy0	4	1	14	8	13	6	2	11	15	12	9	7	3	10	5	0
5	1yyyy1	15	12	8	2	4	9	1	7	5	11	3	14	10	0	6	13

4-bit output data

1 1 0 0

F2: Decrypt(N)

解密

- Use the DES algorithm to decrypt 64-bit data
- Operation process is similar to Encrypt, with the only difference being the usage order of the sub-keys, changing from 1~16 to 16~1

↖ 可以用同一个 sub-key 硬体，but 顺序 reverse



F3: CRC_gen(N)

- Generate a CRC checksum [3]
- Generator polynomial = $x^3 + x^2 + x$
  - This assignment focuses on this Generator polynomial
- Place 3-bit calculation result in iot_out[2:0], and fill the rest with zeros

Assume input data: 1101

CRC Outcome: iot_out[2:0] = 100



Note: 4 bit for example

F4: Top2Max(N)

Total 有16 IoT data

- Find the two largest values in 8 IoT data for each round.
- Output the largest first, then output the second largest.



F5: Last2Min(N)

- Find the two smallest values in 8 IoT data for each round.
- Output the smallest first, then output the second smallest.



Note:
8 bits for example



IOTDF.v

```
`timescale 1ns/10ps
module IOTDF( clk, rst, in_en, iot_in, fn_sel, busy, valid, iot_out);
input          clk;
input          rst;
input          in_en;
input  [7:0]   iot_in;
input  [2:0]   fn_sel;
output         busy;
output         valid;
output [127:0] iot_out;


endmodule
```

rtl_01.f

- Filelist

```
// ------------------------------------------------------------------------------
// Simulation: HW4_IOT
// ------------------------------------------------------------------------------

// testbench
// ------------------------------------------------------------------------------
../00_TESTBED/testfixture.v


// design files
// ------------------------------------------------------------------------------
./IOTDF.v
```

02_SYN

- IOTDF_DC.sdc

```
# operating conditions and boundary conditions #


create_clock -name clk  -period 6.5  [get_ports  clk]      ;#Modify period by yourself
```

- Run the command to do synthesis
  - syn.tcl needs to be written by yourself (can refer to hw3)

```
dc_shell-t -f syn.tcl | tee syn.log
```

rtl_03.f

- Filelist

```
// ------------------------------------------------------------------------------
// Simulation: HW4_IOT
// ------------------------------------------------------------------------------

// testbench
// ------------------------------------------------------------------------------
../00_TESTBED/testfixture.v
/home/raid7_2/course/cvsd/CBDK_IC_Contest_v2.5/Verilog/tsmc13_neg.v


// design files
// ------------------------------------------------------------------------------
./IOTDF_syn.v
```



runall_rtl & runall_syn

- runall_rtl

```
vcs -f rtl_01.f -full64 -R +v2k -sverilog –v2005 –debug_access+all
+notimingcheck +define+p1+F1 | tee rtl_F1.log
```

- runall_syn

```
vcs -f rtl_03.f -full64 -R +v2k -debug_access+all +neg_tchk
+maxdelays –negdelay +define+SDF+p1+F1 | tee rtl_syn_F1.log
```

testfixture.v

- P2 is for hidden pattern

```
`timescale 1ns/10ps
`define SDFFILE     "./IOTDF_syn.sdf"     //Modify your sdf file name
`define CYCLE       6.5                   //Modify your CYCLE
`define DEL         1.0
`define PAT_NUM     60
`define End_CYCLE   1000000
```

```
`elsif p2 // modify the following number according to your pattern
    localparam PAT_NUM = 64;
    localparam F1_NUM = 64;
    localparam F2_NUM = 64;
    localparam F3_NUM = 64;
    localparam F4_NUM = 16;
    localparam F5_NUM = 16;
```

改 hidden patter 用的

Submission

- Create a folder named studentID_hw4 and follow the hierarchy below

```
r11943024_hw4
├── 01_RTL
│   ├── IOTDF.v (and other verilog files)
│   └── rtl_01.f (Remember to include all your verilog files)
├── 02_SYN
│   ├── IOTDF.area
│   └── IOTDF.timing
├── 03_GATE
│   ├── IOTDF_syn.sdf
│   └── IOTDF_syn.v
├── 06_POWER
│   └── F1_5.power
└── reports
    └── report.txt
```

- Compress the folder **studentID_hw4** in a tar file named **studentID_hw4_v*k*.tar** (*k* is the number of version, *k* =1,2,…)
- Submit to NTU Cool



Report

- TAs will run your design with the reported clock periods
- report.txt (record the power and processing time of gate-level simulation)

```
StudentID: r11943024
Clock period: 5.0 (ns)
Area: 30000.00 (um^2)
----------------------------
f1 time: 10016.50 (ns)
f1 power: 0.9197 (mW)
----------------------------
f2 time: 10016.50 (ns)
f2 power: 0.9197 (mW)
----------------------------
f3 time: 10023.00 (ns)
f3 power: 0.9197 (mW)
----------------------------
f4 time: 10023.00 (ns)
f4 power: 0.9197 (mW)
----------------------------
f5 time: 10016.50 (ns)
f5 power: 0.9197 (mW)
```

Grading Policy

- Simulation:

	Score
RTL simulation	30%
Gate-level simulation	20%
Hidden pattern (Gate-level)	10%

- Performance: (Use pattern1)
  - Performance = (Power1 × Time1 + … + Power5 × Time5) × Area
    Unit: Power(mW), Time(ns), Area(um^2)
  - Baseline = 2.25×10^9
  - Need to pass hidden pattern to get the score of this part

	Score
Baseline	10%
Ranking (Need to pass Baseline)	30%

Area

- Area: Cell area from synthesis report (ex. 93677.81um^2 below)

```
Library(s) Used:

    slow (File: /home/raid7_2/course/cvsd/CBDK_IC_Contest/CIC/SynopsysDC/db/slow.db)

Number of ports:                         2094
Number of nets:                          7021
Number of cells:                         5518
Number of combinational cells:           2275
Number of sequential cells:              2756
Number of macros/black boxes:               0
Number of buf/inv:                        245
Number of references:                     543

Combinational area:              19331.688287
Buf/Inv area:                      935.267387
Noncombinational area:           74346.119583
Macro/Black Box area:                0.000000
Net Interconnect area:      undefined  (No wire load specified)

Total cell area:                 93677.807871
Total area:                 undefined
```

Time

- Time: processing time from simulation (ex. 6493.50ns below)

```
P55:  ** Correct!! ** , iot_out=4f767ba1adb71f94c8fb1345d137a58f
P56:  ** Correct!! ** , iot_out=1a8e5ea79f4b656e55686cedcf47d37b
P57:  ** Correct!! ** , iot_out=e2d7c49ad64e0a11b895fc5a1f08b7b5
P58:  ** Correct!! ** , iot_out=12cad57a543ff9929f59ee6a6e7d4509
P59:  ** Correct!! ** , iot_out=323ebd4b7832c2dde1202bfabf121766

-----------------------------------------------------

Congratulations! All data have been generated successfully!

Total cost time:    6493.50 ns
-----------------------PASS-----------------------
```



Power

- Power: Use below command to analyze the power. (Need to source the following .cshrc file first!) (ex. 2.948 mW below)

```
Unix% source /usr/cad/synopsys/CIC/primetime.cshrc
Unix% pt_shell -f ./pt_script.tcl | tee pp.log
```

```
  Net Switching Power  = 4.176e-05   ( 1.42%)
  Cell Internal Power  = 2.837e-03   (96.24%)
  Cell Leakage Power   = 6.923e-05   ( 2.35%)
                         ---------
Total Power            = 2.948e-03   (100.00%)

X Transition Power     = 3.541e-06
Glitching Power        =    0.0000

Peak Power             =    2.2013
Peak Time              =     6.500
```



Grading Policy

- Deadline: 2024/11/19 13:59:59 (UTC+8)
- TA will use **runall_rtl** and **runall_syn** to run your code at RTL and gate-level simulation.
- Do not memorize the answers directly in any way
- **No delay submission is allowed**
- Lose **5 point** for any wrong naming rule or format
  - Pack all files into a single folder and compress the folder
  - Ensure that the files submitted can be decompressed and executed without issues
- **No plagiarism**

Discussion

- **NTU Cool Discussion Forum**
  - For any questions not related to assignment answers or privacy concerns, please use the NTU Cool discussion forum.
  - **TAs will prioritize answering questions on the NTU Cool discussion forum.**

- **Email: r11943024@ntu.edu.tw**
  - **Title should start with [CVSD 2024 Fall HW4]**
  - **Email with wrong title will be moved to trash automatically**



Hints

- Clock gating
- Register sharing
- Pipelining
- Reasonably use LUT



References

- [1] Reference for IOTDF concept
  - IC Design Contest, 2019.
- [2] Reference for DES algorithm
  - DES Algorithm - HackMD
- [3] Reference for CRC calculation
  - On-line CRC calculation and free library - Lammert Bies